
Numerical Optimization

Release 10.8

The Sage Development Team

Dec 23, 2025

CONTENTS

| | |
|--|------------|
| 1 Knapsack Problems | 1 |
| 2 Mixed Integer Linear Programming | 9 |
| 3 Semidefinite Programming | 61 |
| 4 Linear Functions and Constraints | 85 |
| 5 Matrix/Vector-Valued Linear Functions: Parents | 101 |
| 6 Matrix/Vector-Valued Linear Functions: Elements | 109 |
| 7 Constraints on Linear Functions Tensored with a Free Module | 113 |
| 8 Numerical Root Finding and Optimization | 119 |
| 9 Interactive Simplex Method | 133 |
| 10 Gauss-Legendre Integration for Vector-Valued Functions | 219 |
| 11 Linear Optimization (LP) and Mixed Integer Linear Optimization (MIP) Solver backends | 225 |
| 12 Semidefinite Optimization (SDP) Solver backends | 433 |
| 13 Indices and Tables | 459 |
| Python Module Index | 461 |
| Index | 463 |

KNAPSACK PROBLEMS

This module implements a number of solutions to various knapsack problems, otherwise known as linear integer programming problems. Solutions to the following knapsack problems are implemented:

- Solving the subset sum problem for super-increasing sequences.
- General case using Linear Programming

AUTHORS:

- Minh Van Nguyen (2009-04): initial version
- Nathann Cohen (2009-08): Linear Programming version

1.1 Definition of Knapsack problems

You have already had a knapsack problem, so you should know, but in case you do not, a knapsack problem is what happens when you have hundred of items to put into a bag which is too small, and you want to pack the most useful of them.

When you formally write it, here is your problem:

- Your bag can contain a weight of at most W .
- Each item i has a weight w_i .
- Each item i has a usefulness u_i .

You then want to maximize the total usefulness of the items you will store into your bag, while keeping sure the weight of the bag will not go over W .

As a linear program, this problem can be represented this way (if you define b_i as the binary variable indicating whether the item i is to be included in your bag):

$$\begin{aligned} \text{Maximize: } & \sum_i b_i u_i \\ \text{Such that: } & \sum_i b_i w_i \leq W \\ & \forall i, b_i \text{ binary variable} \end{aligned}$$

(For more information, see the [Wikipedia article Knapsack_problem](#))

1.2 Examples

If your knapsack problem is composed of three items (weight, value) defined by (1,2), (1.5,1), (0.5,3), and a bag of maximum weight 2, you can easily solve it this way:

```
sage: from sage.numerical.knapsack import knapsack
sage: knapsack( [(1,2), (1.5,1), (0.5,3)], max=2)
[5.0, [(1, 2), (0.5000000000000000, 3)]]
```

```
>>> from sage.all import *
>>> from sage.numerical.knapsack import knapsack
>>> knapsack( [(Integer(1),Integer(2)), (RealNumber('1.5'),Integer(1)), (RealNumber(
↳'0.5'),Integer(3))], max=Integer(2))
[5.0, [(1, 2), (0.5000000000000000, 3)]]
```

1.3 Super-increasing sequences

We can test for whether or not a sequence is super-increasing:

```
sage: from sage.numerical.knapsack import Superincreasing
sage: L = [1, 2, 5, 21, 69, 189, 376, 919]
sage: seq = Superincreasing(L)
sage: seq
Super-increasing sequence of length 8
sage: seq.is_superincreasing()
True
sage: Superincreasing().is_superincreasing([1,3,5,7])
False
```

```
>>> from sage.all import *
>>> from sage.numerical.knapsack import Superincreasing
>>> L = [Integer(1), Integer(2), Integer(5), Integer(21), Integer(69), Integer(189),
↳Integer(376), Integer(919)]
>>> seq = Superincreasing(L)
>>> seq
Super-increasing sequence of length 8
>>> seq.is_superincreasing()
True
>>> Superincreasing().is_superincreasing([Integer(1), Integer(3), Integer(5),
↳Integer(7)])
False
```

Solving the subset sum problem for a super-increasing sequence and target sum:

```
sage: L = [1, 2, 5, 21, 69, 189, 376, 919]
sage: Superincreasing(L).subset_sum(98)
[69, 21, 5, 2, 1]
```

```
>>> from sage.all import *
>>> L = [Integer(1), Integer(2), Integer(5), Integer(21), Integer(69), Integer(189),
↳Integer(376), Integer(919)]
>>> Superincreasing(L).subset_sum(Integer(98))
[69, 21, 5, 2, 1]
```

```
class sage.numerical.knapsack.Superincreasing(seq=None)
    Bases: SageObject
```

A class for super-increasing sequences.

Let $L = (a_1, a_2, a_3, \dots, a_n)$ be a non-empty sequence of nonnegative integers. Then L is said to be super-increasing if each a_i is strictly greater than the sum of all previous values. That is, for each $a_i \in L$ the sequence L must satisfy the property

$$a_i > \sum_{k=1}^{i-1} a_k$$

in order to be called a super-increasing sequence, where $|L| \geq 2$. If L has only one element, it is also defined to be a super-increasing sequence.

If `seq` is `None`, then construct an empty sequence. By definition, this empty sequence is not super-increasing.

INPUT:

- `seq` – (default: `None`) a non-empty sequence

EXAMPLES:

```
sage: from sage.numerical.knapsack import Superincreasing
sage: L = [1, 2, 5, 21, 69, 189, 376, 919]
sage: Superincreasing(L).is_superincreasing()
True
sage: Superincreasing().is_superincreasing([1, 3, 5, 7])
False
sage: seq = Superincreasing(); seq
An empty sequence.
sage: seq = Superincreasing([1, 3, 6]); seq
Super-increasing sequence of length 3
sage: seq = Superincreasing([1, 2, 5, 21, 69, 189, 376, 919]); seq
Super-increasing sequence of length 8
```

```
>>> from sage.all import *
>>> from sage.numerical.knapsack import Superincreasing
>>> L = [Integer(1), Integer(2), Integer(5), Integer(21), Integer(69),
↳Integer(189), Integer(376), Integer(919)]
>>> Superincreasing(L).is_superincreasing()
True
>>> Superincreasing().is_superincreasing([Integer(1), Integer(3), Integer(5),
↳Integer(7)])
False
>>> seq = Superincreasing(); seq
An empty sequence.
>>> seq = Superincreasing([Integer(1), Integer(3), Integer(6)]); seq
Super-increasing sequence of length 3
>>> seq = Superincreasing([Integer(1), Integer(2), Integer(5), Integer(21),
↳Integer(69), Integer(189), Integer(376), Integer(919)]); seq
Super-increasing sequence of length 8
```

`is_superincreasing` (*seq=None*)

Determine whether or not `seq` is super-increasing.

If `seq=None` then determine whether or not `self` is super-increasing.

Let $L = (a_1, a_2, a_3, \dots, a_n)$ be a non-empty sequence of nonnegative integers. Then L is said to be super-increasing if each a_i is strictly greater than the sum of all previous values. That is, for each $a_i \in L$ the

sequence L must satisfy the property

$$a_i > \sum_{k=1}^{i-1} a_k$$

in order to be called a super-increasing sequence, where $|L| \geq 2$. If L has exactly one element, then it is also defined to be a super-increasing sequence.

INPUT:

- `seq` – (default: `None`) a sequence to test

OUTPUT:

- If `seq` is `None`, then test `self` to determine whether or not it is super-increasing. In that case, return `True` if `self` is super-increasing; `False` otherwise.
- If `seq` is not `None`, then test `seq` to determine whether or not it is super-increasing. Return `True` if `seq` is super-increasing; `False` otherwise.

EXAMPLES:

By definition, an empty sequence is not super-increasing:

```
sage: from sage.numerical.knapsack import Superincreasing
sage: Superincreasing().is_superincreasing([])
False
sage: Superincreasing().is_superincreasing()
False
sage: Superincreasing().is_superincreasing(tuple())
False
sage: Superincreasing().is_superincreasing(())
False
```

```
>>> from sage.all import *
>>> from sage.numerical.knapsack import Superincreasing
>>> Superincreasing().is_superincreasing([])
False
>>> Superincreasing().is_superincreasing()
False
>>> Superincreasing().is_superincreasing(tuple())
False
>>> Superincreasing().is_superincreasing(())
False
```

But here is an example of a super-increasing sequence:

```
sage: L = [1, 2, 5, 21, 69, 189, 376, 919]
sage: Superincreasing(L).is_superincreasing()
True
sage: L = (1, 2, 5, 21, 69, 189, 376, 919)
sage: Superincreasing(L).is_superincreasing()
True
```

```
>>> from sage.all import *
>>> L = [Integer(1), Integer(2), Integer(5), Integer(21), Integer(69), ...
```

(continues on next page)

(continued from previous page)

```

↪Integer(189), Integer(376), Integer(919)]
>>> Superincreasing(L).is_superincreasing()
True
>>> L = (Integer(1), Integer(2), Integer(5), Integer(21), Integer(69), ↪
↪Integer(189), Integer(376), Integer(919))
>>> Superincreasing(L).is_superincreasing()
True

```

A super-increasing sequence can have zero as one of its elements:

```

sage: L = [0, 1, 2, 4]
sage: Superincreasing(L).is_superincreasing()
True

```

```

>>> from sage.all import *
>>> L = [Integer(0), Integer(1), Integer(2), Integer(4)]
>>> Superincreasing(L).is_superincreasing()
True

```

A super-increasing sequence can be of length 1:

```

sage: Superincreasing([randint(0, 100)]).is_superincreasing()
True

```

```

>>> from sage.all import *
>>> Superincreasing([randint(Integer(0), Integer(100))]).is_superincreasing()
True

```

`largest_less_than(N)`

Return the largest integer in the sequence `self` that is less than or equal to `N`.

This function narrows down the candidate solution using a binary trim, similar to the way binary search halves the sequence at each iteration.

INPUT:

- `N` – integer; the target value to search for

OUTPUT:

The largest integer in `self` that is less than or equal to `N`. If no solution exists, then return `None`.

EXAMPLES:

When a solution is found, return it:

```

sage: from sage.numerical.knapsack import Superincreasing
sage: L = [2, 3, 7, 25, 67, 179, 356, 819]
sage: Superincreasing(L).largest_less_than(207)
179
sage: L = (2, 3, 7, 25, 67, 179, 356, 819)
sage: Superincreasing(L).largest_less_than(2)
2

```

```

>>> from sage.all import *
>>> from sage.numerical.knapsack import Superincreasing
>>> L = [Integer(2), Integer(3), Integer(7), Integer(25), Integer(67),
↳Integer(179), Integer(356), Integer(819)]
>>> Superincreasing(L).largest_less_than(Integer(207))
179
>>> L = (Integer(2), Integer(3), Integer(7), Integer(25), Integer(67),
↳Integer(179), Integer(356), Integer(819))
>>> Superincreasing(L).largest_less_than(Integer(2))
2
    
```

But if no solution exists, return None:

```

sage: L = [2, 3, 7, 25, 67, 179, 356, 819]
sage: Superincreasing(L).largest_less_than(-1) is None
True
    
```

```

>>> from sage.all import *
>>> L = [Integer(2), Integer(3), Integer(7), Integer(25), Integer(67),
↳Integer(179), Integer(356), Integer(819)]
>>> Superincreasing(L).largest_less_than(-Integer(1)) is None
True
    
```

subset_sum(N)

Solving the subset sum problem for a super-increasing sequence.

Let $S = (s_1, s_2, s_3, \dots, s_n)$ be a non-empty sequence of nonnegative integers, and let $N \in \mathbf{Z}$ be nonnegative. The subset sum problem asks for a subset $A \subseteq S$ all of whose elements sum to N . This method specializes the subset sum problem to the case of super-increasing sequences. If a solution exists, then it is also a super-increasing sequence.

Note

This method only solves the subset sum problem for super-increasing sequences. In general, solving the subset sum problem for an arbitrary sequence is known to be computationally hard.

INPUT:

- N – nonnegative integer

OUTPUT:

- A non-empty subset of `self` whose elements sum to N . This subset is also a super-increasing sequence. If no such subset exists, then return the empty list.

ALGORITHM:

The algorithm used is adapted from page 355 of [HPS2008].

EXAMPLES:

Solving the subset sum problem for a super-increasing sequence and target sum:

```

sage: from sage.numerical.knapsack import Superincreasing
sage: L = [1, 2, 5, 21, 69, 189, 376, 919]
    
```

(continues on next page)

(continued from previous page)

```
sage: Superincreasing(L).subset_sum(98)
[69, 21, 5, 2, 1]
```

```
>>> from sage.all import *
>>> from sage.numerical.knapsack import Superincreasing
>>> L = [Integer(1), Integer(2), Integer(5), Integer(21), Integer(69),
↳Integer(189), Integer(376), Integer(919)]
>>> Superincreasing(L).subset_sum(Integer(98))
[69, 21, 5, 2, 1]
```

```
sage.numerical.knapsack.knapsack(seq, binary, max=True, value_only=1, solver=False, verbose=None,
integrity_tolerance=0)
```

Solve the knapsack problem.

For more information on the knapsack problem, see the documentation of the *knapsack module* or the [Wikipedia article Knapsack problem](#).

INPUT:

- `seq` – two different possible types:
 - A sequence of tuples (`weight`, `value`, `something1`, `something2`, ...). Note that only the first two coordinates (`weight` and `values`) will be taken into account. The rest (if any) will be ignored. This can be useful if you need to attach some information to the items.
 - A sequence of reals (a value of 1 is assumed).
- `binary` – when set to `True`, an item can be taken 0 or 1 time. When set to `False`, an item can be taken any amount of times (while staying integer and positive).
- `max` – maximum admissible weight
- `value_only` – when set to `True`, only the maximum useful value is returned. When set to `False`, both the maximum useful value and an assignment are returned.
- `solver` – (default: `None`) specify a Mixed Integer Linear Programming (MILP) solver to be used. If set to `None`, the default one is used. For more information on MILP solvers and which default solver is used, see the method `solve` of the class *MixedIntegerLinearProgram*.
- `verbose` – integer (default: 0); sets the level of verbosity. Set to 0 by default, which means quiet.
- `integrity_tolerance` – parameter for use with MILP solvers over an inexact base ring; see *MixedIntegerLinearProgram.get_values()*

OUTPUT:

If `value_only` is set to `True`, only the maximum useful value is returned. Else (the default), the function returns a pair `[value, list]`, where `list` can be of two types according to the type of `seq`:

- The list of tuples (w_i, u_i, \dots) occurring in the solution.
- A list of reals where each real is repeated the number of times it is taken into the solution.

EXAMPLES:

If your knapsack problem is composed of three items (`weight`, `value`) defined by $(1, 2)$, $(1.5, 1)$, $(0.5, 3)$, and a bag of maximum weight 2, you can easily solve it this way:

```
sage: from sage.numerical.knapsack import knapsack
sage: knapsack( [(1,2), (1.5,1), (0.5,3)], max=2)
[5.0, [(1, 2), (0.5000000000000000, 3)]]

sage: knapsack( [(1,2), (1.5,1), (0.5,3)], max=2, value_only=True)
5.0
```

```
>>> from sage.all import *
>>> from sage.numerical.knapsack import knapsack
>>> knapsack( [(Integer(1),Integer(2)), (RealNumber('1.5'),Integer(1)),
↳(RealNumber('0.5'),Integer(3))], max=Integer(2))
[5.0, [(1, 2), (0.5000000000000000, 3)]]

>>> knapsack( [(Integer(1),Integer(2)), (RealNumber('1.5'),Integer(1)),
↳(RealNumber('0.5'),Integer(3))], max=Integer(2), value_only=True)
5.0
```

Besides weight and value, you may attach any data to the items:

```
sage: from sage.numerical.knapsack import knapsack
sage: knapsack( [(1, 2, 'spam'), (0.5, 3, 'a', 'lot')])
[3.0, [(0.5000000000000000, 3, 'a', 'lot')]]
```

```
>>> from sage.all import *
>>> from sage.numerical.knapsack import knapsack
>>> knapsack( [(Integer(1), Integer(2), 'spam'), (RealNumber('0.5'), Integer(3),
↳'a', 'lot')])
[3.0, [(0.5000000000000000, 3, 'a', 'lot')]]
```

In the case where all the values (usefulness) of the items are equal to one, you do not need embarrass yourself with the second values, and you can just type for items (1,1), (1.5,1), (0.5,1) the command:

```
sage: from sage.numerical.knapsack import knapsack
sage: knapsack([1,1.5,0.5], max=2, value_only=True)
2.0
```

```
>>> from sage.all import *
>>> from sage.numerical.knapsack import knapsack
>>> knapsack([Integer(1),RealNumber('1.5'),RealNumber('0.5')], max=Integer(2),
↳value_only=True)
2.0
```

MIXED INTEGER LINEAR PROGRAMMING

This module implements classes and methods for the efficient solving of Linear Programs (LP) and Mixed Integer Linear Programs (MILP).

Do you want to understand how the simplex method works? See the `interactive_simplex_method` module (educational purposes only)

2.1 Definition

A linear program (LP) is an optimization problem (Wikipedia article [Optimization_\(mathematics\)](#)) in the following form

$$\max\{c^T x \mid Ax \leq b, x \geq 0\}$$

with given $A \in \mathbb{R}^{m,n}$, $b \in \mathbb{R}^m$, $c \in \mathbb{R}^n$ and unknown $x \in \mathbb{R}^n$. If some or all variables in the vector x are restricted over the integers \mathbf{Z} , the problem is called mixed integer linear program (MILP). A wide variety of problems in optimization can be formulated in this standard form. Then, solvers are able to calculate a solution.

2.2 Example

Imagine you want to solve the following linear system of three equations:

- $w_0 + w_1 + w_2 - 14w_3 = 0$
- $w_1 + 2w_2 - 8w_3 = 0$
- $2w_2 - 3w_3 = 0$

and this additional inequality:

- $w_0 - w_1 - w_2 \geq 0$

where all $w_i \in \mathbf{Z}^+$. You know that the trivial solution is $w_i = 0$, but what is the first non-trivial one with $w_3 \geq 1$?

A mixed integer linear program can give you an answer:

1. You have to create an instance of `MixedIntegerLinearProgram` and – in our case – specify that it is a minimization.
2. Create a dictionary `w` of nonnegative integer variables `w` via `w = p.new_variable(integer=True, nonnegative=True)`.
3. Add those three equations as equality constraints via `add_constraint`.
4. Also add the inequality constraint.
5. Add an inequality constraint $w_3 \geq 1$ to exclude the trivial solution.

6. Specify the objective function via `set_objective`. In our case that is just w_3 . If it is a pure constraint satisfaction problem, specify it as `None`.
7. To check if everything is set up correctly, you can print the problem via `show`.
8. `Solve` it and print the solution.

The following example shows all these steps:

```
sage: p = MixedIntegerLinearProgram(maximization=False, solver='GLPK')
sage: w = p.new_variable(integer=True, nonnegative=True, name='w')
sage: p.add_constraint(w[0] + w[1] + w[2] - 14*w[3] == 0)
sage: p.add_constraint(w[1] + 2*w[2] - 8*w[3] == 0)
sage: p.add_constraint(2*w[2] - 3*w[3] == 0)
sage: p.add_constraint(w[0] - w[1] - w[2] >= 0)
sage: p.add_constraint(w[3] >= 1)
sage: p.set_objective(w[3])
sage: p.show()
Minimization:
  w[3]
Constraints:
  0.0 <= w[0] + w[1] + w[2] - 14.0 w[3] <= 0.0
  0.0 <= w[1] + 2.0 w[2] - 8.0 w[3] <= 0.0
  0.0 <= 2.0 w[2] - 3.0 w[3] <= 0.0
  - w[0] + w[1] + w[2] <= 0.0
  - w[3] <= -1.0
Variables:
  w[0] = x_0 is an integer variable (min=0.0, max=+oo)
  w[1] = x_1 is an integer variable (min=0.0, max=+oo)
  w[2] = x_2 is an integer variable (min=0.0, max=+oo)
  w[3] = x_3 is an integer variable (min=0.0, max=+oo)
sage: print('Objective Value: {}'.format(p.solve()))
Objective Value: 2.0
sage: for i, v in sorted(p.get_values(w, convert=ZZ, tolerance=1e-3).items()):
....:     print(f'w_{i} = {v}')
w_0 = 15
w_1 = 10
w_2 = 3
w_3 = 2
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=False, solver='GLPK')
>>> w = p.new_variable(integer=True, nonnegative=True, name='w')
>>> p.add_constraint(w[Integer(0)] + w[Integer(1)] + w[Integer(2)] -
↳ Integer(14)*w[Integer(3)] == Integer(0))
>>> p.add_constraint(w[Integer(1)] + Integer(2)*w[Integer(2)] -
↳ Integer(8)*w[Integer(3)] == Integer(0))
>>> p.add_constraint(Integer(2)*w[Integer(2)] - Integer(3)*w[Integer(3)] ==
↳ Integer(0))
>>> p.add_constraint(w[Integer(0)] - w[Integer(1)] - w[Integer(2)] >= Integer(0))
>>> p.add_constraint(w[Integer(3)] >= Integer(1))
>>> p.set_objective(w[Integer(3)])
>>> p.show()
Minimization:
  w[3]
```

(continues on next page)

(continued from previous page)

```

Constraints:
  0.0 <= w[0] + w[1] + w[2] - 14.0 w[3] <= 0.0
  0.0 <= w[1] + 2.0 w[2] - 8.0 w[3] <= 0.0
  0.0 <= 2.0 w[2] - 3.0 w[3] <= 0.0
  - w[0] + w[1] + w[2] <= 0.0
  - w[3] <= -1.0
Variables:
  w[0] = x_0 is an integer variable (min=0.0, max=+oo)
  w[1] = x_1 is an integer variable (min=0.0, max=+oo)
  w[2] = x_2 is an integer variable (min=0.0, max=+oo)
  w[3] = x_3 is an integer variable (min=0.0, max=+oo)
>>> print('Objective Value: {}'.format(p.solve()))
Objective Value: 2.0
>>> for i, v in sorted(p.get_values(w, convert=ZZ, tolerance=RealNumber("1e-3")).
    ↪items()):
...     print(f'w_{i} = {v}')
w_0 = 15
w_1 = 10
w_2 = 3
w_3 = 2

```

If your problem is already in the standard form, for example:

```

sage: A = matrix([[1, 2], [3, 5]])
sage: b = vector([7, 11])
sage: c = vector([5, 9])

```

```

>>> from sage.all import *
>>> A = matrix([[Integer(1), Integer(2)], [Integer(3), Integer(5)]])
>>> b = vector([Integer(7), Integer(11)])
>>> c = vector([Integer(5), Integer(9)])

```

You can add the constraint by treating the variable dictionary as a vector:

```

sage: p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
sage: w = p.new_variable(integer=True, name='w')
sage: p.add_constraint(A * w <= b)
sage: p.set_objective((c.row() * w)[0])
sage: p.show()
Maximization:
  5.0 w[0] + 9.0 w[1]
Constraints:
  w[0] + 2.0 w[1] <= 7.0
  3.0 w[0] + 5.0 w[1] <= 11.0
Variables:
  w[0] = x_0 is an integer variable (min=-oo, max=+oo)
  w[1] = x_1 is an integer variable (min=-oo, max=+oo)
sage: print('Objective Value: {}'.format(p.solve()))
Objective Value: 25.0
sage: for i, v in sorted(p.get_values(w, convert=ZZ, tolerance=1e-3).items()):
...:     print(f'w_{i} = {v}')
w_0 = -13

```

(continues on next page)

(continued from previous page)

```
w_1 = 10
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
>>> w = p.new_variable(integer=True, name='w')
>>> p.add_constraint(A * w <= b)
>>> p.set_objective((c.row() * w)[Integer(0)])
>>> p.show()
Maximization:
  5.0 w[0] + 9.0 w[1]
Constraints:
  w[0] + 2.0 w[1] <= 7.0
  3.0 w[0] + 5.0 w[1] <= 11.0
Variables:
  w[0] = x_0 is an integer variable (min=-oo, max=+oo)
  w[1] = x_1 is an integer variable (min=-oo, max=+oo)
>>> print('Objective Value: {}'.format(p.solve()))
Objective Value: 25.0
>>> for i, v in sorted(p.get_values(w, convert=ZZ, tolerance=RealNumber("1e-3")).
->items()):
...     print(f'w_{i} = {v}')
w_0 = -13
w_1 = 10
```

Different backends compute with different base fields, for example:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.base_ring()
Real Double Field
sage: x = p.new_variable(real=True, nonnegative=True)
sage: 0.5 + 3/2*x[1]
0.5 + 1.5*x_0

sage: p = MixedIntegerLinearProgram(solver='ppl')
sage: p.base_ring()
Rational Field
sage: x = p.new_variable(nonnegative=True)
sage: 0.5 + 3/2*x[1]
1/2 + 3/2*x_0
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.base_ring()
Real Double Field
>>> x = p.new_variable(real=True, nonnegative=True)
>>> RealNumber('0.5') + Integer(3)/Integer(2)*x[Integer(1)]
0.5 + 1.5*x_0

>>> p = MixedIntegerLinearProgram(solver='ppl')
>>> p.base_ring()
Rational Field
>>> x = p.new_variable(nonnegative=True)
```

(continues on next page)

(continued from previous page)

```
>>> RealNumber('0.5') + Integer(3)/Integer(2)*x[Integer(1)]
1/2 + 3/2*x_0
```

2.3 More about MIP variables

The underlying MILP backends always work with matrices where each column corresponds to a linear variable. The variable corresponding to the i -th column (counting from 0) is displayed as x_i .

MixedIntegerLinearProgram maintains a dynamic mapping from the arbitrary keys indexing the components of *MIPVariable* objects to the backend variables (indexed by nonnegative integers). Backend variables are created when a component of a *MIPVariable* is accessed.

To make your code more readable, you can construct one or several *MIPVariable* objects that can be arbitrarily named and indexed. This can be done by calling `new_variable()` several times, or by the following special syntax:

```
sage: mip.<a,b> = MixedIntegerLinearProgram(solver='GLPK')
sage: a
MIPVariable a with 0 real components
sage: 5 + a[1] + 2*b[3]
5 + x_0 + 2*x_1
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(solver='GLPK', names=('a', 'b',)); (a, b,) = mip._
↳first_ngens(2)
>>> a
MIPVariable a with 0 real components
>>> Integer(5) + a[Integer(1)] + Integer(2)*b[Integer(3)]
5 + x_0 + 2*x_1
```

Indices can be any object, not necessarily integers. Multi-indices are also allowed:

```
sage: a[4, 'string', QQ]
x_2
sage: a[4, 'string', QQ] - 7*b[2]
x_2 - 7*x_3
sage: mip.show()
Constraints:
Variables:
  a[1] = x_0 is a continuous variable (min=-oo, max=+oo)
  b[3] = x_1 is a continuous variable (min=-oo, max=+oo)
  a[(4, 'string', Rational Field)] = x_2 is a continuous variable (min=-oo, max=+oo)
  b[2] = x_3 is a continuous variable (min=-oo, max=+oo)
```

```
>>> from sage.all import *
>>> a[Integer(4), 'string', QQ]
x_2
>>> a[Integer(4), 'string', QQ] - Integer(7)*b[Integer(2)]
x_2 - 7*x_3
>>> mip.show()
Constraints:
Variables:
  a[1] = x_0 is a continuous variable (min=-oo, max=+oo)
```

(continues on next page)

(continued from previous page)

```
b[3] = x_1 is a continuous variable (min=-oo, max=+oo)
a[(4, 'string', Rational Field)] = x_2 is a continuous variable (min=-oo, max=+oo)
b[2] = x_3 is a continuous variable (min=-oo, max=+oo)
```

Upper/lower bounds on a variable can be specified either as separate constraints (see *add_constraint*) or using the methods *set_max* and *set_min* respectively.

2.4 The default MIP variable

As a special shortcut, it is not necessary to call *new_variable()*. A *MixedIntegerLinearProgram* has a default *MIPVariable*, whose components are obtained by using the syntax *mip[key]*, where *key* is an arbitrary key:

```
sage: mip = MixedIntegerLinearProgram(solver='GLPK')
sage: 5 + mip[2] + 2*mip[7]
5 + x_0 + 2*x_1
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(solver='GLPK')
>>> Integer(5) + mip[Integer(2)] + Integer(2)*mip[Integer(7)]
5 + x_0 + 2*x_1
```

2.5 Index of functions and methods

Below are listed the methods of *MixedIntegerLinearProgram*. This module also implements the *MIPSolverException* exception, as well as the *MIPVariable* class.

| | |
|-------------------------------------|--|
| <i>add_constraint()</i> | Add a constraint to the <i>MixedIntegerLinearProgram</i> |
| <i>base_ring()</i> | Return the base ring |
| <i>best_known_objective_bound()</i> | Return the value of the currently best known bound |
| <i>constraints()</i> | Return a list of constraints, as 3-tuples |
| <i>default_variable()</i> | Return the default <i>MIPVariable</i> of <i>self</i> . |
| <i>get_backend()</i> | Return the backend instance used |
| <i>get_max()</i> | Return the maximum value of a variable |
| <i>get_min()</i> | Return the minimum value of a variable |
| <i>get_objective_value()</i> | Return the value of the objective function |
| <i>get_relative_objective_gap()</i> | Return the relative objective gap of the best known solution |
| <i>get_values()</i> | Return values found by the previous call to <i>solve()</i> |
| <i>is_binary()</i> | Test whether the variable <i>e</i> is binary |
| <i>is_integer()</i> | Test whether the variable is an integer |
| <i>is_real()</i> | Test whether the variable is real |
| <i>linear_constraints_parent()</i> | Return the parent for all linear constraints |
| <i>linear_functions_parent()</i> | Return the parent for all linear functions |
| <i>new_variable()</i> | Return an instance of <i>MIPVariable</i> associated |
| <i>number_of_constraints()</i> | Return the number of constraints assigned so far |
| <i>number_of_variables()</i> | Return the number of variables used so far |

continues on next page

Table 1 – continued from previous page

| | |
|-----------------------------------|--|
| <code>polyhedron()</code> | Return the polyhedron defined by the Linear Program |
| <code>remove_constraint()</code> | Remove a constraint from self |
| <code>remove_constraints()</code> | Remove several constraints |
| <code>set_binary()</code> | Set a variable or a <code>MIPVariable</code> as binary |
| <code>set_integer()</code> | Set a variable or a <code>MIPVariable</code> as integer |
| <code>set_max()</code> | Set the maximum value of a variable |
| <code>set_min()</code> | Set the minimum value of a variable |
| <code>set_objective()</code> | Set the objective of the <code>MixedIntegerLinearProgram</code> |
| <code>set_problem_name()</code> | Set the name of the <code>MixedIntegerLinearProgram</code> |
| <code>set_real()</code> | Set a variable or a <code>MIPVariable</code> as real |
| <code>show()</code> | Display the <code>MixedIntegerLinearProgram</code> in a human-readable |
| <code>solve()</code> | Solve the <code>MixedIntegerLinearProgram</code> |
| <code>solver_parameter()</code> | Return or define a solver parameter |
| <code>sum()</code> | Efficiently computes the sum of a sequence of <code>LinearFunction</code> elements |
| <code>write_lp()</code> | Write the linear program as a LP file |
| <code>write_mps()</code> | Write the linear program as a MPS file |

AUTHORS:

- Risan (2012/02): added extension for exact computation

exception `sage.numerical.mip.MIPSolverException`Bases: `RuntimeError`

Exception raised when the solver fails.

EXAMPLES:

```
sage: from sage.numerical.mip import MIPSolverException
sage: e = MIPSolverException("Error")
sage: e
MIPSolverException('Error'...)
sage: print(e)
Error
```

```
>>> from sage.all import *
>>> from sage.numerical.mip import MIPSolverException
>>> e = MIPSolverException("Error")
>>> e
MIPSolverException('Error'...)
>>> print(e)
Error
```

class `sage.numerical.mip.MIPVariable`Bases: `FiniteFamily``MIPVariable` is a variable used by the class `MixedIntegerLinearProgram`.**Warning**

You should not instantiate this class directly. Instead, use `MixedIntegerLinearProgram.new_variable()`.

copy_for_mip (*mip*)

Return a copy of `self` suitable for a new *MixedIntegerLinearProgram* instance `mip`.

For this to make sense, `mip` should have been obtained as a copy of `self.mip()`.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: pv = p.new_variable(nonnegative=True)
sage: pv[0]
x_0
sage: q = copy(p)
sage: qv = pv.copy_for_mip(q)
sage: pv[77]
x_1
sage: p.number_of_variables()
2
sage: q.number_of_variables()
1
sage: qv[33]
x_1
sage: p.number_of_variables()
2
sage: q.number_of_variables()
2

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: pv = p.new_variable(indices=[3, 7])
sage: q = copy(p)
sage: qv = pv.copy_for_mip(q)
sage: qv[3]
x_0
sage: qv[5]
Traceback (most recent call last):
...
IndexError: 5 does not index a component of MIPVariable with 2 real components
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> pv = p.new_variable(nonnegative=True)
>>> pv[Integer(0)]
x_0
>>> q = copy(p)
>>> qv = pv.copy_for_mip(q)
>>> pv[Integer(77)]
x_1
>>> p.number_of_variables()
2
>>> q.number_of_variables()
1
>>> qv[Integer(33)]
x_1
>>> p.number_of_variables()
2
```

(continues on next page)

(continued from previous page)

```

>>> q.number_of_variables()
2

>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> pv = p.new_variable(indices=[Integer(3), Integer(7)])
>>> q = copy(p)
>>> qv = pv.copy_for_mip(q)
>>> qv[Integer(3)]
x_0
>>> qv[Integer(5)]
Traceback (most recent call last):
...
IndexError: 5 does not index a component of MIPVariable with 2 real components

```

items()

Return the pairs (keys, value) contained in the dictionary.

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(nonnegative=True)
sage: p.set_objective(v[0] + v[1])
sage: sorted(v.items())
[(0, x_0), (1, x_1)]

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(nonnegative=True)
>>> p.set_objective(v[Integer(0)] + v[Integer(1)])
>>> sorted(v.items())
[(0, x_0), (1, x_1)]

```

keys()

Return the keys already defined in the dictionary.

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(nonnegative=True)
sage: p.set_objective(v[0] + v[1])
sage: sorted(v.keys())
[0, 1]

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(nonnegative=True)
>>> p.set_objective(v[Integer(0)] + v[Integer(1)])
>>> sorted(v.keys())
[0, 1]

```

mip()

Return the *MixedIntegerLinearProgram* in which self is a variable.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(nonnegative=True)
sage: p == v.mip()
True
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(nonnegative=True)
>>> p == v.mip()
True
```

set_max(max)

Set an upper bound on the variable.

INPUT:

- max – an upper bound, or None to mean that the variable is unbounded

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(real=True, nonnegative=True)
sage: p.get_max(v)
sage: p.get_max(v[0])
sage: p.set_max(v, 4)
sage: p.get_max(v)
4
sage: p.get_max(v[0])
4.0
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(real=True, nonnegative=True)
>>> p.get_max(v)
>>> p.get_max(v[Integer(0)])
>>> p.set_max(v, Integer(4))
>>> p.get_max(v)
4
>>> p.get_max(v[Integer(0)])
4.0
```

set_min(min)

Set a lower bound on the variable.

INPUT:

- min – a lower bound, or None to mean that the variable is unbounded

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(real=True, nonnegative=True)
sage: p.get_min(v)
0
sage: p.get_min(v[0])
```

(continues on next page)

(continued from previous page)

```
0.0
sage: p.set_min(v, 4)
sage: p.get_min(v)
4
sage: p.get_min(v[0])
4.0
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(real=True, nonnegative=True)
>>> p.get_min(v)
0
>>> p.get_min(v[Integer(0)])
0.0
>>> p.set_min(v, Integer(4))
>>> p.get_min(v)
4
>>> p.get_min(v[Integer(0)])
4.0
```

values()

Return the symbolic variables associated to the current dictionary.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(nonnegative=True)
sage: p.set_objective(v[0] + v[1])
sage: sorted(v.values(), key=str)
[x_0, x_1]
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(nonnegative=True)
>>> p.set_objective(v[Integer(0)] + v[Integer(1)])
>>> sorted(v.values(), key=str)
[x_0, x_1]
```

class sage.numerical.mip.MixedIntegerLinearProgram

Bases: SageObject

The `MixedIntegerLinearProgram` class is the link between Sage, linear programming (LP) and mixed integer programming (MIP) solvers.

A Mixed Integer Linear Program (MILP) consists of variables, linear constraints on these variables, and an objective function which is to be maximised or minimised under these constraints.

See the thematic tutorial on [Linear Programming \(Mixed Integer\)](#) or [Wikipedia article Linear_programming](#) for further information on linear programming, and the `MILP module` for its use in Sage.

INPUT:

- `solver` – selects a solver; see [Solvers \(backends\)](#) for more information and installation instructions for optional solvers.

- solver="GLPK": the GNU Linear Programming Kit.
 - solver="GLPK/exact": GLPK's implementation of an exact rational simplex method.
 - solver="Coin": the COIN-OR CBC (COIN Branch and Cut) solver.
 - solver="CPLEX": provided by the proprietary IBM ILOG CPLEX Optimization Studio.
 - solver="Gurobi": the proprietary Gurobi solver.
 - solver="CVXOPT": see the CVXOPT web site.
 - solver="PPL": an exact rational solver (for small scale instances) provided by the Parma Polyhedra Library (PPL).
 - solver="InteractiveLP": a didactical implementation of the revised simplex method in Sage. It works over any exact ordered field, the default is \mathbb{Q} .
 - If solver=None (default), the default solver is used (see `default_mip_solver()`).
 - solver can also be a callable (such as a class), see `sage.numerical.backends.generic_backend.get_solver()` for examples.
- maximization
 - When set to True (default), the `MixedIntegerLinearProgram` is defined as a maximization.
 - When set to False, the `MixedIntegerLinearProgram` is defined as a minimization.
 - constraint_generation – only used when solver=None
 - When set to True, after solving the `MixedIntegerLinearProgram`, it is possible to add a constraint, and then solve it again. The effect is that solvers that do not support this feature will not be used.
 - Defaults to False.

 See also

- `default_mip_solver()` – returns/sets the default MIP solver

EXAMPLES:

Computation of a maximum stable set in Petersen's graph:

```
sage: # needs sage.graphs
sage: g = graphs.PetersenGraph()
sage: p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
sage: b = p.new_variable(binary=True)
sage: p.set_objective(sum([b[v] for v in g]))
sage: for (u,v) in g.edges(sort=False, labels=None):
.....:     p.add_constraint(b[u] + b[v], max=1)
sage: p.solve(objective_only=True)
4.0
```

```
>>> from sage.all import *
>>> # needs sage.graphs
>>> g = graphs.PetersenGraph()
>>> p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
>>> b = p.new_variable(binary=True)
>>> p.set_objective(sum([b[v] for v in g]))
```

(continues on next page)

(continued from previous page)

```

>>> for (u,v) in g.edges(sort=False, labels=None):
...     p.add_constraint(b[u] + b[v], max=Integer(1))
>>> p.solve(objective_only=True)
4.0

```

add_constraint (*linear_function*, *max=None*, *min=None*, *name=None*, *return_indices=False*)

Add a constraint to the `MixedIntegerLinearProgram`.

INPUT:

- `linear_function` – four different types of arguments are admissible:
 - A linear function. In this case, one of the arguments `min` or `max` has to be specified.
 - A linear constraint of the form $A \leq B$, $A \geq B$, $A \leq B \leq C$, $A \geq B \geq C$ or $A == B$.
 - A vector-valued linear function, see `linear_tensor`. In this case, one of the arguments `min` or `max` has to be specified.
 - An (in)equality of vector-valued linear functions, that is, elements of the space of linear functions tensored with a vector space. See `linear_tensor_constraints` for details.
- `max` – constant or `None` (default). An upper bound on the linear function. This must be a numerical value for scalar linear functions, or a vector for vector-valued linear functions. Not allowed if the `linear_function` argument is a symbolic (in)-equality.
- `min` – constant or `None` (default). A lower bound on the linear function. This must be a numerical value for scalar linear functions, or a vector for vector-valued linear functions. Not allowed if the `linear_function` argument is a symbolic (in)-equality.
- `name` – a name for the constraint
- `return_indices` – boolean (default: `False`), whether to return the indices of the added constraints

OUTPUT:

The row indices of the constraints added, if `return_indices` is true and the backend guarantees that removing them again yields the original MIP, `None` otherwise.

To set a lower and/or upper bound on the variables use the methods `set_min` and/or `set_max` of `MixedIntegerLinearProgram`.

EXAMPLES:

Consider the following linear program:

```

Maximize:
  x + 5 * y
Constraints:
  x + 0.2 y      <= 4
  1.5 * x + 3 * y <= 4
Variables:
  x is Real (min = 0, max = None)
  y is Real (min = 0, max = None)

```

It can be solved as follows:

```

sage: p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[0] + 5*x[1])

```

(continues on next page)

(continued from previous page)

```
sage: p.add_constraint(x[0] + 0.2*x[1], max=4)
sage: p.add_constraint(1.5*x[0] + 3*x[1], max=4)
sage: p.solve()      # rel tol 1e-15
6.666666666666666
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(0)] + Integer(5)*x[Integer(1)])
>>> p.add_constraint(x[Integer(0)] + RealNumber('0.2')*x[Integer(1)],
↳max=Integer(4))
>>> p.add_constraint(RealNumber('1.5')*x[Integer(0)] +
↳Integer(3)*x[Integer(1)], max=Integer(4))
>>> p.solve()      # rel tol 1e-15
6.666666666666666
```

There are two different ways to add the constraint $x[5] + 3x[7] \leq x[6] + 3$ to a `MixedIntegerLinearProgram`.

The first one consists in giving `add_constraint` this very expression:

```
sage: p.add_constraint(x[5] + 3*x[7] <= x[6] + 3)
```

```
>>> from sage.all import *
>>> p.add_constraint(x[Integer(5)] + Integer(3)*x[Integer(7)] <=
↳x[Integer(6)] + Integer(3))
```

The second (slightly more efficient) one is to use the arguments `min` or `max`, which can only be numerical values:

```
sage: p.add_constraint(x[5] + 3*x[7] - x[6], max=3)
```

```
>>> from sage.all import *
>>> p.add_constraint(x[Integer(5)] + Integer(3)*x[Integer(7)] - x[Integer(6)],
↳max=Integer(3))
```

One can also define double-bounds or equality using symbols `<=`, `>=` and `==`:

```
sage: p.add_constraint(x[5] + 3*x[7] == x[6] + 3)
sage: p.add_constraint(x[5] + 3*x[7] <= x[6] + 3 <= x[8] + 27)
```

```
>>> from sage.all import *
>>> p.add_constraint(x[Integer(5)] + Integer(3)*x[Integer(7)] ==
↳x[Integer(6)] + Integer(3))
>>> p.add_constraint(x[Integer(5)] + Integer(3)*x[Integer(7)] <=
↳x[Integer(6)] + Integer(3) <= x[Integer(8)] + Integer(27))
```

Using this notation, the previous program can be written as:

```
sage: p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[0] + 5*x[1])
```

(continues on next page)

(continued from previous page)

```
sage: p.add_constraint(x[0] + 0.2*x[1] <= 4)
sage: p.add_constraint(1.5*x[0] + 3*x[1] <= 4)
sage: p.solve()      # rel tol 1e-15
6.666666666666666
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(0)] + Integer(5)*x[Integer(1)])
>>> p.add_constraint(x[Integer(0)] + RealNumber('0.2')*x[Integer(1)] <=
↳Integer(4))
>>> p.add_constraint(RealNumber('1.5')*x[Integer(0)] +
↳Integer(3)*x[Integer(1)] <= Integer(4))
>>> p.solve()      # rel tol 1e-15
6.666666666666666
```

The two constraints can also be combined into a single vector-valued constraint:

```
sage: p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[0] + 5*x[1])
sage: f_vec = vector([1, 1.5]) * x[0] + vector([0.2, 3]) * x[1]; f_vec
(1.0, 1.5)*x_0 + (0.2, 3.0)*x_1
sage: p.add_constraint(f_vec, max=vector([4, 4]))
sage: p.solve()      # rel tol 1e-15
6.666666666666666
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(0)] + Integer(5)*x[Integer(1)])
>>> f_vec = vector([Integer(1), RealNumber('1.5')]) * x[Integer(0)] +
↳vector([RealNumber('0.2'), Integer(3)]) * x[Integer(1)]; f_vec
(1.0, 1.5)*x_0 + (0.2, 3.0)*x_1
>>> p.add_constraint(f_vec, max=vector([Integer(4), Integer(4)]))
>>> p.solve()      # rel tol 1e-15
6.666666666666666
```

Instead of specifying the maximum in the optional `max` argument, we can also use (in)equality notation for vector-valued linear functions:

```
sage: f_vec <= 4      # constant rhs becomes vector
(1.0, 1.5)*x_0 + (0.2, 3.0)*x_1 <= (4.0, 4.0)
sage: p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[0] + 5*x[1])
sage: p.add_constraint(f_vec <= 4)
sage: p.solve()      # rel tol 1e-15
6.666666666666666
```

```
>>> from sage.all import *
>>> f_vec <= Integer(4)      # constant rhs becomes vector
```

(continues on next page)

(continued from previous page)

```
(1.0, 1.5)*x_0 + (0.2, 3.0)*x_1 <= (4.0, 4.0)
>>> p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(0)] + Integer(5)*x[Integer(1)])
>>> p.add_constraint(f_vec <= Integer(4))
>>> p.solve()      # rel tol 1e-15
6.666666666666666
```

Finally, one can use the matrix * *MIPVariable* notation to write vector-valued linear functions:

```
sage: m = matrix([[1.0, 0.2], [1.5, 3.0]]); m
[ 1.000000000000000 0.2000000000000000]
[ 1.500000000000000 3.000000000000000]
sage: p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[0] + 5*x[1])
sage: p.add_constraint(m * x <= 4)
sage: p.solve()      # rel tol 1e-15
6.666666666666666
```

```
>>> from sage.all import *
>>> m = matrix([[RealNumber('1.0'), RealNumber('0.2')], [RealNumber('1.5'),
↪RealNumber('3.0')]]); m
[ 1.000000000000000 0.2000000000000000]
[ 1.500000000000000 3.000000000000000]
>>> p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(0)] + Integer(5)*x[Integer(1)])
>>> p.add_constraint(m * x <= Integer(4))
>>> p.solve()      # rel tol 1e-15
6.666666666666666
```

base_ring()

Return the base ring.

OUTPUT: a ring. The coefficients that the chosen solver supports

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.base_ring()
Real Double Field
sage: p = MixedIntegerLinearProgram(solver='ppl')
sage: p.base_ring()
Rational Field
sage: from sage.rings.qqbar import AA #↪
↪needs sage.rings.number_field
sage: p = MixedIntegerLinearProgram(solver='InteractiveLP', base_ring=AA) #↪
↪needs sage.rings.number_field
sage: p.base_ring() #↪
↪needs sage.rings.number_field
Algebraic Real Field
```

(continues on next page)

(continued from previous page)

```

sage: # needs sage.groups sage.rings.number_field
sage: d = polytopes.dodecahedron()
sage: p = MixedIntegerLinearProgram(base_ring=d.base_ring())
sage: p.base_ring()
Number Field in sqrt5 with defining polynomial x^2 - 5 with sqrt5 = 2.
↳236067977499790?

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.base_ring()
Real Double Field
>>> p = MixedIntegerLinearProgram(solver='ppl')
>>> p.base_ring()
Rational Field
>>> from sage.rings.qqbar import AA #_
↳needs sage.rings.number_field
>>> p = MixedIntegerLinearProgram(solver='InteractiveLP', base_ring=AA) #_
↳needs sage.rings.number_field
>>> p.base_ring() #_
↳needs sage.rings.number_field
Algebraic Real Field

>>> # needs sage.groups sage.rings.number_field
>>> d = polytopes.dodecahedron()
>>> p = MixedIntegerLinearProgram(base_ring=d.base_ring())
>>> p.base_ring()
Number Field in sqrt5 with defining polynomial x^2 - 5 with sqrt5 = 2.
↳236067977499790?

```

best_known_objective_bound()

Return the value of the currently best known bound.

This method returns the current best upper (resp. lower) bound on the optimal value of the objective function in a maximization (resp. minimization) problem. It is equal to the output of `get_objective_value()` if the MILP found an optimal solution, but it can differ if it was interrupted manually or after a time limit (cf `solver_parameter()`).

Note

Has no meaning unless `solve` has been called before.

EXAMPLES:

```

sage: # needs sage.graphs
sage: g = graphs.CubeGraph(9)
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.solver_parameter("mip_gap_tolerance", 100)
sage: b = p.new_variable(binary=True)
sage: p.set_objective(p.sum(b[v] for v in g))
sage: for v in g:
....:     p.add_constraint(b[v] + p.sum(b[u] for u in g.neighbors(v)) <= 1)

```

(continues on next page)

(continued from previous page)

```
sage: p.add_constraint(b[v] == 1) # Force an easy non-0 solution
sage: p.solve() # rel tol 100
1.0
sage: p.best_known_objective_bound() # random
48.0
```

```
>>> from sage.all import *
>>> # needs sage.graphs
>>> g = graphs.CubeGraph(Integer(9))
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.solver_parameter("mip_gap_tolerance", Integer(100))
>>> b = p.new_variable(binary=True)
>>> p.set_objective(p.sum(b[v] for v in g))
>>> for v in g:
...     p.add_constraint(b[v] + p.sum(b[u] for u in g.neighbors(v)) <=
↳ Integer(1))
>>> p.add_constraint(b[v] == Integer(1)) # Force an easy non-0 solution
>>> p.solve() # rel tol 100
1.0
>>> p.best_known_objective_bound() # random
48.0
```

constraints (*indices=None*)

Return a list of constraints, as 3-tuples.

INPUT:

- *indices* – select which constraint(s) to return
 - If *indices* = None, the method returns the list of all the constraints.
 - If *indices* is an integer *i*, the method returns constraint *i*.
 - If *indices* is a list of integers, the method returns the list of the corresponding constraints.

OUTPUT:

Each constraint is returned as a triple *lower_bound*, (*indices*, *coefficients*), *upper_bound*. For each of those entries, the corresponding linear function is the one associating to variable *indices*[*i*] the coefficient *coefficients*[*i*], and 0 to all the others.

lower_bound and *upper_bound* are numerical values.

EXAMPLES:

First, let us define a small LP:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.add_constraint(p[0] - p[2], min=1, max=4)
sage: p.add_constraint(p[0] - 2*p[1], min=1)
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.add_constraint(p[Integer(0)] - p[Integer(2)], min=Integer(1),
↳ max=Integer(4))
>>> p.add_constraint(p[Integer(0)] - Integer(2)*p[Integer(1)], min=Integer(1))
```

To obtain the list of all constraints:

```
sage: p.constraints()          # not tested
[(1.0, ([1, 0], [-1.0, 1.0]), 4.0), (1.0, ([2, 0], [-2.0, 1.0]), None)]
```

```
>>> from sage.all import *
>>> p.constraints()          # not tested
[(1.0, ([1, 0], [-1.0, 1.0]), 4.0), (1.0, ([2, 0], [-2.0, 1.0]), None)]
```

Or constraint 0 only:

```
sage: p.constraints(0)       # not tested
(1.0, ([1, 0], [-1.0, 1.0]), 4.0)
```

```
>>> from sage.all import *
>>> p.constraints(Integer(0)) # not tested
(1.0, ([1, 0], [-1.0, 1.0]), 4.0)
```

A list of constraints containing only 1:

```
sage: p.constraints([1])    # not tested
[(1.0, ([2, 0], [-2.0, 1.0]), None)]
```

```
>>> from sage.all import *
>>> p.constraints([Integer(1)]) # not tested
[(1.0, ([2, 0], [-2.0, 1.0]), None)]
```

`default_variable()`

Return the default *MIPVariable* of self.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.default_variable()
MIPVariable with 0 real components
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.default_variable()
MIPVariable with 0 real components
```

`get_backend()`

Return the backend instance used.

This might be useful when access to additional functions provided by the backend is needed.

EXAMPLES:

This example uses the simplex algorithm and prints information:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x, y = p[0], p[1]
sage: p.add_constraint(2*x + 3*y, max=6)
sage: p.add_constraint(3*x + 2*y, max=6)
sage: p.set_objective(x + y + 7)
```

(continues on next page)

(continued from previous page)

```

sage: b = p.get_backend()
sage: b.solver_parameter("simplex_or_intopt", "simplex_only")
sage: b.solver_parameter("verbosity_simplex", "GLP_MSG_ALL")
sage: ans = p.solve()
GLPK Simplex Optimizer...
2 rows, 2 columns, 4 non-zeros
*      0: obj = 7.000000000e+00 inf = 0.000e+00 (2)
*      2: obj = 9.400000000e+00 inf = 0.000e+00 (0)
OPTIMAL LP SOLUTION FOUND
sage: ans # rel tol 1e-5
9.4
    
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x, y = p[Integer(0)], p[Integer(1)]
>>> p.add_constraint(Integer(2)*x + Integer(3)*y, max=Integer(6))
>>> p.add_constraint(Integer(3)*x + Integer(2)*y, max=Integer(6))
>>> p.set_objective(x + y + Integer(7))
>>> b = p.get_backend()
>>> b.solver_parameter("simplex_or_intopt", "simplex_only")
>>> b.solver_parameter("verbosity_simplex", "GLP_MSG_ALL")
>>> ans = p.solve()
GLPK Simplex Optimizer...
2 rows, 2 columns, 4 non-zeros
*      0: obj = 7.000000000e+00 inf = 0.000e+00 (2)
*      2: obj = 9.400000000e+00 inf = 0.000e+00 (0)
OPTIMAL LP SOLUTION FOUND
>>> ans # rel tol 1e-5
9.4
    
```

`get_max(v)`

Return the maximum value of a variable.

INPUT:

- `v` – a variable

OUTPUT:

Maximum value of the variable, or `None` if the variable has no upper bound.

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(nonnegative=True)
sage: p.set_objective(v[1])
sage: p.get_max(v[1])
sage: p.set_max(v[1], 6)
sage: p.get_max(v[1])
6.0
    
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(nonnegative=True)
    
```

(continues on next page)

(continued from previous page)

```

>>> p.set_objective(v[Integer(1)])
>>> p.get_max(v[Integer(1)])
>>> p.set_max(v[Integer(1)], Integer(6))
>>> p.get_max(v[Integer(1)])
6.0

```

get_min(v)

Return the minimum value of a variable.

INPUT:

- `v` – a variable

OUTPUT:

Minimum value of the variable, or `None` if the variable has no lower bound.

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(nonnegative=True)
sage: p.set_objective(v[1])
sage: p.get_min(v[1])
0.0
sage: p.set_min(v[1], 6)
sage: p.get_min(v[1])
6.0
sage: p.set_min(v[1], None)
sage: p.get_min(v[1])

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(nonnegative=True)
>>> p.set_objective(v[Integer(1)])
>>> p.get_min(v[Integer(1)])
0.0
>>> p.set_min(v[Integer(1)], Integer(6))
>>> p.get_min(v[Integer(1)])
6.0
>>> p.set_min(v[Integer(1)], None)
>>> p.get_min(v[Integer(1)])

```

get_objective_value()

Return the value of the objective function.

Note

Behaviour is undefined unless `solve` has been called before.

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x, y = p[0], p[1]

```

(continues on next page)

(continued from previous page)

```

sage: p.add_constraint(2*x + 3*y, max=6)
sage: p.add_constraint(3*x + 2*y, max=6)
sage: p.set_objective(x + y + 7)
sage: p.solve() # rel tol 1e-5
9.4
sage: p.get_objective_value() # rel tol 1e-5
9.4

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x, y = p[Integer(0)], p[Integer(1)]
>>> p.add_constraint(Integer(2)*x + Integer(3)*y, max=Integer(6))
>>> p.add_constraint(Integer(3)*x + Integer(2)*y, max=Integer(6))
>>> p.set_objective(x + y + Integer(7))
>>> p.solve() # rel tol 1e-5
9.4
>>> p.get_objective_value() # rel tol 1e-5
9.4

```

get_relative_objective_gap()

Return the relative objective gap of the best known solution.

For a minimization problem, this value is computed by $(\text{bestinteger} - \text{bestobjective}) / (1e - 10 + |\text{bestobjective}|)$, where `bestinteger` is the value returned by `get_objective_value()` and `bestobjective` is the value returned by `best_known_objective_bound()`. For a maximization problem, the value is computed by $(\text{bestobjective} - \text{bestinteger}) / (1e - 10 + |\text{bestobjective}|)$.

Note

Has no meaning unless `solve` has been called before.

EXAMPLES:

```

sage: # needs sage.graphs
sage: g = graphs.CubeGraph(9)
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.solver_parameter("mip_gap_tolerance", 100)
sage: b = p.new_variable(binary=True)
sage: p.set_objective(p.sum(b[v] for v in g))
sage: for v in g:
....:     p.add_constraint(b[v] + p.sum(b[u] for u in g.neighbors(v)) <= 1)
sage: p.add_constraint(b[v] == 1) # Force an easy non-0 solution
sage: p.solve() # rel tol 100
1.0
sage: p.get_relative_objective_gap() # random
46.99999999999999

```

```

>>> from sage.all import *
>>> # needs sage.graphs
>>> g = graphs.CubeGraph(Integer(9))
>>> p = MixedIntegerLinearProgram(solver='GLPK')

```

(continues on next page)

(continued from previous page)

```

>>> p.solver_parameter("mip_gap_tolerance", Integer(100))
>>> b = p.new_variable(binary=True)
>>> p.set_objective(p.sum(b[v] for v in g))
>>> for v in g:
...     p.add_constraint(b[v] + p.sum(b[u] for u in g.neighbors(v)) <=
↳Integer(1))
↳Integer(1))
>>> p.add_constraint(b[v] == Integer(1)) # Force an easy non-0 solution
>>> p.solve() # rel tol 100
1.0
>>> p.get_relative_objective_gap() # random
46.99999999999999

```

get_values (*convert=None, tolerance=None, *lists*)

Return values found by the previous call to `solve()`.

INPUT:

- **lists* – any instance of `MIPVariable` (or one of its elements), or lists of them
- *convert* – (default: `None`) `ZZ`, `bool`, or `True`:
 - if *convert*=`None` (default), return all variable values as the backend provides them, i.e., as an element of `base_ring()` or a float.
 - if *convert*=`ZZ`, convert all variable values from the `base_ring()` by rounding to the nearest integer.
 - if *convert*=`bool`, convert all variable values from the `base_ring()` by rounding to 0/1 and converting to `bool`.
 - if *convert*=`True`, use `ZZ` for MIP variables declared integer or binary, and convert the values of all other variables to the `base_ring()`.
- *tolerance* – `None`, a positive real number, or 0 (if `base_ring()` is an exact ring). Required if *convert* is not `None` and any integer conversion is to be done. If the variable value differs from the nearest integer by more than *tolerance*, raise a `RuntimeError`.

OUTPUT:

- Each instance of `MIPVariable` is replaced by a dictionary containing the numerical values found for each corresponding variable in the instance.
- Each element of an instance of a `MIPVariable` is replaced by its corresponding numerical value.

Note

While a variable may be declared as binary or integer, its value is an element of the `base_ring()`, or for the numerical solvers, a `float`.

For the numerical solvers, `base_ring()` is `RDF`, an inexact ring. Code using `get_values` should always account for possible numerical errors.

Even for variables declared as binary or integer, or known to be an integer because of the mathematical properties of the model, the returned values cannot be expected to be exact integers. This is normal behavior of the numerical solvers.

For correct operation, any user code needs to avoid exact comparisons (`==`, `!=`) and instead allow for numerical tolerances. The magnitude of the numerical tolerances depends on both the model and the solver.

The arguments `convert` and `tolerance` facilitate writing correct code. See examples below.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: y = p.new_variable(nonnegative=True)
sage: p.set_objective(x[3] + 3*y[2,9] + x[5])
sage: p.add_constraint(x[3] + y[2,9] + 2*x[5], max=2)
sage: p.solve()
6.0
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> y = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(3)] + Integer(3)*y[Integer(2), Integer(9)] +
↳x[Integer(5)])
>>> p.add_constraint(x[Integer(3)] + y[Integer(2), Integer(9)] +
↳Integer(2)*x[Integer(5)], max=Integer(2))
>>> p.solve()
6.0
```

To return the value of `y[2, 9]` in the optimal solution:

```
sage: p.get_values(y[2,9])
2.0
sage: type(_)
<class 'float'>
```

```
>>> from sage.all import *
>>> p.get_values(y[Integer(2), Integer(9)])
2.0
>>> type(_)
<class 'float'>
```

To convert the value to the `base_ring()`:

```
sage: p.get_values(y[2,9], convert=True)
2.0
sage: _.parent()
Real Double Field
```

```
>>> from sage.all import *
>>> p.get_values(y[Integer(2), Integer(9)], convert=True)
2.0
>>> _.parent()
Real Double Field
```

To get a dictionary identical to `x` containing the values for the corresponding variables in the optimal solution:

```
sage: x_sol = p.get_values(x)
sage: sorted(x_sol)
[3, 5]
```

```
>>> from sage.all import *
>>> x_sol = p.get_values(x)
>>> sorted(x_sol)
[3, 5]
```

Obviously, it also works with variables of higher dimension:

```
sage: y_sol = p.get_values(y)
```

```
>>> from sage.all import *
>>> y_sol = p.get_values(y)
```

We could also have tried

```
sage: [x_sol, y_sol] = p.get_values(x, y)
```

```
>>> from sage.all import *
>>> [x_sol, y_sol] = p.get_values(x, y)
```

Or:

```
sage: [x_sol, y_sol] = p.get_values([x, y])
```

```
>>> from sage.all import *
>>> [x_sol, y_sol] = p.get_values([x, y])
```

Using `convert` and `tolerance`. First, a binary knapsack:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x = p.new_variable(binary=True)
sage: p.set_objective(3*x[1] + 4*x[2] + 5*x[3])
sage: p.add_constraint(2*x[1] + 3*x[2] + 4*x[3] <= 6)
sage: p.solve()
8.0
sage: x_opt = p.get_values(x); x_opt
{1: 1.0, 2: 0.0, 3: 1.0}
sage: type(x_opt[1])
<class 'float'>
sage: x_opt_ZZ = p.get_values(x, convert=True, tolerance=1e-6); x_opt_ZZ
{1: 1, 2: 0, 3: 1}
sage: x_opt_ZZ[1].parent()
Integer Ring
sage: x_opt_bool = p.get_values(x, convert=bool, tolerance=1e-6); x_opt_bool
{1: True, 2: False, 3: True}
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x = p.new_variable(binary=True)
```

(continues on next page)

(continued from previous page)

```

>>> p.set_objective(Integer(3)*x[Integer(1)] + Integer(4)*x[Integer(2)] +
↳Integer(5)*x[Integer(3)])
>>> p.add_constraint(Integer(2)*x[Integer(1)] + Integer(3)*x[Integer(2)] +
↳Integer(4)*x[Integer(3)] <= Integer(6))
>>> p.solve()
8.0
>>> x_opt = p.get_values(x); x_opt
{1: 1.0, 2: 0.0, 3: 1.0}
>>> type(x_opt[Integer(1)])
<class 'float'>
>>> x_opt_ZZ = p.get_values(x, convert=True, tolerance=RealNumber('1e-6')); x_
↳opt_ZZ
{1: 1, 2: 0, 3: 1}
>>> x_opt_ZZ[Integer(1)].parent()
Integer Ring
>>> x_opt_bool = p.get_values(x, convert=bool, tolerance=RealNumber('1e-6'));
↳x_opt_bool
{1: True, 2: False, 3: True}
    
```

Thanks to total unimodularity, single-commodity network flow problems with integer capacities and integer supplies/demands have integer vertex solutions. Hence the integrality of solutions is mathematically guaranteed in an optimal solution if we use the simplex algorithm. A numerical LP solver based on the simplex method such as GLPK will return an integer solution only up to a numerical error. Hence, for correct operation, we should use `tolerance`:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK', maximization=False)
sage: x = p.new_variable(nonnegative=True)
sage: x.set_max(1)
sage: p.add_constraint(x['sa'] + x['sb'] == 1)
sage: p.add_constraint(x['sa'] + x['ba'] - x['ab'] - x['at'] == 0)
sage: p.add_constraint(x['sb'] + x['ab'] - x['ba'] - x['bt'] == 0)
sage: p.set_objective(10*x['sa'] + 10*x['bt'])
sage: p.solve()
0.0
sage: x_opt = p.get_values(x); x_opt
{'ab': 0.0, 'at': 1.0, 'ba': 1.0, 'bt': -0.0, 'sa': 0.0, 'sb': 1.0}
sage: x_opt_ZZ = p.get_values(x, convert=ZZ, tolerance=1e-6); x_opt_ZZ
{'ab': 0, 'at': 1, 'ba': 1, 'bt': 0, 'sa': 0, 'sb': 1}
    
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK', maximization=False)
>>> x = p.new_variable(nonnegative=True)
>>> x.set_max(Integer(1))
>>> p.add_constraint(x['sa'] + x['sb'] == Integer(1))
>>> p.add_constraint(x['sa'] + x['ba'] - x['ab'] - x['at'] == Integer(0))
>>> p.add_constraint(x['sb'] + x['ab'] - x['ba'] - x['bt'] == Integer(0))
>>> p.set_objective(Integer(10)*x['sa'] + Integer(10)*x['bt'])
>>> p.solve()
0.0
>>> x_opt = p.get_values(x); x_opt
{'ab': 0.0, 'at': 1.0, 'ba': 1.0, 'bt': -0.0, 'sa': 0.0, 'sb': 1.0}
>>> x_opt_ZZ = p.get_values(x, convert=ZZ, tolerance=RealNumber('1e-6')); x_
    
```

(continues on next page)

(continued from previous page)

```
↪opt_ZZ
{'ab': 0, 'at': 1, 'ba': 1, 'bt': 0, 'sa': 0, 'sb': 1}
```

interactive_lp_problem (*form='standard'*)

Return an InteractiveLPProblem and, if available, a basis.

INPUT:

- *form* – (default: 'standard') a string specifying return type: either None, or 'std' or 'standard', respectively returns an instance of *InteractiveLPProblem* or of *InteractiveLPProblemStandardForm*

OUTPUT:

A 2-tuple consists of an instance of class *InteractiveLPProblem* or *InteractiveLPProblemStandardForm* that is constructed based on a given *MixedIntegerLinearProgram*, and a list of basic variables (the basis) if standard form is chosen (by default), otherwise None.

All variables must have 0 as lower bound and no upper bound.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(names=['m'], solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: y = p.new_variable(nonnegative=True, name='n')
sage: v = p.new_variable(nonnegative=True)
sage: p.add_constraint(x[0] + x[1] - 7*y[0] + v[0] <= 2, name='K')
sage: p.add_constraint(x[1] + 2*y[0] - v[0] <= 3)
sage: p.add_constraint(5*x[0] + y[0] <= 21, name='L')
sage: p.set_objective(2*x[0] + 3*x[1] + 4*y[0] + 5*v[0])
sage: lp, basis = p.interactive_lp_problem()
sage: basis
['K', 'w_1', 'L']
sage: lp.constraint_coefficients()
[ 1.0  1.0 -7.0  1.0]
[ 0.0  1.0  2.0 -1.0]
[ 5.0  0.0  1.0  0.0]
sage: lp.b()
(2.0, 3.0, 21.0)
sage: lp.objective_coefficients()
(2.0, 3.0, 4.0, 5.0)
sage: lp.decision_variables()
(m_0, m_1, n_0, x_3)
sage: view(lp) #not tested
sage: d = lp.dictionary(*basis)
sage: view(d) #not tested
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(names=['m'], solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> y = p.new_variable(nonnegative=True, name='n')
>>> v = p.new_variable(nonnegative=True)
>>> p.add_constraint(x[Integer(0)] + x[Integer(1)] - Integer(7)*y[Integer(0)] -
↪+ v[Integer(0)] <= Integer(2), name='K')
>>> p.add_constraint(x[Integer(1)] + Integer(2)*y[Integer(0)] - v[Integer(0)]
```

(continues on next page)

(continued from previous page)

```

↳<= Integer(3))
>>> p.add_constraint(Integer(5)*x[Integer(0)] + y[Integer(0)] <= Integer(21),
↳name='L')
>>> p.set_objective(Integer(2)*x[Integer(0)] + Integer(3)*x[Integer(1)] +
↳Integer(4)*y[Integer(0)] + Integer(5)*v[Integer(0)])
>>> lp, basis = p.interactive_lp_problem()
>>> basis
['K', 'w_1', 'L']
>>> lp.constraint_coefficients()
[ 1.0  1.0 -7.0  1.0]
[ 0.0  1.0  2.0 -1.0]
[ 5.0  0.0  1.0  0.0]
>>> lp.b()
(2.0, 3.0, 21.0)
>>> lp.objective_coefficients()
(2.0, 3.0, 4.0, 5.0)
>>> lp.decision_variables()
(m_0, m_1, n_0, x_3)
>>> view(lp) #not tested
>>> d = lp.dictionary(*basis)
>>> view(d) #not tested

```

is_binary(*e*)

Test whether the variable *e* is binary. Variables are real by default.

INPUT:

- *e* – a variable (not a MIPVariable, but one of its elements)

OUTPUT: True if the variable *e* is binary; False otherwise

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(nonnegative=True)
sage: p.set_objective(v[1])
sage: p.is_binary(v[1])
False
sage: p.set_binary(v[1])
sage: p.is_binary(v[1])
True

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(nonnegative=True)
>>> p.set_objective(v[Integer(1)])
>>> p.is_binary(v[Integer(1)])
False
>>> p.set_binary(v[Integer(1)])
>>> p.is_binary(v[Integer(1)])
True

```

is_integer(*e*)

Test whether the variable is an integer. Variables are real by default.

INPUT:

- e – a variable (not a `MIPVariable`, but one of its elements)

OUTPUT: True if the variable e is an integer; False otherwise

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(nonnegative=True)
sage: p.set_objective(v[1])
sage: p.is_integer(v[1])
False
sage: p.set_integer(v[1])
sage: p.is_integer(v[1])
True
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(nonnegative=True)
>>> p.set_objective(v[Integer(1)])
>>> p.is_integer(v[Integer(1)])
False
>>> p.set_integer(v[Integer(1)])
>>> p.is_integer(v[Integer(1)])
True
```

is_real (e)

Test whether the variable is real.

INPUT:

- e – a variable (not a `MIPVariable`, but one of its elements)

OUTPUT: True if the variable is real; False otherwise

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(nonnegative=True)
sage: p.set_objective(v[1])
sage: p.is_real(v[1])
True
sage: p.set_binary(v[1])
sage: p.is_real(v[1])
False
sage: p.set_real(v[1])
sage: p.is_real(v[1])
True
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(nonnegative=True)
>>> p.set_objective(v[Integer(1)])
>>> p.is_real(v[Integer(1)])
True
```

(continues on next page)

(continued from previous page)

```

>>> p.set_binary(v[Integer(1)])
>>> p.is_real(v[Integer(1)])
False
>>> p.set_real(v[Integer(1)])
>>> p.is_real(v[Integer(1)])
True

```

linear_constraints_parent()

Return the parent for all linear constraints.

See *linear_functions* for more details.

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.linear_constraints_parent()
Linear constraints over Real Double Field

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.linear_constraints_parent()
Linear constraints over Real Double Field

```

linear_functions_parent()

Return the parent for all linear functions.

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.linear_functions_parent()
Linear functions over Real Double Field

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.linear_functions_parent()
Linear functions over Real Double Field

```

new_variable(real=False, binary=False, integer=False, nonnegative=False, name="", indices=None)

Return a new *MIPVariable* instance.

A new variable x is defined by:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x = p.new_variable(nonnegative=True)

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x = p.new_variable(nonnegative=True)

```

It behaves exactly as a usual dictionary would. It can use any key argument you may like, as $x[5]$ or $x["b"]$, and has methods `items()` and `keys()`.

 See also

- `set_min()`, `get_min()` – set/get the lower bound of a variable
- `set_max()`, `get_max()` – set/get the upper bound of a variable

INPUT:

- `binary`, `integer`, `real` – boolean. Set one of these arguments to `True` to ensure that the variable gets the corresponding type.
- `nonnegative` – boolean (default: `False`); whether the variable should be assumed to be nonnegative. Rather useless for the binary type
- `name` – string; associates a name to the variable. This is only useful when exporting the linear program to a file using `write_mps` or `write_lp`, and has no other effect.
- `indices` – (optional) an iterable of keys; components corresponding to these keys are created in order, and access to components with other keys will raise an error; otherwise components of this variable can be indexed by arbitrary keys and are created dynamically on access

OUTPUT:

A new instance of `MIPVariable` associated to the current `MixedIntegerLinearProgram`.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x = p.new_variable(); x
MIPVariable with 0 real components
sage: x0 = x[0]; x0
x_0
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x = p.new_variable(); x
MIPVariable with 0 real components
>>> x0 = x[Integer(0)]; x0
x_0
```

By default, variables are unbounded:

```
sage: print(p.get_min(x0))
None
sage: print(p.get_max(x0))
None
```

```
>>> from sage.all import *
>>> print(p.get_min(x0))
None
>>> print(p.get_max(x0))
None
```

To define two dictionaries of variables, the first being of real type, and the second of integer type

```

sage: x = p.new_variable(real=True, nonnegative=True)
sage: y = p.new_variable(integer=True, nonnegative=True)
sage: p.add_constraint(x[2] + y[3,5], max=2)
sage: p.is_integer(x[2])
False
sage: p.is_integer(y[3,5])
True
    
```

```

>>> from sage.all import *
>>> x = p.new_variable(real=True, nonnegative=True)
>>> y = p.new_variable(integer=True, nonnegative=True)
>>> p.add_constraint(x[Integer(2)] + y[Integer(3),Integer(5)], max=Integer(2))
>>> p.is_integer(x[Integer(2)])
False
>>> p.is_integer(y[Integer(3),Integer(5)])
True
    
```

An exception is raised when two types are supplied

```

sage: z = p.new_variable(real=True, integer=True)
Traceback (most recent call last):
...
ValueError: Exactly one of the available types has to be True
    
```

```

>>> from sage.all import *
>>> z = p.new_variable(real=True, integer=True)
Traceback (most recent call last):
...
ValueError: Exactly one of the available types has to be True
    
```

Unbounded variables:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x = p.new_variable(real=True)
sage: y = p.new_variable(integer=True)
sage: p.add_constraint(x[0] + x[3] <= 8)
sage: p.add_constraint(y[0] >= y[1])
sage: p.show()
Constraints:
  x_0 + x_1 <= 8.0
 - x_2 + x_3 <= 0.0
Variables:
  x_0 is a continuous variable (min=-oo, max=+oo)
  x_1 is a continuous variable (min=-oo, max=+oo)
  x_2 is an integer variable (min=-oo, max=+oo)
  x_3 is an integer variable (min=-oo, max=+oo)
    
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x = p.new_variable(real=True)
>>> y = p.new_variable(integer=True)
>>> p.add_constraint(x[Integer(0)] + x[Integer(3)] <= Integer(8))
    
```

(continues on next page)

(continued from previous page)

```

>>> p.add_constraint(y[Integer(0)] >= y[Integer(1)])
>>> p.show()
Constraints:
  x_0 + x_1 <= 8.0
  - x_2 + x_3 <= 0.0
Variables:
  x_0 is a continuous variable (min=-oo, max=+oo)
  x_1 is a continuous variable (min=-oo, max=+oo)
  x_2 is an integer variable (min=-oo, max=+oo)
  x_3 is an integer variable (min=-oo, max=+oo)

```

On the Sage command line, generator syntax is accepted as a shorthand for generating new variables with default settings:

```

sage: mip.<x, y, z> = MixedIntegerLinearProgram(solver='GLPK')
sage: mip.add_constraint(x[0] + y[1] + z[2] <= 10)
sage: mip.show()
Constraints:
  x[0] + y[1] + z[2] <= 10.0
Variables:
  x[0] = x_0 is a continuous variable (min=-oo, max=+oo)
  y[1] = x_1 is a continuous variable (min=-oo, max=+oo)
  z[2] = x_2 is a continuous variable (min=-oo, max=+oo)

```

```

>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(solver='GLPK', names=('x', 'y', 'z',));
↳(x, y, z,) = mip._first_ngens(3)
>>> mip.add_constraint(x[Integer(0)] + y[Integer(1)] + z[Integer(2)] <=
↳Integer(10))
>>> mip.show()
Constraints:
  x[0] + y[1] + z[2] <= 10.0
Variables:
  x[0] = x_0 is a continuous variable (min=-oo, max=+oo)
  y[1] = x_1 is a continuous variable (min=-oo, max=+oo)
  z[2] = x_2 is a continuous variable (min=-oo, max=+oo)

```

number_of_constraints()

Return the number of constraints assigned so far.

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.add_constraint(p[0] - p[2], min=1, max=4)
sage: p.add_constraint(p[0] - 2*p[1], min=1)
sage: p.number_of_constraints()
2

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.add_constraint(p[Integer(0)] - p[Integer(2)], min=Integer(1),
↳max=Integer(4))

```

(continues on next page)

(continued from previous page)

```
>>> p.add_constraint(p[Integer(0)] - Integer(2)*p[Integer(1)], min=Integer(1))
>>> p.number_of_constraints()
2
```

number_of_variables()

Return the number of variables used so far.

Note that this is backend-dependent, i.e. we count solver's variables rather than user's variables. An example of the latter can be seen below: Gurobi converts double inequalities, i.e. inequalities like $m \leq c^T x \leq M$, with $m < M$, into equations, by adding extra variables: $c^T x + y = M, 0 \leq y \leq M - m$.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.add_constraint(p[0] - p[2], max=4)
sage: p.number_of_variables()
2
sage: p.add_constraint(p[0] - 2*p[1], min=1)
sage: p.number_of_variables()
3
sage: p = MixedIntegerLinearProgram(solver='glpk')
sage: p.add_constraint(p[0] - p[2], min=1, max=4)
sage: p.number_of_variables()
2
sage: p = MixedIntegerLinearProgram(solver='gurobi') # optional - Gurobi
sage: p.add_constraint(p[0] - p[2], min=1, max=4) # optional - Gurobi
sage: p.number_of_variables() # optional - Gurobi
3
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.add_constraint(p[Integer(0)] - p[Integer(2)], max=Integer(4))
>>> p.number_of_variables()
2
>>> p.add_constraint(p[Integer(0)] - Integer(2)*p[Integer(1)], min=Integer(1))
>>> p.number_of_variables()
3
>>> p = MixedIntegerLinearProgram(solver='glpk')
>>> p.add_constraint(p[Integer(0)] - p[Integer(2)], min=Integer(1),
↳max=Integer(4))
>>> p.number_of_variables()
2
>>> p = MixedIntegerLinearProgram(solver='gurobi') # optional - Gurobi
>>> p.add_constraint(p[Integer(0)] - p[Integer(2)], min=Integer(1),
↳max=Integer(4)) # optional - Gurobi
>>> p.number_of_variables() # optional - Gurobi
3
```

polyhedron(kws)**

Return the polyhedron defined by the Linear Program.

INPUT:

All arguments given to this method are forwarded to the constructor of the `Polyhedron()` class.

OUTPUT:

A `Polyhedron()` object whose i -th variable represents the i -th variable of `self`.

Warning

The polyhedron is built from the variables stored by the LP solver (i.e. the output of `show()`). While they usually match the ones created explicitly when defining the LP, a solver like Gurobi has been known to introduce additional variables to store constraints of the type `lower_bound <= linear_function <= upper_bound`. You should be fine if you did not install Gurobi or if you do not use it as a solver, but keep an eye on the number of variables in the polyhedron, or on the output of `show()`. Just in case.

See also

`to_linear_program()` – return the `MixedIntegerLinearProgram` object associated with a `Polyhedron()` object.

EXAMPLES:

A LP on two variables:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.add_constraint(0 <= 2*p['x'] + p['y'] <= 1)
sage: p.add_constraint(0 <= 3*p['y'] + p['x'] <= 2)
sage: P = p.polyhedron(); P
A 2-dimensional polyhedron in RDF^2 defined as the convex hull of 4 vertices
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.add_constraint(Integer(0) <= Integer(2)*p['x'] + p['y'] <= Integer(1))
>>> p.add_constraint(Integer(0) <= Integer(3)*p['y'] + p['x'] <= Integer(2))
>>> P = p.polyhedron(); P
A 2-dimensional polyhedron in RDF^2 defined as the convex hull of 4 vertices
```

3-D Polyhedron:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.add_constraint(0 <= 2*p['x'] + p['y'] + 3*p['z'] <= 1)
sage: p.add_constraint(0 <= 2*p['y'] + p['z'] + 3*p['x'] <= 1)
sage: p.add_constraint(0 <= 2*p['z'] + p['x'] + 3*p['y'] <= 1)
sage: P = p.polyhedron(); P
A 3-dimensional polyhedron in RDF^3 defined as the convex hull of 8 vertices
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.add_constraint(Integer(0) <= Integer(2)*p['x'] + p['y'] + Integer(3)*p[
↪ 'z'] <= Integer(1))
>>> p.add_constraint(Integer(0) <= Integer(2)*p['y'] + p['z'] + Integer(3)*p[
↪ 'x'] <= Integer(1))
>>> p.add_constraint(Integer(0) <= Integer(2)*p['z'] + p['x'] + Integer(3)*p[
↪ 'y'] <= Integer(1))
```

(continues on next page)

(continued from previous page)

```
>>> P = p.polyhedron(); P
A 3-dimensional polyhedron in RDF^3 defined as the convex hull of 8 vertices
```

An empty polyhedron:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(nonnegative=True)
sage: p.add_constraint(2*v['x'] + v['y'] + 3*v['z'] <= 1)
sage: p.add_constraint(2*v['y'] + v['z'] + 3*v['x'] <= 1)
sage: p.add_constraint(2*v['z'] + v['x'] + 3*v['y'] >= 2)
sage: P = p.polyhedron(); P
The empty polyhedron in RDF^3
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(nonnegative=True)
>>> p.add_constraint(Integer(2)*v['x'] + v['y'] + Integer(3)*v['z'] <=
↳Integer(1))
>>> p.add_constraint(Integer(2)*v['y'] + v['z'] + Integer(3)*v['x'] <=
↳Integer(1))
>>> p.add_constraint(Integer(2)*v['z'] + v['x'] + Integer(3)*v['y'] >=
↳Integer(2))
>>> P = p.polyhedron(); P
The empty polyhedron in RDF^3
```

An unbounded polyhedron:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.add_constraint(2*p['x'] + p['y'] - p['z'] <= 1)
sage: P = p.polyhedron(); P
A 3-dimensional polyhedron in RDF^3 defined as the convex hull of 1 vertex, 1
↳ray, 2 lines
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.add_constraint(Integer(2)*p['x'] + p['y'] - p['z'] <= Integer(1))
>>> P = p.polyhedron(); P
A 3-dimensional polyhedron in RDF^3 defined as the convex hull of 1 vertex, 1
↳ray, 2 lines
```

A square (see [Issue #14395](#))

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x,y = p['x'], p['y']
sage: p.add_constraint(x <= 1)
sage: p.add_constraint(x >= -1)
sage: p.add_constraint(y <= 1)
sage: p.add_constraint(y >= -1)
sage: p.polyhedron()
A 2-dimensional polyhedron in RDF^2 defined as the convex hull of 4 vertices
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x,y = p['x'], p['y']
>>> p.add_constraint(x <= Integer(1))
>>> p.add_constraint(x >= -Integer(1))
>>> p.add_constraint(y <= Integer(1))
>>> p.add_constraint(y >= -Integer(1))
>>> p.polyhedron()
A 2-dimensional polyhedron in RDF^2 defined as the convex hull of 4 vertices

```

We can also use a backend that supports exact arithmetic:

```

sage: p = MixedIntegerLinearProgram(solver='PPL')
sage: x,y = p['x'], p['y']
sage: p.add_constraint(x <= 1)
sage: p.add_constraint(x >= -1)
sage: p.add_constraint(y <= 1)
sage: p.add_constraint(y >= -1)
sage: p.polyhedron()
A 2-dimensional polyhedron in QQ^2 defined as the convex hull of 4 vertices

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='PPL')
>>> x,y = p['x'], p['y']
>>> p.add_constraint(x <= Integer(1))
>>> p.add_constraint(x >= -Integer(1))
>>> p.add_constraint(y <= Integer(1))
>>> p.add_constraint(y >= -Integer(1))
>>> p.polyhedron()
A 2-dimensional polyhedron in QQ^2 defined as the convex hull of 4 vertices

```

`remove_constraint(i)`

Removes a constraint from `self`.

INPUT:

- `i` – index of the constraint to remove

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x, y = p[0], p[1]
sage: p.add_constraint(x + y, max=10)
sage: p.add_constraint(x - y, max=0)
sage: p.add_constraint(x, max=4)
sage: p.show()
Constraints:
  x_0 + x_1 <= 10.0
  x_0 - x_1 <= 0.0
  x_0 <= 4.0
  ...
sage: p.remove_constraint(1)
sage: p.show()
Constraints:

```

(continues on next page)

(continued from previous page)

```

x_0 + x_1 <= 10.0
x_0 <= 4.0
...
sage: p.number_of_constraints()
2

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x, y = p[Integer(0)], p[Integer(1)]
>>> p.add_constraint(x + y, max=Integer(10))
>>> p.add_constraint(x - y, max=Integer(0))
>>> p.add_constraint(x, max=Integer(4))
>>> p.show()
Constraints:
  x_0 + x_1 <= 10.0
  x_0 - x_1 <= 0.0
  x_0 <= 4.0
...
>>> p.remove_constraint(Integer(1))
>>> p.show()
Constraints:
  x_0 + x_1 <= 10.0
  x_0 <= 4.0
...
>>> p.number_of_constraints()
2

```

remove_constraints (*constraints*)

Remove several constraints.

INPUT:

- *constraints* – an iterable containing the indices of the rows to remove

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x, y = p[0], p[1]
sage: p.add_constraint(x + y, max=10)
sage: p.add_constraint(x - y, max=0)
sage: p.add_constraint(x, max=4)
sage: p.show()
Constraints:
  x_0 + x_1 <= 10.0
  x_0 - x_1 <= 0.0
  x_0 <= 4.0
...
sage: p.remove_constraints([0, 1])
sage: p.show()
Constraints:
  x_0 <= 4.0
...
sage: p.number_of_constraints()

```

(continues on next page)

(continued from previous page)

```

1
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x, y = p[Integer(0)], p[Integer(1)]
>>> p.add_constraint(x + y, max=Integer(10))
>>> p.add_constraint(x - y, max=Integer(0))
>>> p.add_constraint(x, max=Integer(4))
>>> p.show()
Constraints:
  x_0 + x_1 <= 10.0
  x_0 - x_1 <= 0.0
  x_0 <= 4.0
...
>>> p.remove_constraints([Integer(0), Integer(1)])
>>> p.show()
Constraints:
  x_0 <= 4.0
...
>>> p.number_of_constraints()
1

```

When checking for redundant constraints, make sure you remove only the constraints that were actually added. Problems could arise if you have a function that builds lps non-interactively, but it fails to check whether adding a constraint actually increases the number of constraints. The function might later try to remove constraints that are not actually there:

```

sage: p = MixedIntegerLinearProgram(check_redundant=True, solver='GLPK')
sage: x, y = p[0], p[1]
sage: p.add_constraint(x + y, max=10)
sage: for each in range(10):
...:     p.add_constraint(x - y, max=10)
sage: p.add_constraint(x, max=4)
sage: p.number_of_constraints()
3
sage: p.remove_constraints(range(1, 9))
Traceback (most recent call last):
...
IndexError: pop index out of range
sage: p.remove_constraint(1)
sage: p.number_of_constraints()
2

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(check_redundant=True, solver='GLPK')
>>> x, y = p[Integer(0)], p[Integer(1)]
>>> p.add_constraint(x + y, max=Integer(10))
>>> for each in range(Integer(10)):
...     p.add_constraint(x - y, max=Integer(10))
>>> p.add_constraint(x, max=Integer(4))
>>> p.number_of_constraints()
3

```

(continues on next page)

(continued from previous page)

```
>>> p.remove_constraints(range(Integer(1), Integer(9)))
Traceback (most recent call last):
...
IndexError: pop index out of range
>>> p.remove_constraint(Integer(1))
>>> p.number_of_constraints()
2
```

We should now be able to add the old constraint back in:

```
sage: for each in range(10):
....:     p.add_constraint(x - y, max=10)
sage: p.number_of_constraints()
3
```

```
>>> from sage.all import *
>>> for each in range(Integer(10)):
...     p.add_constraint(x - y, max=Integer(10))
>>> p.number_of_constraints()
3
```

set_binary(*ee*)

Set a variable or a MIPVariable as binary.

INPUT:

- *ee* – an instance of MIPVariable or one of its elements

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
```

With the following instruction, all the variables from *x* will be binary:

```
sage: p.set_binary(x)
sage: p.set_objective(x[0] + x[1])
sage: p.add_constraint(-3*x[0] + 2*x[1], max=2)
```

```
>>> from sage.all import *
>>> p.set_binary(x)
>>> p.set_objective(x[Integer(0)] + x[Integer(1)])
>>> p.add_constraint(-Integer(3)*x[Integer(0)] + Integer(2)*x[Integer(1)],
↳max=Integer(2))
```

It is still possible, though, to set one of these variables as integer while keeping the others as they are:

```
sage: p.set_integer(x[3])
```

```
>>> from sage.all import *
>>> p.set_integer(x[Integer(3)])
```

set_integer (*ee*)

Set a variable or a MIPVariable as integer.

INPUT:

- *ee* – an instance of MIPVariable or one of its elements

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
```

With the following instruction, all the variables from *x* will be integers:

```
sage: p.set_integer(x)
sage: p.set_objective(x[0] + x[1])
sage: p.add_constraint(-3*x[0] + 2*x[1], max=2)
```

```
>>> from sage.all import *
>>> p.set_integer(x)
>>> p.set_objective(x[Integer(0)] + x[Integer(1)])
>>> p.add_constraint(-Integer(3)*x[Integer(0)] + Integer(2)*x[Integer(1)],
↳max=Integer(2))
```

It is still possible, though, to set one of these variables as binary while keeping the others as they are:

```
sage: p.set_binary(x[3])
```

```
>>> from sage.all import *
>>> p.set_binary(x[Integer(3)])
```

set_max (*v*, *max*)

Set the maximum value of a variable.

INPUT:

- *v* – a variable
- *max* – the maximum value the variable can take; when *max*=None, the variable has no upper bound

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(nonnegative=True)
sage: p.set_objective(v[1])
sage: p.get_max(v[1])
sage: p.set_max(v[1], 6)
sage: p.get_max(v[1])
6.0
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(nonnegative=True)
>>> p.set_objective(v[Integer(1)])
>>> p.get_max(v[Integer(1)])
>>> p.set_max(v[Integer(1)], Integer(6))
>>> p.get_max(v[Integer(1)])
6.0
    
```

With a *MIPVariable* as an argument:

```

sage: vv = p.new_variable(real=True)
sage: p.get_max(vv)
sage: p.get_max(vv[0])
sage: p.set_max(vv, 5)
sage: p.get_max(vv[0])
5.0
sage: p.get_max(vv[9])
5.0
    
```

```

>>> from sage.all import *
>>> vv = p.new_variable(real=True)
>>> p.get_max(vv)
>>> p.get_max(vv[Integer(0)])
>>> p.set_max(vv, Integer(5))
>>> p.get_max(vv[Integer(0)])
5.0
>>> p.get_max(vv[Integer(9)])
5.0
    
```

`set_min(v, min)`

Set the minimum value of a variable.

INPUT:

- `v` – a variable
- `min` – the minimum value the variable can take; when `min=None`, the variable has no lower bound

See also

- `get_min()` – get the minimum value of a variable

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(nonnegative=True)
sage: p.set_objective(v[1])
sage: p.get_min(v[1])
0.0
sage: p.set_min(v[1], 6)
sage: p.get_min(v[1])
6.0
    
```

(continues on next page)

(continued from previous page)

```
sage: p.set_min(v[1], None)
sage: p.get_min(v[1])
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(nonnegative=True)
>>> p.set_objective(v[Integer(1)])
>>> p.get_min(v[Integer(1)])
0.0
>>> p.set_min(v[Integer(1)], Integer(6))
>>> p.get_min(v[Integer(1)])
6.0
>>> p.set_min(v[Integer(1)], None)
>>> p.get_min(v[Integer(1)])
```

With a *MIPVariable* as an argument:

```
sage: vv = p.new_variable(real=True)
sage: p.get_min(vv)
sage: p.get_min(vv[0])
sage: p.set_min(vv, 5)
sage: p.get_min(vv[0])
5.0
sage: p.get_min(vv[9])
5.0
```

```
>>> from sage.all import *
>>> vv = p.new_variable(real=True)
>>> p.get_min(vv)
>>> p.get_min(vv[Integer(0)])
>>> p.set_min(vv, Integer(5))
>>> p.get_min(vv[Integer(0)])
5.0
>>> p.get_min(vv[Integer(9)])
5.0
```

set_objective(*obj*)

Set the objective of the *MixedIntegerLinearProgram*.

INPUT:

- *obj* – a linear function to be optimized (can also be set to *None* or 0 or any number when just looking for a feasible solution)

EXAMPLES:

Let's solve the following linear program:

```
Maximize:
  x + 5 * y
Constraints:
  x + 0.2 y      <= 4
  1.5 * x + 3 * y <= 4
Variables:
```

(continues on next page)

(continued from previous page)

```
x is Real (min = 0, max = None)
y is Real (min = 0, max = None)
```

This linear program can be solved as follows:

```
sage: p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[1] + 5*x[2])
sage: p.add_constraint(x[1] + 2/10*x[2], max=4)
sage: p.add_constraint(1.5*x[1] + 3*x[2], max=4)
sage: round(p.solve(), 5)
6.66667
sage: p.set_objective(None)
sage: _ = p.solve()
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(1)] + Integer(5)*x[Integer(2)])
>>> p.add_constraint(x[Integer(1)] + Integer(2)/Integer(10)*x[Integer(2)],
↳max=Integer(4))
>>> p.add_constraint(RealNumber('1.5')*x[Integer(1)] +
↳Integer(3)*x[Integer(2)], max=Integer(4))
>>> round(p.solve(), Integer(5))
6.66667
>>> p.set_objective(None)
>>> _ = p.solve()
```

set_problem_name (*name*)

Set the name of the `MixedIntegerLinearProgram`.

INPUT:

- *name* – string representing the name of the `MixedIntegerLinearProgram`

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.set_problem_name("Test program")
sage: p
Mixed Integer Program "Test program" (no objective, 0 variables, 0
↳constraints)
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.set_problem_name("Test program")
>>> p
Mixed Integer Program "Test program" (no objective, 0 variables, 0
↳constraints)
```

set_real (*ee*)

Set a variable or a `MIPVariable` as real.

INPUT:

- `ee` – an instance of `MIPVariable` or one of its elements

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
```

With the following instruction, all the variables from `x` will be real:

```
sage: p.set_real(x)
sage: p.set_objective(x[0] + x[1])
sage: p.add_constraint(-3*x[0] + 2*x[1], max=2)
```

It is still possible, though, to set one of these variables as binary while keeping the others as they are::

```
sage: p.set_binary(x[3])
```

show()

Displays the `MixedIntegerLinearProgram` in a human-readable way.

EXAMPLES:

When constraints and variables have names

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x = p.new_variable(name='Hey')
sage: p.set_objective(x[1] + x[2])
sage: p.add_constraint(-3*x[1] + 2*x[2], max=2, name='Constraint_1')
sage: p.show()
```

```
Maximization:
  Hey[1] + Hey[2]
Constraints:
  Constraint_1: -3.0 Hey[1] + 2.0 Hey[2] <= 2.0
Variables:
  Hey[1] = x_0 is a continuous variable (min=-oo, max=+oo)
  Hey[2] = x_1 is a continuous variable (min=-oo, max=+oo)
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x = p.new_variable(name='Hey')
>>> p.set_objective(x[Integer(1)] + x[Integer(2)])
>>> p.add_constraint(-Integer(3)*x[Integer(1)] + Integer(2)*x[Integer(2)],
↳max=Integer(2), name='Constraint_1')
>>> p.show()
```

```
Maximization:
  Hey[1] + Hey[2]
Constraints:
  Constraint_1: -3.0 Hey[1] + 2.0 Hey[2] <= 2.0
Variables:
```

(continues on next page)

(continued from previous page)

```

Hey[1] = x_0 is a continuous variable (min=-oo, max=+oo)
Hey[2] = x_1 is a continuous variable (min=-oo, max=+oo)

```

Without any names

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[1] + x[2])
sage: p.add_constraint(-3*x[1] + 2*x[2], max=2)
sage: p.show()
Maximization:
  x_0 + x_1
Constraints:
  -3.0 x_0 + 2.0 x_1 <= 2.0
Variables:
  x_0 is a continuous variable (min=0.0, max=+oo)
  x_1 is a continuous variable (min=0.0, max=+oo)

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(1)] + x[Integer(2)])
>>> p.add_constraint(-Integer(3)*x[Integer(1)] + Integer(2)*x[Integer(2)],
↳max=Integer(2))
>>> p.show()
Maximization:
  x_0 + x_1
Constraints:
  -3.0 x_0 + 2.0 x_1 <= 2.0
Variables:
  x_0 is a continuous variable (min=0.0, max=+oo)
  x_1 is a continuous variable (min=0.0, max=+oo)

```

With Q coefficients:

```

sage: p = MixedIntegerLinearProgram(solver='ppl')
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[1] + 1/2*x[2])
sage: p.add_constraint(-3/5*x[1] + 2/7*x[2], max=2/5)
sage: p.show()
Maximization:
  x_0 + 1/2 x_1
Constraints:
  constraint_0: -3/5 x_0 + 2/7 x_1 <= 2/5
Variables:
  x_0 is a continuous variable (min=0, max=+oo)
  x_1 is a continuous variable (min=0, max=+oo)

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='ppl')
>>> x = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(1)] + Integer(1)/Integer(2)*x[Integer(2)])

```

(continues on next page)

(continued from previous page)

```

>>> p.add_constraint(-Integer(3)/Integer(5)*x[Integer(1)] + Integer(2)/
↳Integer(7)*x[Integer(2)], max=Integer(2)/Integer(5))
>>> p.show()
Maximization:
  x_0 + 1/2 x_1
Constraints:
  constraint_0: -3/5 x_0 + 2/7 x_1 <= 2/5
Variables:
  x_0 is a continuous variable (min=0, max=+oo)
  x_1 is a continuous variable (min=0, max=+oo)

```

With a constant term in the objective:

```

sage: p = MixedIntegerLinearProgram(solver='ppl')
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[0] + 42)
sage: p.show()
Maximization:
  x_0 + 42
Constraints:
Variables:
  x_0 is a continuous variable (min=0, max=+oo)

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='ppl')
>>> x = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(0)] + Integer(42))
>>> p.show()
Maximization:
  x_0 + 42
Constraints:
Variables:
  x_0 is a continuous variable (min=0, max=+oo)

```

solve (*log=None, objective_only=False*)

Solve the `MixedIntegerLinearProgram`.

INPUT:

- `log` – integer (default: `None`); the verbosity level. Indicates whether progress should be printed during computation. The solver is initialized to report no progress.
- `objective_only` – boolean:
 - When set to `True`, only the objective function is returned.
 - When set to `False` (default), the optimal numerical values are stored (takes computational time).

OUTPUT: the optimal value taken by the objective function

Warning

By default, no additional assumption is made on the domain of an LP variable. See `set_min()` and `set_max()` to change it.

EXAMPLES:

Consider the following linear program:

```
Maximize:
  x + 5 * y
Constraints:
  x + 0.2 y      <= 4
  1.5 * x + 3 * y <= 4
Variables:
  x is Real (min = 0, max = None)
  y is Real (min = 0, max = None)
```

This linear program can be solved as follows:

```
sage: p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[1] + 5*x[2])
sage: p.add_constraint(x[1] + 0.2*x[2], max=4)
sage: p.add_constraint(1.5*x[1] + 3*x[2], max=4)
sage: round(p.solve(),6)
6.666667
sage: x = p.get_values(x)
sage: round(x[1],6) # abs tol 1e-15
0.0
sage: round(x[2],6)
1.333333
```

Computation of a maximum stable set in Petersen's graph::

```
sage: # needs sage.graphs
sage: g = graphs.PetersenGraph()
sage: p = MixedIntegerLinearProgram(maximization=True, solver='GLPK')
sage: b = p.new_variable(nonnegative=True)
sage: p.set_objective(sum([b[v] for v in g]))
sage: for (u,v) in g.edges(sort=False, labels=None):
....:     p.add_constraint(b[u] + b[v], max=1)
sage: p.set_binary(b)
sage: p.solve(objective_only=True)
4.0
```

Constraints in the objective function are respected:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x, y = p[0], p[1]
sage: p.add_constraint(2*x + 3*y, max=6)
sage: p.add_constraint(3*x + 2*y, max=6)
sage: p.set_objective(x + y + 7)
sage: p.set_integer(x); p.set_integer(y)
sage: p.solve()
9.0
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
```

(continues on next page)

(continued from previous page)

```

>>> x, y = p[Integer(0)], p[Integer(1)]
>>> p.add_constraint(Integer(2)*x + Integer(3)*y, max=Integer(6))
>>> p.add_constraint(Integer(3)*x + Integer(2)*y, max=Integer(6))
>>> p.set_objective(x + y + Integer(7))
>>> p.set_integer(x); p.set_integer(y)
>>> p.solve()
9.0

```

solver_parameter (*name*, *value=None*)

Return or define a solver parameter.

The solver parameters are by essence solver-specific, which means their meaning heavily depends on the solver used.

(If you do not know which solver you are using, then you use GLPK).

Aliases:

Very common parameters have aliases making them solver-independent. For example, the following:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.solver_parameter("timelimit", 60)

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.solver_parameter("timelimit", Integer(60))

```

Sets the solver to stop its computations after 60 seconds, and works with GLPK, CPLEX, SCIP, and Gurobi.

- 'timelimit' – defines the maximum time spent on a computation (measured in seconds)

Another example is the 'logfile' parameter, which is used to specify the file in which computation logs are recorded. By default, the logs are not recorded, and we can disable this feature providing an empty filename. This is currently working with CPLEX and Gurobi:

```

sage: # optional - cplex
sage: p = MixedIntegerLinearProgram(solver='CPLEX')
sage: p.solver_parameter("logfile")
''

sage: p.solver_parameter("logfile", "/dev/null")
sage: p.solver_parameter("logfile")
'/dev/null'

sage: p.solver_parameter("logfile", '')
sage: p.solver_parameter("logfile")
''

```

```

>>> from sage.all import *
>>> # optional - cplex
>>> p = MixedIntegerLinearProgram(solver='CPLEX')
>>> p.solver_parameter("logfile")
''

>>> p.solver_parameter("logfile", "/dev/null")
>>> p.solver_parameter("logfile")
'/dev/null'
>>> p.solver_parameter("logfile", '')

```

(continues on next page)

(continued from previous page)

```
>>> p.solver_parameter("logfile")
''
```

Solver-specific parameters:

- **GLPK** : We have implemented very close to comprehensive coverage of the GLPK solver parameters for the simplex and integer optimization methods. For details, see the documentation of *GLPKBackend.solver_parameter*.
- **CPLEX's** parameters are identified by a string. Their list is available on ILOG's website.

The command

```
sage: p = MixedIntegerLinearProgram(solver='CPLEX') # optional - CPLEX
sage: p.solver_parameter("CPX_PARAM_TILIM", 60) # optional - CPLEX
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='CPLEX') # optional - CPLEX
>>> p.solver_parameter("CPX_PARAM_TILIM", Integer(60)) # optional - CPLEX
↪ CPLEX
```

works as intended.

- **Gurobi's** parameters should all be available through this method. Their list is available on Gurobi's website <http://www.gurobi.com/documentation/5.5/reference-manual/node798>.

SCIP's parameter can be found here: <http://scip.zib.de/doc-5.0.1/html/PARAMETERS.php>.

INPUT:

- `name` – string; the parameter
- `value` – the parameter's value if it is to be defined, or `None` (default) to obtain its current value

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.solver_parameter("timelimit", 60)
sage: p.solver_parameter("timelimit")
60.0
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.solver_parameter("timelimit", Integer(60))
>>> p.solver_parameter("timelimit")
60.0
```

sum(*L*)

Efficiently compute the sum of a sequence of *LinearFunction* elements

INPUT:

- `mip` – the *MixedIntegerLinearProgram* parent
- `L` – list of *LinearFunction* instances

Note

The use of the regular `sum` function is not recommended as it is much less efficient than this one

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: v = p.new_variable(nonnegative=True)
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> v = p.new_variable(nonnegative=True)
```

The following command:

```
sage: s = p.sum(v[i] for i in range(90))
```

```
>>> from sage.all import *
>>> s = p.sum(v[i] for i in range(Integer(90)))
```

is much more efficient than:

```
sage: s = sum(v[i] for i in range(90))
```

```
>>> from sage.all import *
>>> s = sum(v[i] for i in range(Integer(90)))
```

`write_lp(filename)`

Write the linear program as a LP file.

This function export the problem as a LP file.

INPUT:

- `filename` – the file in which you want the problem to be written

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[1] + x[2])
sage: p.add_constraint(-3*x[1] + 2*x[2], max=2)
sage: import tempfile
sage: with tempfile.NamedTemporaryFile(suffix='.lp') as f:
....:     p.write_lp(f.name)
Writing problem data to ...
9 lines were written
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(1)] + x[Integer(2)])
>>> p.add_constraint(-Integer(3)*x[Integer(1)] + Integer(2)*x[Integer(2)],
↳max=Integer(2))
```

(continues on next page)

(continued from previous page)

```
>>> import tempfile
>>> with tempfile.NamedTemporaryFile(suffix='.lp') as f:
...     p.write_lp(f.name)
Writing problem data to ...
9 lines were written
```

For more information about the LP file format : <http://lpsolve.sourceforge.net/5.5/lp-format.htm>

write_mps (*filename*, *modern=True*)

Write the linear program as a MPS file.

This function export the problem as a MPS file.

INPUT:

- *filename* – the file in which you want the problem to be written
- *modern* – lets you choose between Fixed MPS and Free MPS:
 - True – outputs the problem in Free MPS
 - False – outputs the problem in Fixed MPS

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[1] + x[2])
sage: p.add_constraint(-3*x[1] + 2*x[2], max=2, name='OneConstraint')
sage: import tempfile
sage: with tempfile.NamedTemporaryFile(suffix='.mps') as f:
....:     p.write_mps(f.name)
Writing problem data to ...
17 records were written
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(1)] + x[Integer(2)])
>>> p.add_constraint(-Integer(3)*x[Integer(1)] + Integer(2)*x[Integer(2)],
↳max=Integer(2), name='OneConstraint')
>>> import tempfile
>>> with tempfile.NamedTemporaryFile(suffix='.mps') as f:
...     p.write_mps(f.name)
Writing problem data to ...
17 records were written
```

For information about the MPS file format, see [Wikipedia article MPS_\(format\)](#)

SEMIDEFINITE PROGRAMMING

A semidefinite program (SDP) is an optimization problem ([Wikipedia article Optimization_\(mathematics\)>](#)) of the following form

$$\begin{aligned} \min \sum_{i,j=1}^n C_{ij} X_{ij} & \quad (\text{Dual problem}) \\ \text{Subject to: } \sum_{i,j=1}^n A_{ijk} X_{ij} = b_k, & \quad k = 1 \dots m \\ X \succeq 0 & \end{aligned}$$

where the X_{ij} , $1 \leq i, j \leq n$ are n^2 variables satisfying the symmetry conditions $x_{ij} = x_{ji}$ for all i, j , the $C_{ij} = C_{ji}$, $A_{ijk} = A_{kji}$ and b_k are real coefficients, and X is positive semidefinite, i.e., all the eigenvalues of X are nonnegative. The closely related dual problem of this one is the following, where we denote by A_k the matrix (A_{kij}) and by C the matrix (C_{ij}) ,

$$\begin{aligned} \max \sum_k b_k x_k & \quad (\text{Primal problem}) \\ \text{Subject to: } \sum_k x_k A_k \preceq C. & \end{aligned}$$

Here (x_1, \dots, x_m) is a vector of scalar variables. A wide variety of problems in optimization can be formulated in one of these two standard forms. Then, solvers are able to calculate an approximation to a solution. Here we refer to the latter problem as primal, and to the former problem as dual. The optimal value of the dual is always at least the optimal value of the primal, and usually (although not always) they are equal.

For instance, suppose you want to maximize $x_1 - x_0$ subject to

$$\begin{pmatrix} 1 & 2 \\ 2 & 3 \end{pmatrix} x_0 + \begin{pmatrix} 3 & 4 \\ 4 & 5 \end{pmatrix} x_1 \preceq \begin{pmatrix} 5 & 6 \\ 6 & 7 \end{pmatrix}, \quad \begin{pmatrix} 1 & 1 \\ 1 & 1 \end{pmatrix} x_0 + \begin{pmatrix} 2 & 2 \\ 2 & 2 \end{pmatrix} x_1 \preceq \begin{pmatrix} 3 & 3 \\ 3 & 3 \end{pmatrix}, \quad x_0 \geq 0, x_1 \geq 0.$$

An SDP can give you an answer to the problem above. Here is how it's done:

1. You have to create an instance of `SemidefiniteProgram`.
2. Create a dictionary x of integer variables via `new_variable()`, for example doing `x = p.new_variable()` if `p` is the name of the SDP instance.
3. Add those two matrix inequalities as inequality constraints via `add_constraint()`.
4. Add another matrix inequality to specify nonnegativity of x .
5. Specify the objective function via `set_objective()`. In our case it is $x_1 - x_0$. If it is a pure constraint satisfaction problem, specify it as `None`.
6. To check if everything is set up correctly, you can print the problem via `show`.

7. *Solve* it and print the solution.

The following example shows all these steps:

```

sage: p = SemidefiniteProgram()
sage: x = p.new_variable()
sage: p.set_objective(x[1] - x[0])
sage: a1 = matrix([[1, 2.], [2., 3.]])
sage: a2 = matrix([[3, 4.], [4., 5.]])
sage: a3 = matrix([[5, 6.], [6., 7.]])
sage: b1 = matrix([[1, 1.], [1., 1.]])
sage: b2 = matrix([[2, 2.], [2., 2.]])
sage: b3 = matrix([[3, 3.], [3., 3.]])
sage: c1 = matrix([[1.0, 0], [0, 0]], sparse=True)
sage: c2 = matrix([[0.0, 0], [0, 1]], sparse=True)
sage: p.add_constraint(a1*x[0] + a2*x[1] <= a3)
sage: p.add_constraint(b1*x[0] + b2*x[1] <= b3)
sage: p.add_constraint(c1*x[0] + c2*x[1] >= matrix.zero(2, 2, sparse=True))

sage: # needs cvxopt
sage: p.solver_parameter("show_progress", True)
sage: opt = p.solve()
      pcost      dcost      gap      pres      dres      k/t
0: ...
...
Optimal solution found.
sage: print('Objective Value: {}'.format(N(opt, 3)))
Objective Value: 1.0
sage: [N(x, 3) for x in sorted(p.get_values(x).values())]
[3.0e-8, 1.0]
sage: p.show()
Maximization:
  x_0 - x_1
Constraints:
  constraint_0: [3.0 4.0][4.0 5.0]x_0 + [1.0 2.0][2.0 3.0]x_1 <= [5.0 6.0][6.0 7.0]
  constraint_1: [2.0 2.0][2.0 2.0]x_0 + [1.0 1.0][1.0 1.0]x_1 <= [3.0 3.0][3.0 3.0]
  constraint_2: [ 0.0  0.0][ 0.0 -1.0]x_0 + [-1.0  0.0][ 0.0  0.0]x_1 <= [0 0][0 0]
Variables:
  x_0,  x_1
    
```

```

>>> from sage.all import *
>>> p = SemidefiniteProgram()
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(1)] - x[Integer(0)])
>>> a1 = matrix([[Integer(1), RealNumber('2.']], [RealNumber('2.'], RealNumber('3.
↵)])
>>> a2 = matrix([[Integer(3), RealNumber('4.']], [RealNumber('4.'], RealNumber('5.
↵)])
>>> a3 = matrix([[Integer(5), RealNumber('6.']], [RealNumber('6.'], RealNumber('7.
↵)])
>>> b1 = matrix([[Integer(1), RealNumber('1.']], [RealNumber('1.'], RealNumber('1.
↵)])
>>> b2 = matrix([[Integer(2), RealNumber('2.']], [RealNumber('2.'], RealNumber('2.
↵)])
    
```

(continues on next page)

(continued from previous page)

```

>>> b3 = matrix([[Integer(3), RealNumber('3.')] , [RealNumber('3. '), RealNumber('3.
↳')]])
>>> c1 = matrix([[RealNumber('1.0'), Integer(0)], [Integer(0), Integer(0)], sparse=True)
>>> c2 = matrix([[RealNumber('0.0'), Integer(0)], [Integer(0), Integer(1)], sparse=True)
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] <= a3)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] <= b3)
>>> p.add_constraint(c1*x[Integer(0)] + c2*x[Integer(1)] >= matrix.zero(Integer(2),
↳Integer(2), sparse=True))

>>> # needs cvxopt
>>> p.solver_parameter("show_progress", True)
>>> opt = p.solve()
      pcost      dcost      gap      pres      dres      k/t
0: ...
...
Optimal solution found.
>>> print('Objective Value: {}'.format(N(opt, Integer(3))))
Objective Value: 1.0
>>> [N(x, Integer(3)) for x in sorted(p.get_values(x).values())]
[3.0e-8, 1.0]
>>> p.show()
Maximization:
  x_0 - x_1
Constraints:
  constraint_0: [3.0 4.0][4.0 5.0]x_0 + [1.0 2.0][2.0 3.0]x_1 <= [5.0 6.0][6.0 7.0]
  constraint_1: [2.0 2.0][2.0 2.0]x_0 + [1.0 1.0][1.0 1.0]x_1 <= [3.0 3.0][3.0 3.0]
  constraint_2: [ 0.0  0.0][ 0.0 -1.0]x_0 + [-1.0  0.0][ 0.0  0.0]x_1 <= [0 0][0 0]
Variables:
  x_0, x_1

```

Most solvers, e.g. the default Sage SDP solver CVXOPT, solve simultaneously the pair of primal and dual problems. Thus we can get the optimizer X of the dual problem as follows, as diagonal blocks, one per each constraint, via `dual_variable()`. E.g.:

```

sage: p.dual_variable(1) # rel tol 2e-03 #_
↳needs cvxopt
[ 85555.0 -85555.0]
[-85555.0  85555.0]

```

```

>>> from sage.all import *
>>> p.dual_variable(Integer(1)) # rel tol 2e-03 #_
↳ # needs cvxopt
[ 85555.0 -85555.0]
[-85555.0  85555.0]

```

We can see that the optimal value of the dual is equal (up to numerical noise) to `opt`:

```

sage: opt - ((p.dual_variable(0)*a3).trace() # tol 8e-08 #_
↳needs cvxopt
.....: + (p.dual_variable(1)*b3).trace())
0.0

```

```
>>> from sage.all import *
>>> opt - ((p.dual_variable(Integer(0))*a3).trace() # tol 8e-08
↳ # needs cvxopt
... + (p.dual_variable(Integer(1))*b3).trace())
0.0
```

Dual variable blocks at optimality are orthogonal to “slack variables”, that is, matrices $C - \sum_k x_k A_k$, cf. (Primal problem) above, available via `slack()`. E.g.:

```
sage: (p.slack(0)*p.dual_variable(0)).trace() # tol 2e-07 #_
↳ needs cvxopt
0.0
```

```
>>> from sage.all import *
>>> (p.slack(Integer(0))*p.dual_variable(Integer(0))).trace() # tol 2e-07
↳ # needs cvxopt
0.0
```

More interesting example, the Lovasz theta of the 7-gon:

```
sage: # needs sage.graphs
sage: c = graphs.CycleGraph(7)
sage: c2 = c.distance_graph(2).adjacency_matrix()
sage: c3 = c.distance_graph(3).adjacency_matrix()
sage: p.<y> = SemidefiniteProgram()
sage: p.add_constraint((1/7)*matrix.identity(7)>=-y[0]*c2-y[1]*c3)
sage: p.set_objective(y[0]*(c2**2).trace()+y[1]*(c3**2).trace())
sage: x = p.solve(); x + 1 #_
↳ needs cvxopt
3.31766...
```

```
>>> from sage.all import *
>>> # needs sage.graphs
>>> c = graphs.CycleGraph(Integer(7))
>>> c2 = c.distance_graph(Integer(2)).adjacency_matrix()
>>> c3 = c.distance_graph(Integer(3)).adjacency_matrix()
>>> p = SemidefiniteProgram(names=('y',)); (y,) = p._first_ngens(1)
>>> p.add_constraint((Integer(1)/Integer(7))*matrix.identity(Integer(7))>=-
↳ y[Integer(0)]*c2-y[Integer(1)]*c3)
>>> p.set_objective(y[Integer(0)]*(c2**Integer(2)).
↳ trace()+y[Integer(1)]*(c3**Integer(2)).trace())
>>> x = p.solve(); x + Integer(1) #_
↳ # needs cvxopt
3.31766...
```

Unlike in the previous example, the slack variable is very far from 0:

```
sage: p.slack(0).trace() # tol 1e-14 #_
↳ needs cvxopt sage.graphs
1.0
```

```
>>> from sage.all import *
>>> p.slack(Integer(0)).trace() # tol 1e-14 #_
```

(continues on next page)

(continued from previous page)

```
→ # needs cvxopt sage.graphs
1.0
```

The default CVXOPT backend computes with the Real Double Field, for example:

```
sage: # needs cvxopt
sage: p = SemidefiniteProgram(solver='cvxopt')
sage: p.base_ring()
Real Double Field
sage: x = p.new_variable()
sage: 0.5 + 3/2*x[1]
0.5 + 1.5*x_0
```

```
>>> from sage.all import *
>>> # needs cvxopt
>>> p = SemidefiniteProgram(solver='cvxopt')
>>> p.base_ring()
Real Double Field
>>> x = p.new_variable()
>>> RealNumber('0.5') + Integer(3)/Integer(2)*x[Integer(1)]
0.5 + 1.5*x_0
```

For representing an SDP with exact data, there is another backend:

```
sage: from sage.numerical.backends.matrix_sdp_backend import MatrixSDPBackend
sage: p = SemidefiniteProgram(solver=MatrixSDPBackend, base_ring=QQ)
sage: p.base_ring()
Rational Field
sage: x = p.new_variable()
sage: 1/2 + 3/2 * x[1]
1/2 + 3/2*x_0
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.matrix_sdp_backend import MatrixSDPBackend
>>> p = SemidefiniteProgram(solver=MatrixSDPBackend, base_ring=QQ)
>>> p.base_ring()
Rational Field
>>> x = p.new_variable()
>>> Integer(1)/Integer(2) + Integer(3)/Integer(2) * x[Integer(1)]
1/2 + 3/2*x_0
```

3.1 Linear Variables and Expressions

To make your code more readable, you can construct `SDPVariable` objects that can be arbitrarily named and indexed. Internally, this is then translated back to the x_i variables. For example:

```
sage: sdp.<a,b> = SemidefiniteProgram()
sage: a
SDPVariable
sage: 5 + a[1] + 2*b[3]
5 + x_0 + 2*x_1
```

```

>>> from sage.all import *
>>> sdp = SemidefiniteProgram(names=('a', 'b',)); (a, b,) = sdp._first_ngens(2)
>>> a
SDPVariable
>>> Integer(5) + a[Integer(1)] + Integer(2)*b[Integer(3)]
5 + x_0 + 2*x_1

```

Indices can be any object, not necessarily integers. Multi-indices are also allowed:

```

sage: a[4, 'string', QQ]
x_2
sage: a[4, 'string', QQ] - 7*b[2]
x_2 - 7*x_3
sage: sdp.show()
Maximization:

Constraints:
Variables:
  a[1], b[3], a[(4, 'string', Rational Field)], b[2]

```

```

>>> from sage.all import *
>>> a[Integer(4), 'string', QQ]
x_2
>>> a[Integer(4), 'string', QQ] - Integer(7)*b[Integer(2)]
x_2 - 7*x_3
>>> sdp.show()
Maximization:
<BLANKLINE>
Constraints:
Variables:
  a[1], b[3], a[(4, 'string', Rational Field)], b[2]

```

3.2 Index of functions and methods

Below are listed the methods of *SemidefiniteProgram*. This module also implements the *SDPSolverException* exception, as well as the *SDPVariable* class.

| | |
|--|---|
| <code>add_constraint()</code> | Add a constraint to the <code>SemidefiniteProgram</code> |
| <code>base_ring()</code> | Return the base ring |
| <code>dual_variable()</code> | Return optimal dual variable block |
| <code>get_backend()</code> | Return the backend instance used |
| <code>get_values()</code> | Return values found by the previous call to <code>solve()</code> |
| <code>linear_constraints_parent()</code> | Return the parent for all linear constraints |
| <code>linear_function()</code> | Construct a new linear function |
| <code>linear_functions_parent()</code> | Return the parent for all linear functions |
| <code>new_variable()</code> | Return an instance of <code>SDPVariable</code> associated to the <code>SemidefiniteProgram</code> |
| <code>number_of_constraints()</code> | Return the number of constraints assigned so far |
| <code>number_of_variables()</code> | Return the number of variables used so far |
| <code>set_objective()</code> | Set the objective of the <code>SemidefiniteProgram</code> |
| <code>set_problem_name()</code> | Set the name of the <code>SemidefiniteProgram</code> |
| <code>slack()</code> | Return the slack variable block at the optimum |
| <code>show()</code> | Display the <code>SemidefiniteProgram</code> in a human-readable way |
| <code>solve()</code> | Solve the <code>SemidefiniteProgram</code> |
| <code>solver_parameter()</code> | Return or define a solver parameter |
| <code>sum()</code> | Efficiently compute the sum of a sequence of <code>LinearFunction</code> elements |

AUTHORS:

- Ingolfur Edvardsson (2014/08): added extension for exact computation
- Dima Pasechnik (2014-) : supervision, minor fixes, duality

exception `sage.numerical.sdp.SDPSolverException`Bases: `RuntimeError`

Exception raised when the solver fails.

`SDPSolverException` is the exception raised when the solver fails.**EXAMPLES:**

```
sage: from sage.numerical.sdp import SDPSolverException
sage: SDPSolverException("Error")
SDPSolverException('Error'...)
```

```
>>> from sage.all import *
>>> from sage.numerical.sdp import SDPSolverException
>>> SDPSolverException("Error")
SDPSolverException('Error'...)
```

class `sage.numerical.sdp.SDPVariable`Bases: `Element``SDPVariable` is a variable used by the class `SemidefiniteProgram`.**Warning**You should not instantiate this class directly. Instead, use `SemidefiniteProgram.new_variable()`.

items()

Return the pairs (keys,value) contained in the dictionary.

EXAMPLES:

```
sage: p = SemidefiniteProgram()
sage: v = p.new_variable()
sage: p.set_objective(v[0] + v[1])
sage: sorted(v.items())
[(0, x_0), (1, x_1)]
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram()
>>> v = p.new_variable()
>>> p.set_objective(v[Integer(0)] + v[Integer(1)])
>>> sorted(v.items())
[(0, x_0), (1, x_1)]
```

keys()

Return the keys already defined in the dictionary.

EXAMPLES:

```
sage: p = SemidefiniteProgram()
sage: v = p.new_variable()
sage: p.set_objective(v[0] + v[1])
sage: sorted(v.keys())
[0, 1]
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram()
>>> v = p.new_variable()
>>> p.set_objective(v[Integer(0)] + v[Integer(1)])
>>> sorted(v.keys())
[0, 1]
```

values()

Return the symbolic variables associated to the current dictionary.

EXAMPLES:

```
sage: p = SemidefiniteProgram()
sage: v = p.new_variable()
sage: p.set_objective(v[0] + v[1])
sage: sorted(v.values(), key=str)
[x_0, x_1]
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram()
>>> v = p.new_variable()
>>> p.set_objective(v[Integer(0)] + v[Integer(1)])
>>> sorted(v.values(), key=str)
[x_0, x_1]
```

class sage.numerical.sdp.SDPVariableParent

Bases: Parent

Parent for *SDPVariable*.

Warning

This class is for internal use. You should not instantiate it yourself. Use *SemidefiniteProgram.new_variable()* to generate sdp variables.

Element

alias of *SDPVariable*

class sage.numerical.sdp.SemidefiniteProgram

Bases: SageObject

The *SemidefiniteProgram* class is the link between Sage, semidefinite programming (SDP) and semidefinite programming solvers.

A Semidefinite Programming (SDP) consists of variables, linear constraints on these variables, and an objective function which is to be maximised or minimised under these constraints.

See the [Wikipedia article Semidefinite_programming](#) for further information on semidefinite programming, and the *SDP module* for its use in Sage.

INPUT:

- `solver` – selects a solver:
 - `CVXOPT` (`solver="CVXOPT"`). See the [CVXOPT website](#).
 - If `solver=None` (default), the default solver is used (see `default_sdp_solver()`)
- `maximization`
 - When set to `True` (default), the *SemidefiniteProgram* is defined as a maximization.
 - When set to `False`, the *SemidefiniteProgram* is defined as a minimization.

See also

- `default_sdp_solver()` – returns/sets the default SDP solver

EXAMPLES:

Computation of a basic Semidefinite Program:

```
sage: p = SemidefiniteProgram(maximization=False)
sage: x = p.new_variable()
sage: p.set_objective(x[0] - x[1])
sage: a1 = matrix([[1, 2.], [2., 3.]])
sage: a2 = matrix([[3, 4.], [4., 5.]])
sage: a3 = matrix([[5, 6.], [6., 7.]])
sage: b1 = matrix([[1, 1.], [1., 1.]])
sage: b2 = matrix([[2, 2.], [2., 2.]])
sage: b3 = matrix([[3, 3.], [3., 3.]])
sage: p.add_constraint(a1*x[0] + a2*x[1] <= a3)
```

(continues on next page)

(continued from previous page)

```
sage: p.add_constraint(b1*x[0] + b2*x[1] <= b3)
sage: N(p.solve(), 2) #_
↳needs cvxopt
-3.0
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram(maximization=False)
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(0)] - x[Integer(1)])
>>> a1 = matrix([[Integer(1), RealNumber('2.']], [RealNumber('2.'], RealNumber('3.
↳'])]])
>>> a2 = matrix([[Integer(3), RealNumber('4.']], [RealNumber('4.'], RealNumber('5.
↳'])]])
>>> a3 = matrix([[Integer(5), RealNumber('6.']], [RealNumber('6.'], RealNumber('7.
↳'])]])
>>> b1 = matrix([[Integer(1), RealNumber('1.']], [RealNumber('1.'], RealNumber('1.
↳'])]])
>>> b2 = matrix([[Integer(2), RealNumber('2.']], [RealNumber('2.'], RealNumber('2.
↳'])]])
>>> b3 = matrix([[Integer(3), RealNumber('3.']], [RealNumber('3.'], RealNumber('3.
↳'])]])
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] <= a3)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] <= b3)
>>> N(p.solve(), Integer(2)) #_
↳ # needs cvxopt
-3.0
```

add_constraint (*linear_function*, *name=None*)

Add a constraint to the SemidefiniteProgram.

INPUT:

- *linear_function* – two different types of arguments are possible:
 - A linear function. In this case, arguments `min` or `max` have to be specified.
 - A linear constraint of the form $A \leq B$, $A \geq B$, $A \leq B \leq C$, $A \geq B \geq C$ or $A == B$. In this case, arguments `min` and `max` will be ignored.
- *name* – a name for the constraint

EXAMPLES:

Let's solve the following semidefinite program:

$$\begin{array}{ll} \text{maximize} & x + 5y \\ \text{subject to} & \begin{pmatrix} 1 & 2 \\ 2 & 3 \end{pmatrix} x + \begin{pmatrix} 1 & 1 \\ 1 & 1 \end{pmatrix} y \preceq \begin{pmatrix} 1 & -1 \\ -1 & 1 \end{pmatrix} \end{array}$$

This SDP can be solved as follows:

```
sage: p = SemidefiniteProgram(maximization=True)
sage: x = p.new_variable()
sage: p.set_objective(x[1] + 5*x[2])
sage: a1 = matrix([[1,2],[2,3]])
```

(continues on next page)

(continued from previous page)

```

sage: a2 = matrix([[1,1],[1,1]])
sage: a3 = matrix([[1,-1],[-1,1]])
sage: p.add_constraint(a1*x[1] + a2*x[2] <= a3)
sage: N(p.solve(), digits=3) #_
↳needs cvxopt
16.2

```

```

>>> from sage.all import *
>>> p = SemidefiniteProgram(maximization=True)
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(1)] + Integer(5)*x[Integer(2)])
>>> a1 = matrix([[Integer(1), Integer(2)], [Integer(2), Integer(3)]])
>>> a2 = matrix([[Integer(1), Integer(1)], [Integer(1), Integer(1)]])
>>> a3 = matrix([[Integer(1), -Integer(1)], [-Integer(1), Integer(1)]])
>>> p.add_constraint(a1*x[Integer(1)] + a2*x[Integer(2)] <= a3)
>>> N(p.solve(), digits=Integer(3)) #_
↳ # needs cvxopt
16.2

```

One can also define double-bounds or equality using the symbol `>=` or `==`:

```

sage: p = SemidefiniteProgram(maximization=True)
sage: x = p.new_variable()
sage: p.set_objective(x[1] + 5*x[2])
sage: a1 = matrix([[1,2],[2,3]])
sage: a2 = matrix([[1,1],[1,1]])
sage: a3 = matrix([[1,-1],[-1,1]])
sage: p.add_constraint(a3 >= a1*x[1] + a2*x[2])
sage: N(p.solve(), digits=3) #_
↳needs cvxopt
16.2

```

```

>>> from sage.all import *
>>> p = SemidefiniteProgram(maximization=True)
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(1)] + Integer(5)*x[Integer(2)])
>>> a1 = matrix([[Integer(1), Integer(2)], [Integer(2), Integer(3)]])
>>> a2 = matrix([[Integer(1), Integer(1)], [Integer(1), Integer(1)]])
>>> a3 = matrix([[Integer(1), -Integer(1)], [-Integer(1), Integer(1)]])
>>> p.add_constraint(a3 >= a1*x[Integer(1)] + a2*x[Integer(2)])
>>> N(p.solve(), digits=Integer(3)) #_
↳ # needs cvxopt
16.2

```

base_ring()

Return the base ring.

OUTPUT: a ring. The coefficients that the chosen solver supports

EXAMPLES:

```

sage: p = SemidefiniteProgram(solver='cvxopt')
sage: p.base_ring()

```

(continues on next page)

(continued from previous page)

Real Double Field

```
>>> from sage.all import *
>>> p = SemidefiniteProgram(solver='cvxopt')
>>> p.base_ring()
Real Double Field
```

dual_variable(*i*, *sparse=False*)The *i*-th dual variable.Available after `self.solve()` is called, otherwise the result is undefined.

INPUT:

- `index` – integer; the constraint's id

OUTPUT: the matrix of the *i*-th dual variable

EXAMPLES:

Dual objective value is the same as the primal one:

```
sage: p = SemidefiniteProgram(maximization=False)
sage: x = p.new_variable()
sage: p.set_objective(x[0] - x[1])
sage: a1 = matrix([[1, 2.], [2., 3.]])
sage: a2 = matrix([[3, 4.], [4., 5.]])
sage: a3 = matrix([[5, 6.], [6., 7.]])
sage: b1 = matrix([[1, 1.], [1., 1.]])
sage: b2 = matrix([[2, 2.], [2., 2.]])
sage: b3 = matrix([[3, 3.], [3., 3.]])
sage: p.add_constraint(a1*x[0] + a2*x[1] <= a3)
sage: p.add_constraint(b1*x[0] + b2*x[1] <= b3)

sage: # needs cvxopt
sage: p.solve()
↪ # tol 1e-08
-3.0
sage: x = p.get_values(x).values()
sage: -(a3*p.dual_variable(0)).trace() - (b3*p.dual_variable(1)).trace()
↪ # tol 1e-07
-3.0
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram(maximization=False)
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(0)] - x[Integer(1)])
>>> a1 = matrix([[Integer(1), RealNumber('2.')] , [RealNumber('2.')] ,
↪ RealNumber('3.')]])
>>> a2 = matrix([[Integer(3), RealNumber('4.')] , [RealNumber('4.')] ,
↪ RealNumber('5.')]])
>>> a3 = matrix([[Integer(5), RealNumber('6.')] , [RealNumber('6.')] ,
↪ RealNumber('7.')]])
>>> b1 = matrix([[Integer(1), RealNumber('1.')] , [RealNumber('1.')] ,
```

(continues on next page)

(continued from previous page)

```

↪RealNumber('1.')]])
>>> b2 = matrix([[Integer(2), RealNumber('2.')] , [RealNumber('2.')] ,
↪RealNumber('2.')]])
>>> b3 = matrix([[Integer(3), RealNumber('3.')] , [RealNumber('3.')] ,
↪RealNumber('3.')]])
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] <= a3)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] <= b3)

>>> # needs cvxopt
>>> p.solve() #
↪tol 1e-08
-3.0
>>> x = p.get_values(x).values()
>>> -(a3*p.dual_variable(Integer(0))).trace() - (b3*p.dual_
↪variable(Integer(1))).trace() # tol 1e-07
-3.0

```

Dual variable is orthogonal to the slack

```

sage: # needs cvxopt
sage: g = sum((p.slack(j)*p.dual_variable(j)).trace() for j in range(2)); g
↪# tol 1.2e-08
0.0

```

```

>>> from sage.all import *
>>> # needs cvxopt
>>> g = sum((p.slack(j)*p.dual_variable(j)).trace() for j in
↪range(Integer(2))); g # tol 1.2e-08
0.0

```

gen(*i*)

Return the linear variable x_i .

EXAMPLES:

```

sage: sdp = SemidefiniteProgram()
sage: sdp.gen(0)
x_0
sage: [sdp.gen(i) for i in range(10)]
[x_0, x_1, x_2, x_3, x_4, x_5, x_6, x_7, x_8, x_9]

```

```

>>> from sage.all import *
>>> sdp = SemidefiniteProgram()
>>> sdp.gen(Integer(0))
x_0
>>> [sdp.gen(i) for i in range(Integer(10))]
[x_0, x_1, x_2, x_3, x_4, x_5, x_6, x_7, x_8, x_9]

```

get_backend()

Return the backend instance used.

This might be useful when access to additional functions provided by the backend is needed.

EXAMPLES:

This example prints a matrix coefficient:

```
sage: p = SemidefiniteProgram(solver='cvxopt')
sage: x = p.new_variable()
sage: a1 = matrix([[1, 2.], [2., 3.]])
sage: a2 = matrix([[3, 4.], [4., 5.]])
sage: p.add_constraint(a1*x[0] + a2*x[1] <= a1)
sage: b = p.get_backend()
sage: b.get_matrix()[0][0]
(
  [-1.0 -2.0]
-1, [-2.0 -3.0]
)
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram(solver='cvxopt')
>>> x = p.new_variable()
>>> a1 = matrix([[Integer(1), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('3.')]])
>>> a2 = matrix([[Integer(3), RealNumber('4.')] , [RealNumber('4.')] ,
↳RealNumber('5.')]])
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] <= a1)
>>> b = p.get_backend()
>>> b.get_matrix()[Integer(0)][Integer(0)]
(
  [-1.0 -2.0]
-1, [-2.0 -3.0]
)
```

`get_values` (*lists)

Return values found by the previous call to `solve()`.

INPUT:

- Any instance of *SDPVariable* (or one of its elements), or lists of them.

OUTPUT:

- Each instance of *SDPVariable* is replaced by a dictionary containing the numerical values found for each corresponding variable in the instance.
- Each element of an instance of a *SDPVariable* is replaced by its corresponding numerical value.

EXAMPLES:

```
sage: p = SemidefiniteProgram(solver = "cvxopt", maximization = False)
sage: x = p.new_variable()
sage: p.set_objective(x[3] - x[5])
sage: a1 = matrix([[1, 2.], [2., 3.]])
sage: a2 = matrix([[3, 4.], [4., 5.]])
sage: a3 = matrix([[5, 6.], [6., 7.]])
sage: b1 = matrix([[1, 1.], [1., 1.]])
sage: b2 = matrix([[2, 2.], [2., 2.]])
sage: b3 = matrix([[3, 3.], [3., 3.]])
sage: p.add_constraint(a1*x[3] + a2*x[5] <= a3)
sage: p.add_constraint(b1*x[3] + b2*x[5] <= b3)
```

(continues on next page)

(continued from previous page)

```
sage: N(p.solve(), 3) #_
↳needs cvxopt
-3.0
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram(solver = "cvxopt", maximization = False)
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(3)] - x[Integer(5)])
>>> a1 = matrix([[Integer(1), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('3.')]])
>>> a2 = matrix([[Integer(3), RealNumber('4.')] , [RealNumber('4.')] ,
↳RealNumber('5.')]])
>>> a3 = matrix([[Integer(5), RealNumber('6.')] , [RealNumber('6.')] ,
↳RealNumber('7.')]])
>>> b1 = matrix([[Integer(1), RealNumber('1.')] , [RealNumber('1.')] ,
↳RealNumber('1.')]])
>>> b2 = matrix([[Integer(2), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('2.')]])
>>> b3 = matrix([[Integer(3), RealNumber('3.')] , [RealNumber('3.')] ,
↳RealNumber('3.')]])
>>> p.add_constraint(a1*x[Integer(3)] + a2*x[Integer(5)] <= a3)
>>> p.add_constraint(b1*x[Integer(3)] + b2*x[Integer(5)] <= b3)
>>> N(p.solve(), Integer(3)) #_
↳ # needs cvxopt
-3.0
```

To return the optimal value of $x[3]$:

```
sage: N(p.get_values(x[3]), 3) #_
↳needs cvxopt
-1.0
```

```
>>> from sage.all import *
>>> N(p.get_values(x[Integer(3)]), Integer(3)) #_
↳ # needs cvxopt
-1.0
```

To get a dictionary identical to x containing optimal values for the corresponding variables

```
sage: x_sol = p.get_values(x) #_
↳needs cvxopt
sage: sorted(x_sol) #_
↳needs cvxopt
[3, 5]
```

```
>>> from sage.all import *
>>> x_sol = p.get_values(x) #_
↳needs cvxopt
>>> sorted(x_sol) #_
↳needs cvxopt
[3, 5]
```

linear_constraints_parent()

Return the parent for all linear constraints.

See [linear_functions](#) for more details.

EXAMPLES:

```
sage: p = SemidefiniteProgram()
sage: p.linear_constraints_parent()
Linear constraints over Real Double Field
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram()
>>> p.linear_constraints_parent()
Linear constraints over Real Double Field
```

linear_function(x)

Construct a new linear function.

EXAMPLES:

```
sage: p = SemidefiniteProgram()
sage: p.linear_function({0:1})
x_0
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram()
>>> p.linear_function({Integer(0):Integer(1)})
x_0
```

linear_functions_parent()

Return the parent for all linear functions.

EXAMPLES:

```
sage: p = SemidefiniteProgram()
sage: p.linear_functions_parent()
Linear functions over Real Double Field
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram()
>>> p.linear_functions_parent()
Linear functions over Real Double Field
```

new_variable(name="")

Return an instance of *SDPVariable* associated to the current instance of *SemidefiniteProgram*.

A new variable *x* is defined by:

```
sage: p = SemidefiniteProgram()
sage: x = p.new_variable()
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram()
>>> x = p.new_variable()
```

It behaves exactly as an usual dictionary would. It can use any key argument you may like, as `x[5]` or `x["b"]`, and has methods `items()` and `keys()`.

INPUT:

- `dim` – integer; defines the dimension of the dictionary. If `x` has dimension 2, its fields will be of the form `x[key1][key2]`. **Deprecated.**
- `name` – string; associates a name to the variable

EXAMPLES:

```
sage: p = SemidefiniteProgram()
sage: x = p.new_variable()
sage: a1 = matrix([[1, 2.], [2., 3.]])
sage: p.add_constraint(a1*x[0] + a1*x[3] <= 0)
sage: p.show()
Maximization:

Constraints:
  constraint_0: [1.0 2.0][2.0 3.0]x_0 + [1.0 2.0][2.0 3.0]x_1 <= [0 0][0 0]
Variables:
  x_0, x_1
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram()
>>> x = p.new_variable()
>>> a1 = matrix([[Integer(1), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('3.')]])
>>> p.add_constraint(a1*x[Integer(0)] + a1*x[Integer(3)] <= Integer(0))
>>> p.show()
Maximization:
<BLANKLINE>
Constraints:
  constraint_0: [1.0 2.0][2.0 3.0]x_0 + [1.0 2.0][2.0 3.0]x_1 <= [0 0][0 0]
Variables:
  x_0, x_1
```

number_of_constraints()

Return the number of constraints assigned so far.

EXAMPLES:

```
sage: p = SemidefiniteProgram(solver = "cvxopt")
sage: x = p.new_variable()
sage: a1 = matrix([[1, 2.], [2., 3.]])
sage: a2 = matrix([[3, 4.], [4., 5.]])
sage: a3 = matrix([[5, 6.], [6., 7.]])
sage: b1 = matrix([[1, 1.], [1., 1.]])
sage: b2 = matrix([[2, 2.], [2., 2.]])
sage: b3 = matrix([[3, 3.], [3., 3.]])
sage: p.add_constraint(a1*x[0] + a2*x[1] <= a3)
sage: p.add_constraint(b1*x[0] + b2*x[1] <= b3)
sage: p.add_constraint(b1*x[0] + a2*x[1] <= b3)
sage: p.number_of_constraints()
3
```

```

>>> from sage.all import *
>>> p = SemidefiniteProgram(solver = "cvxopt")
>>> x = p.new_variable()
>>> a1 = matrix([[Integer(1), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('3.')]])
>>> a2 = matrix([[Integer(3), RealNumber('4.')] , [RealNumber('4.')] ,
↳RealNumber('5.')]])
>>> a3 = matrix([[Integer(5), RealNumber('6.')] , [RealNumber('6.')] ,
↳RealNumber('7.')]])
>>> b1 = matrix([[Integer(1), RealNumber('1.')] , [RealNumber('1.')] ,
↳RealNumber('1.')]])
>>> b2 = matrix([[Integer(2), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('2.')]])
>>> b3 = matrix([[Integer(3), RealNumber('3.')] , [RealNumber('3.')] ,
↳RealNumber('3.')]])
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] <= a3)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] <= b3)
>>> p.add_constraint(b1*x[Integer(0)] + a2*x[Integer(1)] <= b3)
>>> p.number_of_constraints()
3
    
```

`number_of_variables()`

Return the number of variables used so far.

EXAMPLES:

```

sage: p = SemidefiniteProgram()
sage: a = matrix([[1, 2.], [2., 3.]])
sage: p.add_constraint(a*p[0] - a*p[2] <= 2*a*p[4] )
sage: p.number_of_variables()
3
    
```

```

>>> from sage.all import *
>>> p = SemidefiniteProgram()
>>> a = matrix([[Integer(1), RealNumber('2.')] , [RealNumber('2.')] , RealNumber(
↳'3.')]])
>>> p.add_constraint(a*p[Integer(0)] - a*p[Integer(2)] <=
↳Integer(2)*a*p[Integer(4)] )
>>> p.number_of_variables()
3
    
```

`set_objective(obj)`

Set the objective of the *SemidefiniteProgram*.

INPUT:

- `obj` – a semidefinite function to be optimized (can also be set to `None` or `0` when just looking for a feasible solution)

EXAMPLES:

Let's solve the following semidefinite program:

$$\begin{array}{ll}
 \text{maximize} & x + 5y \\
 \text{subject to} & \begin{pmatrix} 1 & 2 \\ 2 & 3 \end{pmatrix} x + \begin{pmatrix} 1 & 1 \\ 1 & 1 \end{pmatrix} y \preceq \begin{pmatrix} 1 & -1 \\ -1 & 1 \end{pmatrix}
 \end{array}$$

This SDP can be solved as follows:

```
sage: p = SemidefiniteProgram(maximization=True)
sage: x = p.new_variable()
sage: p.set_objective(x[1] + 5*x[2])
sage: a1 = matrix([[1,2],[2,3]])
sage: a2 = matrix([[1,1],[1,1]])
sage: a3 = matrix([[1,-1],[-1,1]])
sage: p.add_constraint(a1*x[1] + a2*x[2] <= a3)
sage: N(p.solve(), digits=3) #_
↳needs cvxopt
16.2
sage: p.set_objective(None)
sage: _ = p.solve() #_
↳needs cvxopt
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram(maximization=True)
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(1)] + Integer(5)*x[Integer(2)])
>>> a1 = matrix([[Integer(1),Integer(2)],[Integer(2),Integer(3)]])
>>> a2 = matrix([[Integer(1),Integer(1)],[Integer(1),Integer(1)]])
>>> a3 = matrix([[Integer(1),-Integer(1)],[Integer(1),Integer(1)]])
>>> p.add_constraint(a1*x[Integer(1)] + a2*x[Integer(2)] <= a3)
>>> N(p.solve(), digits=Integer(3)) #_
↳ # needs cvxopt
16.2
>>> p.set_objective(None)
>>> _ = p.solve() #_
↳needs cvxopt
```

set_problem_name (name)

Set the name of the SemidefiniteProgram.

INPUT:

- name – string representing the name of the SemidefiniteProgram

EXAMPLES:

```
sage: p = SemidefiniteProgram()
sage: p.set_problem_name("Test program")
sage: p
Semidefinite Program "Test program" ( maximization, 0 variables, 0_
↳constraints )
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram()
>>> p.set_problem_name("Test program")
>>> p
Semidefinite Program "Test program" ( maximization, 0 variables, 0_
↳constraints )
```

show()

Display the *SemidefiniteProgram* in a human-readable way.

EXAMPLES:

When constraints and variables have names

```

sage: p = SemidefiniteProgram()
sage: x = p.new_variable(name='hihi')
sage: a1 = matrix([[1,2],[2,3]])
sage: a2 = matrix([[2,3],[3,4]])
sage: a3 = matrix([[3,4],[4,5]])
sage: p.set_objective(x[0] - x[1])
sage: p.add_constraint(a1*x[0] + a2*x[1] <= a3)
sage: p.show()
Maximization:
  hihi[0] - hihi[1]
Constraints:
  constraint_0: [1.0 2.0][2.0 3.0]hihi[0] + [2.0 3.0][3.0 4.0]hihi[1] <= [3.
  ↪0 4.0][4.0 5.0]
Variables:
  hihi[0], hihi[1]
    
```

```

>>> from sage.all import *
>>> p = SemidefiniteProgram()
>>> x = p.new_variable(name='hihi')
>>> a1 = matrix([[Integer(1), Integer(2)], [Integer(2), Integer(3)]])
>>> a2 = matrix([[Integer(2), Integer(3)], [Integer(3), Integer(4)]])
>>> a3 = matrix([[Integer(3), Integer(4)], [Integer(4), Integer(5)]])
>>> p.set_objective(x[Integer(0)] - x[Integer(1)])
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] <= a3)
>>> p.show()
Maximization:
  hihi[0] - hihi[1]
Constraints:
  constraint_0: [1.0 2.0][2.0 3.0]hihi[0] + [2.0 3.0][3.0 4.0]hihi[1] <= [3.
  ↪0 4.0][4.0 5.0]
Variables:
  hihi[0], hihi[1]
    
```

slack (*i*, *sparse=False*)

 Slack of the *i*-th constraint.

 Available after `self.solve()` is called, otherwise the result is undefined.

INPUT:

- `index` – integer; the constraint's id

 OUTPUT: the matrix of the slack of the *i*-th constraint

EXAMPLES:

```

sage: p = SemidefiniteProgram(maximization = False)
sage: x = p.new_variable()
sage: p.set_objective(x[0] - x[1])
sage: a1 = matrix([[1, 2.], [2., 3.]])
sage: a2 = matrix([[3, 4.], [4., 5.]])
sage: a3 = matrix([[5, 6.], [6., 7.]])
    
```

(continues on next page)

(continued from previous page)

```

sage: b1 = matrix([[1, 1.], [1., 1.]])
sage: b2 = matrix([[2, 2.], [2., 2.]])
sage: b3 = matrix([[3, 3.], [3., 3.]])
sage: p.add_constraint(a1*x[0] + a2*x[1] <= a3)
sage: p.add_constraint(b1*x[0] + b2*x[1] <= b3)

sage: # needs cvxopt
sage: p.solve() # tol 1e-08
-3.0
sage: B1 = p.slack(1); B1 # tol 1e-08
[0.0 0.0]
[0.0 0.0]
sage: B1.is_positive_definite()
True
sage: x = sorted(p.get_values(x).values())
sage: x[0]*b1 + x[1]*b2 - b3 + B1 # tol 1e-09
[0.0 0.0]
[0.0 0.0]

```

```

>>> from sage.all import *
>>> p = SemidefiniteProgram(maximization = False)
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(0)] - x[Integer(1)])
>>> a1 = matrix([[Integer(1), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('3.')]])
>>> a2 = matrix([[Integer(3), RealNumber('4.')] , [RealNumber('4.')] ,
↳RealNumber('5.')]])
>>> a3 = matrix([[Integer(5), RealNumber('6.')] , [RealNumber('6.')] ,
↳RealNumber('7.')]])
>>> b1 = matrix([[Integer(1), RealNumber('1.')] , [RealNumber('1.')] ,
↳RealNumber('1.')]])
>>> b2 = matrix([[Integer(2), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('2.')]])
>>> b3 = matrix([[Integer(3), RealNumber('3.')] , [RealNumber('3.')] ,
↳RealNumber('3.')]])
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] <= a3)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] <= b3)

>>> # needs cvxopt
>>> p.solve() # tol 1e-08
-3.0
>>> B1 = p.slack(Integer(1)); B1 # tol 1e-08
[0.0 0.0]
[0.0 0.0]
>>> B1.is_positive_definite()
True
>>> x = sorted(p.get_values(x).values())
>>> x[Integer(0)]*b1 + x[Integer(1)]*b2 - b3 + B1 # tol 1e-09
[0.0 0.0]
[0.0 0.0]

```

`solve (objective_only=False)`

Solve the *SemidefiniteProgram*.

INPUT:

- `objective_only` – boolean:
 - when set to `True`, only the objective function is returned
 - when set to `False` (default), the optimal numerical values are stored (takes computational time)

OUTPUT: the optimal value taken by the objective function

solver_parameter (*name*, *value=None*)

Return or define a solver parameter.

The solver parameters are by essence solver-specific, which means their meaning heavily depends on the solver used.

(If you do not know which solver you are using, then you are using CVXOPT).

INPUT:

- `name` – string; the parameter
- `value` – the parameter's value if it is to be defined, or `None` (default) to obtain its current value

EXAMPLES:

```
sage: # needs cvxopt
sage: p.<x> = SemidefiniteProgram(solver='cvxopt',
....:                             maximization=False)
sage: p.solver_parameter("show_progress", True)
sage: p.solver_parameter("show_progress")
True
sage: p.set_objective(x[0] - x[1])
sage: a1 = matrix([[1, 2.], [2., 3.]])
sage: a2 = matrix([[3, 4.], [4., 2.]])
sage: a3 = matrix([[5, 6.], [6., 7.]])
sage: b1 = matrix([[1, 1.], [1., 1.]])
sage: b2 = matrix([[2, 2.], [2., 1.]])
sage: b3 = matrix([[3, 3.], [3., 3.]])
sage: p.add_constraint(a1*x[0] + a2*x[1] <= a3)
sage: p.add_constraint(b1*x[0] + b2*x[1] <= b3)
sage: N(p.solve(), 4)
      pcost      dcost      gap      pres      dres      k/t
0:  1...
...
Optimal solution found.
-11.
```

```
>>> from sage.all import *
>>> # needs cvxopt
>>> p = SemidefiniteProgram(solver='cvxopt',
...                             maximization=False, names=('x',)); (x,) = p._
↳first_ngens(1)
>>> p.solver_parameter("show_progress", True)
>>> p.solver_parameter("show_progress")
True
>>> p.set_objective(x[Integer(0)] - x[Integer(1)])
```

(continues on next page)

(continued from previous page)

```

>>> a1 = matrix([[Integer(1), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('3.')]])
>>> a2 = matrix([[Integer(3), RealNumber('4.')] , [RealNumber('4.')] ,
↳RealNumber('2.')]])
>>> a3 = matrix([[Integer(5), RealNumber('6.')] , [RealNumber('6.')] ,
↳RealNumber('7.')]])
>>> b1 = matrix([[Integer(1), RealNumber('1.')] , [RealNumber('1.')] ,
↳RealNumber('1.')]])
>>> b2 = matrix([[Integer(2), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('1.')]])
>>> b3 = matrix([[Integer(3), RealNumber('3.')] , [RealNumber('3.')] ,
↳RealNumber('3.')]])
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] <= a3)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] <= b3)
>>> N(p.solve(), Integer(4))
      pcost      dcost      gap      pres      dres      k/t
0:  1...
...
Optimal solution found.
-11.

```

sum(L)

Efficiently compute the sum of a sequence of *LinearFunction* elements.

INPUT:

- L – list of *LinearFunction* instances

Note

The use of the regular `sum` function is not recommended as it is much less efficient than this one.

EXAMPLES:

```

sage: p = SemidefiniteProgram()
sage: v = p.new_variable()

```

```

>>> from sage.all import *
>>> p = SemidefiniteProgram()
>>> v = p.new_variable()

```

The following command:

```

sage: s = p.sum(v[i] for i in range(90))

```

```

>>> from sage.all import *
>>> s = p.sum(v[i] for i in range(Integer(90)))

```

is much more efficient than:

```

sage: s = sum(v[i] for i in range(90))

```

```
>>> from sage.all import *  
>>> s = sum(v[i] for i in range(Integer(90)))
```

LINEAR FUNCTIONS AND CONSTRAINTS

This module implements linear functions (see *LinearFunction*) in formal variables and chained (in)equalities between them (see *LinearConstraint*). By convention, these are always written as either equalities or less-or-equal. For example:

```
sage: p = MixedIntegerLinearProgram()
sage: x = p.new_variable()
sage: f = 1 + x[1] + 2*x[2]; f      # a linear function
1 + x_0 + 2*x_1
sage: type(f)
<class 'sage.numerical.linear_functions.LinearFunction'>

sage: c = (0 <= f); c      # a constraint
0 <= 1 + x_0 + 2*x_1
sage: type(c)
<class 'sage.numerical.linear_functions.LinearConstraint'>
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> x = p.new_variable()
>>> f = Integer(1) + x[Integer(1)] + Integer(2)*x[Integer(2)]; f      # a linear_
->function
1 + x_0 + 2*x_1
>>> type(f)
<class 'sage.numerical.linear_functions.LinearFunction'>

>>> c = (Integer(0) <= f); c      # a constraint
0 <= 1 + x_0 + 2*x_1
>>> type(c)
<class 'sage.numerical.linear_functions.LinearConstraint'>
```

Note that you can use this module without any reference to linear programming, it only implements linear functions over a base ring and constraints. However, for ease of demonstration we will always construct them out of linear programs (see *mip*).

Constraints can be equations or (non-strict) inequalities. They can be chained:

```
sage: p = MixedIntegerLinearProgram()
sage: x = p.new_variable()
sage: x[0] == x[1] == x[2] == x[3]
x_0 == x_1 == x_2 == x_3
```

(continues on next page)

(continued from previous page)

```
sage: ieq_01234 = x[0] <= x[1] <= x[2] <= x[3] <= x[4]
sage: ieq_01234
x_0 <= x_1 <= x_2 <= x_3 <= x_4
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> x = p.new_variable()
>>> x[Integer(0)] == x[Integer(1)] == x[Integer(2)] == x[Integer(3)]
x_0 == x_1 == x_2 == x_3

>>> ieq_01234 = x[Integer(0)] <= x[Integer(1)] <= x[Integer(2)] <= x[Integer(3)] <=
↳x[Integer(4)]
>>> ieq_01234
x_0 <= x_1 <= x_2 <= x_3 <= x_4
```

If necessary, the direction of inequality is flipped to always write inequalities as less or equal:

```
sage: x[5] >= ieq_01234
x_0 <= x_1 <= x_2 <= x_3 <= x_4 <= x_5

sage: (x[5] <= x[6]) >= ieq_01234
x_0 <= x_1 <= x_2 <= x_3 <= x_4 <= x_5 <= x_6

sage: (x[5] <= x[6]) <= ieq_01234
x_5 <= x_6 <= x_0 <= x_1 <= x_2 <= x_3 <= x_4
```

```
>>> from sage.all import *
>>> x[Integer(5)] >= ieq_01234
x_0 <= x_1 <= x_2 <= x_3 <= x_4 <= x_5

>>> (x[Integer(5)] <= x[Integer(6)]) >= ieq_01234
x_0 <= x_1 <= x_2 <= x_3 <= x_4 <= x_5 <= x_6

>>> (x[Integer(5)] <= x[Integer(6)]) <= ieq_01234
x_5 <= x_6 <= x_0 <= x_1 <= x_2 <= x_3 <= x_4
```

Warning

The implementation of chained inequalities uses a Python hack to make it work, so it is not completely robust. In particular, while constants are allowed, no two constants can appear next to each other. The following does not work for example:

```
sage: x[0] <= 3 <= 4
True
```

```
>>> from sage.all import *
>>> x[Integer(0)] <= Integer(3) <= Integer(4)
True
```

If you really need this for some reason, you can explicitly convert the constants to a *LinearFunction*:

```
sage: from sage.numerical.linear_functions import LinearFunctionsParent
sage: LF = LinearFunctionsParent(QQ)
sage: x[1] <= LF(3) <= LF(4)
x_1 <= 3 <= 4
```

```

>>> from sage.all import *
>>> from sage.numerical.linear_functions import LinearFunctionsParent
>>> LF = LinearFunctionsParent(QQ)
>>> x[Integer(1)] <= LF(Integer(3)) <= LF(Integer(4))
x_1 <= 3 <= 4

```

class `sage.numerical.linear_functions.LinearConstraint`

Bases: *LinearFunctionOrConstraint*

A class to represent formal Linear Constraints.

A Linear Constraint being an inequality between two linear functions, this class lets the user write `LinearFunction1 <= LinearFunction2` to define the corresponding constraint, which can potentially involve several layers of such inequalities ($A \leq B \leq C$), or even equalities like $A == B == C$.

Trivial constraints (meaning that they have only one term and no relation) are also allowed. They are required for the coercion system to work.

Warning

This class has no reason to be instantiated by the user, and is meant to be used by instances of *MixedIntegerLinearProgram*.

INPUT:

- `parent` – the parent; a *LinearConstraintsParent_class*
- `terms` – list/tuple/iterable of two or more linear functions (or things that can be converted into linear functions)
- `equality` – boolean (default: `False`); whether the terms are the entries of a chained less-or-equal (`<=`) inequality or a chained equality

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram()
sage: b = p.new_variable()
sage: b[2]+2*b[3] <= b[8]-5
x_0 + 2*x_1 <= -5 + x_2

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> b = p.new_variable()
>>> b[Integer(2)]+Integer(2)*b[Integer(3)] <= b[Integer(8)]-Integer(5)
x_0 + 2*x_1 <= -5 + x_2

```

equals (*left, right*)

Compare `left` and `right`.

OUTPUT:

boolean; whether all terms of `left` and `right` are equal. Note that this is stronger than mathematical equivalence of the relations.

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram()
sage: x = p.new_variable()
sage: (x[1] + 1 >= 2).equals(3/3 + 1*x[1] + 0*x[2] >= 8/4)
True
sage: (x[1] + 1 >= 2).equals(x[1] + 1-1 >= 1-1)
False
    
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> x = p.new_variable()
>>> (x[Integer(1)] + Integer(1) >= Integer(2)).equals(Integer(3)/Integer(3) +
↳Integer(1)*x[Integer(1)] + Integer(0)*x[Integer(2)] >= Integer(8)/
↳Integer(4))
True
>>> (x[Integer(1)] + Integer(1) >= Integer(2)).equals(x[Integer(1)] +
↳Integer(1)-Integer(1) >= Integer(1)-Integer(1))
False
    
```

`equations()`

Iterate over the unchained(!) equations.

OUTPUT:

An iterator over pairs (lhs, rhs) such that the individual equations are lhs == rhs.

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram()
sage: b = p.new_variable()
sage: eqns = 1 == b[0] == b[2] == 3 == b[3]; eqns
1 == x_0 == x_1 == 3 == x_2
sage: for lhs, rhs in eqns.equations():
....:     print(str(lhs) + ' == ' + str(rhs))
1 == x_0
x_0 == x_1
x_1 == 3
3 == x_2
    
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> b = p.new_variable()
>>> eqns = Integer(1) == b[Integer(0)] == b[Integer(2)] == Integer(3) ==
↳b[Integer(3)]; eqns
1 == x_0 == x_1 == 3 == x_2
>>> for lhs, rhs in eqns.equations():
...     print(str(lhs) + ' == ' + str(rhs))
1 == x_0
x_0 == x_1
x_1 == 3
3 == x_2
    
```

`inequalities()`

Iterate over the unchained(!) inequalities.

OUTPUT:

An iterator over pairs (lhs, rhs) such that the individual equations are $\text{lhs} \leq \text{rhs}$.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram()
sage: b = p.new_variable()
sage: ieq = 1 <= b[0] <= b[2] <= 3 <= b[3]; ieq
1 <= x_0 <= x_1 <= 3 <= x_2

sage: for lhs, rhs in ieq.inequalities():
....:     print(str(lhs) + ' <= ' + str(rhs))
1 <= x_0
x_0 <= x_1
x_1 <= 3
3 <= x_2
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> b = p.new_variable()
>>> ieq = Integer(1) <= b[Integer(0)] <= b[Integer(2)] <= Integer(3) <=
->b[Integer(3)]; ieq
1 <= x_0 <= x_1 <= 3 <= x_2

>>> for lhs, rhs in ieq.inequalities():
...     print(str(lhs) + ' <= ' + str(rhs))
1 <= x_0
x_0 <= x_1
x_1 <= 3
3 <= x_2
```

is_equation()

Whether the constraint is a chained equation.

OUTPUT: boolean

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram()
sage: b = p.new_variable()
sage: (b[0] == b[1]).is_equation()
True
sage: (b[0] <= b[1]).is_equation()
False
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> b = p.new_variable()
>>> (b[Integer(0)] == b[Integer(1)]).is_equation()
True
>>> (b[Integer(0)] <= b[Integer(1)]).is_equation()
False
```

is_less_or_equal()

Whether the constraint is a chained less-or_equal inequality.

OUTPUT: boolean

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram()
sage: b = p.new_variable()
sage: (b[0] == b[1]).is_less_or_equal()
False
sage: (b[0] <= b[1]).is_less_or_equal()
True
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> b = p.new_variable()
>>> (b[Integer(0)] == b[Integer(1)]).is_less_or_equal()
False
>>> (b[Integer(0)] <= b[Integer(1)]).is_less_or_equal()
True
```

is_trivial()

Test whether the constraint is trivial.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram()
sage: LC = p.linear_constraints_parent()
sage: ieq = LC(1,2); ieq
1 <= 2
sage: ieq.is_trivial()
False

sage: ieq = LC(1); ieq
trivial constraint starting with 1
sage: ieq.is_trivial()
True
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> LC = p.linear_constraints_parent()
>>> ieq = LC(Integer(1),Integer(2)); ieq
1 <= 2
>>> ieq.is_trivial()
False

>>> ieq = LC(Integer(1)); ieq
trivial constraint starting with 1
>>> ieq.is_trivial()
True
```

`sage.numerical.linear_functions.LinearConstraintsParent()`

Return the parent for linear functions over `base_ring`.

The output is cached, so only a single parent is ever constructed for a given base ring.

INPUT:

- **linear_functions_parent – a**
LinearFunctionsParent_class; the type of linear functions that the constraints are made out of

OUTPUT: the parent of the linear constraints with the given linear functions

EXAMPLES:

```
sage: from sage.numerical.linear_functions import (
....:     LinearFunctionsParent, LinearConstraintsParent)
sage: LF = LinearFunctionsParent(QQ)
sage: LinearConstraintsParent(LF)
Linear constraints over Rational Field
```

```
>>> from sage.all import *
>>> from sage.numerical.linear_functions import (
...     LinearFunctionsParent, LinearConstraintsParent)
>>> LF = LinearFunctionsParent(QQ)
>>> LinearConstraintsParent(LF)
Linear constraints over Rational Field
```

class sage.numerical.linear_functions.LinearConstraintsParent_class

Bases: Parent

Parent for *LinearConstraint*.

Warning

This class has no reason to be instantiated by the user, and is meant to be used by instances of *MixedIntegerLinearProgram*. Also, use the *LinearConstraintsParent()* factory function.

INPUT/OUTPUT: see *LinearFunctionsParent()*

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram()
sage: LC = p.linear_constraints_parent(); LC
Linear constraints over Real Double Field
sage: from sage.numerical.linear_functions import LinearConstraintsParent
sage: LinearConstraintsParent(p.linear_functions_parent()) is LC
True
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> LC = p.linear_constraints_parent(); LC
Linear constraints over Real Double Field
>>> from sage.numerical.linear_functions import LinearConstraintsParent
>>> LinearConstraintsParent(p.linear_functions_parent()) is LC
True
```

linear_functions_parent()

Return the parent for the linear functions.

EXAMPLES:

```
sage: LC = MixedIntegerLinearProgram().linear_constraints_parent()
sage: LC.linear_functions_parent()
Linear functions over Real Double Field
```

```
>>> from sage.all import *
>>> LC = MixedIntegerLinearProgram().linear_constraints_parent()
>>> LC.linear_functions_parent()
Linear functions over Real Double Field
```

class sage.numerical.linear_functions.**LinearFunction**

Bases: *LinearFunctionOrConstraint*

An elementary algebra to represent symbolic linear functions.

Warning

You should never instantiate *LinearFunction* manually. Use the element constructor in the parent instead.

EXAMPLES:

For example, do this:

```
sage: p = MixedIntegerLinearProgram()
sage: parent = p.linear_functions_parent()
sage: parent({0 : 1, 3 : -8})
x_0 - 8*x_3
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> parent = p.linear_functions_parent()
>>> parent({Integer(0) : Integer(1), Integer(3) : -Integer(8)})
x_0 - 8*x_3
```

instead of this:

```
sage: from sage.numerical.linear_functions import LinearFunction
sage: LinearFunction(p.linear_functions_parent(), {0 : 1, 3 : -8})
x_0 - 8*x_3
```

```
>>> from sage.all import *
>>> from sage.numerical.linear_functions import LinearFunction
>>> LinearFunction(p.linear_functions_parent(), {Integer(0) : Integer(1), ↵
↵Integer(3) : -Integer(8)})
x_0 - 8*x_3
```

coefficient (*x*)

Return one of the coefficients.

INPUT:

- *x* – a linear variable or an integer; if an integer *i* is passed, then x_i is used as linear variable

OUTPUT:

A base ring element. The coefficient of *x* in the linear function. Pass -1 for the constant term.

EXAMPLES:

```

sage: mip.<b> = MixedIntegerLinearProgram()
sage: lf = -8 * b[3] + b[0] - 5; lf
-5 - 8*x_0 + x_1
sage: lf.coefficient(b[3])
-8.0
sage: lf.coefficient(0)      # x_0 is b[3]
-8.0
sage: lf.coefficient(4)
0.0
sage: lf.coefficient(-1)
-5.0

```

```

>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(names=('b',)); (b,) = mip._first_ngens(1)
>>> lf = -Integer(8) * b[Integer(3)] + b[Integer(0)] - Integer(5); lf
-5 - 8*x_0 + x_1
>>> lf.coefficient(b[Integer(3)])
-8.0
>>> lf.coefficient(Integer(0))      # x_0 is b[3]
-8.0
>>> lf.coefficient(Integer(4))
0.0
>>> lf.coefficient(-Integer(1))
-5.0

```

dict()

Return the dictionary corresponding to the Linear Function.

OUTPUT:

The linear function is represented as a dictionary. The value are the coefficient of the variable represented by the keys (which are integers). The key -1 corresponds to the constant term.

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram()
sage: LF = p.linear_functions_parent()
sage: lf = LF({0 : 1, 3 : -8})
sage: lf.dict()
{0: 1.0, 3: -8.0}

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> LF = p.linear_functions_parent()
>>> lf = LF({Integer(0) : Integer(1), Integer(3) : -Integer(8)})
>>> lf.dict()
{0: 1.0, 3: -8.0}

```

equals (*left, right*)

Logically compare left and right.

OUTPUT: boolean**EXAMPLES:**

```

sage: p = MixedIntegerLinearProgram()
sage: x = p.new_variable()
sage: (x[1] + 1).equals(3/3 + 1*x[1] + 0*x[2])
True
    
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> x = p.new_variable()
>>> (x[Integer(1)] + Integer(1)).equals(Integer(3)/Integer(3) +
↳ Integer(1)*x[Integer(1)] + Integer(0)*x[Integer(2)])
True
    
```

is_zero()

Test whether `self` is zero.

OUTPUT: boolean

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram()
sage: x = p.new_variable()
sage: (x[1] - x[1] + 0*x[2]).is_zero()
True
    
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> x = p.new_variable()
>>> (x[Integer(1)] - x[Integer(1)] + Integer(0)*x[Integer(2)]).is_zero()
True
    
```

items()

Iterate over the index, coefficient pairs.

OUTPUT:

An iterator over the `(key, coefficient)` pairs. The keys are integers indexing the variables. The key `-1` corresponds to the constant term.

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver = 'ppl')
sage: x = p.new_variable()
sage: f = 0.5 + 3/2*x[1] + 0.6*x[3]
sage: for id, coeff in sorted(f.items()):
....:     print(f'id = {id}   coeff = {coeff}')
id = -1   coeff = 1/2
id = 0   coeff = 3/2
id = 1   coeff = 3/5
    
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver = 'ppl')
>>> x = p.new_variable()
>>> f = RealNumber('0.5') + Integer(3)/Integer(2)*x[Integer(1)] + RealNumber(
↳ '0.6')*x[Integer(3)]
    
```

(continues on next page)

(continued from previous page)

```
>>> for id, coeff in sorted(f.items()):
...     print(f'id = {id}   coeff = {coeff}')
id = -1   coeff = 1/2
id = 0    coeff = 3/2
id = 1    coeff = 3/5
```

`iteritems(*args, **kwds)`

Deprecated: Use `items()` instead. See [Issue #40996](#) for details.

class `sage.numerical.linear_functions.LinearFunctionOrConstraint`

Bases: `ModuleElement`

Base class for `LinearFunction` and `LinearConstraint`.

This class exists solely to implement chaining of inequalities in constraints.

`sage.numerical.linear_functions.LinearFunctionsParent()`

Return the parent for linear functions over `base_ring`.

The output is cached, so only a single parent is ever constructed for a given base ring.

INPUT:

- `base_ring` – a ring; the coefficient ring for the linear functions

OUTPUT: the parent of the linear functions over `base_ring`

EXAMPLES:

```
sage: from sage.numerical.linear_functions import LinearFunctionsParent
sage: LinearFunctionsParent(QQ)
Linear functions over Rational Field
```

```
>>> from sage.all import *
>>> from sage.numerical.linear_functions import LinearFunctionsParent
>>> LinearFunctionsParent(QQ)
Linear functions over Rational Field
```

class `sage.numerical.linear_functions.LinearFunctionsParent_class`

Bases: `Parent`

The parent for all linear functions over a fixed base ring.

Warning

You should use `LinearFunctionsParent()` to construct instances of this class.

INPUT/OUTPUT: see `LinearFunctionsParent()`

EXAMPLES:

```
sage: from sage.numerical.linear_functions import LinearFunctionsParent_class
sage: LinearFunctionsParent_class
<class 'sage.numerical.linear_functions.LinearFunctionsParent_class'>
```

```
>>> from sage.all import *
>>> from sage.numerical.linear_functions import LinearFunctionsParent_class
>>> LinearFunctionsParent_class
<class 'sage.numerical.linear_functions.LinearFunctionsParent_class'>
```

gen(*i*)

Return the linear variable x_i .

INPUT:

- *i* – nonnegative integer

OUTPUT: the linear function x_i

EXAMPLES:

```
sage: LF = MixedIntegerLinearProgram().linear_functions_parent()
sage: LF.gen(23)
x_23
```

```
>>> from sage.all import *
>>> LF = MixedIntegerLinearProgram().linear_functions_parent()
>>> LF.gen(Integer(23))
x_23
```

set_multiplication_symbol(*symbol*='*')

Set the multiplication symbol when pretty-printing linear functions.

INPUT:

- *symbol* – string (default: '*'); the multiplication symbol to be used

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram()
sage: x = p.new_variable()
sage: f = -1-2*x[0]-3*x[1]
sage: LF = f.parent()
sage: LF._get_multiplication_symbol()
'*'
sage: f
-1 - 2*x_0 - 3*x_1
sage: LF.set_multiplication_symbol(' ')
sage: f
-1 - 2 x_0 - 3 x_1
sage: LF.set_multiplication_symbol()
sage: f
-1 - 2*x_0 - 3*x_1
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> x = p.new_variable()
>>> f = -Integer(1)-Integer(2)*x[Integer(0)]-Integer(3)*x[Integer(1)]
>>> LF = f.parent()
>>> LF._get_multiplication_symbol()
```

(continues on next page)

(continued from previous page)

```

'''
>>> f
-1 - 2*x_0 - 3*x_1
>>> LF.set_multiplication_symbol(' ')
>>> f
-1 - 2 x_0 - 3 x_1
>>> LF.set_multiplication_symbol()
>>> f
-1 - 2*x_0 - 3*x_1

```

tensor (*free_module*)Return the tensor product with `free_module`.

INPUT:

- `free_module` – vector space or matrix space over the same base ring

OUTPUT:

Instance of `sage.numerical.linear_tensor.LinearTensorParent_class`.

EXAMPLES:

```

sage: LF = MixedIntegerLinearProgram().linear_functions_parent()
sage: LF.tensor(RDF^3)
Tensor product of Vector space of dimension 3 over Real Double Field
and Linear functions over Real Double Field
sage: LF.tensor(QQ^2)
Traceback (most recent call last):
...
ValueError: base rings must match

```

```

>>> from sage.all import *
>>> LF = MixedIntegerLinearProgram().linear_functions_parent()
>>> LF.tensor(RDF**Integer(3))
Tensor product of Vector space of dimension 3 over Real Double Field
and Linear functions over Real Double Field
>>> LF.tensor(QQ**Integer(2))
Traceback (most recent call last):
...
ValueError: base rings must match

```

`sage.numerical.linear_functions.is_LinearConstraint(x)`Test whether `x` is a linear constraint.

INPUT:

- `x` – anything

OUTPUT: boolean

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram()
sage: x = p.new_variable()
sage: ieq = (x[0] <= x[1])

```

(continues on next page)

(continued from previous page)

```

sage: from sage.numerical.linear_functions import is_LinearConstraint
sage: is_LinearConstraint(ieq)
doctest:warning...
DeprecationWarning: The function is_LinearConstraint is deprecated;
use 'isinstance(..., LinearConstraint)' instead.
See https://github.com/sagemath/sage/issues/38184 for details.
True
sage: is_LinearConstraint('a string')
False

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> x = p.new_variable()
>>> ieq = (x[Integer(0)] <= x[Integer(1)])
>>> from sage.numerical.linear_functions import is_LinearConstraint
>>> is_LinearConstraint(ieq)
doctest:warning...
DeprecationWarning: The function is_LinearConstraint is deprecated;
use 'isinstance(..., LinearConstraint)' instead.
See https://github.com/sagemath/sage/issues/38184 for details.
True
>>> is_LinearConstraint('a string')
False

```

`sage.numerical.linear_functions.is_LinearFunction(x)`

Test whether x is a linear function.

INPUT:

- x – anything

OUTPUT: boolean

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram()
sage: x = p.new_variable()
sage: from sage.numerical.linear_functions import is_LinearFunction
sage: is_LinearFunction(x[0] - 2*x[2])
doctest:warning...
DeprecationWarning: The function is_LinearFunction is deprecated;
use 'isinstance(..., LinearFunction)' instead.
See https://github.com/sagemath/sage/issues/38184 for details.
True
sage: is_LinearFunction('a string')
False

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> x = p.new_variable()
>>> from sage.numerical.linear_functions import is_LinearFunction
>>> is_LinearFunction(x[Integer(0)] - Integer(2)*x[Integer(2)])
doctest:warning...

```

(continues on next page)

(continued from previous page)

```
DeprecationWarning: The function is_LinearFunction is deprecated;  
use 'isinstance(..., LinearFunction)' instead.  
See https://github.com/sagemath/sage/issues/38184 for details.  
True  
>>> is_LinearFunction('a string')  
False
```


MATRIX/VECTOR-VALUED LINEAR FUNCTIONS: PARENTS

In Sage, matrices assume that the base is a ring. Hence, we cannot construct matrices whose entries are linear functions in Sage. Really, they should be thought of as the tensor product of the R -module of linear functions and the R -vector/matrix space, with the latter viewed as an R -module (R is usually $\mathbb{Q}\mathbb{Q}$ or $\mathbb{R}\mathbb{D}\mathbb{F}$ for our purposes).

You should not construct any tensor products by calling the parent directly. This is also why none of the classes are imported in the global namespace. They come into play whenever you have vector or matrix MIP linear expressions/constraints. The intended way to construct them is implicitly by acting with vectors or matrices on linear functions. For example:

```
sage: mip.<x> = MixedIntegerLinearProgram('ppl') # base ring is QQ
sage: 3 + x[0] + 2*x[1] # a linear function
3 + x_0 + 2*x_1
sage: x[0] * vector([3,4]) + 1 # vector linear function
(1, 1) + (3, 4)*x_0
sage: x[0] * matrix([[3,1],[4,0]]) + 1 # matrix linear function
[1 + 3*x_0 x_0]
[4*x_0 1 ]
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram('ppl', names=('x',)); (x,) = mip._first_ngens(1) #_
↳base ring is QQ
>>> Integer(3) + x[Integer(0)] + Integer(2)*x[Integer(1)] # a linear_
↳function
3 + x_0 + 2*x_1
>>> x[Integer(0)] * vector([Integer(3),Integer(4)]) + Integer(1) # vector linear_
↳function
(1, 1) + (3, 4)*x_0
>>> x[Integer(0)] * matrix([[Integer(3),Integer(1)],[Integer(4),Integer(0)]]) +_
↳Integer(1) # matrix linear function
[1 + 3*x_0 x_0]
[4*x_0 1 ]
```

Internally, all linear functions are stored as a dictionary whose

- keys are the index of the linear variable (and -1 for the constant term)
- values are the coefficient of that variable. That is, a number for linear functions, a vector for vector-valued functions, etc.

The entire dictionary can be accessed with the `dict()` method. For convenience, you can also retrieve a single coefficient with `coefficient()`. For example:

```

sage: mip.<b> = MixedIntegerLinearProgram()
sage: f_scalar = (3 + b[7] + 2*b[9]); f_scalar
3 + x_0 + 2*x_1
sage: f_scalar.dict()
{-1: 3.0, 0: 1.0, 1: 2.0}
sage: f_scalar.dict()[1]
2.0
sage: f_scalar.coefficient(b[9])
2.0
sage: f_scalar.coefficient(1)
2.0

sage: f_vector = b[7] * vector([3,4]) + 1; f_vector
(1.0, 1.0) + (3.0, 4.0)*x_0
sage: f_vector.coefficient(-1)
(1.0, 1.0)
sage: f_vector.coefficient(b[7])
(3.0, 4.0)
sage: f_vector.coefficient(0)
(3.0, 4.0)
sage: f_vector.coefficient(1)
(0.0, 0.0)

sage: f_matrix = b[7] * matrix([[0,1], [2,0]]) + b[9] - 3; f_matrix
[-3 + x_1 x_0      ]
[2*x_0      -3 + x_1]
sage: f_matrix.coefficient(-1)
[-3.0  0.0]
[ 0.0 -3.0]
sage: f_matrix.coefficient(0)
[0.0 1.0]
[2.0 0.0]
sage: f_matrix.coefficient(1)
[1.0 0.0]
[0.0 1.0]
    
```

```

>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(names=('b',)); (b,) = mip._first_ngens(1)
>>> f_scalar = (Integer(3) + b[Integer(7)] + Integer(2)*b[Integer(9)]); f_scalar
3 + x_0 + 2*x_1
>>> f_scalar.dict()
{-1: 3.0, 0: 1.0, 1: 2.0}
>>> f_scalar.dict()[Integer(1)]
2.0
>>> f_scalar.coefficient(b[Integer(9)])
2.0
>>> f_scalar.coefficient(Integer(1))
2.0

>>> f_vector = b[Integer(7)] * vector([Integer(3),Integer(4)]) + Integer(1); f_vector
(1.0, 1.0) + (3.0, 4.0)*x_0
>>> f_vector.coefficient(-Integer(1))
    
```

(continues on next page)

(continued from previous page)

```
(1.0, 1.0)
>>> f_vector.coefficient(b[Integer(7)])
(3.0, 4.0)
>>> f_vector.coefficient(Integer(0))
(3.0, 4.0)
>>> f_vector.coefficient(Integer(1))
(0.0, 0.0)

>>> f_matrix = b[Integer(7)] * matrix([[Integer(0), Integer(1)], [Integer(2),
↳Integer(0)]]) + b[Integer(9)] - Integer(3); f_matrix
[-3 + x_1 x_0      ]
[2*x_0      -3 + x_1]
>>> f_matrix.coefficient(-Integer(1))
[-3.0  0.0]
[ 0.0 -3.0]
>>> f_matrix.coefficient(Integer(0))
[0.0 1.0]
[2.0 0.0]
>>> f_matrix.coefficient(Integer(1))
[1.0 0.0]
[0.0 1.0]
```

Just like `sage.numerical.linear_functions`, (in)equalities become symbolic inequalities. See `linear_tensor_constraints` for details.

Note

For brevity, we just use `LinearTensor` in class names. It is understood that this refers to the above tensor product construction.

`sage.numerical.linear_tensor.LinearTensorParent` (*linear_functions_parent*)

Return the parent for the tensor product over the common `base_ring`.

The output is cached, so only a single parent is ever constructed for a given base ring.

INPUT:

- `free_module_parent` – a free module, like vector or matrix space
- `linear_functions_parent` – linear functions; the linear functions parent

OUTPUT:

The parent of the tensor product of a free module and linear functions over a common base ring.

EXAMPLES:

```
sage: from sage.numerical.linear_functions import LinearFunctionsParent
sage: from sage.numerical.linear_tensor import LinearTensorParent
sage: LinearTensorParent(QQ^3, LinearFunctionsParent(QQ))
Tensor product of Vector space of dimension 3 over Rational Field and Linear_
↳functions over Rational Field

sage: LinearTensorParent(ZZ^3, LinearFunctionsParent(QQ))
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```
...
ValueError: base rings must match
```

```
>>> from sage.all import *
>>> from sage.numerical.linear_functions import LinearFunctionsParent
>>> from sage.numerical.linear_tensor import LinearTensorParent
>>> LinearTensorParent(QQ**Integer(3), LinearFunctionsParent(QQ))
Tensor product of Vector space of dimension 3 over Rational Field and Linear_
↳ functions over Rational Field

>>> LinearTensorParent(ZZ**Integer(3), LinearFunctionsParent(QQ))
Traceback (most recent call last):
...
ValueError: base rings must match
```

```
class sage.numerical.linear_tensor.LinearTensorParent_class(free_module, linear_functions)
```

Bases: Parent

The parent for all linear functions over a fixed base ring.

Warning

You should use `LinearTensorParent()` to construct instances of this class.

INPUT/OUTPUT: see `LinearTensorParent()`

EXAMPLES:

```
sage: from sage.numerical.linear_tensor import LinearTensorParent_class
sage: LinearTensorParent_class
<class 'sage.numerical.linear_tensor.LinearTensorParent_class'>
```

```
>>> from sage.all import *
>>> from sage.numerical.linear_tensor import LinearTensorParent_class
>>> LinearTensorParent_class
<class 'sage.numerical.linear_tensor.LinearTensorParent_class'>
```

Element

alias of `LinearTensor`

free_module()

Return the linear functions.

See also `free_module()`.

OUTPUT:

Parent of the linear functions, one of the factors in the tensor product construction.

EXAMPLES:

```
sage: mip.<x> = MixedIntegerLinearProgram()
sage: lt = x[0] * vector(RDF, [1,2])
sage: lt.parent().free_module()
```

(continues on next page)

(continued from previous page)

```
Vector space of dimension 2 over Real Double Field
sage: lt.parent().free_module() is vector(RDF, [1,2]).parent()
True
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(names=('x',)); (x,) = mip._first_ngens(1)
>>> lt = x[Integer(0)] * vector(RDF, [Integer(1), Integer(2)])
>>> lt.parent().free_module()
Vector space of dimension 2 over Real Double Field
>>> lt.parent().free_module() is vector(RDF, [Integer(1), Integer(2)]).parent()
True
```

is_matrix_space()

Return whether the free module is a matrix space.

OUTPUT: boolean; whether the *free_module()* factor in the tensor product is a matrix space

EXAMPLES:

```
sage: mip = MixedIntegerLinearProgram()
sage: LF = mip.linear_functions_parent()
sage: LF.tensor(RDF^2).is_matrix_space()
False
sage: LF.tensor(RDF^(2,2)).is_matrix_space()
True
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram()
>>> LF = mip.linear_functions_parent()
>>> LF.tensor(RDF**Integer(2)).is_matrix_space()
False
>>> LF.tensor(RDF**(Integer(2), Integer(2))).is_matrix_space()
True
```

is_vector_space()

Return whether the free module is a vector space.

OUTPUT: boolean; whether the *free_module()* factor in the tensor product is a vector space

EXAMPLES:

```
sage: mip = MixedIntegerLinearProgram()
sage: LF = mip.linear_functions_parent()
sage: LF.tensor(RDF^2).is_vector_space()
True
sage: LF.tensor(RDF^(2,2)).is_vector_space()
False
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram()
>>> LF = mip.linear_functions_parent()
>>> LF.tensor(RDF**Integer(2)).is_vector_space()
True
```

(continues on next page)

(continued from previous page)

```
>>> LF.tensor(RDF**(Integer(2), Integer(2))).is_vector_space()
False
```

linear_functions()

Return the linear functions.

See also `free_module()`.

OUTPUT:

Parent of the linear functions, one of the factors in the tensor product construction.

EXAMPLES:

```
sage: mip.<x> = MixedIntegerLinearProgram()
sage: lt = x[0] * vector([1, 2])
sage: lt.parent().linear_functions()
Linear functions over Real Double Field
sage: lt.parent().linear_functions() is mip.linear_functions_parent()
True
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(names=('x',)); (x,) = mip._first_ngens(1)
>>> lt = x[Integer(0)] * vector([Integer(1), Integer(2)])
>>> lt.parent().linear_functions()
Linear functions over Real Double Field
>>> lt.parent().linear_functions() is mip.linear_functions_parent()
True
```

`sage.numerical.linear_tensor.is_LinearTensor(x)`

Test whether x is a tensor product of linear functions with a free module.

INPUT:

- x – anything

OUTPUT: boolean

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram()
sage: x = p.new_variable(nonnegative=False)
sage: from sage.numerical.linear_tensor import is_LinearTensor
sage: is_LinearTensor(x[0] - 2*x[2])
doctest:warning...
DeprecationWarning: The function is_LinearTensor is deprecated;
use 'isinstance(..., LinearTensor)' instead.
See https://github.com/sagemath/sage/issues/38184 for details.
False
sage: is_LinearTensor('a string')
False
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> x = p.new_variable(nonnegative=False)
```

(continues on next page)

(continued from previous page)

```
>>> from sage.numerical.linear_tensor import is_LinearTensor
>>> is_LinearTensor(x[Integer(0)] - Integer(2)*x[Integer(2)])
doctest:warning...
DeprecationWarning: The function is_LinearTensor is deprecated;
use 'isinstance(..., LinearTensor)' instead.
See https://github.com/sagemath/sage/issues/38184 for details.
False
>>> is_LinearTensor('a string')
False
```


MATRIX/VECTOR-VALUED LINEAR FUNCTIONS: ELEMENTS

Here is an example of a linear function tensored with a vector space:

```
sage: mip.<x> = MixedIntegerLinearProgram('ppl') # base ring is QQ
sage: lt = x[0] * vector([3,4]) + 1; lt
(1, 1) + (3, 4)*x_0
sage: type(lt)
<class 'sage.numerical.linear_tensor_element.LinearTensor'>
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram('ppl', names=('x',)); (x,) = mip._first_ngens(1) #_
↳base ring is QQ
>>> lt = x[Integer(0)] * vector([Integer(3),Integer(4)]) + Integer(1); lt
(1, 1) + (3, 4)*x_0
>>> type(lt)
<class 'sage.numerical.linear_tensor_element.LinearTensor'>
```

class sage.numerical.linear_tensor_element.**LinearTensor**

Bases: ModuleElement

A linear function tensored with a free module.

Warning

You should never instantiate *LinearTensor* manually. Use the element constructor in the parent instead.

EXAMPLES:

```
sage: parent = MixedIntegerLinearProgram().linear_functions_parent().tensor(RDF^2)
sage: parent({0: [1,2], 3: [-7,-8]})
(1.0, 2.0)*x_0 + (-7.0, -8.0)*x_3
```

```
>>> from sage.all import *
>>> parent = MixedIntegerLinearProgram().linear_functions_parent().
↳tensor(RDF**Integer(2))
>>> parent({Integer(0): [Integer(1),Integer(2)], Integer(3): [-Integer(7),-
↳Integer(8)]})
(1.0, 2.0)*x_0 + (-7.0, -8.0)*x_3
```

coefficient(*x*)

Return one of the coefficients.

INPUT:

- x – a linear variable or an integer. If an integer i is passed, then x_i is used as linear variable. Pass -1 for the constant term.

OUTPUT:

A constant, that is, an element of the free module factor. The coefficient of x in the linear function.

EXAMPLES:

```
sage: mip.<b> = MixedIntegerLinearProgram()
sage: lt = vector([1,2]) * b[3] + vector([4,5]) * b[0] - 5; lt
(-5.0, -5.0) + (1.0, 2.0)*x_0 + (4.0, 5.0)*x_1
sage: lt.coefficient(b[3])
(1.0, 2.0)
sage: lt.coefficient(0)      # x_0 is b[3]
(1.0, 2.0)
sage: lt.coefficient(4)
(0.0, 0.0)
sage: lt.coefficient(-1)
(-5.0, -5.0)
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(names=('b',)); (b,) = mip._first_ngens(1)
>>> lt = vector([Integer(1), Integer(2)]) * b[Integer(3)] + vector([Integer(4),
↳ Integer(5)]) * b[Integer(0)] - Integer(5); lt
(-5.0, -5.0) + (1.0, 2.0)*x_0 + (4.0, 5.0)*x_1
>>> lt.coefficient(b[Integer(3)])
(1.0, 2.0)
>>> lt.coefficient(Integer(0))      # x_0 is b[3]
(1.0, 2.0)
>>> lt.coefficient(Integer(4))
(0.0, 0.0)
>>> lt.coefficient(-Integer(1))
(-5.0, -5.0)
```

dict()

Return the dictionary corresponding to the tensor product.

OUTPUT:

The linear function tensor product is represented as a dictionary. The value are the coefficient (free module elements) of the variable represented by the keys (which are integers). The key -1 corresponds to the constant term.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram().linear_functions_parent().tensor(RDF^2)
sage: lt = p({0:[1,2], 3:[4,5]})
sage: lt.dict()
{0: (1.0, 2.0), 3: (4.0, 5.0)}
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram().linear_functions_parent().
↳ tensor(RDF**Integer(2))
```

(continues on next page)

(continued from previous page)

```
>>> lt = p({Integer(0):[Integer(1),Integer(2)], Integer(3):[Integer(4),  
↪Integer(5)]})  
>>> lt.dict()  
{0: (1.0, 2.0), 3: (4.0, 5.0)}
```


CONSTRAINTS ON LINEAR FUNCTIONS TENSORED WITH A FREE MODULE

Here is an example of a vector-valued linear function:

```
sage: mip.<x> = MixedIntegerLinearProgram('ppl') # base ring is QQ
sage: x[0] * vector([3,4]) + 1 # vector linear function
(1, 1) + (3, 4)*x_0
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram('ppl', names=('x',)); (x,) = mip._first_ngens(1) #
↳base ring is QQ
>>> x[Integer(0)] * vector([Integer(3),Integer(4)]) + Integer(1) # vector linear
↳function
(1, 1) + (3, 4)*x_0
```

Just like *linear_functions*, (in)equalities become symbolic inequalities:

```
sage: 3 + x[0] + 2*x[1] <= 10
3 + x_0 + 2*x_1 <= 10
sage: x[0] * vector([3,4]) + 1 <= 10
(1, 1) + (3, 4)*x_0 <= (10, 10)
sage: x[0] * matrix([[0,0,1],[0,1,0],[1,0,0]]) + x[1] * identity_matrix(3) >= 0
[0 0 0] [x_1 0 x_0]
[0 0 0] <= [0 x_0 + x_1 0 ]
[0 0 0] [x_0 0 x_1]
```

```
>>> from sage.all import *
>>> Integer(3) + x[Integer(0)] + Integer(2)*x[Integer(1)] <= Integer(10)
3 + x_0 + 2*x_1 <= 10
>>> x[Integer(0)] * vector([Integer(3),Integer(4)]) + Integer(1) <= Integer(10)
(1, 1) + (3, 4)*x_0 <= (10, 10)
>>> x[Integer(0)] * matrix([[Integer(0),Integer(0),Integer(1)],[Integer(0),Integer(1),
↳Integer(0)],[Integer(1),Integer(0),Integer(0)]]) + x[Integer(1)] * identity_
↳matrix(Integer(3)) >= Integer(0)
[0 0 0] [x_1 0 x_0]
[0 0 0] <= [0 x_0 + x_1 0 ]
[0 0 0] [x_0 0 x_1]
```

```
class sage.numerical.linear_tensor_constraints.LinearTensorConstraint (parent, lhs, rhs,
equality)
```

Bases: Element

Formal constraint involving two module-valued linear functions.

Note

In the code, we use “linear tensor” as abbreviation for the tensor product (over the common base ring) of a *linear function* and a free module like a vector/matrix space.

Warning

This class has no reason to be instantiated by the user, and is meant to be used by instances of *MixedIntegerLinearProgram*.

INPUT:

- `parent` – the parent, a *LinearTensorConstraintsParent_class*
- `lhs, rhs` – two *sage.numerical.linear_tensor_element.LinearTensor*. The left and right hand side of the constraint (in)equality.
- `equality` – boolean (default: `False`); whether the constraint is an equality. If `False`, it is a `<=` inequality.

EXAMPLES:

```
sage: mip.<b> = MixedIntegerLinearProgram()
sage: (b[2]+2*b[3]) * vector([1,2]) <= b[8] * vector([2,3]) - 5
(1.0, 2.0)*x_0 + (2.0, 4.0)*x_1 <= (-5.0, -5.0) + (2.0, 3.0)*x_2
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(names=('b',)); (b,) = mip._first_ngens(1)
>>> (b[Integer(2)]+Integer(2)*b[Integer(3)]) * vector([Integer(1),Integer(2)]) <=
↳b[Integer(8)] * vector([Integer(2),Integer(3)]) - Integer(5)
(1.0, 2.0)*x_0 + (2.0, 4.0)*x_1 <= (-5.0, -5.0) + (2.0, 3.0)*x_2
```

`is_equation()`

Whether the constraint is a chained equation.

OUTPUT: boolean

EXAMPLES:

```
sage: mip.<b> = MixedIntegerLinearProgram()
sage: (b[0] * vector([1,2]) == 0).is_equation()
True
sage: (b[0] * vector([1,2]) >= 0).is_equation()
False
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(names=('b',)); (b,) = mip._first_ngens(1)
>>> (b[Integer(0)] * vector([Integer(1),Integer(2)]) == Integer(0)).is_
↳equation()
True
>>> (b[Integer(0)] * vector([Integer(1),Integer(2)]) >= Integer(0)).is_
↳equation()
False
```

is_less_or_equal()

Whether the constraint is a chained less-or_equal inequality.

OUTPUT: boolean

EXAMPLES:

```
sage: mip.<b> = MixedIntegerLinearProgram()
sage: (b[0] * vector([1,2]) == 0).is_less_or_equal()
False
sage: (b[0] * vector([1,2]) >= 0).is_less_or_equal()
True
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(names=('b',)); (b,) = mip._first_ngens(1)
>>> (b[Integer(0)] * vector([Integer(1), Integer(2)]) == Integer(0)).is_less_
↳ or_equal()
False
>>> (b[Integer(0)] * vector([Integer(1), Integer(2)]) >= Integer(0)).is_less_
↳ or_equal()
True
```

lhs()

Return the left side of the (in)equality.

OUTPUT:

Instance of *sage.numerical.linear_tensor_element.LinearTensor*. A linear function valued in a free module.

EXAMPLES:

```
sage: mip.<x> = MixedIntegerLinearProgram()
sage: (x[0] * vector([1,2]) == 0).lhs()
(1.0, 2.0)*x_0
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(names=('x',)); (x,) = mip._first_ngens(1)
>>> (x[Integer(0)] * vector([Integer(1), Integer(2)]) == Integer(0)).lhs()
(1.0, 2.0)*x_0
```

rhs()

Return the right side of the (in)equality.

OUTPUT:

Instance of *sage.numerical.linear_tensor_element.LinearTensor*. A linear function valued in a free module.

EXAMPLES:

```
sage: mip.<x> = MixedIntegerLinearProgram()
sage: (x[0] * vector([1,2]) == 0).rhs()
(0.0, 0.0)
```

```

>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(names=('x',)); (x,) = mip._first_ngens(1)
>>> (x[Integer(0)] * vector([Integer(1), Integer(2)]) == Integer(0)).rhs()
(0.0, 0.0)
    
```

`sage.numerical.linear_tensor_constraints.LinearTensorConstraintsParent()`

Return the parent for linear functions over `base_ring`.

The output is cached, so only a single parent is ever constructed for a given base ring.

INPUT:

- `linear_functions_parent` – a `LinearFunctionsParent_class`. The type of linear functions that the constraints are made out of.

OUTPUT: the parent of the linear constraints with the given linear functions

EXAMPLES:

```

sage: from sage.numerical.linear_functions import LinearFunctionsParent
sage: from sage.numerical.linear_tensor import LinearTensorParent
sage: from sage.numerical.linear_tensor_constraints import      ....:  _
↳LinearTensorConstraintsParent, LinearTensorConstraintsParent
sage: LF = LinearFunctionsParent(QQ)
sage: LT = LinearTensorParent(QQ^2, LF)
sage: LinearTensorConstraintsParent(LT)
Linear constraints in the tensor product of Vector space of dimension 2
over Rational Field and Linear functions over Rational Field
    
```

```

>>> from sage.all import *
>>> from sage.numerical.linear_functions import LinearFunctionsParent
>>> from sage.numerical.linear_tensor import LinearTensorParent
>>> from sage.numerical.linear_tensor_constraints import      Ellipsis.:  _
↳LinearTensorConstraintsParent, LinearTensorConstraintsParent
>>> LF = LinearFunctionsParent(QQ)
>>> LT = LinearTensorParent(QQ**Integer(2), LF)
>>> LinearTensorConstraintsParent(LT)
Linear constraints in the tensor product of Vector space of dimension 2
over Rational Field and Linear functions over Rational Field
    
```

`class sage.numerical.linear_tensor_constraints.LinearTensorConstraintsParent_class` (*linear_tensor_constraints.Parent*)

Bases: `Parent`

Parent for `LinearTensorConstraint`.

Warning

This class has no reason to be instantiated by the user, and is meant to be used by instances of `MixedIntegerLinearProgram`. Also, use the `LinearTensorConstraintsParent()` factory function.

INPUT/OUTPUT: see `LinearTensorConstraintsParent()`

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram()
sage: LT = p.linear_functions_parent().tensor(RDF^2); LT
Tensor product of Vector space of dimension 2 over Real Double
Field and Linear functions over Real Double Field
sage: from sage.numerical.linear_tensor_constraints import _
↳LinearTensorConstraintsParent
sage: LTC = LinearTensorConstraintsParent(LT); LTC
Linear constraints in the tensor product of Vector space of
dimension 2 over Real Double Field and Linear functions over
Real Double Field
sage: type(LTC)
<class 'sage.numerical.linear_tensor_constraints.LinearTensorConstraintsParent_
↳class'>

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram()
>>> LT = p.linear_functions_parent().tensor(RDF**Integer(2)); LT
Tensor product of Vector space of dimension 2 over Real Double
Field and Linear functions over Real Double Field
>>> from sage.numerical.linear_tensor_constraints import _
↳LinearTensorConstraintsParent
>>> LTC = LinearTensorConstraintsParent(LT); LTC
Linear constraints in the tensor product of Vector space of
dimension 2 over Real Double Field and Linear functions over
Real Double Field
>>> type(LTC)
<class 'sage.numerical.linear_tensor_constraints.LinearTensorConstraintsParent_
↳class'>

```

Element

alias of *LinearTensorConstraint*

linear_functions()

Return the parent for the linear functions.

OUTPUT: instance of *sage.numerical.linear_functions.LinearFunctionsParent_class*

EXAMPLES:

```

sage: mip.<x> = MixedIntegerLinearProgram()
sage: ieq = (x[0] * vector([1,2]) >= 0)
sage: ieq.parent().linear_functions()
Linear functions over Real Double Field

```

```

>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(names=('x',)); (x,) = mip._first_ngens(1)
>>> ieq = (x[Integer(0)] * vector([Integer(1), Integer(2)]) >= Integer(0))
>>> ieq.parent().linear_functions()
Linear functions over Real Double Field

```

linear_tensors()

Return the parent for the linear functions.

OUTPUT: instance of `sage.numerical.linear_tensor.LinearTensorParent_class`

EXAMPLES:

```
sage: mip.<x> = MixedIntegerLinearProgram()
sage: ieq = (x[0] * vector([1,2]) >= 0)
sage: ieq.parent().linear_tensors()
Tensor product of Vector space of dimension 2 over Real Double
Field and Linear functions over Real Double Field
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(names=('x',)); (x,) = mip._first_ngens(1)
>>> ieq = (x[Integer(0)] * vector([Integer(1), Integer(2)]) >= Integer(0))
>>> ieq.parent().linear_tensors()
Tensor product of Vector space of dimension 2 over Real Double
Field and Linear functions over Real Double Field
```

`sage.numerical.linear_tensor_constraints.is_LinearTensorConstraint(x)`

Test whether `x` is a constraint on module-valued linear functions.

INPUT:

- `x` – anything

OUTPUT: boolean

EXAMPLES:

```
sage: mip.<x> = MixedIntegerLinearProgram()
sage: vector_ineq = (x[0] * vector([1,2]) <= x[1] * vector([2,3]))
sage: from sage.numerical.linear_tensor_constraints import is_
↳LinearTensorConstraint
sage: is_LinearTensorConstraint(vector_ineq)
doctest:warning...
DeprecationWarning: The function is_LinearTensorConstraint is deprecated;
use 'isinstance(..., LinearTensorConstraint)' instead.
See https://github.com/sagemath/sage/issues/38184 for details.
True
sage: is_LinearTensorConstraint('a string')
False
```

```
>>> from sage.all import *
>>> mip = MixedIntegerLinearProgram(names=('x',)); (x,) = mip._first_ngens(1)
>>> vector_ineq = (x[Integer(0)] * vector([Integer(1), Integer(2)]) <=
↳x[Integer(1)] * vector([Integer(2), Integer(3)]))
>>> from sage.numerical.linear_tensor_constraints import is_LinearTensorConstraint
>>> is_LinearTensorConstraint(vector_ineq)
doctest:warning...
DeprecationWarning: The function is_LinearTensorConstraint is deprecated;
use 'isinstance(..., LinearTensorConstraint)' instead.
See https://github.com/sagemath/sage/issues/38184 for details.
True
>>> is_LinearTensorConstraint('a string')
False
```

NUMERICAL ROOT FINDING AND OPTIMIZATION

AUTHOR:

- William Stein (2007): initial version
- Nathann Cohen (2008): Bin Packing

8.1 Functions and Methods

`sage.numerical.optimize.binpacking` (*items*, *maximum*, *k=1*, *solver=None*, *verbose=None*,
integrality_tolerance=0)

Solve the bin packing problem.

The Bin Packing problem is the following :

Given a list of items of weights p_i and a real value k , what is the least number of bins such that all the items can be packed in the bins, while ensuring that the sum of the weights of the items packed in each bin is at most k ?

For more informations, see [Wikipedia article Bin_packing_problem](#).

Two versions of this problem are solved by this algorithm :

- Is it possible to put the given items in k bins ?
- What is the assignment of items using the least number of bins with the given list of items ?

INPUT:

- *items* – list or dict; either a list of real values (the items' weight), or a dictionary associating to each item its weight
- *maximum* – (default: 1) the maximal size of a bin
- *k* – integer (default: `None`); number of bins:
 - When set to an integer value, the function returns a partition of the items into k bins if possible, and raises an exception otherwise.
 - When set to `None`, the function returns a partition of the items using the least possible number of bins.
- *solver* – (default: `None`) specify a Mixed Integer Linear Programming (MILP) solver to be used. If set to `None`, the default one is used. For more information on MILP solvers and which default solver is used, see the method `solve` of the class `MixedIntegerLinearProgram`.
- *verbose* – integer (default: 0); sets the level of verbosity. Set to 0 by default, which means quiet.
- *integrality_tolerance* – parameter for use with MILP solvers over an inexact base ring; see `MixedIntegerLinearProgram.get_values()`

OUTPUT:

A list of lists, each member corresponding to a bin and containing either the list of the weights inside it when `items` is a list of items' weight, or the list of items inside it when `items` is a dictionary. If there is no solution, an exception is raised (this can only happen when `k` is specified or if `maximum` is less than the weight of one item).

EXAMPLES:

Trying to find the minimum amount of boxes for 5 items of weights $1/5, 1/4, 2/3, 3/4, 5/7$:

```
sage: from sage.numerical.optimize import binpacking
sage: values = [1/5, 1/3, 2/3, 3/4, 5/7]
sage: bins = binpacking(values) #_
↳needs sage.numerical.mip
sage: len(bins) #_
↳needs sage.numerical.mip
3
```

```
>>> from sage.all import *
>>> from sage.numerical.optimize import binpacking
>>> values = [Integer(1)/Integer(5), Integer(1)/Integer(3), Integer(2)/Integer(3),
↳ Integer(3)/Integer(4), Integer(5)/Integer(7)]
>>> bins = binpacking(values) #_
↳needs sage.numerical.mip
>>> len(bins) #_
↳needs sage.numerical.mip
3
```

Checking the bins are of correct size

```
sage: all(sum(b) <= 1 for b in bins) #_
↳needs sage.numerical.mip
True
```

```
>>> from sage.all import *
>>> all(sum(b) <= Integer(1) for b in bins) #_
↳ # needs sage.numerical.mip
True
```

Checking every item is in a bin

```
sage: b1, b2, b3 = bins #_
↳needs sage.numerical.mip
sage: all((v in b1 or v in b2 or v in b3) for v in values) #_
↳needs sage.numerical.mip
True
```

```
>>> from sage.all import *
>>> b1, b2, b3 = bins #_
↳needs sage.numerical.mip
>>> all((v in b1 or v in b2 or v in b3) for v in values) #_
↳needs sage.numerical.mip
True
```

And only in one bin

```
sage: sum(len(b) for b in bins) == len(values) #_
↳needs sage.numerical.mip
True
```

```
>>> from sage.all import *
>>> sum(len(b) for b in bins) == len(values) #_
↳needs sage.numerical.mip
True
```

One way to use only three boxes (which is best possible) is to put $1/5 + 3/4$ together in a box, $1/3 + 2/3$ in another, and $5/7$ by itself in the third one.

Of course, we can also check that there is no solution using only two boxes

```
sage: from sage.numerical.optimize import binpacking
sage: binpacking([0.2,0.3,0.8,0.9], k=2) #_
↳needs sage.numerical.mip
Traceback (most recent call last):
...
ValueError: this problem has no solution
```

```
>>> from sage.all import *
>>> from sage.numerical.optimize import binpacking
>>> binpacking([RealNumber('0.2'), RealNumber('0.3'), RealNumber('0.8'), RealNumber('0.9')], k=Integer(2)) # needs sage.
↳numerical.mip
Traceback (most recent call last):
...
ValueError: this problem has no solution
```

We can also provide a dictionary keyed by items and associating to each item its weight. Then, the bins contain the name of the items inside it

```
sage: values = {'a':1/5, 'b':1/3, 'c':2/3, 'd':3/4, 'e':5/7}
sage: bins = binpacking(values) #_
↳needs sage.numerical.mip
sage: set(flatten(bins)) == set(values.keys()) #_
↳needs sage.numerical.mip
True
```

```
>>> from sage.all import *
>>> values = {'a':Integer(1)/Integer(5), 'b':Integer(1)/Integer(3), 'c'
↳':Integer(2)/Integer(3), 'd':Integer(3)/Integer(4), 'e':Integer(5)/Integer(7)}
>>> bins = binpacking(values) #_
↳needs sage.numerical.mip
>>> set(flatten(bins)) == set(values.keys()) #_
↳needs sage.numerical.mip
True
```

sage.numerical.optimize.**find_fit**(*data*, *model*, *initial_guess=None*, *parameters=None*, *variables=None*, *solution_dict=False*)

Finds numerical estimates for the parameters of the function model to give a best fit to data.

INPUT:

- `data` – a two dimensional table of floating point numbers of the form $[[x_{1,1}, x_{1,2}, \dots, x_{1,k}, f_1], [x_{2,1}, x_{2,2}, \dots, x_{2,k}, f_2], \dots, [x_{n,1}, x_{n,2}, \dots, x_{n,k}, f_n]]$ given as either a list of lists, matrix, or numpy array.
- `model` – either a symbolic expression, symbolic function, or a Python function. `model` has to be a function of the variables (x_1, x_2, \dots, x_k) and free parameters (a_1, a_2, \dots, a_l) .
- `initial_guess` – (default: `None`) initial estimate for the parameters (a_1, a_2, \dots, a_l) , given as either a list, tuple, vector or numpy array. If `None`, the default estimate for each parameter is 1.
- `parameters` – (default: `None`) a list of the parameters (a_1, a_2, \dots, a_l) . If `model` is a symbolic function it is ignored, and the free parameters of the symbolic function are used.
- `variables` – (default: `None`) a list of the variables (x_1, x_2, \dots, x_k) . If `model` is a symbolic function it is ignored, and the variables of the symbolic function are used.
- `solution_dict` – boolean (default: `False`); if `True`, return the solution as a dictionary rather than an equation

EXAMPLES:

First we create some data points of a sine function with some “random” perturbations:

```
sage: set_random_seed(0)
sage: data = [(i, 1.2 * sin(0.5*i-0.2) + 0.1 * normalvariate(0, 1)) #_
↳needs sage.symbolic
.....:         for i in xrange(0, 4*pi, 0.2)]
sage: var('a, b, c, x') #_
↳needs sage.symbolic
(a, b, c, x)
```

```
>>> from sage.all import *
>>> set_random_seed(Integer(0))
>>> data = [(i, RealNumber('1.2') * sin(RealNumber('0.5')*i-RealNumber('0.2')) +_
↳RealNumber('0.1') * normalvariate(Integer(0), Integer(1))) # needs_
↳sage.symbolic
...         for i in xrange(Integer(0), Integer(4)*pi, RealNumber('0.2'))]
>>> var('a, b, c, x') #_
↳needs sage.symbolic
(a, b, c, x)
```

We define a function with free parameters a , b and c :

```
sage: model(x) = a * sin(b * x - c) #_
↳needs sage.symbolic
```

```
>>> from sage.all import *
>>> __tmp__=var("x"); model = symbolic_expression(a * sin(b * x - c) #_
↳                                     ).function(x) # needs sage.symbolic
```

We search for the parameters that give the best fit to the data:

```
sage: find_fit(data, model) #_
↳needs sage.symbolic
[a == 1.21..., b == 0.49..., c == 0.19...]
```

```
>>> from sage.all import *
>>> find_fit(data, model) #_
↳needs sage.symbolic
[a == 1.21..., b == 0.49..., c == 0.19...]
```

We can also use a Python function for the model:

```
sage: def f(x, a, b, c): return a * sin(b * x - c)
sage: fit = find_fit(data, f, parameters=[a, b, c], variables=[x], #_
↳needs sage.symbolic
.....:         solution_dict = True)
sage: fit[a], fit[b], fit[c] #_
↳needs sage.symbolic
(1.21..., 0.49..., 0.19...)
```

```
>>> from sage.all import *
>>> def f(x, a, b, c): return a * sin(b * x - c)
>>> fit = find_fit(data, f, parameters=[a, b, c], variables=[x], #_
↳needs sage.symbolic
...         solution_dict = True)
>>> fit[a], fit[b], fit[c] #_
↳needs sage.symbolic
(1.21..., 0.49..., 0.19...)
```

We search for a formula for the n -th prime number:

```
sage: # needs sage.libs.pari
sage: dataprime = [(i, nth_prime(i)) for i in range(1, 5000, 100)]
sage: find_fit(dataprime, a * x * log(b * x), #_
↳needs sage.symbolic
.....:         parameters=[a, b], variables=[x])
[a == 1.11..., b == 1.24...]
```

```
>>> from sage.all import *
>>> # needs sage.libs.pari
>>> dataprime = [(i, nth_prime(i)) for i in range(Integer(1), Integer(5000), #_
↳Integer(100))]
>>> find_fit(dataprime, a * x * log(b * x), #_
↳needs sage.symbolic
...         parameters=[a, b], variables=[x])
[a == 1.11..., b == 1.24...]
```

ALGORITHM:

Uses `scipy.optimize.leastsq()` which in turn uses MINPACK's `lmdif` and `lmdcr` algorithms.

`sage.numerical.optimize.find_local_maximum(f, a, b, tol=1.48e-08, maxfun=500)`

Numerically find a local maximum of the expression f on the interval $[a, b]$ (or $[b, a]$) along with the point at which the maximum is attained.

Note that this function only finds a *local* maximum, and not the global maximum on that interval – see the examples with `find_local_maximum()`.

See the documentation for `find_local_maximum()` for more details and possible workarounds for finding the global minimum on an interval.

EXAMPLES:

```

sage: f = lambda x: x*cos(x)
sage: find_local_maximum(f, 0, 5)
(0.561096338191..., 0.8603335890...)
sage: find_local_maximum(f, 0, 5, tol=0.1, maxfun=10)
(0.561090323458..., 0.857926501456...)
sage: find_local_maximum(8*e^(-x)*sin(x) - 1, 0, 7) #_
↳needs sage.symbolic
(1.579175535558..., 0.7853981...)
    
```

```

>>> from sage.all import *
>>> f = lambda x: x*cos(x)
>>> find_local_maximum(f, Integer(0), Integer(5))
(0.561096338191..., 0.8603335890...)
>>> find_local_maximum(f, Integer(0), Integer(5), tol=RealNumber('0.1'),_
↳maxfun=Integer(10))
(0.561090323458..., 0.857926501456...)
>>> find_local_maximum(Integer(8)*e**(-x)*sin(x) - Integer(1), Integer(0),_
↳Integer(7)) # needs sage.symbolic
(1.579175535558..., 0.7853981...)
    
```

sage.numerical.optimize.**find_local_minimum**(f , a , b , $tol=1.48e-08$, $maxfun=500$)

Numerically find a local minimum of the expression f on the interval $[a, b]$ (or $[b, a]$) and the point at which it attains that minimum. Note that f must be a function of (at most) one variable.

Note that this function only finds a *local* minimum, and not the global minimum on that interval – see the examples below.

INPUT:

- f – a function of at most one variable
- a, b – endpoints of interval on which to minimize f
- tol – the convergence tolerance
- $maxfun$ – maximum function evaluations

OUTPUT:

- $minval$ – (float) the minimum value that f takes on in the interval $[a, b]$
- x – (float) the point at which f takes on the minimum value

EXAMPLES:

```

sage: f = lambda x: x*cos(x)
sage: find_local_minimum(f, 1, 5)
(-3.28837139559..., 3.4256184695...)
sage: find_local_minimum(f, 1, 5, tol=1e-3)
(-3.28837136189098..., 3.42575079030572...)
sage: find_local_minimum(f, 1, 5, tol=1e-2, maxfun=10)
(-3.28837084598..., 3.4250840220...)
sage: show(plot(f, 0, 20)) #_
↳needs sage.plot
sage: find_local_minimum(f, 1, 15)
(-9.4772942594..., 9.5293344109...)
    
```

```

>>> from sage.all import *
>>> f = lambda x: x*cos(x)
>>> find_local_minimum(f, Integer(1), Integer(5))
(-3.28837139559..., 3.4256184695...)
>>> find_local_minimum(f, Integer(1), Integer(5), tol=RealNumber('1e-3'))
(-3.28837136189098..., 3.42575079030572...)
>>> find_local_minimum(f, Integer(1), Integer(5), tol=RealNumber('1e-2'),
↳maxfun=Integer(10))
(-3.28837084598..., 3.4250840220...)
>>> show(plot(f, Integer(0), Integer(20)))
↳
↳ # needs sage.plot
>>> find_local_minimum(f, Integer(1), Integer(15))
(-9.4772942594..., 9.5293344109...)

```

Only local minima are found; if you enlarge the interval, the returned minimum may be *larger*! See [Issue #2607](#).

```

sage: # needs sage.symbolic
sage: f(x) = -x*sin(x^2)
sage: find_local_minimum(f, -2.5, -1)
(-2.182769784677722, -2.1945027498534686)

```

```

>>> from sage.all import *
>>> # needs sage.symbolic
>>> __tmp__=var("x"); f = symbolic_expression(-x*sin(x**Integer(2))).function(x)
>>> find_local_minimum(f, -RealNumber('2.5'), -Integer(1))
(-2.182769784677722, -2.1945027498534686)

```

Enlarging the interval returns a larger minimum:

```

sage: # needs sage.symbolic
sage: find_local_minimum(f, -2.5, 2)
(-1.3076194129914434, 1.3552111405712108)

```

```

>>> from sage.all import *
>>> # needs sage.symbolic
>>> find_local_minimum(f, -RealNumber('2.5'), Integer(2))
(-1.3076194129914434, 1.3552111405712108)

```

One work-around is to plot the function and grab the minimum from that, although the plotting code does not necessarily do careful numerics (observe the small number of decimal places that we actually test):

```

sage: # needs sage.plot sage.symbolic
sage: plot(f, (x, -2.5, -1)).ymin()
-2.182...
sage: plot(f, (x, -2.5, 2)).ymin()
-2.182...

```

```

>>> from sage.all import *
>>> # needs sage.plot sage.symbolic
>>> plot(f, (x, -RealNumber('2.5'), -Integer(1))).ymin()
-2.182...
>>> plot(f, (x, -RealNumber('2.5'), Integer(2))).ymin()
-2.182...

```

ALGORITHM:

Uses `scipy.optimize.fminbound()` which uses Brent's method.

AUTHOR:

- William Stein (2007-12-07)

```
sage.numerical.optimize.find_root(f, a, b, xtol=1e-12, rtol=8.81784197001252e-16, maxiter=100,
                                full_output=False)
```

Numerically find a root of f on the closed interval $[a, b]$ (or $[b, a]$) if possible, where f is a function in the one variable. Note: this function only works in fixed (machine) precision, it is not possible to get arbitrary precision approximations with it.

INPUT:

- f – a function of one variable or symbolic equality
- a, b – endpoints of the interval
- $xtol, rtol$ – the routine converges when a root is known to lie within $xtol$ of the value return. Should be ≥ 0 . The routine modifies this to take into account the relative precision of doubles. By default, $rtol$ is $4 * \text{numpy.finfo(float).eps}$, the minimum allowed value for `scipy.optimize.brentq()`, which is what this method uses underneath. This value is equal to 2.0^{*-50} for IEEE-754 double precision floats as used by Python.
- $maxiter$ – integer; if convergence is not achieved in $maxiter$ iterations, an error is raised. Must be ≥ 0 .
- $full_output$ – boolean (default: `False`); if `True`, also return object that contains information about convergence

EXAMPLES:

An example involving an algebraic polynomial function:

```
sage: R.<x> = QQ[]
sage: f = (x+17)*(x-3)*(x-1/8)^3
sage: find_root(f, 0,4)
2.999999999999995
sage: find_root(f, 0,1) # abs tol 1e-6 (note -- precision of answer isn't very_
->good on some machines)
0.124999
sage: find_root(f, -20,-10)
-17.0
```

```
>>> from sage.all import *
>>> R = QQ['x']; (x,) = R._first_ngens(1)
>>> f = (x+Integer(17))*(x-Integer(3))*(x-Integer(1)/Integer(8))**Integer(3)
>>> find_root(f, Integer(0),Integer(4))
2.999999999999995
>>> find_root(f, Integer(0),Integer(1)) # abs tol 1e-6 (note -- precision of_
->answer isn't very good on some machines)
0.124999
>>> find_root(f, -Integer(20),-Integer(10))
-17.0
```

In Pomerance's book on primes he asserts that the famous Riemann Hypothesis is equivalent to the statement that the function $f(x)$ defined below is positive for all $x \geq 2.01$:

```
sage: def f(x):
.....:     return sqrt(x) * log(x) - abs(Li(x) - prime_pi(x))
```

```
>>> from sage.all import *
>>> def f(x):
...     return sqrt(x) * log(x) - abs(Li(x) - prime_pi(x))
```

We find where f equals, i.e., what value that is slightly smaller than 2.01 that could have been used in the formulation of the Riemann Hypothesis:

```
sage: find_root(f, 2, 4, rtol=0.0001)
2.0082...
```

```
>>> from sage.all import *
>>> find_root(f, Integer(2), Integer(4), rtol=RealNumber('0.0001'))
2.0082...
```

This agrees with the plot:

```
sage: plot(f, 2, 2.01)
Graphics object consisting of 1 graphics primitive
```

```
>>> from sage.all import *
>>> plot(f, Integer(2), RealNumber('2.01'))
Graphics object consisting of 1 graphics primitive
```

The following example was added due to [Issue #4942](#) and demonstrates that the function need not be defined at the endpoints:

```
sage: find_root(x^2*log(x,2)-1,0, 2) # abs tol 1e-6
1.41421356237
```

```
>>> from sage.all import *
>>> find_root(x**Integer(2)*log(x,Integer(2))-Integer(1),Integer(0), Integer(2))
↪ # abs tol 1e-6
1.41421356237
```

The following is an example, again from [Issue #4942](#) where Brent's method fails. Currently no other method is implemented, but at least we acknowledge the fact that the algorithm fails:

```
sage: find_root(1/(x-1)+1,0, 2)
0.0
sage: find_root(1/(x-1)+1,0.00001, 2)
Traceback (most recent call last):
...
NotImplementedError: Brent's method failed to find a zero for f on the interval
```

```
>>> from sage.all import *
>>> find_root(Integer(1)/(x-Integer(1))+Integer(1),Integer(0), Integer(2))
0.0
>>> find_root(Integer(1)/(x-Integer(1))+Integer(1),RealNumber('0.00001'), ↪
↪ Integer(2))
```

(continues on next page)

(continued from previous page)

```
Traceback (most recent call last):
...
NotImplementedError: Brent's method failed to find a zero for f on the interval
```

An example of a function which evaluates to NaN on the entire interval:

```
sage: f(x) = 0.0 / max(0, x)
sage: find_root(f, -1, 0)
Traceback (most recent call last):
...
RuntimeError: f appears to have no zero on the interval
```

```
>>> from sage.all import *
>>> __tmp__=var("x"); f = symbolic_expression(RealNumber('0.0') / max(Integer(0), u
↪x)).function(x)
>>> find_root(f, -Integer(1), Integer(0))
Traceback (most recent call last):
...
RuntimeError: f appears to have no zero on the interval
```

```
sage.numerical.optimize.minimize(func, x0, gradient=None, hessian=None, algorithm='default',
                               verbose=False, **args)
```

This function is an interface to a variety of algorithms for computing the minimum of a function of several variables.

INPUT:

- `func` – either a symbolic function or a Python function whose argument is a tuple with n components
- `x0` – initial point for finding minimum
- `gradient` – (optional) gradient function. This will be computed automatically for symbolic functions. For Python functions, it allows the use of algorithms requiring derivatives. It should accept a tuple of arguments and return a NumPy array containing the partial derivatives at that point.
- `hessian` – (optional) hessian function. This will be computed automatically for symbolic functions. For Python functions, it allows the use of algorithms requiring derivatives. It should accept a tuple of arguments and return a NumPy array containing the second partial derivatives of the function.
- `algorithm` – string specifying algorithm to use. Options are 'default' (for Python functions, the simplex method is the default) (for symbolic functions bfgs is the default):
 - 'simplex' – using the downhill simplex algorithm
 - 'powell' – use the modified Powell algorithm
 - 'bfgs' – (Broyden-Fletcher-Goldfarb-Shanno) requires gradient
 - 'cg' – (conjugate-gradient) requires gradient
 - 'ncg' – (newton-conjugate gradient) requires gradient and hessian
- `verbose` – boolean (default: False); print convergence message

Note

For additional information on the algorithms implemented in this function, consult SciPy's [documentation on optimization and root finding](#).

EXAMPLES:

Minimize a fourth order polynomial in three variables (see the [Wikipedia article Rosenbrock_function](#)):

```
sage: vars = var('x y z') #_
↳needs sage.symbolic
sage: f = 100*(y-x^2)^2 + (1-x)^2 + 100*(z-y^2)^2 + (1-y)^2 #_
↳needs sage.symbolic
sage: minimize(f, [.1, .3, .4]) # abs tol 1e-6 #_
↳needs sage.symbolic
(1.0, 1.0, 1.0)
```

```
>>> from sage.all import *
>>> vars = var('x y z') #_
↳needs sage.symbolic
>>> f = Integer(100)*(y-x**Integer(2))**Integer(2) + (Integer(1)-x)**Integer(2) +_
↳Integer(100)*(z-y**Integer(2))**Integer(2) + (Integer(1)-y)**Integer(2) #_
↳ # needs sage.symbolic
>>> minimize(f, [RealNumber('.1'), RealNumber('.3'), RealNumber('.4')]) # abs tol_
↳1e-6 # needs sage.symbolic
(1.0, 1.0, 1.0)
```

Try the newton-conjugate gradient method; the gradient and hessian are computed automatically:

```
sage: minimize(f, [.1, .3, .4], algorithm='ncg') # abs tol 1e-6 #_
↳needs sage.symbolic
(1.0, 1.0, 1.0)
```

```
>>> from sage.all import *
>>> minimize(f, [RealNumber('.1'), RealNumber('.3'), RealNumber('.4')], algorithm=_
↳'ncg') # abs tol 1e-6 # needs sage.symbolic
(1.0, 1.0, 1.0)
```

We get additional convergence information with the *verbose* option:

```
sage: minimize(f, [.1, .3, .4], algorithm='ncg', verbose=True) #_
↳needs sage.symbolic
Optimization terminated successfully.
...
(0.9999999..., 0.9999999..., 0.9999999...)
```

```
>>> from sage.all import *
>>> minimize(f, [RealNumber('.1'), RealNumber('.3'), RealNumber('.4')], algorithm=_
↳'ncg', verbose=True) # needs sage.symbolic
Optimization terminated successfully.
...
(0.9999999..., 0.9999999..., 0.9999999...)
```

Same example with just Python functions:

```
sage: def rosen(x): # The Rosenbrock function
.....:     return sum(100.0r*(x[1r:]-x[:-1r]**2.0r)**2.0r + (1r-x[:-1r])**2.0r)
sage: minimize(rosen, [.1, .3, .4]) # abs tol 3e-5
(1.0, 1.0, 1.0)
```

```

>>> from sage.all import *
>>> def rosen(x): # The Rosenbrock function
...     return sum(100.0*(x[1:]-x[:-1])**2.0)**2.0 + (1-x[:-1])**2.0
>>> minimize(rosen, [RealNumber('.1'),RealNumber('.3'),RealNumber('.4')]) # abs_
↳tol 3e-5
(1.0, 1.0, 1.0)
    
```

Same example with a pure Python function and a Python function to compute the gradient:

```

sage: # needs numpy
sage: def rosen(x): # The Rosenbrock function
.....:     return sum(100.0r*(x[1r:]-x[:-1r])**2.0r + (1r-x[:-1r])**2.0r)
sage: import numpy
sage: if int(numpy.version.short_version[0]) > 1:
.....:     _ = numpy.set_printoptions(legacy="1.25")
sage: from numpy import zeros
sage: def rosen_der(x):
.....:     xm = x[1r:-1r]
.....:     xm_m1 = x[:-2r]
.....:     xm_p1 = x[2r:]
.....:     der = zeros(x.shape, dtype=float)
.....:     der[1r:-1r] = 200r*(xm-xm_m1**2r) - 400r*(xm_p1 - xm**2r)*xm - 2r*(1r-xm)
.....:     der[0] = -400r*x[0r]*(x[1r]-x[0r]**2r) - 2r*(1r-x[0])
.....:     der[-1] = 200r*(x[-1r]-x[-2r]**2r)
.....:     return der
sage: minimize(rosen, [.1,.3,.4], gradient=rosen_der, # abs tol 1e-6
.....:           algorithm='bfgs')
(1.0, 1.0, 1.0)
    
```

```

>>> from sage.all import *
>>> # needs numpy
>>> def rosen(x): # The Rosenbrock function
...     return sum(100.0*(x[1:]-x[:-1])**2.0 + (1-x[:-1])**2.0)
>>> import numpy
>>> if int(numpy.version.short_version[Integer(0)]) > Integer(1):
...     _ = numpy.set_printoptions(legacy="1.25")
>>> from numpy import zeros
>>> def rosen_der(x):
...     xm = x[1:-1]
...     xm_m1 = x[:-2]
...     xm_p1 = x[2:]
...     der = zeros(x.shape, dtype=float)
...     der[1:-1] = 200*(xm-xm_m1**2) - 400*(xm_p1 - xm**2)*xm - 2*(1-xm)
...     der[Integer(0)] = -400*x[0]*(x[1]-x[0]**2) - 2*(1-x[Integer(0)])
...     der[-Integer(1)] = 200*(x[-1]-x[-2]**2)
...     return der
>>> minimize(rosen, [RealNumber('.1'),RealNumber('.3'),RealNumber('.4')],_
↳gradient=rosen_der, # abs tol 1e-6
...     algorithm='bfgs')
(1.0, 1.0, 1.0)
    
```

```

sage.numerical.optimize.minimize_constrained(func, cons, x0, gradient=None, algorithm='default',
**args)
    
```

Minimize a function with constraints.

INPUT:

- `func` – either a symbolic function, or a Python function whose argument is a tuple with n components
- `cons` – constraints. This should be either a function or list of functions that must be positive. Alternatively, the constraints can be specified as a list of intervals that define the region we are minimizing in. If the constraints are specified as functions, the functions should be functions of a tuple with n components (assuming n variables). If the constraints are specified as a list of intervals and there are no constraints for a given variable, that component can be `(None, None)`.
- `x0` – initial point for finding minimum
- `algorithm` – (optional) specify the algorithm to use:
 - `'default'` – default choices
 - `'l-bfgs-b'` – only effective if you specify bound constraints; see [ZBN1997]
- `gradient` – (optional) gradient function. This will be computed automatically for symbolic functions. This is only used when the constraints are specified as a list of intervals.

EXAMPLES:

Let us maximize $x + y - 50$ subject to the following constraints: $50x + 24y \leq 2400$, $30x + 33y \leq 2100$, $x \geq 45$, and $y \geq 5$:

```
sage: f = lambda p: -p[0]-p[1]+50
sage: c_1 = lambda p: p[0]-45
sage: c_2 = lambda p: p[1]-5
sage: c_3 = lambda p: -50*p[0]-24*p[1]+2400
sage: c_4 = lambda p: -30*p[0]-33*p[1]+2100
sage: a = minimize_constrained(f, [c_1,c_2,c_3,c_4], [2,3])
sage: a
(45.0, 6.25...)
```

```
>>> from sage.all import *
>>> f = lambda p: -p[Integer(0)]-p[Integer(1)]+Integer(50)
>>> c_1 = lambda p: p[Integer(0)]-Integer(45)
>>> c_2 = lambda p: p[Integer(1)]-Integer(5)
>>> c_3 = lambda p: -Integer(50)*p[Integer(0)]-
↳ Integer(24)*p[Integer(1)]+Integer(2400)
>>> c_4 = lambda p: -Integer(30)*p[Integer(0)]-
↳ Integer(33)*p[Integer(1)]+Integer(2100)
>>> a = minimize_constrained(f, [c_1,c_2,c_3,c_4], [Integer(2), Integer(3)])
>>> a
(45.0, 6.25...)
```

Let's find a minimum of $\sin(xy)$:

```
sage: x,y = var('x y') #_
↳needs sage.symbolic
sage: f(x,y) = sin(x*y) #_
↳needs sage.symbolic
sage: minimize_constrained(f, [(None, None), (4,10)], [5,5]) #_
↳needs sage.symbolic
(4.8..., 4.8...)
```

```

>>> from sage.all import *
>>> x,y = var('x y')
↳needs sage.symbolic
>>> __tmp__=var("x,y"); f = symbolic_expression(sin(x*y)
↳                                     ).function(x,y) # needs sage.symbolic
>>> minimize_constrained(f, [(None, None), (Integer(4), Integer(10))], [Integer(5),
↳Integer(5)])
↳                                     # needs sage.symbolic
(4.8..., 4.8...)
    
```

Check if L-BFGS-B finds the same minimum:

```

sage: minimize_constrained(f, [(None, None), (4, 10)], [5, 5],
↳needs sage.symbolic
.....:                                     algorithm='l-bfgs-b')
(4.7..., 4.9...)
    
```

```

>>> from sage.all import *
>>> minimize_constrained(f, [(None, None), (Integer(4), Integer(10))], [Integer(5),
↳Integer(5)],
...                                     algorithm='l-bfgs-b')
(4.7..., 4.9...)
    
```

Rosenbrock function (see the [Wikipedia article Rosenbrock_function](#)):

```

sage: from scipy.optimize import rosen, rosen_der
sage: minimize_constrained(rosen, [(-50, -10), (5, 10)], [1, 1],
.....:                                     gradient=rosen_der, algorithm='l-bfgs-b')
(-10.0, 10.0)
sage: minimize_constrained(rosen, [(-50, -10), (5, 10)], [1, 1],
.....:                                     algorithm='l-bfgs-b')
(-10.0, 10.0)
    
```

```

>>> from sage.all import *
>>> from scipy.optimize import rosen, rosen_der
>>> minimize_constrained(rosen, [(-Integer(50), -Integer(10)), (Integer(5),
↳Integer(10))], [Integer(1), Integer(1)],
...                                     gradient=rosen_der, algorithm='l-bfgs-b')
(-10.0, 10.0)
>>> minimize_constrained(rosen, [(-Integer(50), -Integer(10)), (Integer(5),
↳Integer(10))], [Integer(1), Integer(1)],
...                                     algorithm='l-bfgs-b')
(-10.0, 10.0)
    
```

INTERACTIVE SIMPLEX METHOD

This module, meant for **educational purposes only**, supports learning and exploring of the simplex method.

Do you want to solve Linear Programs efficiently? use `MixedIntegerLinearProgram` instead.

The methods implemented here allow solving Linear Programming Problems (LPPs) in a number of ways, may require explicit (and correct!) description of steps and are likely to be much slower than “regular” LP solvers. If, however, you want to learn how the simplex method works and see what happens in different situations using different strategies, but don’t want to deal with tedious arithmetic, this module is for you!

Historically it was created to complement the Math 373 course on Mathematical Programming and Optimization at the University of Alberta, Edmonton, Canada.

AUTHORS:

- Andrey Novoseltsev (2013-03-16): initial version.
- Matthias Koeppel, Peijun Xiao (2015-07-05): allow different output styles.

EXAMPLES:

Most of the module functionality is demonstrated on the following problem.

Corn & Barley

A farmer has 1000 acres available to grow corn and barley. Corn has a net profit of 10 dollars per acre while barley has a net profit of 5 dollars per acre. The farmer has 1500 kg of fertilizer available with 3 kg per acre needed for corn and 1 kg per acre needed for barley. The farmer wants to maximize profit. (Sometimes we also add one more constraint to make the initial dictionary infeasible: the farmer has to use at least 40% of the available land.)

Using variables C and B for land used to grow corn and barley respectively, in acres, we can construct the following LP problem:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P
LP problem (use 'view(...)' or '%display typeset' for details)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
```

(continues on next page)

(continued from previous page)

```
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P
LP problem (use 'view(...)' or '%display typeset' for details)
```

It is recommended to copy-paste such examples into your own worksheet, so that you can run these commands with typeset mode on (`%display typeset`) and get

$$\begin{aligned} \max \quad & 10C + 5B \\ & C + B \leq 1000 \\ & 3C + B \leq 1500 \\ & C, B \geq 0 \end{aligned}$$

Since it has only two variables, we can solve it graphically:

```
sage: P.plot()
↳needs sage.plot
Graphics object consisting of 19 graphics primitives
```

```
>>> from sage.all import *
>>> P.plot()
↳needs sage.plot
Graphics object consisting of 19 graphics primitives
```

The simplex method can be applied only to *problems in standard form*, which can be created either directly

```
sage: InteractiveLPPProblemStandardForm(A, b, c, ["C", "B"])
LP problem (use ...)
```

```
>>> from sage.all import *
>>> InteractiveLPPProblemStandardForm(A, b, c, ["C", "B"])
LP problem (use ...)
```

or from an already constructed problem of “general type”:

```
sage: P = P.standard_form()
```

```
>>> from sage.all import *
>>> P = P.standard_form()
```

In this case the problem does not require any modifications to be written in standard form, but this step is still necessary to enable methods related to the simplex method.

The simplest way to use the simplex method is:

```
sage: P.run_simplex_method()
\begin{equation*}
...
The optimal value: $6250$. An optimal solution: $\left(250, \, 750\right)$.
```

```
>>> from sage.all import *
>>> P.run_simplex_method()
\begin{equation*}
...
The optimal value: $6250$. An optimal solution: $\left(250, \, 750\right)$.
```

(This method produces quite long formulas which have been omitted here.) But, of course, it is much more fun to do most of the steps by hand. Let's start by creating the initial dictionary:

```
sage: D = P.initial_dictionary()
sage: D
LP problem dictionary (use ...)
```

```
>>> from sage.all import *
>>> D = P.initial_dictionary()
>>> D
LP problem dictionary (use ...)
```

Using typeset mode as recommended, you'll see

| | | | | | | |
|-------|-----|--------|-----|-------|-----|------|
| x_3 | $=$ | 1000 | $-$ | C | $-$ | B |
| x_4 | $=$ | 1500 | $-$ | $3C$ | $-$ | B |
| z | $=$ | 0 | $+$ | $10C$ | $+$ | $5B$ |

With the initial or any other dictionary you can perform a number of checks:

```
sage: D.is_feasible()
True
sage: D.is_optimal()
False
```

```
>>> from sage.all import *
>>> D.is_feasible()
True
>>> D.is_optimal()
False
```

You can look at many of its pieces and associated data:

```
sage: D.basic_variables()
(x3, x4)
sage: D.basic_solution()
(0, 0)
sage: D.objective_value()
0
```

```
>>> from sage.all import *
>>> D.basic_variables()
(x3, x4)
>>> D.basic_solution()
(0, 0)
>>> D.objective_value()
0
```

Most importantly, you can perform steps of the simplex method by picking an entering variable, a leaving variable, and updating the dictionary:

```
sage: D.enter("C")
sage: D.leave(4)
sage: D.update()
```

```
>>> from sage.all import *
>>> D.enter("C")
>>> D.leave(Integer(4))
>>> D.update()
```

If everything was done correctly, the new dictionary is still feasible and the objective value did not decrease:

```
sage: D.is_feasible()
True
sage: D.objective_value()
5000
```

```
>>> from sage.all import *
>>> D.is_feasible()
True
>>> D.objective_value()
5000
```

If you are unsure about picking entering and leaving variables, you can use helper methods that will try their best to tell you what are your next options:

```
sage: D.possible_entering()
[B]
sage: D.possible_leaving()
Traceback (most recent call last):
...
ValueError: leaving variables can be determined
for feasible dictionaries with a set entering variable
or for dual feasible dictionaries
```

```
>>> from sage.all import *
>>> D.possible_entering()
[B]
>>> D.possible_leaving()
Traceback (most recent call last):
...
ValueError: leaving variables can be determined
for feasible dictionaries with a set entering variable
or for dual feasible dictionaries
```

It is also possible to obtain *feasible sets* and *final dictionaries* of problems, work with *revised dictionaries*, and use the dual simplex method!

Note

Currently this does not have a display format for the terminal.

9.1 Classes and functions

```
class sage.numerical.interactive_simplex_method.InteractiveLPProblem(A, b, c, x='x',
                                                                    constraint_type='<=',
                                                                    variable_type="",
                                                                    problem_type='max',
                                                                    base_ring=None,
                                                                    is_primal=True, objective_constant_term=0)
```

Bases: SageObject

Construct an LP (Linear Programming) problem.

Note

This class is for **educational purposes only**: if you want to solve Linear Programs efficiently, use *MixedIntegerLinearProgram* instead.

This class supports LP problems with “variables on the left” constraints.

INPUT:

- A – a matrix of constraint coefficients
- b – a vector of constraint constant terms
- c – a vector of objective coefficients
- x – (default: 'x') a vector of decision variables or a string giving the base name
- `constraint_type` – (default: '<=') a string specifying constraint type(s): either '<=', '>=', '==', or a list of them
- `variable_type` – (default: "") a string specifying variable type(s): either '>=', '<=', "" (the empty string), or a list of them, corresponding, respectively, to nonnegative, nonpositive, and free variables
- `problem_type` – (default: 'max') a string specifying the problem type: 'max', 'min', '-max', or '-min'
- `base_ring` – (default: the fraction field of a common ring for all input coefficients) a field to which all input coefficients will be converted
- `is_primal` – boolean (default: True); whether this problem is primal or dual: each problem is of course dual to its own dual, this flag is mostly for internal use and affects default variable names only
- `objective_constant_term` – (default: 0) a constant term of the objective

EXAMPLES:

We will construct the following problem:

$$\begin{aligned} \max \quad & 10C + 5B \\ & C + B \leq 1000 \\ & 3C + B \leq 1500 \\ & C, B \geq 0 \end{aligned}$$

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
```

(continues on next page)

(continued from previous page)

```
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
```

Same problem, but more explicitly:

```
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"],
.....:     constraint_type='<=', variable_type='>=')
```

```
>>> from sage.all import *
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"],
...     constraint_type='<=', variable_type='>=')
```

Even more explicitly:

```
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], problem_type='max',
.....:     constraint_type=["<=", "<="], variable_type=[">=", ">="])
```

```
>>> from sage.all import *
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], problem_type='max',
...     constraint_type=["<=", "<="], variable_type=[">=", ">="])
```

Using the last form you should be able to represent any LP problem, as long as all like terms are collected and in constraints variables and constants are on different sides.

A()

alias of `constraint_coefficients()`.

Abcx()

Return A , b , c , and x of `self` as a tuple.

OUTPUT: a tuple

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.Abcx()
(
 [1 1]
 [3 1], (1000, 1500), (10, 5), (C, B)
)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
```

(continues on next page)

(continued from previous page)

```

>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.Abcx()
(
 [1 1]
 [3 1], (1000, 1500), (10, 5), (C, B)
)

```

add_constraint (*coefficients, constant_term, constraint_type='<='*)

Return a new LP problem by adding a constraint to ``self``.

INPUT:

- *coefficients* – coefficients of the new constraint
- *constant_term* – a constant term of the new constraint
- *constraint_type* – (default: '<=') a string indicating the constraint type of the new constraint

OUTPUT: an *LP problem*

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c)
sage: P1 = P.add_constraint([2, 4], 2000, "<=")
sage: P1.Abcx()
(
 [1 1]
 [3 1]
 [2 4], (1000, 1500, 2000), (10, 5), (x1, x2)
)
sage: P1.constraint_types()
('<=', '<=', '<=')
sage: P.Abcx()
(
 [1 1]
 [3 1], (1000, 1500), (10, 5), (x1, x2)
)
sage: P.constraint_types()
('<=', '<=')
sage: P2 = P.add_constraint([2, 4, 6], 2000, "<=")
Traceback (most recent call last):
...
TypeError: number of columns must be the same, not 2 and 3
sage: P3 = P.add_constraint([2, 4], 2000, "<")
Traceback (most recent call last):
...
ValueError: unknown constraint type

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))

```

(continues on next page)

(continued from previous page)

```

>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPProblem(A, b, c)
>>> P1 = P.add_constraint([[Integer(2), Integer(4)]], Integer(2000), "<=")
>>> P1.Abcx()
(
 [1 1]
 [3 1]
 [2 4], (1000, 1500, 2000), (10, 5), (x1, x2)
)
>>> P1.constraint_types()
('<=', '<=', '<=')
>>> P.Abcx()
(
 [1 1]
 [3 1], (1000, 1500), (10, 5), (x1, x2)
)
>>> P.constraint_types()
('<=', '<=')
>>> P2 = P.add_constraint([[Integer(2), Integer(4), Integer(6)]],
↳Integer(2000), "<=")
Traceback (most recent call last):
...
TypeError: number of columns must be the same, not 2 and 3
>>> P3 = P.add_constraint([[Integer(2), Integer(4)]], Integer(2000), "<")
Traceback (most recent call last):
...
ValueError: unknown constraint type

```

b()alias of `constant_terms()`.**base_ring()**Return the base ring of `self`.**Note**

The base ring of LP problems is always a field.

OUTPUT: a ring

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.base_ring()
Rational Field

sage: c = (10, 5.)
sage: P = InteractiveLPProblem(A, b, c, ["C", "B"], variable_type='>=')

```

(continues on next page)

(continued from previous page)

```
sage: P.base_ring()
Real Field with 53 bits of precision
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.base_ring()
Rational Field

>>> c = (Integer(10), RealNumber('5.'))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.base_ring()
Real Field with 53 bits of precision
```

c()alias of `objective_coefficients()`.**constant_terms()**Return constant terms of constraints of `self`, i.e. `b`.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.constant_terms()
(1000, 1500)
sage: P.b()
(1000, 1500)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.constant_terms()
(1000, 1500)
>>> P.b()
(1000, 1500)
```

constraint_coefficients()Return coefficients of constraints of `self`, i.e. `A`.

OUTPUT: a matrix

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
```

(continues on next page)

(continued from previous page)

```

sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.constraint_coefficients()
[1 1]
[3 1]
sage: P.A()
[1 1]
[3 1]

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.constraint_coefficients()
[1 1]
[3 1]
>>> P.A()
[1 1]
[3 1]

```

constraint_types()

Return a tuple listing the constraint types of all rows.

OUTPUT: a tuple of strings

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=',
↳constraint_type=["<=", "=="])
sage: P.constraint_types()
('<=', '==')

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=',
↳constraint_type=["<=", "=="])
>>> P.constraint_types()
('<=', '==')

```

decision_variables()

Return decision variables of `self`, i.e. x .

OUTPUT: a vector

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.decision_variables()
(C, B)
sage: P.x()
(C, B)

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.decision_variables()
(C, B)
>>> P.x()
(C, B)

```

dual ($y=None$)

Construct the dual LP problem for *self*.

INPUT:

- y – (default: depends on *style()*) a vector of dual decision variables or a string giving the base name

OUTPUT: an *InteractiveLPPProblem*

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: DP = P.dual()
sage: DP.b() == P.c()
True
sage: DP.dual(["C", "B"]) == P
True

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> DP = P.dual()
>>> DP.b() == P.c()
True
>>> DP.dual(["C", "B"]) == P
True

```

feasible_set ()

Return the feasible set of *self*.

OUTPUT: a *Polyhedron*

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.feasible_set()
A 2-dimensional polyhedron in QQ^2
defined as the convex hull of 4 vertices
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.feasible_set()
A 2-dimensional polyhedron in QQ^2
defined as the convex hull of 4 vertices
```

is_bounded()

Check if self is bounded.

OUTPUT: True if self is bounded, False otherwise

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.is_bounded()
True
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.is_bounded()
True
```

Note that infeasible problems are always bounded:

```
sage: b = (-1000, 1500)
sage: P = InteractiveLPPProblem(A, b, c, variable_type='>=')
sage: P.is_feasible()
False
sage: P.is_bounded()
True
```

```
>>> from sage.all import *
>>> b = (-Integer(1000), Integer(1500))
>>> P = InteractiveLPPProblem(A, b, c, variable_type='>=')
>>> P.is_feasible()
```

(continues on next page)

(continued from previous page)

```
False
>>> P.is_bounded()
True
```

is_feasible(*x)

Check if `self` or given solution is feasible.

INPUT:

- (optional) anything that can be interpreted as a valid solution for this problem, i.e. a sequence of values for all decision variables

OUTPUT:

- True if this problem or given solution is feasible, False otherwise

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, variable_type='>=')
sage: P.is_feasible()
True
sage: P.is_feasible(100, 200)
True
sage: P.is_feasible(1000, 200)
False
sage: P.is_feasible([1000, 200])
False
sage: P.is_feasible(1000)
Traceback (most recent call last):
...
TypeError: given input is not a solution for this problem
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, variable_type='>=')
>>> P.is_feasible()
True
>>> P.is_feasible(Integer(100), Integer(200))
True
>>> P.is_feasible(Integer(1000), Integer(200))
False
>>> P.is_feasible([Integer(1000), Integer(200)])
False
>>> P.is_feasible(Integer(1000))
Traceback (most recent call last):
...
TypeError: given input is not a solution for this problem
```

is_negative()

Return True when the problem is of type '-max' or '-min'.

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.is_negative()
False
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=',
↪problem_type='-min')
sage: P.is_negative()
True
    
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.is_negative()
False
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=', problem_
↪type='-min')
>>> P.is_negative()
True
    
```

is_optimal(*x)

Check if given solution is feasible.

INPUT:

- anything that can be interpreted as a valid solution for this problem, i.e. a sequence of values for all decision variables

OUTPUT: True if the given solution is optimal, False otherwise

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (15, 5)
sage: P = InteractiveLPPProblem(A, b, c, variable_type='>=')
sage: P.is_optimal(100, 200)
False
sage: P.is_optimal(500, 0)
True
sage: P.is_optimal(499, 3)
True
sage: P.is_optimal(501, -3)
False
    
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(15), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, variable_type='>=')
    
```

(continues on next page)

(continued from previous page)

```

>>> P.is_optimal(Integer(100), Integer(200))
False
>>> P.is_optimal(Integer(500), Integer(0))
True
>>> P.is_optimal(Integer(499), Integer(3))
True
>>> P.is_optimal(Integer(501), -Integer(3))
False

```

is_primal()

Check if we consider this problem to be primal or dual.

This distinction affects only some automatically chosen variable names.

OUTPUT: boolean

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.is_primal()
True
sage: P.dual().is_primal()
False

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.is_primal()
True
>>> P.dual().is_primal()
False

```

m()

alias of `n_constraints()`.

n()

alias of `n_variables()`.

n_constraints()

Return the number of constraints of `self`, i.e. m .

OUTPUT: integer

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.n_constraints()

```

(continues on next page)

(continued from previous page)

```
2
sage: P.m()
2
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.n_constraints()
2
>>> P.m()
2
```

n_variables()

Return the number of decision variables of `self`, i.e. n .

OUTPUT: integer

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.n_variables()
2
sage: P.n()
2
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.n_variables()
2
>>> P.n()
2
```

objective_coefficients()

Return coefficients of the objective of `self`, i.e. c .

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.objective_coefficients()
(10, 5)
```

(continues on next page)

(continued from previous page)

```
sage: P.c()
(10, 5)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.objective_coefficients()
(10, 5)
>>> P.c()
(10, 5)
```

objective_constant_term()

Return the constant term of the objective.

OUTPUT: a number

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.objective_constant_term()
0
sage: P.optimal_value()
6250
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"],
....:     variable_type='>=', objective_constant_term=-1250)
sage: P.objective_constant_term()
-1250
sage: P.optimal_value()
5000
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.objective_constant_term()
0
>>> P.optimal_value()
6250
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"],
...     variable_type='>=', objective_constant_term=-Integer(1250))
>>> P.objective_constant_term()
-1250
>>> P.optimal_value()
5000
```

objective_value(*x)

Return the value of the objective on the given solution.

INPUT:

- anything that can be interpreted as a valid solution for this problem, i.e. a sequence of values for all decision variables

OUTPUT:

- the value of the objective on the given solution taking into account `objective_constant_term()` and `is_negative()`

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, variable_type='>=')
sage: P.objective_value(100, 200)
2000
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, variable_type='>=')
>>> P.objective_value(Integer(100), Integer(200))
2000
```

`optimal_solution()`

Return an optimal solution of `self`.

OUTPUT: a vector or `None` if there are no optimal solutions

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.optimal_solution()
(250, 750)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.optimal_solution()
(250, 750)
```

`optimal_value()`

Return the optimal value for `self`.

OUTPUT:

- a number if the problem is bounded, $\pm\infty$ if it is unbounded, or `None` if it is infeasible

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.optimal_value()
6250

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.optimal_value()
6250

```

plot (*args, **kwds)

Return a plot for solving `self` graphically.

INPUT:

- `xmin, xmax, ymin, ymax` – bounds for the axes, if not given, an attempt will be made to pick reasonable values
- `alpha` – (default: 0.2) determines how opaque are shadows

OUTPUT: a plot

This only works for problems with two decision variables. On the plot the black arrow indicates the direction of growth of the objective. The lines perpendicular to it are level curves of the objective. If there are optimal solutions, the arrow originates in one of them and the corresponding level curve is solid: all points of the feasible set on it are optimal solutions. Otherwise the arrow is placed in the center. If the problem is infeasible or the objective is zero, a plot of the feasible set only is returned.

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: p = P.plot() #_
↳needs sage.plot
sage: p.show() #_
↳needs sage.plot

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> p = P.plot() #_
↳needs sage.plot
>>> p.show() #_
↳needs sage.plot

```

In this case the plot works better with the following axes ranges:

```

sage: p = P.plot(0, 1000, 0, 1500) #_
↪needs sage.plot
sage: p.show() #_
↪needs sage.plot
    
```

```

>>> from sage.all import *
>>> p = P.plot(Integer(0), Integer(1000), Integer(0), Integer(1500)) #_
↪ # needs sage.plot
>>> p.show() #_
↪needs sage.plot
    
```

plot_feasible_set (*xmin=None, xmax=None, ymin=None, ymax=None, alpha=0.2*)

Return a plot of the feasible set of *self*.

INPUT:

- *xmin, xmax, ymin, ymax* – bounds for the axes, if not given, an attempt will be made to pick reasonable values
- *alpha* – (default: 0.2) determines how opaque are shadows

OUTPUT: a plot

This only works for a problem with two decision variables. The plot shows boundaries of constraints with a shadow on one side for inequalities. If the *feasible_set()* is not empty and at least part of it is in the given boundaries, it will be shaded gray and *F* will be placed in its middle.

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: p = P.plot_feasible_set() #_
↪needs sage.plot
sage: p.show() #_
↪needs sage.plot
    
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> p = P.plot_feasible_set() #_
↪needs sage.plot
>>> p.show() #_
↪needs sage.plot
    
```

In this case the plot works better with the following axes ranges:

```

sage: p = P.plot_feasible_set(0, 1000, 0, 1500) #_
↪needs sage.plot
sage: p.show() #_
↪needs sage.plot
    
```

```

>>> from sage.all import *
>>> p = P.plot_feasible_set(Integer(0), Integer(1000), Integer(0),
↳Integer(1500)) # needs sage.plot
>>> p.show() #
↳needs sage.plot

```

problem_type()

Return the problem type.

Needs to be used together with `is_negative`.

OUTPUT: string, one of 'max', 'min'

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
sage: P.problem_type()
'max'
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=',
↳problem_type='-min')
sage: P.problem_type()
'min'

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=')
>>> P.problem_type()
'max'
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type='>=', problem_
↳type='-min')
>>> P.problem_type()
'min'

```

standard_form(transformation=False, **kws)

Construct the LP problem in standard form equivalent to `self`.

INPUT:

- `transformation` – boolean (default: `False`); if `True`, a map converting solutions of the problem in standard form to the original one will be returned as well
- you can pass (as keywords only) `slack_variables`, `auxiliary_variable`, `objective_name` to the constructor of `InteractiveLPPProblemStandardForm`

OUTPUT:

- an `InteractiveLPPProblemStandardForm` by itself or a tuple with variable transformation as the second component

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblem(A, b, c, variable_type='>=')
sage: DP = P.dual()
sage: DPSF = DP.standard_form()
sage: DPSF.b()
(-10, -5)
sage: DPSF.slack_variables()
(y3, y4)
sage: DPSF = DP.standard_form(slack_variables=["L", "F"])
sage: DPSF.slack_variables()
(L, F)
sage: DPSF, f = DP.standard_form(True)
sage: f
Vector space morphism represented by the matrix:
[1 0]
[0 1]
Domain: Vector space of dimension 2 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, variable_type='>=')
>>> DP = P.dual()
>>> DPSF = DP.standard_form()
>>> DPSF.b()
(-10, -5)
>>> DPSF.slack_variables()
(y3, y4)
>>> DPSF = DP.standard_form(slack_variables=["L", "F"])
>>> DPSF.slack_variables()
(L, F)
>>> DPSF, f = DP.standard_form(True)
>>> f
Vector space morphism represented by the matrix:
[1 0]
[0 1]
Domain: Vector space of dimension 2 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field

```

A more complicated transformation map:

```

sage: P = InteractiveLPPProblem(A, b, c, variable_type=["<=", ""],
....:                               objective_constant_term=42)
sage: PSF, f = P.standard_form(True)
sage: f
Vector space morphism represented by the matrix:
[-1 0]
[ 0 1]
[ 0 -1]

```

(continues on next page)

(continued from previous page)

```

Domain: Vector space of dimension 3 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field
sage: PSF.optimal_solution()
(0, 1000, 0)
sage: P.optimal_solution()
(0, 1000)
sage: P.is_optimal(PSF.optimal_solution())
Traceback (most recent call last):
...
TypeError: given input is not a solution for this problem
sage: P.is_optimal(f(PSF.optimal_solution()))
True
sage: PSF.optimal_value()
5042
sage: P.optimal_value()
5042

```

```

>>> from sage.all import *
>>> P = InteractiveLPPProblem(A, b, c, variable_type=["<=", "="],
...                          objective_constant_term=Integer(42))
>>> PSF, f = P.standard_form(True)
>>> f
Vector space morphism represented by the matrix:
[-1  0]
[ 0  1]
[ 0 -1]
Domain: Vector space of dimension 3 over Rational Field
Codomain: Vector space of dimension 2 over Rational Field
>>> PSF.optimal_solution()
(0, 1000, 0)
>>> P.optimal_solution()
(0, 1000)
>>> P.is_optimal(PSF.optimal_solution())
Traceback (most recent call last):
...
TypeError: given input is not a solution for this problem
>>> P.is_optimal(f(PSF.optimal_solution()))
True
>>> PSF.optimal_value()
5042
>>> P.optimal_value()
5042

```

variable_types()

Return a tuple listing the variable types of all decision variables.

OUTPUT: a tuple of strings

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)

```

(continues on next page)

(continued from previous page)

```
sage: P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type=[">=", ""])
sage: P.variable_types()
('>=', '')
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblem(A, b, c, ["C", "B"], variable_type=[">=", ""])
>>> P.variable_types()
('>=', '')
```

x()

alias of `decision_variables()`.

```
class sage.numerical.interactive_simplex_method.InteractiveLPPProblemStandardForm(A, b, c,
x='x',
prob-
lem_type='max',
slack_vari-
ables=None,
auxil-
iary_vari-
able=None,
base_ring=None,
is_pri-
mal=True,
objec-
tive_name=None,
objec-
tive_con-
stant_term=0)
```

Bases: `InteractiveLPPProblem`

Construct an LP (Linear Programming) problem in standard form.

Note

This class is for **educational purposes only**: if you want to solve Linear Programs efficiently, use `MixedIntegerLinearProgram` instead.

The used standard form is:

$$\begin{aligned} &\pm \max cx \\ &Ax \leq b \\ &x \geq 0 \end{aligned}$$

INPUT:

- A – a matrix of constraint coefficients
- b – a vector of constraint constant terms
- c – a vector of objective coefficients

- `x` – (default: 'x') a vector of decision variables or a string the base name giving
- `problem_type` – (default: 'max') a string specifying the problem type: either 'max' or '-max'
- `slack_variables` – (default: depends on `style()`) a vector of slack variables or a string giving the base name
- `auxiliary_variable` – (default: same as `x` parameter with adjoined '0' if it was given as a string, otherwise 'x0') the auxiliary name, expected to be the same as the first decision variable for auxiliary problems
- `base_ring` – (default: the fraction field of a common ring for all input coefficients) a field to which all input coefficients will be converted
- `is_primal` – boolean (default: True); whether this problem is primal or dual: each problem is of course dual to its own dual, this flag is mostly for internal use and affects default variable names only
- `objective_name` – string or symbolic expression for the objective used in dictionaries (default: depends on `style()`)
- `objective_constant_term` – (default: 0) a constant term of the objective

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
```

Unlike `InteractiveLPPProblem`, this class does not allow you to adjust types of constraints (they are always '`<=`') and variables (they are always '`>=`'), and the problem type may only be 'max' or '-max'. You may give custom names to slack and auxiliary variables, but in most cases defaults should work:

```
sage: P.decision_variables()
(x1, x2)
sage: P.slack_variables()
(x3, x4)
```

```
>>> from sage.all import *
>>> P.decision_variables()
(x1, x2)
>>> P.slack_variables()
(x3, x4)
```

add_constraint (*coefficients, constant_term, slack_variable=None*)

Return a new LP problem by adding a constraint to ``self``.

INPUT:

- `coefficients` – coefficients of the new constraint
- `constant_term` – a constant term of the new constraint
- `slack_variable` – (default: depends on `style()`) a string giving the name of the slack variable of the new constraint

OUTPUT: an *LP problem in standard form*

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: P.Abcx()
(
[1 1]
[3 1], (1000, 1500), (10, 5), (x1, x2)
)
sage: P.slack_variables()
(x3, x4)
sage: P1 = P.add_constraint(([2, 4]), 2000)
sage: P1.Abcx()
(
[1 1]
[3 1]
[2 4], (1000, 1500, 2000), (10, 5), (x1, x2)
)
sage: P1.slack_variables()
(x3, x4, x5)
sage: P2 = P.add_constraint(([2, 4]), 2000, slack_variable='c')
sage: P2.slack_variables()
(x3, x4, c)
sage: P3 = P.add_constraint(([2, 4, 6]), 2000)
Traceback (most recent call last):
...
TypeError: number of columns must be the same, not 2 and 3
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> P.Abcx()
(
[1 1]
[3 1], (1000, 1500), (10, 5), (x1, x2)
)
>>> P.slack_variables()
(x3, x4)
>>> P1 = P.add_constraint(([Integer(2), Integer(4)]), Integer(2000))
>>> P1.Abcx()
(
[1 1]
[3 1]
[2 4], (1000, 1500, 2000), (10, 5), (x1, x2)
)
>>> P1.slack_variables()
(x3, x4, x5)
>>> P2 = P.add_constraint(([Integer(2), Integer(4)]), Integer(2000), slack_
```

(continues on next page)

(continued from previous page)

```

↪variable='c')
>>> P2.slack_variables()
(x3, x4, c)
>>> P3 = P.add_constraint(([Integer(2), Integer(4), Integer(6)]), ↪
↪Integer(2000))
Traceback (most recent call last):
...
TypeError: number of columns must be the same, not 2 and 3

```

auxiliary_problem (*objective_name=None*)Construct the auxiliary problem for `self`.

INPUT:

- `objective_name`—string or symbolic expression for the objective used in dictionaries (default: depends on `style()`)

OUTPUT: an *LP problem in standard form*The auxiliary problem with the auxiliary variable x_0 is

$$\begin{aligned}
 &\max -x_0 \\
 &-x_0 + A_i x \leq b_i \text{ for all } i \quad . \\
 &x \geq 0
 \end{aligned}$$

Such problems are used when the `initial_dictionary()` is infeasible.

EXAMPLES:

```

sage: A = ([1, 1], [3, 1], [-1, -1])
sage: b = (1000, 1500, -400)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: AP = P.auxiliary_problem()

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)], [-Integer(1), -
↪Integer(1)])
>>> b = (Integer(1000), Integer(1500), -Integer(400))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> AP = P.auxiliary_problem()

```

auxiliary_variable ()Return the auxiliary variable of `self`.Note that the auxiliary variable may or may not be among `decision_variables()`.OUTPUT: a variable of the `coordinate_ring()` of `self`

EXAMPLES:

```

sage: A = ([1, 1], [3, 1], [-1, -1])
sage: b = (1000, 1500, -400)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)

```

(continues on next page)

(continued from previous page)

```

sage: P.auxiliary_variable()
x0
sage: P.decision_variables()
(x1, x2)
sage: AP = P.auxiliary_problem()
sage: AP.auxiliary_variable()
x0
sage: AP.decision_variables()
(x0, x1, x2)
    
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)], [-Integer(1), -
↳Integer(1)])
>>> b = (Integer(1000), Integer(1500), -Integer(400))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> P.auxiliary_variable()
x0
>>> P.decision_variables()
(x1, x2)
>>> AP = P.auxiliary_problem()
>>> AP.auxiliary_variable()
x0
>>> AP.decision_variables()
(x0, x1, x2)
    
```

`coordinate_ring()`

Return the coordinate ring of self.

OUTPUT:

- a polynomial ring over the `base_ring()` of self in the `auxiliary_variable()`, `decision_variables()`, and `slack_variables()` with “neglex” order

EXAMPLES:

```

sage: A = ([1, 1], [3, 1], [-1, -1])
sage: b = (1000, 1500, -400)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: P.coordinate_ring()
Multivariate Polynomial Ring in x0, x1, x2, x3, x4, x5
over Rational Field
sage: P.base_ring()
Rational Field
sage: P.auxiliary_variable()
x0
sage: P.decision_variables()
(x1, x2)
sage: P.slack_variables()
(x3, x4, x5)
    
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)], [-Integer(1), -
↳Integer(1)])
>>> b = (Integer(1000), Integer(1500), -Integer(400))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> P.coordinate_ring()
Multivariate Polynomial Ring in x0, x1, x2, x3, x4, x5
over Rational Field
>>> P.base_ring()
Rational Field
>>> P.auxiliary_variable()
x0
>>> P.decision_variables()
(x1, x2)
>>> P.slack_variables()
(x3, x4, x5)

```

dictionary (*x_B)

Construct a dictionary for `self` with given basic variables.

INPUT:

- basic variables for the dictionary to be constructed

OUTPUT: a *dictionary*

Note

This is a synonym for `self.revised_dictionary(x_B).dictionary()`, but basic variables are mandatory.

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.dictionary("x1", "x2")
sage: D.basic_variables()
(x1, x2)

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.dictionary("x1", "x2")
>>> D.basic_variables()
(x1, x2)

```

feasible_dictionary (*auxiliary_dictionary*)

Construct a feasible dictionary for `self`.

INPUT:

- `auxiliary_dictionary` – an optimal dictionary for the `auxiliary_problem()` of `self` with the optimal value 0 and a non-basic auxiliary variable

OUTPUT: a feasible *dictionary* for `self`

EXAMPLES:

```
sage: A = ([1, 1], [3, 1], [-1, -1])
sage: b = (1000, 1500, -400)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: AP = P.auxiliary_problem()
sage: D = AP.initial_dictionary()
sage: D.enter(0)
sage: D.leave(5)
sage: D.update()
sage: D.enter(1)
sage: D.leave(0)
sage: D.update()
sage: D.is_optimal()
True
sage: D.objective_value()
0
sage: D.basic_solution()
(0, 400, 0)
sage: D = P.feasible_dictionary(D)
sage: D.is_optimal()
False
sage: D.is_feasible()
True
sage: D.objective_value()
4000
sage: D.basic_solution()
(400, 0)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)], [-Integer(1), -
↳ Integer(1)])
>>> b = (Integer(1000), Integer(1500), -Integer(400))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> AP = P.auxiliary_problem()
>>> D = AP.initial_dictionary()
>>> D.enter(Integer(0))
>>> D.leave(Integer(5))
>>> D.update()
>>> D.enter(Integer(1))
>>> D.leave(Integer(0))
>>> D.update()
>>> D.is_optimal()
True
>>> D.objective_value()
0
```

(continues on next page)

(continued from previous page)

```

>>> D.basic_solution()
(0, 400, 0)
>>> D = P.feasible_dictionary(D)
>>> D.is_optimal()
False
>>> D.is_feasible()
True
>>> D.objective_value()
4000
>>> D.basic_solution()
(400, 0)

```

final_dictionary()

Return the final dictionary of the simplex method applied to `self`.

See `run_simplex_method()` for the description of possibilities.

OUTPUT: a *dictionary*

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.final_dictionary()
sage: D.is_optimal()
True

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.final_dictionary()
>>> D.is_optimal()
True

```

final_revised_dictionary()

Return the final dictionary of the revised simplex method applied to `self`.

See `run_revised_simplex_method()` for the description of possibilities.

OUTPUT: a *revised dictionary*

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.final_revised_dictionary()
sage: D.is_optimal()
True

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.final_revised_dictionary()
>>> D.is_optimal()
True
    
```

`initial_dictionary()`

Construct the initial dictionary of `self`.

The initial dictionary “defines” `slack_variables()` in terms of the `decision_variables()`, i.e. it has slack variables as basic ones.

OUTPUT: a *dictionary*

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
    
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
    
```

`inject_variables(scope=None, verbose=True)`

Inject variables of `self` into scope.

INPUT:

- `scope` – namespace (default: `global`)
- `verbose` – if `True` (default), names of injected variables will be printed

OUTPUT: `none`

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: P.inject_variables()
Defining x0, x1, x2, x3, x4
sage: 3*x1 + x2
x2 + 3*x1
    
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
    
```

(continues on next page)

(continued from previous page)

```

>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> P.inject_variables()
Defining x0, x1, x2, x3, x4
>>> Integer(3)*x1 + x2
x2 + 3*x1

```

objective_name()

Return the objective name used in dictionaries for this problem.

OUTPUT: a symbolic expression

EXAMPLES:

```

sage: A = ([1, 1], [3, 1], [-1, -1])
sage: b = (1000, 1500, -400)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: P.objective_name()
z
sage: sage.numerical.interactive_simplex_method.style("Vanderbei")
'Vanderbei'
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: P.objective_name()
zeta
sage: sage.numerical.interactive_simplex_method.style("UAlberta")
'UAlberta'
sage: P = InteractiveLPPProblemStandardForm(A, b, c, objective_name='custom')
sage: P.objective_name()
custom

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)], [-Integer(1), -
↳ Integer(1)])
>>> b = (Integer(1000), Integer(1500), -Integer(400))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> P.objective_name()
z
>>> sage.numerical.interactive_simplex_method.style("Vanderbei")
'Vanderbei'
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> P.objective_name()
zeta
>>> sage.numerical.interactive_simplex_method.style("UAlberta")
'UAlberta'
>>> P = InteractiveLPPProblemStandardForm(A, b, c, objective_name='custom')
>>> P.objective_name()
custom

```

static random_element(m, n, bound=5, special_probability=0.2, **kws)

Construct a random InteractiveLPPProblemStandardForm.

INPUT:

- m – the number of constraints/basic variables
- n – the number of decision/non-basic variables
- `bound` – (default: 5) a bound on coefficients
- `special_probability` – (default: 0.2) probability of constructing a problem whose initial dictionary is allowed to be primal infeasible or dual feasible

All other keyword arguments are passed to the constructor.

EXAMPLES:

```
sage: InteractiveLPPProblemStandardForm.random_element(3, 4)
LP problem (use 'view(...)' or '%display typeset' for details)
```

```
>>> from sage.all import *
>>> InteractiveLPPProblemStandardForm.random_element(Integer(3), Integer(4))
LP problem (use 'view(...)' or '%display typeset' for details)
```

revised_dictionary (* x_B)

Construct a revised dictionary for `self`.

INPUT:

- basic variables for the dictionary to be constructed; if not given, `slack_variables()` will be used, perhaps with the `auxiliary_variable()` to give a feasible dictionary

OUTPUT: a *revised dictionary*

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary("x1", "x2")
sage: D.basic_variables()
(x1, x2)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary("x1", "x2")
>>> D.basic_variables()
(x1, x2)
```

If basic variables are not given the initial dictionary is constructed:

```
sage: P.revised_dictionary().basic_variables()
(x3, x4)
sage: P.initial_dictionary().basic_variables()
(x3, x4)
```

```
>>> from sage.all import *
>>> P.revised_dictionary().basic_variables()
(x3, x4)
>>> P.initial_dictionary().basic_variables()
(x3, x4)
```

Unless it is infeasible, in which case a feasible dictionary for the auxiliary problem is constructed:

```
sage: A = ([1, 1], [3, 1], [-1, -1])
sage: b = (1000, 1500, -400)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: P.initial_dictionary().is_feasible()
False
sage: P.revised_dictionary().basic_variables()
(x3, x4, x0)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)], [-Integer(1), -
↳Integer(1)])
>>> b = (Integer(1000), Integer(1500), -Integer(400))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> P.initial_dictionary().is_feasible()
False
>>> P.revised_dictionary().basic_variables()
(x3, x4, x0)
```

`run_revised_simplex_method()`

Apply the revised simplex method and return all steps.

OUTPUT:

- `HtmlFragment` with HTML/L^AT_EX code of all encountered dictionaries

Note

You can access the `final_revised_dictionary()`, which can be one of the following:

- an optimal dictionary with the `auxiliary_variable()` among `basic_variables()` and a nonzero optimal value indicating that `self` is infeasible;
- a non-optimal dictionary that has marked entering variable for which there is no choice of the leaving variable, indicating that `self` is unbounded;
- an optimal dictionary.

EXAMPLES:

```
sage: A = ([1, 1], [3, 1], [-1, -1])
sage: b = (1000, 1500, -400)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: P.run_revised_simplex_method()
\begin{equation*}
...
```

(continues on next page)

(continued from previous page)

```

\end{equation*}
Entering:  $x_1$ . Leaving:  $x_0$ .
\begin{equation*}
...
\end{equation*}
Entering:  $x_5$ . Leaving:  $x_4$ .
\begin{equation*}
...
\end{equation*}
Entering:  $x_2$ . Leaving:  $x_3$ .
\begin{equation*}
...
\end{equation*}
The optimal value: $6250$. An optimal solution:  $\left(250, \, 750\right)$ .

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)], [-Integer(1), -
↳Integer(1)])
>>> b = (Integer(1000), Integer(1500), -Integer(400))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> P.run_revised_simplex_method()
\begin{equation*}
...
\end{equation*}
Entering:  $x_1$ . Leaving:  $x_0$ .
\begin{equation*}
...
\end{equation*}
Entering:  $x_5$ . Leaving:  $x_4$ .
\begin{equation*}
...
\end{equation*}
Entering:  $x_2$ . Leaving:  $x_3$ .
\begin{equation*}
...
\end{equation*}
The optimal value: $6250$. An optimal solution:  $\left(250, \, 750\right)$ .

```

run_simplex_method()

Apply the simplex method and return all steps and intermediate states.

OUTPUT:

- `HtmlFragment` with HTML/L^AT_EX code of all encountered dictionaries

Note

You can access the `final_dictionary()`, which can be one of the following:

- an optimal dictionary for the `auxiliary_problem()` with a nonzero optimal value indicating that `self` is infeasible;

- a non-optimal dictionary for `self` that has marked entering variable for which there is no choice of the leaving variable, indicating that `self` is unbounded;
- an optimal dictionary for `self`.

EXAMPLES:

```

sage: A = ([1, 1], [3, 1], [-1, -1])
sage: b = (1000, 1500, -400)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: P.run_simplex_method()
\begin{equation*}
...
\end{equation*}
The initial dictionary is infeasible, solving auxiliary problem.
...
Entering:  $x_{0}$ . Leaving:  $x_{5}$ .
...
Entering:  $x_{1}$ . Leaving:  $x_{0}$ .
...
Back to the original problem.
...
Entering:  $x_{5}$ . Leaving:  $x_{4}$ .
...
Entering:  $x_{2}$ . Leaving:  $x_{3}$ .
...
The optimal value: $6250$. An optimal solution:  $\left(250, \, 750\right)$ .

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)], [-Integer(1), -
↳Integer(1)])
>>> b = (Integer(1000), Integer(1500), -Integer(400))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> P.run_simplex_method()
\begin{equation*}
...
\end{equation*}
The initial dictionary is infeasible, solving auxiliary problem.
...
Entering:  $x_{0}$ . Leaving:  $x_{5}$ .
...
Entering:  $x_{1}$ . Leaving:  $x_{0}$ .
...
Back to the original problem.
...
Entering:  $x_{5}$ . Leaving:  $x_{4}$ .
...
Entering:  $x_{2}$ . Leaving:  $x_{3}$ .
...
The optimal value: $6250$. An optimal solution:  $\left(250, \, 750\right)$ .

```

`slack_variables()`

Return slack variables of `self`.

Slack variables are differences between the constant terms and left hand sides of the constraints.

If you want to give custom names to slack variables, you have to do so during construction of the problem.

OUTPUT: a tuple

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: P.slack_variables()
(x3, x4)
sage: P = InteractiveLPPProblemStandardForm(A, b, c, ["C", "B"],
....:     slack_variables=["L", "F"])
sage: P.slack_variables()
(L, F)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> P.slack_variables()
(x3, x4)
>>> P = InteractiveLPPProblemStandardForm(A, b, c, ["C", "B"],
...     slack_variables=["L", "F"])
>>> P.slack_variables()
(L, F)
```

class `sage.numerical.interactive_simplex_method.LPAbstractDictionary`

Bases: `SageObject`

Abstract base class for dictionaries for LP problems.

Instantiating this class directly is meaningless, see `LPDictionary` and `LPRevisedDictionary` for useful extensions.

add_row (*nonbasic_coefficients*, *constant*, *basic_variable=None*)

Return a dictionary with an additional row based on a given dictionary.

INPUT:

- `nonbasic_coefficients` – list of the coefficients for the new row (with which nonbasic variables are subtracted in the relation for the new basic variable)
- `constant` – the constant term for the new row
- `basic_variable` – (default: depends on `style()`) a string giving the name of the basic variable of the new row

OUTPUT: a new dictionary of the same class

EXAMPLES:

```

sage: A = ([-1, 1, 7], [8, 2, 13], [34, 17, 12])
sage: b = (2, 17, 6)
sage: c = (55/10, 21/10, 14/30)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.dictionary("x1", "x2", "x4")
sage: D1 = D.add_row([7, 11, 19], 42, basic_variable='c')
sage: D1.row_coefficients("c")
(7, 11, 19)

```

```

>>> from sage.all import *
>>> A = ([-Integer(1), Integer(1), Integer(7)], [Integer(8), Integer(2),
↳Integer(13)], [Integer(34), Integer(17), Integer(12)])
>>> b = (Integer(2), Integer(17), Integer(6))
>>> c = (Integer(55)/Integer(10), Integer(21)/Integer(10), Integer(14)/
↳Integer(30))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.dictionary("x1", "x2", "x4")
>>> D1 = D.add_row([Integer(7), Integer(11), Integer(19)], Integer(42), basic_
↳variable='c')
>>> D1.row_coefficients("c")
(7, 11, 19)

```

base_ring()

Return the base ring of `self`, i.e. the ring of coefficients.

OUTPUT: a ring

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.base_ring()
Rational Field
sage: D = P.revised_dictionary()
sage: D.base_ring()
Rational Field

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.base_ring()
Rational Field
>>> D = P.revised_dictionary()
>>> D.base_ring()
Rational Field

```

basic_solution (*include_slack_variables=False*)

Return the basic solution of `self`.

The basic solution associated to a dictionary is obtained by setting to zero all `nonbasic_variables()`, in which case `basic_variables()` have to be equal to `constant_terms()` in equations. It may refer to values of `decision_variables()` only or include `slack_variables()` as well.

INPUT:

- `include_slack_variables` – boolean (default: `False`); if `True`, values of slack variables will be appended at the end

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.basic_solution()
(0, 0)
sage: D.basic_solution(True)
(0, 0, 1000, 1500)
sage: D = P.revised_dictionary()
sage: D.basic_solution()
(0, 0)
sage: D.basic_solution(True)
(0, 0, 1000, 1500)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.basic_solution()
(0, 0)
>>> D.basic_solution(True)
(0, 0, 1000, 1500)
>>> D = P.revised_dictionary()
>>> D.basic_solution()
(0, 0)
>>> D.basic_solution(True)
(0, 0, 1000, 1500)
```

`basic_variables()`

Return the basic variables of `self`.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
```

(continues on next page)

(continued from previous page)

```
sage: D.basic_variables()
(x3, x4)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.basic_variables()
(x3, x4)
```

column_coefficients(v)

Return the coefficients of a nonbasic variable.

INPUT:

- v – a nonbasic variable of `self`, can be given as a string, an actual variable, or an integer interpreted as the index of a variable

OUTPUT: a vector of coefficients of a nonbasic variable

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.column_coefficients(1)
(1, 3)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.column_coefficients(Integer(1))
(1, 3)
```

constant_terms()

Return the constant terms of relations of `self`.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.constant_terms()
(1000, 1500)
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.constant_terms()
(1000, 1500)
    
```

`coordinate_ring()`

Return the coordinate ring of self.

OUTPUT:

- a polynomial ring in `auxiliary_variable()`, `decision_variables()`, and `slack_variables()` of self over the `base_ring()`

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.coordinate_ring()
Multivariate Polynomial Ring in x0, x1, x2, x3, x4
over Rational Field
sage: D = P.revised_dictionary()
sage: D.coordinate_ring()
Multivariate Polynomial Ring in x0, x1, x2, x3, x4
over Rational Field
    
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.coordinate_ring()
Multivariate Polynomial Ring in x0, x1, x2, x3, x4
over Rational Field
>>> D = P.revised_dictionary()
>>> D.coordinate_ring()
Multivariate Polynomial Ring in x0, x1, x2, x3, x4
over Rational Field
    
```

`dual_ratios()`

Return ratios used to determine the entering variable based on leaving.

OUTPUT:

- A list of pairs (r_j, x_j) where x_j is a non-basic variable and $r_j = c_j/a_{ij}$ is the ratio of the objective coefficient c_j to the coefficient a_{ij} of x_j in the relation for the leaving variable x_i :

$$x_i = b_i - \dots - a_{ij}x_j - \dots .$$

The order of pairs matches the order of `nonbasic_variables()`, but only x_j with negative a_{ij} are considered.

EXAMPLES:

```
sage: A = ([1, 1], [3, 1], [-1, -1])
sage: b = (1000, 1500, -400)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.dictionary(2, 3, 5)
sage: D.leave(3)
sage: D.dual_ratios()
[(5/2, x1), (5, x4)]
sage: D = P.revised_dictionary(2, 3, 5)
sage: D.leave(3)
sage: D.dual_ratios()
[(5/2, x1), (5, x4)]
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)], [-Integer(1), -
↳ Integer(1)])
>>> b = (Integer(1000), Integer(1500), -Integer(400))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.dictionary(Integer(2), Integer(3), Integer(5))
>>> D.leave(Integer(3))
>>> D.dual_ratios()
[(5/2, x1), (5, x4)]
>>> D = P.revised_dictionary(Integer(2), Integer(3), Integer(5))
>>> D.leave(Integer(3))
>>> D.dual_ratios()
[(5/2, x1), (5, x4)]
```

enter(v)

Set v as the entering variable of `self`.

INPUT:

- v – a non-basic variable of `self`, can be given as a string, an actual variable, or an integer interpreted as the index of a variable. It is also possible to enter `None` to reset choice.

OUTPUT:

- none, but the selected variable will be used as entering by methods that require an entering variable and the corresponding column will be typeset in green

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.enter("x1")
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.enter("x1")
    
```

We can also use indices of variables:

```
sage: D.enter(1)
```

```

>>> from sage.all import *
>>> D.enter(Integer(1))
    
```

Or variable names without quotes after injecting them:

```

sage: P.inject_variables()
Defining x0, x1, x2, x3, x4
sage: D.enter(x1)
    
```

```

>>> from sage.all import *
>>> P.inject_variables()
Defining x0, x1, x2, x3, x4
>>> D.enter(x1)
    
```

The same works for revised dictionaries as well:

```

sage: D = P.revised_dictionary()
sage: D.enter(x1)
    
```

```

>>> from sage.all import *
>>> D = P.revised_dictionary()
>>> D.enter(x1)
    
```

entering()

Return the currently chosen entering variable.

OUTPUT: a variable if the entering one was chosen, otherwise None

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.entering() is None
True
sage: D.enter(1)
sage: D.entering()
x1
    
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.entering() is None
True
>>> D.enter(Integer(1))
>>> D.entering()
x1

```

entering_coefficients()

Return coefficients of the entering variable.

OUTPUT: a vector

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.enter(1)
sage: D.entering_coefficients()
(1, 3)

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.enter(Integer(1))
>>> D.entering_coefficients()
(1, 3)

```

is_dual_feasible()

Check if `self` is dual feasible.

OUTPUT:

- True if all `objective_coefficients()` are nonpositive, False otherwise

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.is_dual_feasible()
False
sage: D = P.revised_dictionary()

```

(continues on next page)

(continued from previous page)

```
sage: D.is_dual_feasible()
False
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.is_dual_feasible()
False
>>> D = P.revised_dictionary()
>>> D.is_dual_feasible()
False
```

is_feasible()

Check if self is feasible.

OUTPUT:

- True if all *constant_terms()* are nonnegative, False otherwise

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.is_feasible()
True
sage: D = P.revised_dictionary()
sage: D.is_feasible()
True
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.is_feasible()
True
>>> D = P.revised_dictionary()
>>> D.is_feasible()
True
```

is_optimal()

Check if self is optimal.

OUTPUT:

- True if self *is_feasible()* and *is_dual_feasible()* (i.e. all *constant_terms()* are non-negative and all *objective_coefficients()* are nonpositive), False otherwise.

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.is_optimal()
False
sage: D = P.revised_dictionary()
sage: D.is_optimal()
False
sage: D = P.revised_dictionary(1, 2)
sage: D.is_optimal()
True

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.is_optimal()
False
>>> D = P.revised_dictionary()
>>> D.is_optimal()
False
>>> D = P.revised_dictionary(Integer(1), Integer(2))
>>> D.is_optimal()
True

```

leave(*v*)

Set *v* as the leaving variable of *self*.

INPUT:

- *v* – a basic variable of *self*, can be given as a string, an actual variable, or an integer interpreted as the index of a variable. It is also possible to leave `None` to reset choice.

OUTPUT:

- none, but the selected variable will be used as leaving by methods that require a leaving variable and the corresponding row will be typeset in red

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.leave("x4")

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])

```

(continues on next page)

(continued from previous page)

```

>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.leave("x4")

```

We can also use indices of variables:

```
sage: D.leave(4)
```

```

>>> from sage.all import *
>>> D.leave(Integer(4))

```

Or variable names without quotes after injecting them:

```

sage: P.inject_variables()
Defining x0, x1, x2, x3, x4
sage: D.leave(x4)

```

```

>>> from sage.all import *
>>> P.inject_variables()
Defining x0, x1, x2, x3, x4
>>> D.leave(x4)

```

The same works for revised dictionaries as well:

```

sage: D = P.revised_dictionary()
sage: D.leave(x4)

```

```

>>> from sage.all import *
>>> D = P.revised_dictionary()
>>> D.leave(x4)

```

leaving()

Return the currently chosen leaving variable.

OUTPUT: a variable if the leaving one was chosen, otherwise None

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.leaving() is None
True
sage: D.leave(4)
sage: D.leaving()
x4

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.leaving() is None
True
>>> D.leave(Integer(4))
>>> D.leaving()
x4

```

leaving_coefficients()

Return coefficients of the leaving variable.

OUTPUT: a vector

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.dictionary(2, 3)
sage: D.leave(3)
sage: D.leaving_coefficients()
(-2, -1)

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.dictionary(Integer(2), Integer(3))
>>> D.leave(Integer(3))
>>> D.leaving_coefficients()
(-2, -1)

```

The same works for revised dictionaries as well:

```

sage: D = P.revised_dictionary(2, 3)
sage: D.leave(3)
sage: D.leaving_coefficients()
(-2, -1)

```

```

>>> from sage.all import *
>>> D = P.revised_dictionary(Integer(2), Integer(3))
>>> D.leave(Integer(3))
>>> D.leaving_coefficients()
(-2, -1)

```

nonbasic_variables()

Return non-basic variables of `self`.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.nonbasic_variables()
(x1, x2)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.nonbasic_variables()
(x1, x2)
```

objective_coefficients()

Return coefficients of the objective of *self*.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.objective_coefficients()
(10, 5)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.objective_coefficients()
(10, 5)
```

objective_name()

Return the objective name of *self*.

OUTPUT: a symbolic expression

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
```

(continues on next page)

(continued from previous page)

```
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.objective_name()
z
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.objective_name()
z
```

objective_value()

Return the value of the objective at the *basic_solution()* of self.

OUTPUT: a number

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.objective_value()
0
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.objective_value()
0
```

possible_dual_simplex_method_steps()

Return possible dual simplex method steps for self.

OUTPUT:

- A list of pairs (leaving, entering), where leaving is a basic variable that may *leave()* and entering is a list of non-basic variables that may *enter()* when leaving leaves. Note that entering may be empty, indicating that the problem is infeasible (since the dual one is unbounded).

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.dictionary(2, 3)
```

(continues on next page)

(continued from previous page)

```
sage: D.possible_dual_simplex_method_steps()
[(x3, [x1])]
sage: D = P.revised_dictionary(2, 3)
sage: D.possible_dual_simplex_method_steps()
[(x3, [x1])]
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.dictionary(Integer(2), Integer(3))
>>> D.possible_dual_simplex_method_steps()
[(x3, [x1])]
>>> D = P.revised_dictionary(Integer(2), Integer(3))
>>> D.possible_dual_simplex_method_steps()
[(x3, [x1])]
```

possible_entering()

Return possible entering variables for *self*.

OUTPUT:

- a list of non-basic variables of *self* that can *enter()* on the next step of the (dual) simplex method

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.possible_entering()
[x1, x2]
sage: D = P.revised_dictionary()
sage: D.possible_entering()
[x1, x2]
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.possible_entering()
[x1, x2]
>>> D = P.revised_dictionary()
>>> D.possible_entering()
[x1, x2]
```

possible_leaving()

Return possible leaving variables for *self*.

OUTPUT:

- a list of basic variables of `self` that can `leave()` on the next step of the (dual) simplex method

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.enter(1)
sage: D.possible_leaving()
[x4]
sage: D = P.revised_dictionary()
sage: D.enter(1)
sage: D.possible_leaving()
[x4]
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.enter(Integer(1))
>>> D.possible_leaving()
[x4]
>>> D = P.revised_dictionary()
>>> D.enter(Integer(1))
>>> D.possible_leaving()
[x4]
```

possible_simplex_method_steps()

Return possible simplex method steps for `self`.

OUTPUT:

- A list of pairs `(entering, leaving)`, where `entering` is a non-basic variable that may `enter()` and `leaving` is a list of basic variables that may `leave()` when `entering` enters. Note that `leaving` may be empty, indicating that the problem is unbounded.

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.possible_simplex_method_steps()
[(x1, [x4]), (x2, [x3])]
sage: D = P.revised_dictionary()
sage: D.possible_simplex_method_steps()
[(x1, [x4]), (x2, [x3])]
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
```

(continues on next page)

(continued from previous page)

```

>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.possible_simplex_method_steps()
[(x1, [x4]), (x2, [x3])]
>>> D = P.revised_dictionary()
>>> D.possible_simplex_method_steps()
[(x1, [x4]), (x2, [x3])]
    
```

`ratios()`

Return ratios used to determine the leaving variable based on entering.

OUTPUT:

- A list of pairs (r_i, x_i) where x_i is a basic variable and $r_i = b_i/a_{ik}$ is the ratio of the constant term b_i to the coefficient a_{ik} of the entering variable x_k in the relation for x_i :

$$x_i = b_i - \dots - a_{ik}x_k - \dots .$$

The order of pairs matches the order of `basic_variables()`, but only x_i with positive a_{ik} are considered.

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.enter(1)
sage: D.ratios()
[(1000, x3), (500, x4)]
sage: D = P.revised_dictionary()
sage: D.enter(1)
sage: D.ratios()
[(1000, x3), (500, x4)]
    
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.enter(Integer(1))
>>> D.ratios()
[(1000, x3), (500, x4)]
>>> D = P.revised_dictionary()
>>> D.enter(Integer(1))
>>> D.ratios()
[(1000, x3), (500, x4)]
    
```

`row_coefficients(v)`

Return the coefficients of the basic variable v .

These are the coefficients with which nonbasic variables are subtracted in the relation for v .

INPUT:

- v – a basic variable of `self`, can be given as a string, an actual variable, or an integer interpreted as the index of a variable

OUTPUT: a vector of coefficients of a basic variable

EXAMPLES:

```
sage: A = ([-1, 1], [8, 2])
sage: b = (2, 17)
sage: c = (55/10, 21/10)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.final_dictionary()
sage: D.row_coefficients("x1")
(1/10, -1/5)
```

```
>>> from sage.all import *
>>> A = ([-Integer(1), Integer(1)], [Integer(8), Integer(2)])
>>> b = (Integer(2), Integer(17))
>>> c = (Integer(55)/Integer(10), Integer(21)/Integer(10))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.final_dictionary()
>>> D.row_coefficients("x1")
(1/10, -1/5)
```

We can also use indices of variables:

```
sage: D.row_coefficients(1)
(1/10, -1/5)
```

```
>>> from sage.all import *
>>> D.row_coefficients(Integer(1))
(1/10, -1/5)
```

Or use variable names without quotes after injecting them:

```
sage: P.inject_variables()
Defining x0, x1, x2, x3, x4
sage: D.row_coefficients(x1)
(1/10, -1/5)
```

```
>>> from sage.all import *
>>> P.inject_variables()
Defining x0, x1, x2, x3, x4
>>> D.row_coefficients(x1)
(1/10, -1/5)
```

`run_dual_simplex_method()`

Apply the dual simplex method and return all steps/intermediate states.

If either entering or leaving variables were already set, they will be used.

OUTPUT:

- `HtmlFragment` with HTML/L^AT_EX code of all encountered dictionaries

EXAMPLES:

```
sage: A = ([1, 1], [3, 1], [-1, -1])
sage: b = (1000, 1500, -400)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.run_dual_simplex_method()
Traceback (most recent call last):
...
ValueError: leaving variables can be determined for feasible
dictionaries with a set entering variable or for dual feasible
dictionaries
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)], [-Integer(1), -
↳Integer(1)])
>>> b = (Integer(1000), Integer(1500), -Integer(400))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.run_dual_simplex_method()
Traceback (most recent call last):
...
ValueError: leaving variables can be determined for feasible
dictionaries with a set entering variable or for dual feasible
dictionaries
```

Let's start with a dual feasible dictionary then:

```
sage: D = P.dictionary(2, 3, 5)
sage: D.is_dual_feasible()
True
sage: D.is_optimal()
False
sage: D.run_dual_simplex_method()
\begin{equation*}
...
\end{equation*}
Leaving:  $x_3$ . Entering:  $x_1$ .
\begin{equation*}
...
\end{equation*}
sage: D.is_optimal()
True
```

```
>>> from sage.all import *
>>> D = P.dictionary(Integer(2), Integer(3), Integer(5))
>>> D.is_dual_feasible()
True
>>> D.is_optimal()
False
```

(continues on next page)

(continued from previous page)

```

>>> D.run_dual_simplex_method()
\begin{equation*}
...
\end{equation*}
Leaving:  $x_3$ . Entering:  $x_1$ .
\begin{equation*}
...
\end{equation*}
>>> D.is_optimal()
True

```

This method detects infeasible problems:

```

sage: A = ([1, 0],)
sage: b = (-1,)
sage: c = (0, -1)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.run_dual_simplex_method()
\begin{equation*}
...
\end{equation*}
The problem is infeasible because of  $x_3$  constraint.

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(0)],)
>>> b = (-Integer(1),)
>>> c = (Integer(0), -Integer(1))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.run_dual_simplex_method()
\begin{equation*}
...
\end{equation*}
The problem is infeasible because of  $x_3$  constraint.

```

`run_simplex_method()`

Apply the simplex method and return all steps and intermediate states.

If either entering or leaving variables were already set, they will be used.

OUTPUT:

- `HtmlFragment` with HTML/L^AT_EX code of all encountered dictionaries

EXAMPLES:

```

sage: A = ([1, 1], [3, 1], [-1, -1])
sage: b = (1000, 1500, -400)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.run_simplex_method()
Traceback (most recent call last):

```

(continues on next page)

(continued from previous page)

```
...
ValueError: entering variables can be determined for feasible
dictionaries or for dual feasible dictionaries with a set leaving
variable
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)], [-Integer(1), -
↳Integer(1)])
>>> b = (Integer(1000), Integer(1500), -Integer(400))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.run_simplex_method()
Traceback (most recent call last):
...
ValueError: entering variables can be determined for feasible
dictionaries or for dual feasible dictionaries with a set leaving
variable
```

Let's start with a feasible dictionary then:

```
sage: D = P.dictionary(1, 3, 4)
sage: D.is_feasible()
True
sage: D.is_optimal()
False
sage: D.run_simplex_method()
\begin{equation*}
...
\end{equation*}
Entering:  $x_5$ . Leaving:  $x_4$ .
\begin{equation*}
...
\end{equation*}
Entering:  $x_2$ . Leaving:  $x_3$ .
\begin{equation*}
...
\end{equation*}
sage: D.is_optimal()
True
```

```
>>> from sage.all import *
>>> D = P.dictionary(Integer(1), Integer(3), Integer(4))
>>> D.is_feasible()
True
>>> D.is_optimal()
False
>>> D.run_simplex_method()
\begin{equation*}
...
\end{equation*}
Entering:  $x_5$ . Leaving:  $x_4$ .
```

(continues on next page)

(continued from previous page)

```

\begin{equation*}
...
\end{equation*}
Entering:  $x_2$ . Leaving:  $x_3$ .
\begin{equation*}
...
\end{equation*}
>>> D.is_optimal()
True

```

This method detects unbounded problems:

```

sage: A = ([1, 0],)
sage: b = (1,)
sage: c = (0, 1)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.run_simplex_method()
\begin{equation*}
...
\end{equation*}
The problem is unbounded in  $x_2$  direction.

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(0)],)
>>> b = (Integer(1),)
>>> c = (Integer(0), Integer(1))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.run_simplex_method()
\begin{equation*}
...
\end{equation*}
The problem is unbounded in  $x_2$  direction.

```

update ()

Update self using previously set entering and leaving variables.

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.objective_value()
0
sage: D.enter("x1")
sage: D.leave("x4")
sage: D.update()
sage: D.objective_value()
5000

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.objective_value()
0
>>> D.enter("x1")
>>> D.leave("x4")
>>> D.update()
>>> D.objective_value()
5000
    
```

```

class sage.numerical.interactive_simplex_method.LPDictionary(A, b, c, objective_value,
                                                           basic_variables,
                                                           nonbasic_variables,
                                                           objective_name)
    
```

Bases: *LPAbstractDictionary*

Construct a dictionary for an LP problem.

A dictionary consists of the following data:

$$\begin{array}{l} x_B = b - Ax_N \\ z = z^* + cx_N \end{array}$$

INPUT:

- A – a matrix of relation coefficients
- b – a vector of relation constant terms
- c – a vector of objective coefficients
- `objective_value` – current value of the objective z^*
- `basic_variables` – list of basic variables x_B
- `nonbasic_variables` – list of non-basic variables x_N
- `objective_name` – a “name” for the objective z

OUTPUT: a *dictionary for an LP problem*

Note

This constructor does not check correctness of input, as it is intended to be used internally by *InteractiveLPProblemStandardForm*.

EXAMPLES:

The intended way to use this class is indirect:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPProblemStandardForm(A, b, c)
    
```

(continues on next page)

(continued from previous page)

```
sage: D = P.initial_dictionary()
sage: D
LP problem dictionary (use ...)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D
LP problem dictionary (use ...)
```

But if you want you can create a dictionary without starting with an LP problem, here is construction of the same dictionary as above:

```
sage: A = matrix(QQ, ([1, 1], [3, 1]))
sage: b = vector(QQ, (1000, 1500))
sage: c = vector(QQ, (10, 5))
sage: R = PolynomialRing(QQ, "x1, x2, x3, x4", order='neglex')
sage: from sage.numerical.interactive_simplex_method \
.....:     import LPDictionary
sage: D2 = LPDictionary(A, b, c, 0, R.gens()[2:], R.gens()[2:], "z")
sage: D2 == D
True
```

```
>>> from sage.all import *
>>> A = matrix(QQ, ([Integer(1), Integer(1)], [Integer(3), Integer(1)]))
>>> b = vector(QQ, (Integer(1000), Integer(1500)))
>>> c = vector(QQ, (Integer(10), Integer(5)))
>>> R = PolynomialRing(QQ, "x1, x2, x3, x4", order='neglex')
>>> from sage.numerical.interactive_simplex_method import LPDictionary
>>> D2 = LPDictionary(A, b, c, Integer(0), R.gens()[Integer(2):], R.
↳gens()[Integer(2):], "z")
>>> D2 == D
True
```

add_row (*nonbasic_coefficients*, *constant*, *basic_variable=None*)

Return a dictionary with an additional row based on a given dictionary.

INPUT:

- *nonbasic_coefficients* – list of the coefficients for the new row (with which nonbasic variables are subtracted in the relation for the new basic variable)
- *constant* – the constant term for the new row
- *basic_variable* – (default: depends on *style()*) a string giving the name of the basic variable of the new row

OUTPUT: a *dictionary*

EXAMPLES:

```

sage: A = ([-1, 1, 7], [8, 2, 13], [34, 17, 12])
sage: b = (2, 17, 6)
sage: c = (55/10, 21/10, 14/30)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.dictionary("x1", "x2", "x4")
sage: D1 = D.add_row([7, 11, 19], 42, basic_variable='c')
sage: D1.row_coefficients("c")
(7, 11, 19)
sage: D1.constant_terms() [-1]
42
sage: D1.basic_variables() [-1]
c
    
```

```

>>> from sage.all import *
>>> A = ([-Integer(1), Integer(1), Integer(7)], [Integer(8), Integer(2),
↳Integer(13)], [Integer(34), Integer(17), Integer(12)])
>>> b = (Integer(2), Integer(17), Integer(6))
>>> c = (Integer(55)/Integer(10), Integer(21)/Integer(10), Integer(14)/
↳Integer(30))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.dictionary("x1", "x2", "x4")
>>> D1 = D.add_row([Integer(7), Integer(11), Integer(19)], Integer(42), basic_
↳variable='c')
>>> D1.row_coefficients("c")
(7, 11, 19)
>>> D1.constant_terms() [-Integer(1)]
42
>>> D1.basic_variables() [-Integer(1)]
c
    
```

`basic_variables()`

Return the basic variables of `self`.

OUTPUT: a vector

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.basic_variables()
(x3, x4)
    
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.basic_variables()
(x3, x4)
    
```

column_coefficients(*v*)

Return coefficients of a nonbasic variable.

INPUT:

- *v* – a nonbasic variable of *self*, can be given as a string, an actual variable, or an integer interpreted as the index of a variable

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.column_coefficients(1)
(1, 3)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.column_coefficients(Integer(1))
(1, 3)
```

constant_terms()

Return the constant terms of relations of *self*.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.constant_terms()
(1000, 1500)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.constant_terms()
(1000, 1500)
```

nonbasic_variables()

Return non-basic variables of *self*.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.nonbasic_variables()
(x1, x2)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.nonbasic_variables()
(x1, x2)
```

objective_coefficients()

Return coefficients of the objective of self.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.objective_coefficients()
(10, 5)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.objective_coefficients()
(10, 5)
```

objective_name()

Return the objective name of self.

OUTPUT: a symbolic expression

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
```

(continues on next page)

(continued from previous page)

```
sage: D.objective_name()
z
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.objective_name()
z
```

objective_value()

Return the value of the objective at the *basic_solution()* of self.

OUTPUT: a number

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.objective_value()
0
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.objective_value()
0
```

static random_element(m, n, bound=5, special_probability=0.2)

Construct a random dictionary.

INPUT:

- *m* – the number of constraints/basic variables
- *n* – the number of decision/non-basic variables
- *bound* – (default: 5) a bound on dictionary entries
- *special_probability* – (default: 0.2) probability of constructing a potentially infeasible or potentially optimal dictionary

OUTPUT: an *LP problem dictionary*

EXAMPLES:

```
sage: from sage.numerical.interactive_simplex_method \
....:     import random_dictionary
```

(continues on next page)

(continued from previous page)

```
sage: random_dictionary(3, 4) # indirect doctest
LP problem dictionary (use 'view(...)' or '%display typeset' for details)
```

```
>>> from sage.all import *
>>> from sage.numerical.interactive_simplex_method import random_
↳dictionary
>>> random_dictionary(Integer(3), Integer(4)) # indirect doctest
LP problem dictionary (use 'view(...)' or '%display typeset' for details)
```

row_coefficients(*v*)

Return the coefficients of the basic variable *v*.

These are the coefficients with which nonbasic variables are subtracted in the relation for *v*.

INPUT:

- *v* – a basic variable of *self*, can be given as a string, an actual variable, or an integer interpreted as the index of a variable

OUTPUT: a vector of coefficients of a basic variable

EXAMPLES:

```
sage: A = ([-1, 1], [8, 2])
sage: b = (2, 17)
sage: c = (55/10, 21/10)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.final_dictionary()
sage: D.row_coefficients("x1")
(1/10, -1/5)
```

```
>>> from sage.all import *
>>> A = ([-Integer(1), Integer(1)], [Integer(8), Integer(2)])
>>> b = (Integer(2), Integer(17))
>>> c = (Integer(55)/Integer(10), Integer(21)/Integer(10))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.final_dictionary()
>>> D.row_coefficients("x1")
(1/10, -1/5)
```

We can also use indices of variables:

```
sage: D.row_coefficients(1)
(1/10, -1/5)
```

```
>>> from sage.all import *
>>> D.row_coefficients(Integer(1))
(1/10, -1/5)
```

Or use variable names without quotes after injecting them:

```
sage: P.inject_variables()
Defining x0, x1, x2, x3, x4
```

(continues on next page)

(continued from previous page)

```
sage: D.row_coefficients(x1)
(1/10, -1/5)
```

```
>>> from sage.all import *
>>> P.inject_variables()
Defining x0, x1, x2, x3, x4
>>> D.row_coefficients(x1)
(1/10, -1/5)
```

update ()

Update self using previously set entering and leaving variables.

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.initial_dictionary()
sage: D.objective_value()
0
sage: D.enter("x1")
sage: D.leave("x4")
sage: D.update()
sage: D.objective_value()
5000
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.initial_dictionary()
>>> D.objective_value()
0
>>> D.enter("x1")
>>> D.leave("x4")
>>> D.update()
>>> D.objective_value()
5000
```

class sage.numerical.interactive_simplex_method.LPRevisedDictionary (*problem, basic_variables*)

Bases: *LPAbstractDictionary*

Construct a revised dictionary for an LP problem.

INPUT:

- *problem* – an LP problem in standard form
- *basic_variables* – list of basic variables or their indices

OUTPUT: a revised dictionary for an LP problem

A revised dictionary encodes the same relations as a *regular dictionary*, but stores only what is “necessary to efficiently compute data for the simplex method”.

Let the original problem be

$$\begin{aligned} \pm \max \quad & cx \\ \text{subject to} \quad & Ax \leq b \\ & x \geq 0 \end{aligned}$$

Let \bar{x} be the vector of `decision_variables()` x followed by the `slack_variables()`. Let \bar{c} be the vector of `objective_coefficients()` c followed by zeroes for all slack variables. Let $\bar{A} = (A|I)$ be the matrix of `constraint_coefficients()` A augmented by the identity matrix as columns corresponding to the slack variables. Then the problem above can be written as

$$\begin{aligned} \pm \max \quad & \bar{c}\bar{x} \\ \text{subject to} \quad & \bar{A}\bar{x} = b \\ & \bar{x} \geq 0 \end{aligned}$$

and any dictionary is a system of equations equivalent to $\bar{A}\bar{x} = b$, but resolved for `basic_variables()` x_B in terms of `nonbasic_variables()` x_N together with the expression for the objective in terms of x_N . Let $c_B()$ and $c_N()$ be vectors “splitting \bar{c} into basic and non-basic parts”. Let $B()$ and $A_N()$ be the splitting of \bar{A} . Then the corresponding dictionary is

$$\begin{array}{l} x_B = B^{-1}b - B^{-1}A_Nx_N \\ z = yb + (c_N - y^T A_N)x_N \end{array}$$

where $y = c_B^T B^{-1}$. To proceed with the simplex method, it is not necessary to compute all entries of this dictionary. On the other hand, any entry is easy to compute, if you know B^{-1} , so we keep track of it through the update steps.

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPProblemStandardForm(A, b, c)
sage: from sage.numerical.interactive_simplex_method \
....:     import LPRevisedDictionary
sage: D = LPRevisedDictionary(P, [1, 2])
sage: D.basic_variables()
(x1, x2)
sage: D
LP problem dictionary (use ...)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPProblemStandardForm(A, b, c)
>>> from sage.numerical.interactive_simplex_method import LPRevisedDictionary
>>> D = LPRevisedDictionary(P, [Integer(1), Integer(2)])
>>> D.basic_variables()
(x1, x2)
>>> D
LP problem dictionary (use ...)
```

The same dictionary can be constructed through the problem:

```
sage: P.revised_dictionary(1, 2) == D
True
```

```
>>> from sage.all import *
>>> P.revised_dictionary(Integer(1), Integer(2)) == D
True
```

When this dictionary is typeset, you will see two tables like these ones:

| x_B | c_B | B^{-1} | | y | $B^{-1}b$ |
|-------|-------|----------------|----------------|---------------|-----------|
| x_1 | 10 | $-\frac{1}{2}$ | $\frac{1}{2}$ | $\frac{5}{2}$ | 250 |
| x_2 | 5 | $\frac{3}{2}$ | $-\frac{1}{2}$ | $\frac{5}{2}$ | 750 |

| x_N | x_3 | x_4 |
|-------------------|----------------|----------------|
| c_N^T | 0 | 0 |
| $y^T A_N$ | $\frac{5}{2}$ | $\frac{5}{2}$ |
| $c_N^T - y^T A_N$ | $-\frac{5}{2}$ | $-\frac{5}{2}$ |

More details will be shown if entering and leaving variables are set, but in any case the top table shows B^{-1} and a few extra columns, while the bottom one shows several rows: these are related to columns and rows of dictionary entries.

A(v)

Return the column of constraint coefficients corresponding to v .

INPUT:

- v – a variable, its name, or its index

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.A(1)
(1, 3)
sage: D.A(0)
(-1, -1)
sage: D.A("x3")
(1, 0)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
```

(continues on next page)

(continued from previous page)

```

>>> D.A(Integer(1))
(1, 3)
>>> D.A(Integer(0))
(-1, -1)
>>> D.A("x3")
(1, 0)

```

A_N()

Return the A_N matrix, constraint coefficients of non-basic variables.

OUTPUT: a matrix

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.A_N()
[1 1]
[3 1]

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.A_N()
[1 1]
[3 1]

```

B()

Return the B matrix, i.e. constraint coefficients of basic variables.

OUTPUT: a matrix

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary(1, 2)
sage: D.B()
[1 1]
[3 1]

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))

```

(continues on next page)

(continued from previous page)

```

>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary(Integer(1), Integer(2))
>>> D.B()
[1 1]
[3 1]

```

B_inverse()

Return the inverse of the $B()$ matrix.

This inverse matrix is stored and computed during dictionary update in a more efficient way than generic inversion.

OUTPUT: a matrix

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary(1, 2)
sage: D.B_inverse()
[-1/2  1/2]
[ 3/2 -1/2]

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary(Integer(1), Integer(2))
>>> D.B_inverse()
[-1/2  1/2]
[ 3/2 -1/2]

```

E()

Return the eta matrix between `self` and the next dictionary.

OUTPUT: a matrix

If B_{old} is the current matrix B and B_{new} is the B matrix of the next dictionary (after the update step), then $B_{\text{new}} = B_{\text{old}}E$.

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.enter(1)
sage: D.leave(4)
sage: D.E()
[1 1]
[0 3]

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.enter(Integer(1))
>>> D.leave(Integer(4))
>>> D.E()
[1 1]
[0 3]

```

E_inverse()

Return the inverse of the matrix $E()$.

This inverse matrix is computed in a more efficient way than generic inversion.

OUTPUT: a matrix

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.enter(1)
sage: D.leave(4)
sage: D.E_inverse()
[ 1 -1/3]
[ 0  1/3]

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.enter(Integer(1))
>>> D.leave(Integer(4))
>>> D.E_inverse()
[ 1 -1/3]
[ 0  1/3]

```

add_row(nonbasic_coefficients, constant, basic_variable=None)

Return a dictionary with an additional row based on a given dictionary.

The implementation of this method for revised dictionaries adds a new inequality constraint to the problem, in which the given `basic_variable` becomes the slack variable. The resulting dictionary (with `basic_variable` added to the basis) will have the given `nonbasic_coefficients` and `constant` as a new row.

INPUT:

- `nonbasic_coefficients` – list of the coefficients for the new row (with which nonbasic variables are subtracted in the relation for the new basic variable)

- `constant` – the constant term for the new row
- `basic_variable` – (default: depends on `style()`) a string giving the name of the basic variable of the new row

OUTPUT: a *revised dictionary*

EXAMPLES:

```
sage: A = ([-1, 1111, 3, 17], [8, 222, 7, 6],
....: [3, 7, 17, 5], [9, 5, 7, 3])
sage: b = (2, 17, 11, 27)
sage: c = (5/133, 1/10, 1/18, 47/3)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.final_revised_dictionary()
sage: D1 = D.add_row([7, 11, 13, 9], 42)
sage: D1.row_coefficients("x9")
(7, 11, 13, 9)
sage: D1.constant_terms()[-1]
42
sage: D1.basic_variables()[-1]
x9

sage: A = ([-9, 7, 48, 31, 23], [5, 2, 9, 13, 98],
....: [14, 15, 97, 49, 1], [9, 5, 7, 3, 17],
....: [119, 7, 121, 5, 111])
sage: b = (33, 27, 1, 272, 61)
sage: c = (51/133, 1/100, 149/18, 47/37, 13/17)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary("x1", "x2", "x3", "x4", "x5")
sage: D2 = D.add_row([5, 7, 11, 13, 9], 99, basic_variable='c')
sage: D2.row_coefficients("c")
(5, 7, 11, 13, 9)
sage: D2.constant_terms()[-1]
99
sage: D2.basic_variables()[-1]
c

sage: D = P.revised_dictionary(0, 1, 2, 3, 4)
sage: D.add_row([1, 2, 3, 4, 5, 6], 0)
Traceback (most recent call last):
...
ValueError: the sum of coefficients of nonbasic slack variables has
to be equal to -1 when inserting a row into a dictionary for the
auxiliary problem
sage: D3 = D.add_row([1, 2, 3, 4, 5, -15], 0)
sage: D3.row_coefficients(11)
(1, 2, 3, 4, 5, -15)
```

```
>>> from sage.all import *
>>> A = ([-Integer(1), Integer(1111), Integer(3), Integer(17)], [Integer(8),
↵Integer(222), Integer(7), Integer(6)],
... [Integer(3), Integer(7), Integer(17), Integer(5)], [Integer(9),
↵Integer(5), Integer(7), Integer(3)])
>>> b = (Integer(2), Integer(17), Integer(11), Integer(27))
```

(continues on next page)

(continued from previous page)

```

>>> c = (Integer(5)/Integer(133), Integer(1)/Integer(10), Integer(1)/
↳Integer(18), Integer(47)/Integer(3))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.final_revised_dictionary()
>>> D1 = D.add_row([Integer(7), Integer(11), Integer(13), Integer(9)],↳
↳Integer(42))
>>> D1.row_coefficients("x9")
(7, 11, 13, 9)
>>> D1.constant_terms()[-Integer(1)]
42
>>> D1.basic_variables()[-Integer(1)]
x9

>>> A = ([-Integer(9), Integer(7), Integer(48), Integer(31), Integer(23)],↳
↳[Integer(5), Integer(2), Integer(9), Integer(13), Integer(98)],
... [Integer(14), Integer(15), Integer(97), Integer(49), Integer(1)],↳
↳[Integer(9), Integer(5), Integer(7), Integer(3), Integer(17)],
... [Integer(119), Integer(7), Integer(121), Integer(5), Integer(111)])
>>> b = (Integer(33), Integer(27), Integer(1), Integer(272), Integer(61))
>>> c = (Integer(51)/Integer(133), Integer(1)/Integer(100), Integer(149)/
↳Integer(18), Integer(47)/Integer(37), Integer(13)/Integer(17))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary("x1", "x2", "x3", "x4", "x5")
>>> D2 = D.add_row([Integer(5), Integer(7), Integer(11), Integer(13),↳
↳Integer(9)], Integer(99), basic_variable='c')
>>> D2.row_coefficients("c")
(5, 7, 11, 13, 9)
>>> D2.constant_terms()[-Integer(1)]
99
>>> D2.basic_variables()[-Integer(1)]
c

>>> D = P.revised_dictionary(Integer(0), Integer(1), Integer(2), Integer(3),↳
↳Integer(4))
>>> D.add_row([Integer(1), Integer(2), Integer(3), Integer(4), Integer(5),↳
↳Integer(6)], Integer(0))
Traceback (most recent call last):
...
ValueError: the sum of coefficients of nonbasic slack variables has
to be equal to -1 when inserting a row into a dictionary for the
auxiliary problem
>>> D3 = D.add_row([Integer(1), Integer(2), Integer(3), Integer(4),↳
↳Integer(5), -Integer(15)], Integer(0))
>>> D3.row_coefficients(Integer(11))
(1, 2, 3, 4, 5, -15)

```

basic_indices()Return the basic indices of *self*.**Note**Basic indices are indices of *basic_variables()* in the list of generators of the *coordinate_ring()*

of the `problem()` of `self`, they may not coincide with the indices of variables which are parts of their names. (They will for the default indexed names.)

OUTPUT: list

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.basic_indices()
[3, 4]
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.basic_indices()
[3, 4]
```

basic_variables()

Return the basic variables of `self`.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.basic_variables()
(x3, x4)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.basic_variables()
(x3, x4)
```

c_B()

Return the c_B vector, objective coefficients of basic variables.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary(1, 2)
sage: D.c_B()
(10, 5)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary(Integer(1), Integer(2))
>>> D.c_B()
(10, 5)
```

c_N()

Return the c_N vector, objective coefficients of non-basic variables.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.c_N()
(10, 5)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.c_N()
(10, 5)
```

column_coefficients(v)

Return the coefficients of a nonbasic variable.

INPUT:

- v – a nonbasic variable of `self`, can be given as a string, an actual variable, or an integer interpreted as the index of a variable

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
```

(continues on next page)

(continued from previous page)

```
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.column_coefficients(1)
(1, 3)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.column_coefficients(Integer(1))
(1, 3)
```

constant_terms()

Return constant terms in the relations of *self*.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.constant_terms()
(1000, 1500)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.constant_terms()
(1000, 1500)
```

dictionary()

Return a regular LP dictionary matching *self*.

OUTPUT: an *LP dictionary*

EXAMPLES:

```
sage: A = ([1, 1], [3, 1], [-1, -1])
sage: b = (1000, 1500, -400)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.dictionary()
LP problem dictionary (use ...)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)], [-Integer(1), -
↳Integer(1)])
>>> b = (Integer(1000), Integer(1500), -Integer(400))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.dictionary()
LP problem dictionary (use ...)
```

nonbasic_indices()

Return the non-basic indices of *self*.

Note

Non-basic indices are indices of *nonbasic_variables()* in the list of generators of the *coordinate_ring()* of the *problem()* of *self*, they may not coincide with the indices of variables which are parts of their names. (They will for the default indexed names.)

OUTPUT: list

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.nonbasic_indices()
[1, 2]
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.nonbasic_indices()
[1, 2]
```

nonbasic_variables()

Return non-basic variables of *self*.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
```

(continues on next page)

(continued from previous page)

```
sage: D.nonbasic_variables()
(x1, x2)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.nonbasic_variables()
(x1, x2)
```

objective_coefficients()

Return coefficients of the objective of *self*.

OUTPUT: a vector

These are coefficients of non-basic variables when basic variables are eliminated.

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.objective_coefficients()
(10, 5)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.objective_coefficients()
(10, 5)
```

objective_name()

Return the objective name of *self*.

OUTPUT: a symbolic expression

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.objective_name()
z
```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.objective_name()
z

```

objective_value()

Return the value of the objective at the basic solution of *self*.

OUTPUT: a number

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.objective_value()
0

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.objective_value()
0

```

problem()

Return the original problem.

OUTPUT: an *LP problem in standard form*

EXAMPLES:

```

sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.problem() is P
True

```

```

>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()

```

(continues on next page)

(continued from previous page)

```
>>> D.problem() is P
True
```

row_coefficients(v)

Return the coefficients of the basic variable v .

These are the coefficients with which nonbasic variables are subtracted in the relation for v .

INPUT:

- v – a basic variable of `self`, can be given as a string, an actual variable, or an integer interpreted as the index of a variable

OUTPUT: a vector of coefficients of a basic variable

EXAMPLES:

```
sage: A = ([-1, 1], [8, 2])
sage: b = (2, 17)
sage: c = (55/10, 21/10)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.row_coefficients("x3")
(-1, 1)
```

```
>>> from sage.all import *
>>> A = ([-Integer(1), Integer(1)], [Integer(8), Integer(2)])
>>> b = (Integer(2), Integer(17))
>>> c = (Integer(55)/Integer(10), Integer(21)/Integer(10))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.row_coefficients("x3")
(-1, 1)
```

We can also use indices of variables:

```
sage: D.row_coefficients(3)
(-1, 1)
```

```
>>> from sage.all import *
>>> D.row_coefficients(Integer(3))
(-1, 1)
```

Or variable names without quotes after injecting them:

```
sage: P.inject_variables()
Defining x0, x1, x2, x3, x4
sage: D.row_coefficients(x3)
(-1, 1)
```

```
>>> from sage.all import *
>>> P.inject_variables()
Defining x0, x1, x2, x3, x4
```

(continues on next page)

(continued from previous page)

```
>>> D.row_coefficients(x3)
(-1, 1)
```

update()

Update self using previously set entering and leaving variables.

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
sage: D.objective_value()
0
sage: D.enter("x1")
sage: D.leave("x4")
sage: D.update()
sage: D.objective_value()
5000
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.objective_value()
0
>>> D.enter("x1")
>>> D.leave("x4")
>>> D.update()
>>> D.objective_value()
5000
```

x_B()

alias of *basic_variables()*.

x_N()

alias of *nonbasic_variables()*.

y()

Return the y vector, the product of *c_B()* and *B_inverse()*.

OUTPUT: a vector

EXAMPLES:

```
sage: A = ([1, 1], [3, 1])
sage: b = (1000, 1500)
sage: c = (10, 5)
sage: P = InteractiveLPPProblemStandardForm(A, b, c)
sage: D = P.revised_dictionary()
```

(continues on next page)

(continued from previous page)

```
sage: D.y()
(0, 0)
```

```
>>> from sage.all import *
>>> A = ([Integer(1), Integer(1)], [Integer(3), Integer(1)])
>>> b = (Integer(1000), Integer(1500))
>>> c = (Integer(10), Integer(5))
>>> P = InteractiveLPPProblemStandardForm(A, b, c)
>>> D = P.revised_dictionary()
>>> D.y()
(0, 0)
```

sage.numerical.interactive_simplex_method.**default_variable_name**(*variable*)

Return default variable name for the current *style*().

INPUT:

- *variable* – string describing requested name

OUTPUT: string with the requested name for current style

EXAMPLES:

```
sage: sage.numerical.interactive_simplex_method.default_variable_name("primal_
↳slack")
'x'
sage: sage.numerical.interactive_simplex_method.style('Vanderbei')
'Vanderbei'
sage: sage.numerical.interactive_simplex_method.default_variable_name("primal_
↳slack")
'w'
sage: sage.numerical.interactive_simplex_method.style('UAlberta')
'UAlberta'
```

```
>>> from sage.all import *
>>> sage.numerical.interactive_simplex_method.default_variable_name("primal slack
↳")
'x'
>>> sage.numerical.interactive_simplex_method.style('Vanderbei')
'Vanderbei'
>>> sage.numerical.interactive_simplex_method.default_variable_name("primal slack
↳")
'w'
>>> sage.numerical.interactive_simplex_method.style('UAlberta')
'UAlberta'
```

sage.numerical.interactive_simplex_method.**random_dictionary**(*m, n, bound=5,*
special_probability=0.2)

alias of `random_element()`.

sage.numerical.interactive_simplex_method.**style**(*new_style=None*)

Set or get the current style of problems and dictionaries.

INPUT:

- `new_style` – string or None (default)

OUTPUT:

- a string with current style (same as `new_style` if it was given)

If the input is not recognized as a valid style, a `ValueError` exception is raised.

Currently supported styles are:

- ‘UAlberta’ (default): Follows the style used in the Math 373 course on Mathematical Programming and Optimization at the University of Alberta, Edmonton, Canada; based on Chvatal’s book.
 - Objective functions of dictionaries are printed at the bottom.

Variable names default to

- z for primal objective
- z for dual objective
- w for auxiliary objective
- x_1, x_2, \dots, x_n for primal decision variables
- $x_{n+1}, x_{n+2}, \dots, x_{n+m}$ for primal slack variables
- y_1, y_2, \dots, y_m for dual decision variables
- $y_{m+1}, y_{m+2}, \dots, y_{m+n}$ for dual slack variables

- ‘Vanderbei’: Follows the style of Robert Vanderbei’s textbook, Linear Programming – Foundations and Extensions.

- Objective functions of dictionaries are printed at the top.

Variable names default to

- $zeta$ for primal objective
- x_i for dual objective
- x_i for auxiliary objective
- x_1, x_2, \dots, x_n for primal decision variables
- w_1, w_2, \dots, w_m for primal slack variables
- y_1, y_2, \dots, y_m for dual decision variables
- z_1, z_2, \dots, z_n for dual slack variables

EXAMPLES:

```
sage: sage.numerical.interactive_simplex_method.style()
'UAlberta'
sage: sage.numerical.interactive_simplex_method.style('Vanderbei')
'Vanderbei'
sage: sage.numerical.interactive_simplex_method.style('Doesntexist')
Traceback (most recent call last):
...
ValueError: Style must be one of: UAlberta, Vanderbei
sage: sage.numerical.interactive_simplex_method.style('UAlberta')
'UAlberta'
```

```

>>> from sage.all import *
>>> sage.numerical.interactive_simplex_method.style()
'UAlberta'
>>> sage.numerical.interactive_simplex_method.style('Vanderbei')
'Vanderbei'
>>> sage.numerical.interactive_simplex_method.style('Doesntexist')
Traceback (most recent call last):
...
ValueError: Style must be one of: UAlberta, Vanderbei
>>> sage.numerical.interactive_simplex_method.style('UAlberta')
'UAlberta'

```

sage.numerical.interactive_simplex_method.**variable**(v)

Interpret v as a variable of R .

INPUT:

- R – a polynomial ring
- v – a variable of R or convertible into R , a string with the name of a variable of R or an index of a variable in R

OUTPUT: a variable of R

EXAMPLES:

```

sage: from sage.numerical.interactive_simplex_method \
.....:     import variable
sage: R = PolynomialRing(QQ, "x3, y5, x5, y")
sage: R.inject_variables()
Defining x3, y5, x5, y
sage: variable(R, "x3")
x3
sage: variable(R, x3)
x3
sage: variable(R, 3)
x3
sage: variable(R, 0)
Traceback (most recent call last):
...
ValueError: there is no variable with the given index
sage: variable(R, 5)
Traceback (most recent call last):
...
ValueError: the given index is ambiguous
sage: variable(R, 2 * x3)
Traceback (most recent call last):
...
ValueError: cannot interpret given data as a variable
sage: variable(R, "z")
Traceback (most recent call last):
...
ValueError: cannot interpret given data as a variable

```

```
>>> from sage.all import *
>>> from sage.numerical.interactive_simplex_method import variable
>>> R = PolynomialRing(QQ, "x3, y5, x5, y")
>>> R.inject_variables()
Defining x3, y5, x5, y
>>> variable(R, "x3")
x3
>>> variable(R, x3)
x3
>>> variable(R, Integer(3))
x3
>>> variable(R, Integer(0))
Traceback (most recent call last):
...
ValueError: there is no variable with the given index
>>> variable(R, Integer(5))
Traceback (most recent call last):
...
ValueError: the given index is ambiguous
>>> variable(R, Integer(2) * x3)
Traceback (most recent call last):
...
ValueError: cannot interpret given data as a variable
>>> variable(R, "z")
Traceback (most recent call last):
...
ValueError: cannot interpret given data as a variable
```

GAUSS-LEGENDRE INTEGRATION FOR VECTOR-VALUED FUNCTIONS

Routine to perform Gauss-Legendre integration for vector-functions.

EXAMPLES:

We verify that $\int_0^1 nx^{n-1} dx = 1$ for $n = 1, \dots, 4$:

```
sage: from sage.numerical.gauss_legendre import integrate_vector
sage: prec = 100
sage: K = RealField(prec)
sage: N = 4
sage: V = VectorSpace(K, N)
sage: f = lambda x: V([(n+1)*x^n for n in range(N)])
sage: I = integrate_vector(f, prec)
sage: max([c.abs() for c in I-V(N*[1])])
0.00000000000000000000000000000000
```

```
>>> from sage.all import *
>>> from sage.numerical.gauss_legendre import integrate_vector
>>> prec = Integer(100)
>>> K = RealField(prec)
>>> N = Integer(4)
>>> V = VectorSpace(K, N)
>>> f = lambda x: V([(n+Integer(1))*x**n for n in range(N)])
>>> I = integrate_vector(f, prec)
>>> max([c.abs() for c in I-V(N*[Integer(1)])])
0.00000000000000000000000000000000
```

AUTHORS:

- Nils Bruin (2017-06-06): initial version
- Linden Disney-Hogg (2021-06-17): documentation and integrate_vector method changes

Note

The code here is directly based on mpmath (see <http://mpmath.org>), but has a highly optimized routine to compute the nodes.

sage.numerical.gauss_legendre.estimate_error(results, prec, epsilon)

Routine to estimate the error in a list of quadrature approximations.

The method used is based on Borwein, Bailey, and Girgensohn. As mentioned in `mpmath`: Although not very conservative, this method seems to be very robust in practice.

The routine takes a list of vector results and, under assumption that these vectors approximate a given vector approximately quadratically, gives an estimate of the maximum norm of the error in the last approximation.

INPUT:

- `results` – list of approximations to estimate the error from; should be at least length 2
- `prec` – integer; binary precision at which computations are happening
- `epsilon` – multiprecision float; default error estimate in case of insufficient data

OUTPUT: an estimate of the error

EXAMPLES:

```
sage: from sage.numerical.gauss_legendre import estimate_error
sage: prec = 200
sage: K = RealField(prec)
sage: V = VectorSpace(K, 2)
sage: a = V([1, -1])
sage: b = V([1, 1/2])
sage: L = [a + 2^(-2^i)*b for i in [0..5]]
sage: estimate_error(L, prec, K(2^(-prec)))
2.328235...e-10
```

```
>>> from sage.all import *
>>> from sage.numerical.gauss_legendre import estimate_error
>>> prec = Integer(200)
>>> K = RealField(prec)
>>> V = VectorSpace(K, Integer(2))
>>> a = V([Integer(1), -Integer(1)])
>>> b = V([Integer(1), Integer(1)/Integer(2)])
>>> L = [a + Integer(2)**(-Integer(2)**i)*b for i in (ellipsis_range(Integer(0),
↳Ellipsis,Integer(5)))]
>>> estimate_error(L, prec, K(Integer(2)**(-prec)))
2.328235...e-10
```

`sage.numerical.gauss_legendre.integrate_vector` (f , $prec$, $epsilon=None$)

Integrate a one-argument vector-valued function numerically using Gauss-Legendre.

This function uses the Gauss-Legendre quadrature scheme to approximate the integral $\int_0^1 f(t) dt$.

INPUT:

- f – callable; vector-valued integrand
- `prec` – integer; binary precision to be used
- `epsilon` – multiprecision float (default: $2^{-(prec+3)}$); target error bound

OUTPUT: vector approximating value of the integral

EXAMPLES:

```
sage: from sage.numerical.gauss_legendre import integrate_vector
sage: prec = 200
sage: K = RealField(prec)
```

(continues on next page)

(continued from previous page)

```

sage: V = VectorSpace(K, 2)
sage: epsilon = K(2^(-prec + 4))
sage: f = lambda t:V((1 + t^2, 1/(1 + t^2)))
sage: I = integrate_vector(f, prec, epsilon=epsilon)
sage: J = V((4/3, pi/4)) #_
↳needs sage.symbolic
sage: max(c.abs() for c in (I - J)) < epsilon #_
↳needs sage.symbolic
True

```

```

>>> from sage.all import *
>>> from sage.numerical.gauss_legendre import integrate_vector
>>> prec = Integer(200)
>>> K = RealField(prec)
>>> V = VectorSpace(K, Integer(2))
>>> epsilon = K(Integer(2)**(-prec + Integer(4)))
>>> f = lambda t:V((Integer(1) + t**Integer(2), Integer(1)/(Integer(1) +
↳t**Integer(2))))
>>> I = integrate_vector(f, prec, epsilon=epsilon)
>>> J = V((Integer(4)/Integer(3), pi/Integer(4))) #_
↳ # needs sage.symbolic
>>> max(c.abs() for c in (I - J)) < epsilon #_
↳needs sage.symbolic
True

```

We can also use complex-valued integrands:

```

sage: prec = 200
sage: Kreal = RealField(prec)
sage: K = ComplexField(prec)
sage: V = VectorSpace(K, 2)
sage: epsilon = Kreal(2^(-prec + 4))
sage: f = lambda t: V((t, K(exp(2*pi*t*K.0)))) #_
↳needs sage.symbolic
sage: I = integrate_vector(f, prec, epsilon=epsilon) #_
↳needs sage.symbolic
sage: J = V((1/2, 0))
sage: max(c.abs() for c in (I - J)) < epsilon #_
↳needs sage.symbolic
True

```

```

>>> from sage.all import *
>>> prec = Integer(200)
>>> Kreal = RealField(prec)
>>> K = ComplexField(prec)
>>> V = VectorSpace(K, Integer(2))
>>> epsilon = Kreal(Integer(2)**(-prec + Integer(4)))
>>> f = lambda t: V((t, K(exp(Integer(2)*pi*t*K.gen(0)))) #_
↳ # needs sage.symbolic
>>> I = integrate_vector(f, prec, epsilon=epsilon) #_
↳needs sage.symbolic
>>> J = V((Integer(1)/Integer(2), Integer(0)))

```

(continues on next page)

(continued from previous page)

```
>>> max(c.abs() for c in (I - J)) < epsilon #_
↪needs sage.symbolic
True
```

sage.numerical.gauss_legendre.**integrate_vector_N**(*f*, *prec*, *N*=3)

Integrate a one-argument vector-valued function numerically using Gauss-Legendre, setting the number of nodes.

This function uses the Gauss-Legendre quadrature scheme to approximate the integral $\int_0^1 f(t) dt$. It is different from `integrate_vector` by using a specific number of nodes rather than targeting a specified error bound on the result.

INPUT:

- *f* – callable; vector-valued integrand
- *prec* – integer; binary precision to be used
- *N* – integer (default: 3); number of nodes to use

OUTPUT: vector approximating value of the integral

EXAMPLES:

```
sage: from sage.numerical.gauss_legendre import integrate_vector_N
sage: prec = 100
sage: K = RealField(prec)
sage: V = VectorSpace(K, 1)
sage: f = lambda t: V([t])
sage: integrate_vector_N(f, prec, 4)
(0.50000000000000000000000000000000)
```

```
>>> from sage.all import *
>>> from sage.numerical.gauss_legendre import integrate_vector_N
>>> prec = Integer(100)
>>> K = RealField(prec)
>>> V = VectorSpace(K, Integer(1))
>>> f = lambda t: V([t])
>>> integrate_vector_N(f, prec, Integer(4))
(0.50000000000000000000000000000000)
```

Note

The nodes and weights are calculated in the real field with `prec` bits of precision. If the vector space in which `f` takes values is over a field which is incompatible with this field (e.g. a finite field) then a `TypeError` occurs.

sage.numerical.gauss_legendre.**nodes**(*prec*)

Compute the integration nodes and weights for the Gauss-Legendre quadrature scheme, caching the output

Works by calling `nodes_uncached`.

INPUT:

- *degree* – integer; the number of nodes (must be 3 or even)
- *prec* – integer (minimal value 53); binary precision with which the nodes and weights are computed

OUTPUT: list of (node, weight) pairs.

EXAMPLES:

The nodes for the Gauss-Legendre scheme are roots of Legendre polynomials. The weights can be computed by a straightforward formula (note that evaluating a derivative of a Legendre polynomial isn't particularly numerically stable, so the results from this routine are actually more accurate than what the values the closed formula produces):

```
sage: from sage.numerical.gauss_legendre import nodes
sage: L1 = nodes(24, 53)
sage: P = RR['x'](sage.functions.orthogonal_polys.legendre_P(24, x)) #_
↳needs sage.symbolic
sage: Pdif = P.diff() #_
↳needs sage.symbolic
sage: L2 = [(r + 1)/2, 1/(1 - r^2)/Pdif(r)^2] #_
↳needs sage.symbolic
....:     for r, _ in RR['x'](P).roots()
sage: all((a[0] - b[0]).abs() < 1e-15 and (a[1] - b[1]).abs() < 1e-9) #_
↳needs sage.symbolic
....:     for a, b in zip(L1, L2)
True
```

```
>>> from sage.all import *
>>> from sage.numerical.gauss_legendre import nodes
>>> L1 = nodes(Integer(24), Integer(53))
>>> P = RR['x'](sage.functions.orthogonal_polys.legendre_P(Integer(24), x)) #_
↳ # needs sage.symbolic
>>> Pdif = P.diff() #_
↳needs sage.symbolic
>>> L2 = [(r + Integer(1))/Integer(2), Integer(1)/(Integer(1) - r**Integer(2))/
↳Pdif(r)**Integer(2)] # needs sage.symbolic
...     for r, _ in RR['x'](P).roots()
>>> all((a[Integer(0)] - b[Integer(0)]).abs() < RealNumber('1e-15') and_
↳(a[Integer(1)] - b[Integer(1)]).abs() < RealNumber('1e-9') # needs_
↳sage.symbolic
...     for a, b in zip(L1, L2))
True
```

`sage.numerical.gauss_legendre.nodes_uncached` (*degree*, *prec*)

Compute the integration nodes and weights for the Gauss-Legendre quadrature scheme

We use the recurrence relations for Legendre polynomials to compute their values. This is a version of the algorithm that in [Neu2018] is called the REC algorithm.

INPUT:

- `degree` – integer; the number of nodes (must be 3 or even)
- `prec` – integer (minimal value 53); binary precision with which the nodes and weights are computed

OUTPUT: list of (node, weight) pairs

EXAMPLES:

The nodes for the Gauss-Legendre scheme are roots of Legendre polynomials. The weights can be computed by a straightforward formula (note that evaluating a derivative of a Legendre polynomial isn't particularly numerically stable, so the results from this routine are actually more accurate than what the values the closed formula produces):

```

sage: from sage.numerical.gauss_legendre import nodes_uncached
sage: L1 = nodes_uncached(24, 53)
sage: P = RR['x'](sage.functions.orthogonal_polys.legendre_P(24, x)) #_
↳needs sage.symbolic
sage: Pdif = P.diff() #_
↳needs sage.symbolic
sage: L2 = [(r + 1)/2, 1/(1 - r^2)/Pdif(r)^2] #_
↳needs sage.symbolic
.....:     for r, _ in RR['x'](P).roots()
sage: all((a[0] - b[0]).abs() < 1e-15 and (a[1] - b[1]).abs() < 1e-9) #_
↳needs sage.symbolic
.....:     for a, b in zip(L1, L2)
True

```

```

>>> from sage.all import *
>>> from sage.numerical.gauss_legendre import nodes_uncached
>>> L1 = nodes_uncached(Integer(24), Integer(53))
>>> P = RR['x'](sage.functions.orthogonal_polys.legendre_P(Integer(24), x)) #_
↳ # needs sage.symbolic
>>> Pdif = P.diff() #_
↳needs sage.symbolic
>>> L2 = [(r + Integer(1))/Integer(2), Integer(1)/(Integer(1) - r**Integer(2))/
↳Pdif(r)**Integer(2)] # needs sage.symbolic
...     for r, _ in RR['x'](P).roots()
>>> all((a[Integer(0)] - b[Integer(0)]).abs() < RealNumber('1e-15') and_
↳(a[Integer(1)] - b[Integer(1)]).abs() < RealNumber('1e-9') # needs_
↳sage.symbolic
...     for a, b in zip(L1, L2)
True

```

Todo

It may be worth testing if using the FLINT/Arb algorithm for finding the nodes and weights in `src/acb_calc/integrate_gl_auto_deg.c` has better performance.

LINEAR OPTIMIZATION (LP) AND MIXED INTEGER LINEAR OPTIMIZATION (MIP) SOLVER BACKENDS

11.1 Generic Backend for LP solvers

This class only lists the methods that should be defined by any interface with a LP Solver. All these methods immediately raise `NotImplementedError` exceptions when called, and are obviously meant to be replaced by the solver-specific method. This file can also be used as a template to create a new interface : one would only need to replace the occurrences of "Nonexistent_LP_solver" by the solver's name, and replace `GenericBackend` by `SolverName (GenericBackend)` so that the new solver extends this class.

AUTHORS:

- Nathann Cohen (2010-10) : initial implementation
- Risan (2012-02) : extension for PPL backend
- Ingolfur Edvardsson (2014-06): extension for CVXOPT backend

```
class sage.numerical.backends.generic_backend.GenericBackend
```

```
    Bases: SageObject
```

```
    add_col (indices, coeffs)
```

Add a column.

INPUT:

- `indices` – list of integers; this list contains the indices of the constraints in which the variable's coefficient is nonzero
- `coeffs` – list of real values; associates a coefficient to the variable in each of the constraints in which it appears. Namely, the *i*-th entry of `coeffs` corresponds to the coefficient of the variable in the constraint represented by the *i*-th entry in `indices`.

Note

`indices` and `coeffs` are expected to be of the same length.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
```

(continues on next page)

(continued from previous page)

```

0
sage: p.nrows()
0
sage: p.add_linear_constraints(5, 0, None)
sage: p.add_col(list(range(5)), list(range(5)))
sage: p.nrows()
5

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.nrows()
0
>>> p.add_linear_constraints(Integer(5), Integer(0), None)
>>> p.add_col(list(range(Integer(5))), list(range(Integer(5))))
>>> p.nrows()
5

```

add_linear_constraint (*coefficients, lower_bound, upper_bound, name=None*)

Add a linear constraint.

INPUT:

- *coefficients* – an iterable of pairs (*i*, *v*). In each pair, *i* is a variable index (integer) and *v* is a value (element of *base_ring()*).
- *lower_bound* – element of *base_ring()* or None; the lower bound
- *upper_bound* – element of *base_ring()* or None; the upper bound
- *name* – string or None; optional name for this row

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint( zip(range(5), range(5)), 2.0, 2.0)
sage: p.row(0)
([0, 1, 2, 3, 4], [0.0, 1.0, 2.0, 3.0, 4.0])
sage: p.row_bounds(0)
(2.0, 2.0)
sage: p.add_linear_constraint( zip(range(5), range(5)), 1.0, 1.0, name='foo')
sage: p.row_name(1)
'foo'

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver

```

(continues on next page)

(continued from previous page)

```

>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint( zip(range(Integer(5)), range(Integer(5))),
↳ RealNumber('2.0'), RealNumber('2.0'))
>>> p.row(Integer(0))
([0, 1, 2, 3, 4], [0.0, 1.0, 2.0, 3.0, 4.0])
>>> p.row_bounds(Integer(0))
(2.0, 2.0)
>>> p.add_linear_constraint( zip(range(Integer(5)), range(Integer(5))),
↳ RealNumber('1.0'), RealNumber('1.0'), name='foo')
>>> p.row_name(Integer(1))
'foo'

```

add_linear_constraint_vector (*degree, coefficients, lower_bound, upper_bound, name=None*)

Add a vector-valued linear constraint.

Note

This is the generic implementation, which will split the vector-valued constraint into components and add these individually. Backends are encouraged to replace it with their own optimized implementation.

INPUT:

- *degree* – integer; the vector degree, that is, the number of new scalar constraints
- *coefficients* – an iterable of pairs (*i*, *v*). In each pair, *i* is a variable index (integer) and *v* is a vector (real and of length *degree*).
- *lower_bound* – either a vector or *None*; the component-wise lower bound
- *upper_bound* – either a vector or *None*; the component-wise upper bound
- *name* – string or *None*; an optional name for all new rows

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: coeffs = ([0, vector([1, 2])], [1, vector([2, 3])])
sage: upper = vector([5, 5])
sage: lower = vector([0, 0])
sage: p.add_variables(2)
1
sage: p.add_linear_constraint_vector(2, coeffs, lower, upper, 'foo')

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> coeffs = ([Integer(0), vector([Integer(1), Integer(2)])], [Integer(1),
↳ vector([Integer(2), Integer(3)])])
>>> upper = vector([Integer(5), Integer(5)])

```

(continues on next page)

(continued from previous page)

```

>>> lower = vector([Integer(0), Integer(0)])
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint_vector(Integer(2), coeffs, lower, upper, 'foo')

```

add_linear_constraints (*number, lower_bound, upper_bound, names=None*)

Add 'number' linear constraints.

INPUT:

- *number* – integer; the number of constraints to add
- *lower_bound* – a lower bound, either a real value or None
- *upper_bound* – an upper bound, either a real value or None
- *names* – an optional list of names (default: None)

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
5
sage: p.add_linear_constraints(5, None, 2)
sage: p.row(4)
([], [])
sage: p.row_bounds(4)
(None, 2.0)

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
5
>>> p.add_linear_constraints(Integer(5), None, Integer(2))
>>> p.row(Integer(4))
([], [])
>>> p.row_bounds(Integer(4))
(None, 2.0)

```

add_variable (*lower_bound=0, upper_bound=None, binary=False, continuous=True, integer=False, obj=None, name=None*)

Add a variable.

This amounts to adding a new column to the matrix. By default, the variable is both positive and real.

INPUT:

- *lower_bound* – the lower bound of the variable (default: 0)
- *upper_bound* – the upper bound of the variable (default: None)
- *binary* – True if the variable is binary (default: False)
- *continuous* – True if the variable is continuous (default: True)

- `integer` – True if the variable is integral (default: False)
- `obj` – (optional) coefficient of this variable in the objective function (default: 0.0)
- `name` – an optional name for the newly added variable (default: None)

OUTPUT: the index of the newly created variable

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.ncols()
1
sage: p.add_variable(binary=True)
1
sage: p.add_variable(lower_bound=-2.0, integer=True)
2
sage: p.add_variable(continuous=True, integer=True)
Traceback (most recent call last):
...
ValueError: ...
sage: p.add_variable(name='x', obj=1.0)
3
sage: p.col_name(3)
'x'
sage: p.objective_coefficient(3)
1.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.ncols()
1
>>> p.add_variable(binary=True)
1
>>> p.add_variable(lower_bound=-RealNumber('2.0'), integer=True)
2
>>> p.add_variable(continuous=True, integer=True)
Traceback (most recent call last):
...
ValueError: ...
>>> p.add_variable(name='x', obj=RealNumber('1.0'))
3
>>> p.col_name(Integer(3))
```

(continues on next page)

(continued from previous page)

```
'x'
>>> p.objective_coefficient(Integer(3))
1.0
```

add_variables (*n*, *lower_bound=False*, *upper_bound=None*, *binary=False*, *continuous=True*, *integer=False*, *obj=None*, *names=None*)

Add *n* variables.

This amounts to adding new columns to the matrix. By default, the variables are both nonnegative and real.

INPUT:

- *n* – the number of new variables (must be > 0)
- *lower_bound* – the lower bound of the variable (default: 0)
- *upper_bound* – the upper bound of the variable (default: None)
- *binary* – True if the variable is binary (default: False)
- *continuous* – True if the variable is binary (default: True)
- *integer* – True if the variable is binary (default: False)
- *obj* – coefficient of all variables in the objective function (default: 0.0)
- *names* – list of names (default: None)

OUTPUT: the index of the variable created last

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variables(5)
4
sage: p.ncols()
5
sage: p.add_variables(2, lower_bound=-2.0, integer=True, names=['a', 'b'])
6
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variables(Integer(5))
4
>>> p.ncols()
5
>>> p.add_variables(Integer(2), lower_bound=-RealNumber('2.0'), integer=True,
↳ names=['a', 'b'])
6
```

`base_ring()`

`best_known_objective_bound()`

Return the value of the currently best known bound.

This method returns the current best upper (resp. lower) bound on the optimal value of the objective function in a maximization (resp. minimization) problem. It is equal to the output of `get_objective_value()` if the MILP found an optimal solution, but it can differ if it was interrupted manually or after a time limit (cf `solver_parameter()`).

Note

Has no meaning unless `solve` has been called before.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
sage: b = p.new_variable(binary=True)
sage: for u,v in graphs.CycleGraph(5).edges(labels=False):
....:     p.add_constraint(b[u]+b[v]<=1)
sage: p.set_objective(p.sum(b[x] for x in range(5)))
sage: p.solve()
2.0
sage: pb = p.get_backend()
sage: pb.get_objective_value()
2.0
sage: pb.best_known_objective_bound()
2.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
>>> b = p.new_variable(binary=True)
>>> for u,v in graphs.CycleGraph(Integer(5)).edges(labels=False):
...     p.add_constraint(b[u]+b[v]<=Integer(1))
>>> p.set_objective(p.sum(b[x] for x in range(Integer(5))))
>>> p.solve()
2.0
>>> pb = p.get_backend()
>>> pb.get_objective_value()
2.0
>>> pb.best_known_objective_bound()
2.0
```

`col_bounds(index)`

Return the bounds of a specific variable.

INPUT:

- `index` – integer; the variable's id

OUTPUT:

A pair (lower_bound, upper_bound). Each of them can be set to None if the variable is not bounded in the corresponding direction, and is a real value otherwise.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variable()
0
sage: p.col_bounds(0)
(0.0, None)
sage: p.variable_upper_bound(0, 5)
sage: p.col_bounds(0)
(0.0, 5.0)
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variable()
0
>>> p.col_bounds(Integer(0))
(0.0, None)
>>> p.variable_upper_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(0.0, 5.0)
```

col_name (*index*)

Return the index-th column name.

INPUT:

- index – integer; the column id
- name – (char *) its name; when set to NULL (default), the method returns the current name

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variable(name="I am a variable")
1
sage: p.col_name(0)
'I am a variable'
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variable(name="I am a variable")
1
>>> p.col_name(Integer(0))
'I am a variable'
```

copy()

Return a copy of `self`.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
sage: b = p.new_variable()
sage: p.add_constraint(b[1] + b[2] <= 6)
sage: p.set_objective(b[1] + b[2])
sage: copy(p).solve()
6.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
>>> b = p.new_variable()
>>> p.add_constraint(b[Integer(1)] + b[Integer(2)] <= Integer(6))
>>> p.set_objective(b[Integer(1)] + b[Integer(2)])
>>> copy(p).solve()
6.0
```

get_objective_value()

Return the value of the objective function.

Note

Behavior is undefined unless `solve` has been called before.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([(0,1), (1,2)], None, 3)
sage: p.set_objective([2, 5])
sage: p.solve()
0
sage: p.get_objective_value()
7.5
sage: p.get_variable_value(0)
0.0
sage: p.get_variable_value(1)
1.5
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
```

(continues on next page)

(continued from previous page)

```

>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([(Integer(0), Integer(1)), (Integer(1),
↳Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> p.solve()
0
>>> p.get_objective_value()
7.5
>>> p.get_variable_value(Integer(0))
0.0
>>> p.get_variable_value(Integer(1))
1.5

```

get_relative_objective_gap()

Return the relative objective gap of the best known solution.

For a minimization problem, this value is computed by $(\text{bestinteger} - \text{bestobjective}) / (1e - 10 + |\text{bestobjective}|)$, where `bestinteger` is the value returned by `get_objective_value()` and `bestobjective` is the value returned by `best_known_objective_bound()`. For a maximization problem, the value is computed by $(\text{bestobjective} - \text{bestinteger}) / (1e - 10 + |\text{bestobjective}|)$.

Note

Has no meaning unless `solve` has been called before.

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
sage: b = p.new_variable(binary=True)
sage: for u,v in graphs.CycleGraph(5).edges(labels=False):
...:     p.add_constraint(b[u]+b[v]<=1)
sage: p.set_objective(p.sum(b[x] for x in range(5)))
sage: p.solve()
2.0
sage: pb = p.get_backend()
sage: pb.get_objective_value()
2.0
sage: pb.get_relative_objective_gap()
0.0

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
>>> b = p.new_variable(binary=True)
>>> for u,v in graphs.CycleGraph(Integer(5)).edges(labels=False):
...     p.add_constraint(b[u]+b[v]<=Integer(1))
>>> p.set_objective(p.sum(b[x] for x in range(Integer(5))))
>>> p.solve()

```

(continues on next page)

(continued from previous page)

```

2.0
>>> pb = p.get_backend()
>>> pb.get_objective_value()
2.0
>>> pb.get_relative_objective_gap()
0.0

```

get_variable_value (*variable*)

Return the value of a variable given by the solver.

NoteBehavior is undefined unless `solve` has been called before.

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([(0,1), (1, 2)], None, 3)
sage: p.set_objective([2, 5])
sage: p.solve()
0
sage: p.get_objective_value()
7.5
sage: p.get_variable_value(0)
0.0
sage: p.get_variable_value(1)
1.5

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([(Integer(0), Integer(1)), (Integer(1), Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> p.solve()
0
>>> p.get_objective_value()
7.5
>>> p.get_variable_value(Integer(0))
0.0
>>> p.get_variable_value(Integer(1))
1.5

```

is_maximization ()

Test whether the problem is a maximization

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False
```

is_slack_variable_basic (*index*)

Test whether the slack variable of the given row is basic.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(maximization=True,
...:                               solver="Nonexistent_LP_solver")
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(5.5 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: # Backend-specific commands to instruct solver to use simplex method.
      ↪ here
sage: b.solve()
0
sage: b.is_slack_variable_basic(0)
True
sage: b.is_slack_variable_basic(1)
False
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(maximization=True,
...:                               solver="Nonexistent_LP_solver")
>>> x = p.new_variable(nonnegative=True)
```

(continues on next page)

(continued from previous page)

```

>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↳<= Integer(17))
>>> p.set_objective(RealNumber('5.5') * x[Integer(0)] - Integer(3) *
↳x[Integer(1)])
>>> b = p.get_backend()
>>> # Backend-specific commands to instruct solver to use simplex method here
>>> b.solve()
0
>>> b.is_slack_variable_basic(Integer(0))
True
>>> b.is_slack_variable_basic(Integer(1))
False

```

is_slack_variable_nonbasic_at_lower_bound(index)

Test whether the given variable is nonbasic at lower bound.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- index – integer; the variable's id

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(maximization=True,
...:                               solver="Nonexistent_LP_solver")
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(5.5 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: # Backend-specific commands to instruct solver to use simplex method
↳here
sage: b.solve()
0
sage: b.is_slack_variable_nonbasic_at_lower_bound(0)
False
sage: b.is_slack_variable_nonbasic_at_lower_bound(1)
True

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(maximization=True,
...                               solver="Nonexistent_LP_solver")
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↳<= Integer(17))
>>> p.set_objective(RealNumber('5.5') * x[Integer(0)] - Integer(3) *
↳x[Integer(1)])
>>> b = p.get_backend()

```

(continues on next page)

(continued from previous page)

```

>>> # Backend-specific commands to instruct solver to use simplex method here
>>> b.solve()
0
>>> b.is_slack_variable_nonbasic_at_lower_bound(Integer(0))
False
>>> b.is_slack_variable_nonbasic_at_lower_bound(Integer(1))
True

```

is_variable_basic (*index*)

Test whether the given variable is basic.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(maximization=True,
...:                               solver="Nonexistent_LP_solver")
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(5.5 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: # Backend-specific commands to instruct solver to use simplex method
↪here
sage: b.solve()
0
sage: b.is_variable_basic(0)
True
sage: b.is_variable_basic(1)
False

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(maximization=True,
...:                               solver="Nonexistent_LP_solver")
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↪<= Integer(17))
>>> p.set_objective(RealNumber('5.5') * x[Integer(0)] - Integer(3) *
↪x[Integer(1)])
>>> b = p.get_backend()
>>> # Backend-specific commands to instruct solver to use simplex method here
>>> b.solve()
0
>>> b.is_variable_basic(Integer(0))
True

```

(continues on next page)

(continued from previous page)

```
>>> b.is_variable_basic(Integer(1))
False
```

is_variable_binary (*index*)

Test whether the given variable is of binary type.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.set_variable_type(0,0)
sage: p.is_variable_binary(0)
True
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.set_variable_type(Integer(0), Integer(0))
>>> p.is_variable_binary(Integer(0))
True
```

is_variable_continuous (*index*)

Test whether the given variable is of continuous/real type.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.is_variable_continuous(0)
True
sage: p.set_variable_type(0,1)
```

(continues on next page)

(continued from previous page)

```
sage: p.is_variable_continuous(0)
False
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.is_variable_continuous(Integer(0))
True
>>> p.set_variable_type(Integer(0), Integer(1))
>>> p.is_variable_continuous(Integer(0))
False
```

is_variable_integer (*index*)

Test whether the given variable is of integer type.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.set_variable_type(0,1)
sage: p.is_variable_integer(0)
True
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.set_variable_type(Integer(0), Integer(1))
>>> p.is_variable_integer(Integer(0))
True
```

is_variable_nonbasic_at_lower_bound (*index*)

Test whether the given variable is nonbasic at lower bound.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- index – integer; the variable's id

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(maximization=True,
...:                               solver="Nonexistent_LP_solver")
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(5.5 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: # Backend-specific commands to instruct solver to use simplex method
↳here
sage: b.solve()
0
sage: b.is_variable_nonbasic_at_lower_bound(0)
False
sage: b.is_variable_nonbasic_at_lower_bound(1)
True
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(maximization=True,
...:                               solver="Nonexistent_LP_solver")
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↳<= Integer(17))
>>> p.set_objective(RealNumber('5.5') * x[Integer(0)] - Integer(3) *
↳x[Integer(1)])
>>> b = p.get_backend()
>>> # Backend-specific commands to instruct solver to use simplex method here
>>> b.solve()
0
>>> b.is_variable_nonbasic_at_lower_bound(Integer(0))
False
>>> b.is_variable_nonbasic_at_lower_bound(Integer(1))
True
```

ncols()

Return the number of columns/variables.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variables(2)
1
```

(continues on next page)

(continued from previous page)

```
sage: p.ncols()
2
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variables(Integer(2))
1
>>> p.ncols()
2
```

nrows()

Return the number of rows/constraints.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.nrows()
0
sage: p.add_linear_constraints(2, 2.0, None)
sage: p.nrows()
2
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.nrows()
0
>>> p.add_linear_constraints(Integer(2), RealNumber('2.0'), None)
>>> p.nrows()
2
```

objective_coefficient (*variable*, *coeff=None*)

Set or get the coefficient of a variable in the objective function

INPUT:

- *variable* – integer; the variable's id
- *coeff* – double; its coefficient

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variable()
0
```

(continues on next page)

(continued from previous page)

```
sage: p.objective_coefficient(0)
0.0
sage: p.objective_coefficient(0,2)
sage: p.objective_coefficient(0)
2.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variable()
0
>>> p.objective_coefficient(Integer(0))
0.0
>>> p.objective_coefficient(Integer(0), Integer(2))
>>> p.objective_coefficient(Integer(0))
2.0
```

objective_constant_term (*d=None*)

Set or get the constant term in the objective function.

INPUT:

- *d* – double; its coefficient. If *None* (default), return the current value.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.objective_constant_term()
0.0
sage: p.objective_constant_term(42)
sage: p.objective_constant_term()
42.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.objective_constant_term()
0.0
>>> p.objective_constant_term(Integer(42))
>>> p.objective_constant_term()
42.0
```

problem_name (*name=None*)

Return or define the problem's name.

INPUT:

- *name* – string; the problem's name. When set to *None* (default), the method returns the problem's name.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver") # optional -
↳Nonexistent_LP_solver
sage: p.problem_name("There once was a french fry") # optional - Nonexistent_
↳LP_solver
sage: print(p.problem_name()) # optional - Nonexistent_
↳LP_solver
There once was a french fry
    
```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver") # optional - Nonexistent_
↳LP_solver
>>> p.problem_name("There once was a french fry") # optional - Nonexistent_LP_
↳solver
>>> print(p.problem_name()) # optional - Nonexistent_LP_
↳solver
There once was a french fry
    
```

`remove_constraint(i)`

Remove a constraint.

INPUT:

- i – index of the constraint to remove

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
sage: v = p.new_variable(nonnegative=True)
sage: x,y = v[0], v[1]
sage: p.add_constraint(2*x + 3*y, max=6)
sage: p.add_constraint(3*x + 2*y, max=6)
sage: p.set_objective(x + y + 7)
sage: p.set_integer(x); p.set_integer(y)
sage: p.solve()
9.0
sage: p.remove_constraint(0)
sage: p.solve()
10.0
sage: p.get_values([x,y])
[0.0, 3.0]
    
```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
>>> v = p.new_variable(nonnegative=True)
>>> x,y = v[Integer(0)], v[Integer(1)]
>>> p.add_constraint(Integer(2)*x + Integer(3)*y, max=Integer(6))
>>> p.add_constraint(Integer(3)*x + Integer(2)*y, max=Integer(6))
>>> p.set_objective(x + y + Integer(7))
>>> p.set_integer(x); p.set_integer(y)
>>> p.solve()
    
```

(continues on next page)

(continued from previous page)

```

9.0
>>> p.remove_constraint(Integer(0))
>>> p.solve()
10.0
>>> p.get_values([x,y])
[0.0, 3.0]

```

remove_constraints (*constraints*)

Remove several constraints.

INPUT:

- *constraints* – an iterable containing the indices of the rows to remove

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([(0, 2), (1, 3)], None, 6)
sage: p.add_linear_constraint([(0, 3), (1, 2)], None, 6)
sage: p.remove_constraints([0, 1])

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([(Integer(0), Integer(2)), (Integer(1),
↳Integer(3))], None, Integer(6))
>>> p.add_linear_constraint([(Integer(0), Integer(3)), (Integer(1),
↳Integer(2))], None, Integer(6))
>>> p.remove_constraints([Integer(0), Integer(1)])

```

row (*i*)

Return a row.

INPUT:

- *index* – integer; the constraint's id

OUTPUT:

A pair (*indices*, *coeffs*) where *indices* lists the entries whose coefficient is nonzero, and to which *coeffs* associates their coefficient on the model of the `add_linear_constraint` method.

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
4

```

(continues on next page)

(continued from previous page)

```

sage: p.add_linear_constraint(zip(range(5), range(5)), 2, 2)
sage: p.row(0)
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0]) ## FIXME: Why backwards?
sage: p.row_bounds(0)
(2.0, 2.0)
    
```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))),
↳Integer(2), Integer(2))
>>> p.row(Integer(0))
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0]) ## FIXME: Why backwards?
>>> p.row_bounds(Integer(0))
(2.0, 2.0)
    
```

`row_bounds` (*index*)

Return the bounds of a specific constraint.

INPUT:

- `index` – integer; the constraint's id

OUTPUT:

A pair (`lower_bound`, `upper_bound`). Each of them can be set to `None` if the constraint is not bounded in the corresponding direction, and is a real value otherwise.

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(list(range(5)), list(range(5)), 2, 2)
sage: p.row(0)
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0]) ## FIXME: Why backwards?
sage: p.row_bounds(0)
(2.0, 2.0)
    
```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(list(range(Integer(5))), list(range(Integer(5))),
↳Integer(2), Integer(2))
>>> p.row(Integer(0))
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0]) ## FIXME: Why backwards?
    
```

(continues on next page)

(continued from previous page)

```
>>> p.row_bounds(Integer(0))
(2.0, 2.0)
```

row_name (*index*)Return the *index*-th row name.

INPUT:

- *index* – integer; the row's id

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_linear_constraints(1, 2, None, names=['Empty constraint 1'])
sage: p.row_name(0)
'Empty constraint 1'
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_linear_constraints(Integer(1), Integer(2), None, names=['Empty_
↳constraint 1'])
>>> p.row_name(Integer(0))
'Empty constraint 1'
```

set_objective (*coeff*, *d=0.0*)

Set the objective function.

INPUT:

- *coeff* – list of real values, whose *i*-th element is the coefficient of the *i*-th variable in the objective function
- *d* – double; the constant term in the linear function (set to 0 by default)

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
4
sage: p.set_objective([1, 1, 2, 1, 3])
sage: [p.objective_coefficient(x) for x in range(5)]
[1.0, 1.0, 2.0, 1.0, 3.0]
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
4
```

(continues on next page)

(continued from previous page)

```
>>> p.set_objective([Integer(1), Integer(1), Integer(2), Integer(1),
↳Integer(3)])
>>> [p.objective_coefficient(x) for x in range(Integer(5))]
[1.0, 1.0, 2.0, 1.0, 3.0]
```

Constants in the objective function are respected:

```
sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(solver='Nonexistent_LP_solver')
sage: x,y = p[0], p[1]
sage: p.add_constraint(2*x + 3*y, max=6)
sage: p.add_constraint(3*x + 2*y, max=6)
sage: p.set_objective(x + y + 7)
sage: p.set_integer(x); p.set_integer(y)
sage: p.solve()
9.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(solver='Nonexistent_LP_solver')
>>> x,y = p[Integer(0)], p[Integer(1)]
>>> p.add_constraint(Integer(2)*x + Integer(3)*y, max=Integer(6))
>>> p.add_constraint(Integer(3)*x + Integer(2)*y, max=Integer(6))
>>> p.set_objective(x + y + Integer(7))
>>> p.set_integer(x); p.set_integer(y)
>>> p.solve()
9.0
```

set_sense (*sense*)

Set the direction (maximization/minimization).

INPUT:

- sense – integer:
 - +1 => Maximization
 - -1 => Minimization

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
```

(continues on next page)

(continued from previous page)

```

>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False

```

set_variable_type (*variable*, *vtype*)

Set the type of a variable.

INPUT:

- *variable* – integer; the variable's id
- *vtype* – integer:
 - 1 Integer
 - 0 Binary
 - -1 Continuous

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.set_variable_type(0,1)
sage: p.is_variable_integer(0)
True

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.set_variable_type(Integer(0), Integer(1))
>>> p.is_variable_integer(Integer(0))
True

```

set_verbosity (*level*)

Set the log (verbosity) level.

INPUT:

- *level* – integer; from 0 (no verbosity) to 3

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver") # optional -

```

(continues on next page)

(continued from previous page)

```
↪Nonexistent_LP_solver
sage: p.set_verbosity(2) # optional -
↪Nonexistent_LP_solver
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver") # optional - Nonexistent_
↪LP_solver
>>> p.set_verbosity(Integer(2)) # optional -
↪Nonexistent_LP_solver
```

`solve()`

Solve the problem.

Note

This method raises `MIPSolverException` exceptions when the solution cannot be computed for any reason (none exists, or the LP solver was not able to find it, etc...)

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_linear_constraints(5, 0, None)
sage: p.add_col(list(range(5)), list(range(5)))
sage: p.solve()
0
sage: p.objective_coefficient(0,1)
sage: p.solve()
Traceback (most recent call last):
...
MIPSolverException: ...
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_linear_constraints(Integer(5), Integer(0), None)
>>> p.add_col(list(range(Integer(5))), list(range(Integer(5))))
>>> p.solve()
0
>>> p.objective_coefficient(Integer(0), Integer(1))
>>> p.solve()
Traceback (most recent call last):
...
MIPSolverException: ...
```

`solver_parameter` (*name*, *value=None*)

Return or define a solver parameter.

INPUT:

- `name` – string; the parameter
- `value` – the parameter’s value if it is to be defined, or `None` (default) to obtain its current value

Note

The list of available parameters is available at `solver_parameter()`.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.solver_parameter("timelimit")
sage: p.solver_parameter("timelimit", 60)
sage: p.solver_parameter("timelimit")
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.solver_parameter("timelimit")
>>> p.solver_parameter("timelimit", Integer(60))
>>> p.solver_parameter("timelimit")
```

variable_lower_bound (*index*, *value=False*)

Return or define the lower bound on a variable.

INPUT:

- `index` – integer; the variable’s id
- `value` – real value, or `None` to mean that the variable has not lower bound. When set to `False` (default), the method returns the current value.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variable()
0
sage: p.col_bounds(0)
(0.0, None)
sage: p.variable_lower_bound(0, 5)
sage: p.col_bounds(0)
(5.0, None)
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variable()
0
```

(continues on next page)

(continued from previous page)

```
>>> p.col_bounds(Integer(0))
(0.0, None)
>>> p.variable_lower_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(5.0, None)
```

variable_upper_bound(*index*, *value=False*)

Return or define the upper bound on a variable.

INPUT:

- *index* – integer; the variable's id
- *value* – real value, or `None` to mean that the variable has not upper bound. When set to `False` (default), the method returns the current value.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variable()
0
sage: p.col_bounds(0)
(0.0, None)
sage: p.variable_upper_bound(0, 5)
sage: p.col_bounds(0)
(0.0, 5.0)
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variable()
0
>>> p.col_bounds(Integer(0))
(0.0, None)
>>> p.variable_upper_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(0.0, 5.0)
```

write_lp(*name*)Write the problem to a `.lp` file.

INPUT:

- *filename* – string

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(2)
2
```

(continues on next page)

(continued from previous page)

```

sage: p.add_linear_constraint([(0, 1], (1, 2)], None, 3)
sage: p.set_objective([2, 5])
sage: from tempfile import NamedTemporaryFile
sage: with NamedTemporaryFile(suffix='.lp') as f:
.....:     p.write_lp(f.name)

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(2))
2
>>> p.add_linear_constraint([(Integer(0), Integer(1)], (Integer(1),
↳Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> from tempfile import NamedTemporaryFile
>>> with NamedTemporaryFile(suffix='.lp') as f:
...     p.write_lp(f.name)

```

write_mps (*name, modern*)

Write the problem to a .mps file.

INPUT:

- filename – string

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(2)
2
sage: p.add_linear_constraint([(0, 1), (1, 2)], None, 3)
sage: p.set_objective([2, 5])
sage: from tempfile import NamedTemporaryFile
sage: with NamedTemporaryFile(suffix='.lp') as f:
.....:     p.write_lp(f.name)

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(2))
2
>>> p.add_linear_constraint([(Integer(0), Integer(1)], (Integer(1),
↳Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> from tempfile import NamedTemporaryFile
>>> with NamedTemporaryFile(suffix='.lp') as f:
...     p.write_lp(f.name)

```

zero ()

`sage.numerical.backends.generic_backend.default_mip_solver` (*solver=None*)

Return/set the default MILP solver used by Sage.

INPUT:

- `solver` – one of the following:
 - a string indicating one of the available solvers (see *MixedIntegerLinearProgram*);
 - a callable (typically a subclass of *sage.numerical.backends.generic_backend.GenericBackend*);
 - `None` – (default) in which case the current default solver is returned; this is either a string or a callable

OUTPUT:

This function returns the current default solver's name if `solver = None` (default). Otherwise, it sets the default solver to the one given. If this solver does not exist, or is not available, a `ValueError` exception is raised.

EXAMPLES:

```
sage: former_solver = default_mip_solver()
sage: default_mip_solver("GLPK")
sage: default_mip_solver()
'Glpk'
sage: default_mip_solver("PPL")
sage: default_mip_solver()
'Ppl'
sage: default_mip_solver("GUROBI") # random
Traceback (most recent call last):
...
ValueError: Gurobi is not available. Please refer to the documentation to install_
↪it.
sage: default_mip_solver("Yeahhhhhhhhhhh")
Traceback (most recent call last):
...
ValueError: 'solver' should be set to ...
sage: default_mip_solver(former_solver)
```

```
>>> from sage.all import *
>>> former_solver = default_mip_solver()
>>> default_mip_solver("GLPK")
>>> default_mip_solver()
'Glpk'
>>> default_mip_solver("PPL")
>>> default_mip_solver()
'Ppl'
>>> default_mip_solver("GUROBI") # random
Traceback (most recent call last):
...
ValueError: Gurobi is not available. Please refer to the documentation to install_
↪it.
>>> default_mip_solver("Yeahhhhhhhhhhh")
Traceback (most recent call last):
...
ValueError: 'solver' should be set to ...
>>> default_mip_solver(former_solver)
```

```
sage.numerical.backends.generic_backend.get_solver (constraint_generation=False, solver=None,
                                                    base_ring=None)
```

Return a solver according to the given preferences.

INPUT:

- `solver` – one of the following:
 - a string indicating one of the available solvers (see *MixedIntegerLinearProgram*);
 - `None` – (default) in which case the default solver is used (see *default_mip_solver()*);
 - or a callable (such as a class), in which case it is called, and its result is returned.
- `base_ring` – if not `None`, request a solver that works over this (ordered) field. If `base_ring` is not a field, its fraction field is used.

For example, if `base_ring=ZZ` is provided, the solver will work over the rational numbers. This is unrelated to whether variables are constrained to be integers or not.
- `constraint_generation` – only used when `solver=None`:
 - When set to `True`, after solving the *MixedIntegerLinearProgram*, it is possible to add a constraint, and then solve it again. The effect is that solvers that do not support this feature will not be used. (Coin and SCIP are such solvers.)
 - Defaults to `False`.

➔ See also

- *default_mip_solver()* – returns/sets the default MIP solver

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver()
sage: p = get_solver(base_ring=RDF)
sage: p.base_ring()
Real Double Field
sage: p = get_solver(base_ring=QQ); p
<...sage.numerical.backends.ppl_backend.PPLBackend...>
sage: p = get_solver(base_ring=ZZ); p
<...sage.numerical.backends.ppl_backend.PPLBackend...>
sage: p.base_ring()
Rational Field
sage: p = get_solver(base_ring=AA); p #_
↪needs sage.rings.number_field
<...sage.numerical.backends.interactivelp_backend.InteractiveLPBackend...>
sage: p.base_ring() #_
↪needs sage.rings.number_field
Algebraic Real Field

sage: # needs sage.groups sage.rings.number_field
sage: d = polytopes.dodecahedron()
sage: p = get_solver(base_ring=d.base_ring()); p
<...sage.numerical.backends.interactivelp_backend.InteractiveLPBackend...>
sage: p.base_ring()
```

(continues on next page)

(continued from previous page)

```

Number Field in sqrt5 with defining polynomial x^2 - 5 with sqrt5 = 2.
↪236067977499790?
sage: p = get_solver(solver='InteractiveLP', base_ring=QQ); p
<...sage.numerical.backends.interactivelp_backend.InteractiveLPBackend...>
sage: p.base_ring()
Rational Field
    
```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver()
>>> p = get_solver(base_ring=RDF)
>>> p.base_ring()
Real Double Field
>>> p = get_solver(base_ring=QQ); p
<...sage.numerical.backends.ppl_backend.PPLBackend...>
>>> p = get_solver(base_ring=ZZ); p
<...sage.numerical.backends.ppl_backend.PPLBackend...>
>>> p.base_ring()
Rational Field
>>> p = get_solver(base_ring=AA); p                                     #_
↪needs sage.rings.number_field
<...sage.numerical.backends.interactivelp_backend.InteractiveLPBackend...>
>>> p.base_ring()                                                     #_
↪needs sage.rings.number_field
Algebraic Real Field

>>> # needs sage.groups sage.rings.number_field
>>> d = polytopes.dodecahedron()
>>> p = get_solver(base_ring=d.base_ring()); p
<...sage.numerical.backends.interactivelp_backend.InteractiveLPBackend...>
>>> p.base_ring()
Number Field in sqrt5 with defining polynomial x^2 - 5 with sqrt5 = 2.
↪236067977499790?
>>> p = get_solver(solver='InteractiveLP', base_ring=QQ); p
<...sage.numerical.backends.interactivelp_backend.InteractiveLPBackend...>
>>> p.base_ring()
Rational Field
    
```

Passing a callable as the solver:

```

sage: from sage.numerical.backends.glpk_backend import GLPKBackend
sage: p = get_solver(solver=GLPKBackend); p
<...sage.numerical.backends.glpk_backend.GLPKBackend...>
    
```

```

>>> from sage.all import *
>>> from sage.numerical.backends.glpk_backend import GLPKBackend
>>> p = get_solver(solver=GLPKBackend); p
<...sage.numerical.backends.glpk_backend.GLPKBackend...>
    
```

Passing a callable that customizes a backend:

```

sage: def glpk_exact_solver():
.....:     from sage.numerical.backends.generic_backend import get_solver
.....:     b = get_solver(solver='GLPK')
.....:     b.solver_parameter('simplex_or_intopt', 'exact_simplex_only')
.....:     return b
sage: codes.bounds.delsarte_bound_additive_hamming_space(11,3,4,solver=glpk_exact_
↪solver) # long time
8

```

```

>>> from sage.all import *
>>> def glpk_exact_solver():
...     from sage.numerical.backends.generic_backend import get_solver
...     b = get_solver(solver='GLPK')
...     b.solver_parameter('simplex_or_intopt', 'exact_simplex_only')
...     return b
>>> codes.bounds.delsarte_bound_additive_hamming_space(Integer(11),Integer(3),
↪Integer(4),solver=glpk_exact_solver) # long time
8

```

11.2 InteractiveLP Backend

AUTHORS:

- Nathann Cohen (2010-10) : generic_backend template
- Matthias Koeppel (2016-03) : this backend

class sage.numerical.backends.interactivelp_backend.**InteractiveLPBackend**

Bases: *GenericBackend*

MIP Backend that works with *InteractiveLPProblem*.

This backend should be used only for linear programs over general fields, or for educational purposes. For fast computations with floating point arithmetic, use one of the numerical backends. For exact computations with rational numbers, use backend 'PPL'.

There is no support for integer variables.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")

```

add_col (*indices, coeffs*)

Add a column.

INPUT:

- *indices* – list of integers; this list contains the indices of the constraints in which the variable's coefficient is nonzero

- `coeffs` – list of real values; associates a coefficient to the variable in each of the constraints in which it appears. Namely, the i -th entry of `coeffs` corresponds to the coefficient of the variable in the constraint represented by the i -th entry in `indices`.

Note

`indices` and `coeffs` are expected to be of the same length.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.ncols()
0
sage: p.nrows()
0
sage: p.add_linear_constraints(5, 0, None)
sage: p.add_col(list(range(5)), list(range(5)))
sage: p.nrows()
5
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.ncols()
0
>>> p.nrows()
0
>>> p.add_linear_constraints(Integer(5), Integer(0), None)
>>> p.add_col(list(range(Integer(5))), list(range(Integer(5))))
>>> p.nrows()
5
```

add_linear_constraint (*coefficients, lower_bound, upper_bound, name=None*)

Add a linear constraint.

INPUT:

- `coefficients` – an iterable of pairs (i, v) . In each pair, i is a variable index (integer) and v is a value (element of `base_ring()`).
- `lower_bound` – element of `base_ring()` or `None`; the lower bound
- `upper_bound` – element of `base_ring()` or `None`; the upper bound
- `name` – string or `None`; optional name for this row

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint( zip(range(5), range(5)), 2, 2)
sage: p.row(0)
```

(continues on next page)

(continued from previous page)

```

([1, 2, 3, 4], [1, 2, 3, 4])
sage: p.row_bounds(0)
(2, 2)
sage: p.add_linear_constraint( zip(range(5), range(5)), 1, 1, name='foo')
sage: p.row_name(1)
'foo'

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint( zip(range(Integer(5)), range(Integer(5))),
↳ Integer(2), Integer(2))
>>> p.row(Integer(0))
([1, 2, 3, 4], [1, 2, 3, 4])
>>> p.row_bounds(Integer(0))
(2, 2)
>>> p.add_linear_constraint( zip(range(Integer(5)), range(Integer(5))),
↳ Integer(1), Integer(1), name='foo')
>>> p.row_name(Integer(1))
'foo'

```

add_variable (*lower_bound=0, upper_bound=None, binary=False, continuous=True, integer=False, obj=None, name=None, coefficients=None*)

Add a variable.

This amounts to adding a new column to the matrix. By default, the variable is both nonnegative and real.

In this backend, variables are always continuous (real). If integer variables are requested via the parameters `binary` and `integer`, an error will be raised.

INPUT:

- `lower_bound` – the lower bound of the variable (default: 0)
- `upper_bound` – the upper bound of the variable (default: None)
- `binary` – True if the variable is binary (default: False)
- `continuous` – True if the variable is continuous (default: True)
- `integer` – True if the variable is integral (default: False)
- `obj` – (optional) coefficient of this variable in the objective function (default: 0)
- `name` – an optional name for the newly added variable (default: None)
- `coefficients` – (optional) an iterable of pairs (*i*, *v*). In each pair, *i* is a variable index (integer) and *v* is a value (element of `base_ring()`).

OUTPUT: the index of the newly created variable

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.ncols()

```

(continues on next page)

(continued from previous page)

```

0
sage: p.add_variable()
0
sage: p.ncols()
1
sage: p.add_variable(continuous=True, integer=True)
Traceback (most recent call last):
...
ValueError: ...
sage: p.add_variable(name='x',obj=1)
1
sage: p.col_name(1)
'x'
sage: p.objective_coefficient(1)
1

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.ncols()
1
>>> p.add_variable(continuous=True, integer=True)
Traceback (most recent call last):
...
ValueError: ...
>>> p.add_variable(name='x',obj=Integer(1))
1
>>> p.col_name(Integer(1))
'x'
>>> p.objective_coefficient(Integer(1))
1

```

base_ring()

Return the base ring.

OUTPUT: a ring; the coefficients that the chosen solver supports

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.base_ring()
Rational Field

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.base_ring()
Rational Field

```

col_bounds (*index*)

Return the bounds of a specific variable.

INPUT:

- *index* – integer; the variable's id

OUTPUT:

A pair (*lower_bound*, *upper_bound*). Each of them can be set to `None` if the variable is not bounded in the corresponding direction, and is a real value otherwise.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.add_variable(lower_bound=None)
0
sage: p.col_bounds(0)
(None, None)
sage: p.variable_lower_bound(0, 0)
sage: p.col_bounds(0)
(0, None)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.add_variable(lower_bound=None)
0
>>> p.col_bounds(Integer(0))
(None, None)
>>> p.variable_lower_bound(Integer(0), Integer(0))
>>> p.col_bounds(Integer(0))
(0, None)
```

col_name (*index*)

Return the *index*-th column name.

INPUT:

- *index* – integer; the column id
- *name* – (`char *`) its name; when set to `NULL` (default), the method returns the current name

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.add_variable(name='I_am_a_variable')
0
sage: p.col_name(0)
'I_am_a_variable'
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.add_variable(name='I_am_a_variable')
```

(continues on next page)

(continued from previous page)

```
0
>>> p.col_name(Integer(0))
'I_am_a_variable'
```

dictionary()

Return a dictionary representing the current basis.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(maximization=True, Ellipsis.:
↳ solver='InteractiveLP')
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(11/2 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: # Backend-specific commands to instruct solver to use simplex method
↳ here
sage: b.solve()
0
sage: d = b.dictionary(); d
LP problem dictionary ...
sage: set(d.basic_variables())
{x1, x3}
sage: d.basic_solution()
(17/8, 0)
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True, Ellipsis.:
↳ solver='InteractiveLP')
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↳ <= Integer(17))
>>> p.set_objective(Integer(11)/Integer(2) * x[Integer(0)] - Integer(3) *
↳ x[Integer(1)])
>>> b = p.get_backend()
>>> # Backend-specific commands to instruct solver to use simplex method here
>>> b.solve()
0
>>> d = b.dictionary(); d
LP problem dictionary ...
>>> set(d.basic_variables())
{x1, x3}
>>> d.basic_solution()
(17/8, 0)
```

get_objective_value()

Return the value of the objective function.

Note

Behavior is undefined unless `solve` has been called before.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([(0,1), (1,2)], None, 3)
sage: p.set_objective([2, 5])
sage: p.solve()
0
sage: p.get_objective_value()
15/2
sage: p.get_variable_value(0)
0
sage: p.get_variable_value(1)
3/2
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([(Integer(0),Integer(1)), (Integer(1),
↳Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> p.solve()
0
>>> p.get_objective_value()
15/2
>>> p.get_variable_value(Integer(0))
0
>>> p.get_variable_value(Integer(1))
3/2
```

`get_variable_value` (*variable*)

Return the value of a variable given by the solver.

Note

Behavior is undefined unless `solve` has been called before.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([(0,1), (1, 2)], None, 3)
sage: p.set_objective([2, 5])
```

(continues on next page)

(continued from previous page)

```

sage: p.solve()
0
sage: p.get_objective_value()
15/2
sage: p.get_variable_value(0)
0
sage: p.get_variable_value(1)
3/2
    
```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([(Integer(0), Integer(1)), (Integer(1), Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> p.solve()
0
>>> p.get_objective_value()
15/2
>>> p.get_variable_value(Integer(0))
0
>>> p.get_variable_value(Integer(1))
3/2
    
```

`interactive_lp_problem()`

Return the *InteractiveLPProblem* object associated with this backend.

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(maximization=True, solver='InteractiveLP')
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(11/2 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: b.interactive_lp_problem()
LP problem ...
    
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True, solver='InteractiveLP')
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)] <= Integer(17))
>>> p.set_objective(Integer(11)/Integer(2) * x[Integer(0)] - Integer(3) * x[Integer(1)])
>>> b = p.get_backend()
>>> b.interactive_lp_problem()
    
```

(continues on next page)

(continued from previous page)

```
LP problem ...
```

is_maximization()

Test whether the problem is a maximization

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False
```

is_slack_variable_basic(index)

Test whether the slack variable of the given row is basic.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- `index` – integer; the variable's id

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(maximization=True,          ....:
↳ solver='InteractiveLP')
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(11/2 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: # Backend-specific commands to instruct solver to use simplex method.
↳ here
sage: b.solve()
0
sage: b.is_slack_variable_basic(0)
True
sage: b.is_slack_variable_basic(1)
False
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True,          Ellipsis.:
↳
```

(continues on next page)

(continued from previous page)

```

↪ solver='InteractiveLP')
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↪ <= Integer(17))
>>> p.set_objective(Integer(11)/Integer(2) * x[Integer(0)] - Integer(3) *
↪ x[Integer(1)])
>>> b = p.get_backend()
>>> # Backend-specific commands to instruct solver to use simplex method here
>>> b.solve()
0
>>> b.is_slack_variable_basic(Integer(0))
True
>>> b.is_slack_variable_basic(Integer(1))
False

```

is_slack_variable_nonbasic_at_lower_bound(index)

Test whether the given variable is nonbasic at lower bound.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- index – integer; the variable's id

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(maximization=True,      ....:
↪ solver='InteractiveLP')
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(11/2 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: # Backend-specific commands to instruct solver to use simplex method
↪ here
sage: b.solve()
0
sage: b.is_slack_variable_nonbasic_at_lower_bound(0)
False
sage: b.is_slack_variable_nonbasic_at_lower_bound(1)
True

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True, Ellipsis.:
↪ solver='InteractiveLP')
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↪ <= Integer(17))
>>> p.set_objective(Integer(11)/Integer(2) * x[Integer(0)] - Integer(3) *
↪ x[Integer(1)])
>>> b = p.get_backend()

```

(continues on next page)

(continued from previous page)

```

>>> # Backend-specific commands to instruct solver to use simplex method here
>>> b.solve()
0
>>> b.is_slack_variable_nonbasic_at_lower_bound(Integer(0))
False
>>> b.is_slack_variable_nonbasic_at_lower_bound(Integer(1))
True

```

is_variable_basic (*index*)

Test whether the given variable is basic.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(maximization=True,          Ellipsis.:
↳ solver='InteractiveLP')
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(11/2 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: # Backend-specific commands to instruct solver to use simplex method
↳ here
sage: b.solve()
0
sage: b.is_variable_basic(0)
True
sage: b.is_variable_basic(1)
False

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True,          Ellipsis.:
↳ solver='InteractiveLP')
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↳ <= Integer(17))
>>> p.set_objective(Integer(11)/Integer(2) * x[Integer(0)] - Integer(3) *
↳ x[Integer(1)])
>>> b = p.get_backend()
>>> # Backend-specific commands to instruct solver to use simplex method here
>>> b.solve()
0
>>> b.is_variable_basic(Integer(0))
True
>>> b.is_variable_basic(Integer(1))
False

```

is_variable_binary (*index*)

Test whether the given variable is of binary type.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.is_variable_binary(0)
False
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.is_variable_binary(Integer(0))
False
```

is_variable_continuous (*index*)

Test whether the given variable is of continuous/real type.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.is_variable_continuous(0)
True
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.is_variable_continuous(Integer(0))
True
```

is_variable_integer (*index*)

Test whether the given variable is of integer type.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.is_variable_integer(0)
False
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.is_variable_integer(Integer(0))
False
```

is_variable_nonbasic_at_lower_bound (*index*)

Test whether the given variable is nonbasic at lower bound.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(maximization=True, solver='InteractiveLP')
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(11/2 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: # Backend-specific commands to instruct solver to use simplex method
sage: # here
sage: b.solve()
0
sage: b.is_variable_nonbasic_at_lower_bound(0)
False
sage: b.is_variable_nonbasic_at_lower_bound(1)
True
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True, Ellipsis.:
↳ solver='InteractiveLP')
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↳ <= Integer(17))
>>> p.set_objective(Integer(11)/Integer(2) * x[Integer(0)] - Integer(3) *
↳ x[Integer(1)])
>>> b = p.get_backend()
>>> # Backend-specific commands to instruct solver to use simplex method here
>>> b.solve()
0
>>> b.is_variable_nonbasic_at_lower_bound(Integer(0))
False
>>> b.is_variable_nonbasic_at_lower_bound(Integer(1))
True
    
```

`ncols()`

Return the number of columns/variables.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.ncols()
0
sage: p.add_variables(2)
1
sage: p.ncols()
2
    
```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.ncols()
0
>>> p.add_variables(Integer(2))
1
>>> p.ncols()
2
    
```

`nrows()`

Return the number of rows/constraints.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.nrows()
0
sage: p.add_linear_constraints(2, 0, None)
sage: p.nrows()
2
    
```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.nrows()
0
>>> p.add_linear_constraints(Integer(2), Integer(0), None)
>>> p.nrows()
2

```

objective_coefficient (*variable, coeff=None*)

Set or get the coefficient of a variable in the objective function

INPUT:

- *variable* – integer; the variable's id
- *coeff* – double; its coefficient

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.add_variable()
0
sage: p.objective_coefficient(0)
0
sage: p.objective_coefficient(0,2)
sage: p.objective_coefficient(0)
2

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.add_variable()
0
>>> p.objective_coefficient(Integer(0))
0
>>> p.objective_coefficient(Integer(0), Integer(2))
>>> p.objective_coefficient(Integer(0))
2

```

objective_constant_term (*d=None*)

Set or get the constant term in the objective function.

INPUT:

- *d* – double; its coefficient. If *None* (default), return the current value.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.objective_constant_term()
0
sage: p.objective_constant_term(42)

```

(continues on next page)

(continued from previous page)

```
sage: p.objective_constant_term()
42
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.objective_constant_term()
0
>>> p.objective_constant_term(Integer(42))
>>> p.objective_constant_term()
42
```

problem_name (*name=None*)

Return or define the problem's name.

INPUT:

- *name* – string; the problem's name. When set to *None* (default), the method returns the problem's name.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.problem_name("There_once_was_a_french_fry")
sage: print(p.problem_name())
There_once_was_a_french_fry
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.problem_name("There_once_was_a_french_fry")
>>> print(p.problem_name())
There_once_was_a_french_fry
```

remove_constraint (*i*)

Remove a constraint.

INPUT:

- *i* – index of the constraint to remove

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='InteractiveLP')
sage: v = p.new_variable(nonnegative=True)
sage: x,y = v[0], v[1]
sage: p.add_constraint(2*x + 3*y, max = 6)
sage: p.add_constraint(3*x + 2*y, max = 6)
sage: p.set_objective(x + y + 7)
sage: p.solve()
47/5
sage: p.remove_constraint(0)
sage: p.solve()
10
```

(continues on next page)

(continued from previous page)

```
sage: p.get_values([x,y])
[0, 3]
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='InteractiveLP')
>>> v = p.new_variable(nonnegative=True)
>>> x,y = v[Integer(0)], v[Integer(1)]
>>> p.add_constraint(Integer(2)*x + Integer(3)*y, max = Integer(6))
>>> p.add_constraint(Integer(3)*x + Integer(2)*y, max = Integer(6))
>>> p.set_objective(x + y + Integer(7))
>>> p.solve()
47/5
>>> p.remove_constraint(Integer(0))
>>> p.solve()
10
>>> p.get_values([x,y])
[0, 3]
```

row(*i*)

Return a row.

INPUT:

- *index* – integer; the constraint's id

OUTPUT:

A pair (*indices*, *coeffs*) where *indices* lists the entries whose coefficient is nonzero, and to which *coeffs* associates their coefficient on the model of the `add_linear_constraint` method.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(zip(range(5), range(5)), 0, None)
sage: p.row(0)
([1, 2, 3, 4], [1, 2, 3, 4])
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))),
↳ Integer(0), None)
>>> p.row(Integer(0))
([1, 2, 3, 4], [1, 2, 3, 4])
```

row_bounds(*index*)

Return the bounds of a specific constraint.

INPUT:

- `index` – integer; the constraint's id

OUTPUT:

A pair (`lower_bound`, `upper_bound`). Each of them can be set to `None` if the constraint is not bounded in the corresponding direction, and is a real value otherwise.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(zip(range(5), range(5)), 2, 2)
sage: p.row_bounds(0)
(2, 2)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))),
↳ Integer(2), Integer(2))
>>> p.row_bounds(Integer(0))
(2, 2)
```

row_name (*index*)

Return the `index`-th row name.

INPUT:

- `index` – integer; the row's id

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.add_linear_constraints(1, 2, None, names=['Empty constraint 1'])
sage: p.row_name(0)
'Empty constraint 1'
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.add_linear_constraints(Integer(1), Integer(2), None, names=['Empty_
↳ constraint 1'])
>>> p.row_name(Integer(0))
'Empty constraint 1'
```

set_objective (*coeff*, *d=0*)

Set the objective function.

INPUT:

- `coeff` – list of real values, whose `i`-th element is the coefficient of the `i`-th variable in the objective function

- d – real; the constant term in the linear function (set to 0 by default)

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.add_variables(5)
4
sage: p.set_objective([1, 1, 2, 1, 3])
sage: [p.objective_coefficient(x) for x in range(5)]
[1, 1, 2, 1, 3]
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.add_variables(Integer(5))
4
>>> p.set_objective([Integer(1), Integer(1), Integer(2), Integer(1),
↳Integer(3)])
>>> [p.objective_coefficient(x) for x in range(Integer(5))]
[1, 1, 2, 1, 3]
```

Constants in the objective function are respected:

```
sage: p = MixedIntegerLinearProgram(solver='InteractiveLP')
sage: x,y = p[0], p[1]
sage: p.add_constraint(2*x + 3*y, max = 6)
sage: p.add_constraint(3*x + 2*y, max = 6)
sage: p.set_objective(x + y + 7)
sage: p.solve()
47/5
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='InteractiveLP')
>>> x,y = p[Integer(0)], p[Integer(1)]
>>> p.add_constraint(Integer(2)*x + Integer(3)*y, max = Integer(6))
>>> p.add_constraint(Integer(3)*x + Integer(2)*y, max = Integer(6))
>>> p.set_objective(x + y + Integer(7))
>>> p.solve()
47/5
```

set_sense (*sense*)

Set the direction (maximization/minimization).

INPUT:

- *sense* – integer:
 - +1 => Maximization
 - -1 => Minimization

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
```

(continues on next page)

(continued from previous page)

```
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False
```

set_variable_type (*variable*, *vtype*)

Set the type of a variable.

In this backend, variables are always continuous (real). If integer or binary variables are requested via the parameter *vtype*, an error will be raised.

INPUT:

- *variable* – integer; the variable's id
- *vtype* – integer:
 - 1 Integer
 - 0 Binary
 - **-1** Continuous

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.set_variable_type(0, -1)
sage: p.is_variable_continuous(0)
True
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.set_variable_type(Integer(0), -Integer(1))
>>> p.is_variable_continuous(Integer(0))
True
```

set_verbosity (*level*)

Set the log (verbosity) level.

INPUT:

- *level* – integer; from 0 (no verbosity) to 3

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.set_verbosity(2)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.set_verbosity(Integer(2))
```

solve ()

Solve the problem.

Note

This method raises `MIPSolverException` exceptions when the solution cannot be computed for any reason (none exists, or the LP solver was not able to find it, etc...)

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.add_linear_constraints(5, 0, None)
sage: p.add_col(list(range(5)), list(range(5)))
sage: p.solve()
0
sage: p.objective_coefficient(0,1)
sage: p.solve()
Traceback (most recent call last):
...
MIPSolverException: ...
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.add_linear_constraints(Integer(5), Integer(0), None)
>>> p.add_col(list(range(Integer(5))), list(range(Integer(5))))
>>> p.solve()
0
>>> p.objective_coefficient(Integer(0), Integer(1))
>>> p.solve()
Traceback (most recent call last):
...
MIPSolverException: ...
```

variable_lower_bound (*index*, *value=False*)

Return or define the lower bound on a variable.

INPUT:

- *index* – integer; the variable's id
- *value* – real value, or `None` to mean that the variable has no lower bound. When set to `False` (default), the method returns the current value.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.add_variable(lower_bound=None)
0
sage: p.col_bounds(0)
(None, None)
sage: p.variable_lower_bound(0) is None
True
sage: p.variable_lower_bound(0, 0)
sage: p.col_bounds(0)
(0, None)
sage: p.variable_lower_bound(0)
0
sage: p.variable_lower_bound(0, None)
sage: p.variable_lower_bound(0) is None
True
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.add_variable(lower_bound=None)
0
>>> p.col_bounds(Integer(0))
(None, None)
>>> p.variable_lower_bound(Integer(0)) is None
True
>>> p.variable_lower_bound(Integer(0), Integer(0))
>>> p.col_bounds(Integer(0))
(0, None)
>>> p.variable_lower_bound(Integer(0))
0
>>> p.variable_lower_bound(Integer(0), None)
>>> p.variable_lower_bound(Integer(0)) is None
True
```

variable_upper_bound (*index*, *value=False*)

Return or define the upper bound on a variable.

INPUT:

- *index* – integer; the variable's id
- *value* – real value, or `None` to mean that the variable has not upper bound. When set to `False` (default), the method returns the current value.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "InteractiveLP")
sage: p.add_variable(lower_bound=None)
0
sage: p.col_bounds(0)
(None, None)
sage: p.variable_upper_bound(0) is None
True
sage: p.variable_upper_bound(0, 0)
sage: p.col_bounds(0)
(None, 0)
sage: p.variable_upper_bound(0)
0
sage: p.variable_upper_bound(0, None)
sage: p.variable_upper_bound(0) is None
True

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "InteractiveLP")
>>> p.add_variable(lower_bound=None)
0
>>> p.col_bounds(Integer(0))
(None, None)
>>> p.variable_upper_bound(Integer(0)) is None
True
>>> p.variable_upper_bound(Integer(0), Integer(0))
>>> p.col_bounds(Integer(0))
(None, 0)
>>> p.variable_upper_bound(Integer(0))
0
>>> p.variable_upper_bound(Integer(0), None)
>>> p.variable_upper_bound(Integer(0)) is None
True

```

11.3 GLPK Backend

AUTHORS:

- Nathann Cohen (2010-10): initial implementation
- John Perry (2012-01): glp_simplex preprocessing
- John Perry and Raniere Gaia Silva (2012-03): solver parameters
- Christian Kuper (2012-10): Additions for sensitivity analysis

```
class sage.numerical.backends.glpk_backend.GLPKBackend
```

Bases: *GenericBackend*

MIP Backend that uses the GLPK solver.

```
add_col(indices, coeffs)
```

Add a column.

INPUT:

- `indices` – list of integers; this list contains the indices of the constraints in which the variable's coefficient is nonzero
- `coeffs` – list of real values; associates a coefficient to the variable in each of the constraints in which it appears. Namely, the i -th entry of `coeffs` corresponds to the coefficient of the variable in the constraint represented by the i -th entry in `indices`.

Note

`indices` and `coeffs` are expected to be of the same length.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.ncols()
0
sage: p.nrows()
0
sage: p.add_linear_constraints(5, 0, None)
sage: p.add_col(range(5), range(5))
sage: p.nrows()
5
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.ncols()
0
>>> p.nrows()
0
>>> p.add_linear_constraints(Integer(5), Integer(0), None)
>>> p.add_col(range(Integer(5)), range(Integer(5)))
>>> p.nrows()
5
```

add_linear_constraint (*coefficients, lower_bound, upper_bound, name=None*)

Add a linear constraint.

INPUT:

- `coefficients` an iterable with (c, v) pairs where c is a variable index (integer) and v is a value (real value).
- `lower_bound` – a lower bound, either a real value or `None`
- `upper_bound` – an upper bound, either a real value or `None`
- `name` – an optional name for this row (default: `None`)

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
```

(continues on next page)

(continued from previous page)

```

sage: p.add_variables(5)
4
sage: p.add_linear_constraint(zip(range(5), range(5)), 2.0, 2.0)
sage: p.row(0)
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0])
sage: p.row_bounds(0)
(2.0, 2.0)
sage: p.add_linear_constraint(zip(range(5), range(5)), 1.0, 1.0, name='foo')
sage: p.row_name(1)
'foo'

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))),
↳RealNumber('2.0'), RealNumber('2.0'))
>>> p.row(Integer(0))
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0])
>>> p.row_bounds(Integer(0))
(2.0, 2.0)
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))),
↳RealNumber('1.0'), RealNumber('1.0'), name='foo')
>>> p.row_name(Integer(1))
'foo'

```

add_linear_constraints (*number, lower_bound, upper_bound, names=None*)

Add 'number' linear constraints.

INPUT:

- *number* – integer; the number of constraints to add
- *lower_bound* – a lower bound, either a real value or None
- *upper_bound* – an upper bound, either a real value or None
- *names* – an optional list of names (default: None)

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variables(5)
4
sage: p.add_linear_constraints(5, None, 2)
sage: p.row(4)
([], [])
sage: p.row_bounds(4)
(None, 2.0)
sage: p.add_linear_constraints(2, None, 2, names=['foo', 'bar'])

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraints(Integer(5), None, Integer(2))
>>> p.row(Integer(4))
([], [])
>>> p.row_bounds(Integer(4))
(None, 2.0)
>>> p.add_linear_constraints(Integer(2), None, Integer(2), names=['foo', 'bar'
↪'])
    
```

add_variable (*lower_bound=0.0, upper_bound=None, binary=False, continuous=False, integer=False, obj=0.0, name=None*)

Add a variable.

This amounts to adding a new column to the matrix. By default, the variable is both positive, real and the coefficient in the objective function is 0.0.

INPUT:

- *lower_bound* – the lower bound of the variable (default: 0)
- *upper_bound* – the upper bound of the variable (default: None)
- *binary* – True if the variable is binary (default: False)
- *continuous* – True if the variable is continuous (default: True)
- *integer* – True if the variable is integral (default: False)
- *obj* – (optional) coefficient of this variable in the objective function (default: 0.0)
- *name* – an optional name for the newly added variable (default: None)

OUTPUT: the index of the newly created variable

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.ncols()
1
sage: p.add_variable(binary=True)
1
sage: p.add_variable(lower_bound=-2.0, integer=True)
2
sage: p.add_variable(continuous=True, integer=True)
Traceback (most recent call last):
...
ValueError: ...
sage: p.add_variable(name='x', obj=1.0)
3
    
```

(continues on next page)

(continued from previous page)

```
sage: p.col_name(3)
'x'
sage: p.objective_coefficient(3)
1.0
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.ncols()
1
>>> p.add_variable(binary=True)
1
>>> p.add_variable(lower_bound=-RealNumber('2.0'), integer=True)
2
>>> p.add_variable(continuous=True, integer=True)
Traceback (most recent call last):
...
ValueError: ...
>>> p.add_variable(name='x', obj=RealNumber('1.0'))
3
>>> p.col_name(Integer(3))
'x'
>>> p.objective_coefficient(Integer(3))
1.0
```

add_variables (*number*, *lower_bound*=0.0, *upper_bound*=None, *binary*=False, *continuous*=False, *integer*=False, *obj*=0.0, *names*=None)

Add *number* new variables.

This amounts to adding new columns to the matrix. By default, the variables are both positive, real and their coefficient in the objective function is 0.0.

INPUT:

- *n* – the number of new variables (must be > 0)
- *lower_bound* – the lower bound of the variable (default: 0)
- *upper_bound* – the upper bound of the variable (default: None)
- *binary* – True if the variable is binary (default: False)
- *continuous* – True if the variable is binary (default: True)
- *integer* – True if the variable is binary (default: False)
- *obj* – coefficient of all variables in the objective function (default: 0.0)
- *names* – list of names (default: None)

OUTPUT: the index of the variable created last

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.ncols()
0
sage: p.add_variables(5)
4
sage: p.ncols()
5
sage: p.add_variables(2, lower_bound=-2.0, integer=True, obj=42.0, names=['a',
↳ 'b'])
6
    
```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.ncols()
0
>>> p.add_variables(Integer(5))
4
>>> p.ncols()
5
>>> p.add_variables(Integer(2), lower_bound=-RealNumber('2.0'), integer=True,
↳ obj=RealNumber('42.0'), names=['a', 'b'])
6
    
```

`best_known_objective_bound()`

Return the value of the currently best known bound.

This method returns the current best upper (resp. lower) bound on the optimal value of the objective function in a maximization (resp. minimization) problem. It is equal to the output of `get_objective_value()` if the MILP found an optimal solution, but it can differ if it was interrupted manually or after a time limit (cf `solver_parameter()`).

Note

Has no meaning unless `solve` has been called before.

EXAMPLES:

```

sage: # needs sage.graphs
sage: g = graphs.CubeGraph(9)
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.solver_parameter("mip_gap_tolerance", 100)
sage: b = p.new_variable(binary=True)
sage: p.set_objective(p.sum(b[v] for v in g))
sage: for v in g:
...:     p.add_constraint(b[v]+p.sum(b[u] for u in g.neighbors(v)) <= 1)
sage: p.add_constraint(b[v] == 1) # Force an easy non-0 solution
sage: p.solve() # rel tol 100
1.0
sage: backend = p.get_backend()
sage: backend.best_known_objective_bound() # random
    
```

(continues on next page)

(continued from previous page)

48.0

```

>>> from sage.all import *
>>> # needs sage.graphs
>>> g = graphs.CubeGraph(Integer(9))
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.solver_parameter("mip_gap_tolerance", Integer(100))
>>> b = p.new_variable(binary=True)
>>> p.set_objective(p.sum(b[v] for v in g))
>>> for v in g:
...     p.add_constraint(b[v]+p.sum(b[u] for u in g.neighbors(v)) <=
↳ Integer(1))
>>> p.add_constraint(b[v] == Integer(1)) # Force an easy non-0 solution
>>> p.solve() # rel tol 100
1.0
>>> backend = p.get_backend()
>>> backend.best_known_objective_bound() # random
48.0

```

col_bounds (*index*)

Return the bounds of a specific variable.

INPUT:

- *index* – integer; the variable's id

OUTPUT:

A pair (*lower_bound*, *upper_bound*). Each of them can be set to `None` if the variable is not bounded in the corresponding direction, and is a real value otherwise.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variable()
0
sage: p.col_bounds(0)
(0.0, None)
sage: p.variable_upper_bound(0, 5)
sage: p.col_bounds(0)
(0.0, 5.0)

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variable()
0
>>> p.col_bounds(Integer(0))
(0.0, None)
>>> p.variable_upper_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(0.0, 5.0)

```

col_name (*index*)Return the *index*-th col name.

INPUT:

- *index* – integer; the col's id

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variable(name='I am a variable')
0
sage: p.col_name(0)
'I am a variable'
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variable(name='I am a variable')
0
>>> p.col_name(Integer(0))
'I am a variable'
```

eval_tab_col (*k*)

Compute a column of the current simplex tableau.

A (column) corresponds to some non-basic variable specified by the parameter *k* as follows:

- if $0 \leq k \leq m - 1$, the non-basic variable is *k*-th auxiliary variable,
- if $m \leq k \leq m + n - 1$, the non-basic variable is (*k* - *m*)-th structural variable,

where *m* is the number of rows and *n* is the number of columns in the specified problem object.**Note**

The basis factorization must exist and the variable with index *k* must not be basic. Otherwise, a `ValueError` is be raised.

INPUT:

- *k* – integer; the id of the non-basic variable

OUTPUT:

A pair (*indices*, *coeffs*) where *indices* lists the entries whose coefficient is nonzero, and to which *coeffs* associates their coefficient in the computed column of the current simplex tableau.

Note

Elements in *indices* have the same sense as index *k*. All these variables are basic by definition.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: lp = get_solver(solver = "GLPK")
sage: lp.add_variables(3)
2
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [8, 6, 1])), None, 48)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [4, 2, 1.5])), None, 20)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [2, 1.5, 0.5])), None, 8)
sage: lp.set_objective([60, 30, 20])
sage: import sage.numerical.backends.glpk_backend as backend
sage: lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
sage: lp.eval_tab_col(1)
Traceback (most recent call last):
...
ValueError: basis factorization does not exist
sage: lp.solve()
0
sage: lp.eval_tab_col(1)
([0, 5, 3], [-2.0, 2.0, -0.5])
sage: lp.eval_tab_col(2)
([0, 5, 3], [8.0, -4.0, 1.5])
sage: lp.eval_tab_col(4)
([0, 5, 3], [-2.0, 2.0, -1.25])
sage: lp.eval_tab_col(0)
Traceback (most recent call last):
...
ValueError: slack variable 0 is basic
sage: lp.eval_tab_col(-1)
Traceback (most recent call last):
...
ValueError: ...

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> lp = get_solver(solver = "GLPK")
>>> lp.add_variables(Integer(3))
2
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(8), Integer(6), Integer(1)])), None, Integer(48))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(4), Integer(2), RealNumber('1.5')])), None, Integer(20))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(2), RealNumber('1.5'), RealNumber('0.5')])), None, Integer(8))
>>> lp.set_objective([Integer(60), Integer(30), Integer(20)])
>>> import sage.numerical.backends.glpk_backend as backend
>>> lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
>>> lp.eval_tab_col(Integer(1))
Traceback (most recent call last):
...
ValueError: basis factorization does not exist
>>> lp.solve()

```

(continues on next page)

(continued from previous page)

```

0
>>> lp.eval_tab_col(Integer(1))
([0, 5, 3], [-2.0, 2.0, -0.5])
>>> lp.eval_tab_col(Integer(2))
([0, 5, 3], [8.0, -4.0, 1.5])
>>> lp.eval_tab_col(Integer(4))
([0, 5, 3], [-2.0, 2.0, -1.25])
>>> lp.eval_tab_col(Integer(0))
Traceback (most recent call last):
...
ValueError: slack variable 0 is basic
>>> lp.eval_tab_col(-Integer(1))
Traceback (most recent call last):
...
ValueError: ...

```

eval_tab_row(*k*)

Compute a row of the current simplex tableau.

A row corresponds to some basic variable specified by the parameter *k* as follows:

- if $0 \leq k \leq m - 1$, the basic variable is *k*-th auxiliary variable,
- if $m \leq k \leq m + n - 1$, the basic variable is $(k - m)$ -th structural variable,

where *m* is the number of rows and *n* is the number of columns in the specified problem object.

Note

The basis factorization must exist and the variable with index *k* must be basic. Otherwise, a `ValueError` is be raised.

INPUT:

- *k* – integer; the id of the basic variable

OUTPUT:

A pair (*indices*, *coeffs*) where *indices* lists the entries whose coefficient is nonzero, and to which *coeffs* associates their coefficient in the computed row of the current simplex tableau.

Note

Elements in *indices* have the same sense as index *k*. All these variables are non-basic by definition.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: lp = get_solver(solver = "GLPK")
sage: lp.add_variables(3)
2
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [8, 6, 1])), None, 48)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [4, 2, 1.5])), None, 20)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [2, 1.5, 0.5])), None, 8)

```

(continues on next page)

(continued from previous page)

```

sage: lp.set_objective([60, 30, 20])
sage: import sage.numerical.backends.glpk_backend as backend
sage: lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
sage: lp.eval_tab_row(0)
Traceback (most recent call last):
...
ValueError: basis factorization does not exist
sage: lp.solve()
0
sage: lp.eval_tab_row(0)
([1, 2, 4], [-2.0, 8.0, -2.0])
sage: lp.eval_tab_row(3)
([1, 2, 4], [-0.5, 1.5, -1.25])
sage: lp.eval_tab_row(5)
([1, 2, 4], [2.0, -4.0, 2.0])
sage: lp.eval_tab_row(1)
Traceback (most recent call last):
...
ValueError: slack variable 1 is not basic
sage: lp.eval_tab_row(-1)
Traceback (most recent call last):
...
ValueError: ...

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> lp = get_solver(solver = "GLPK")
>>> lp.add_variables(Integer(3))
2
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(8), Integer(6), Integer(1)])), None, Integer(48))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(4), Integer(2), RealNumber('1.5')])), None, Integer(20))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(2), RealNumber('1.5'), RealNumber('0.5')])), None, Integer(8))
>>> lp.set_objective([Integer(60), Integer(30), Integer(20)])
>>> import sage.numerical.backends.glpk_backend as backend
>>> lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
>>> lp.eval_tab_row(Integer(0))
Traceback (most recent call last):
...
ValueError: basis factorization does not exist
>>> lp.solve()
0
>>> lp.eval_tab_row(Integer(0))
([1, 2, 4], [-2.0, 8.0, -2.0])
>>> lp.eval_tab_row(Integer(3))
([1, 2, 4], [-0.5, 1.5, -1.25])
>>> lp.eval_tab_row(Integer(5))
([1, 2, 4], [2.0, -4.0, 2.0])

```

(continues on next page)

(continued from previous page)

```
>>> lp.eval_tab_row(Integer(1))
Traceback (most recent call last):
...
ValueError: slack variable 1 is not basic
>>> lp.eval_tab_row(-Integer(1))
Traceback (most recent call last):
...
ValueError: ...
```

get_col_dual (*variable*)

Return the dual value (reduced cost) of a variable

The dual value is the reduced cost of a variable. The reduced cost is the amount by which the objective coefficient of a non basic variable has to change to become a basic variable.

INPUT:

- *variable* – the number of the variable

Note

Behaviour is undefined unless `solve` has been called before. If the simplex algorithm has not been used for solving just a 0.0 will be returned.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variables(3)
2
sage: p.add_linear_constraint(list(zip([0, 1, 2], [8, 6, 1])), None, 48)
sage: p.add_linear_constraint(list(zip([0, 1, 2], [4, 2, 1.5])), None, 20)
sage: p.add_linear_constraint(list(zip([0, 1, 2], [2, 1.5, 0.5])), None, 8)
sage: p.set_objective([60, 30, 20])
sage: import sage.numerical.backends.glpk_backend as backend
sage: p.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
sage: p.solve()
0
sage: p.get_col_dual(1)
-5.0
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variables(Integer(3))
2
>>> p.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(8), Integer(6), Integer(1)])), None, Integer(48))
>>> p.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(4), Integer(2), RealNumber('1.5')])), None, Integer(20))
>>> p.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳
```

(continues on next page)

(continued from previous page)

```

↪[Integer(2), RealNumber('1.5'), RealNumber('0.5')]), None, Integer(8))
>>> p.set_objective([Integer(60), Integer(30), Integer(20)])
>>> import sage.numerical.backends.glpk_backend as backend
>>> p.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↪only)
>>> p.solve()
0
>>> p.get_col_dual(Integer(1))
-5.0

```

get_col_stat(j)

Retrieve the status of a variable.

INPUT:

- j – the index of the variable

OUTPUT:

Current status assigned to the structural variable associated with j-th column:

- GLP_BS = 1 basic variable
- GLP_NL = 2 non-basic variable on lower bound
- GLP_NU = 3 non-basic variable on upper bound
- GLP_NF = 4 non-basic free (unbounded) variable
- GLP_NS = 5 non-basic fixed variable

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: lp = get_solver(solver = "GLPK")
sage: lp.add_variables(3)
2
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [8, 6, 1])), None, 48)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [4, 2, 1.5])), None, 20)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [2, 1.5, 0.5])), None, 8)
sage: lp.set_objective([60, 30, 20])
sage: import sage.numerical.backends.glpk_backend as backend
sage: lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↪only)
sage: lp.solve()
0
sage: lp.get_col_stat(0)
1
sage: lp.get_col_stat(1)
2
sage: lp.get_col_stat(100)
Traceback (most recent call last):
...
ValueError: The variable's index j must satisfy 0 <= j < number_of_variables

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver

```

(continues on next page)

(continued from previous page)

```

>>> lp = get_solver(solver = "GLPK")
>>> lp.add_variables(Integer(3))
2
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(8), Integer(6), Integer(1)])), None, Integer(48))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(4), Integer(2), RealNumber('1.5')])), None, Integer(20))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(2), RealNumber('1.5'), RealNumber('0.5')])), None, Integer(8))
>>> lp.set_objective([Integer(60), Integer(30), Integer(20)])
>>> import sage.numerical.backends.glpk_backend as backend
>>> lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
>>> lp.solve()
0
>>> lp.get_col_stat(Integer(0))
1
>>> lp.get_col_stat(Integer(1))
2
>>> lp.get_col_stat(Integer(100))
Traceback (most recent call last):
...
ValueError: The variable's index j must satisfy 0 <= j < number_of_variables

```

get_objective_value()

Return the value of the objective function.

NoteBehaviour is undefined unless `solve` has been called before.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([[0, 1], [1, 2]], None, 3)
sage: p.set_objective([2, 5])
sage: p.solve()
0
sage: p.get_objective_value()
7.5
sage: p.get_variable_value(0) # abs tol 1e-15
0.0
sage: p.get_variable_value(1)
1.5

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")

```

(continues on next page)

(continued from previous page)

```

>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([[Integer(0), Integer(1)], [Integer(1),
↳Integer(2)]], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> p.solve()
0
>>> p.get_objective_value()
7.5
>>> p.get_variable_value(Integer(0)) # abs tol 1e-15
0.0
>>> p.get_variable_value(Integer(1))
1.5

```

get_relative_objective_gap()

Return the relative objective gap of the best known solution.

For a minimization problem, this value is computed by $(\text{bestinteger} - \text{bestobjective}) / (1e - 10 + |\text{bestobjective}|)$, where `bestinteger` is the value returned by `get_objective_value()` and `bestobjective` is the value returned by `best_known_objective_bound()`. For a maximization problem, the value is computed by $(\text{bestobjective} - \text{bestinteger}) / (1e - 10 + |\text{bestobjective}|)$.

Note

Has no meaning unless `solve` has been called before.

EXAMPLES:

```

sage: # needs sage.graphs
sage: g = graphs.CubeGraph(9)
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.solver_parameter("mip_gap_tolerance", 100)
sage: b = p.new_variable(binary=True)
sage: p.set_objective(p.sum(b[v] for v in g))
sage: for v in g:
...:     p.add_constraint(b[v] + p.sum(b[u] for u in g.neighbors(v)) <= 1)
sage: p.add_constraint(b[v] == 1) # Force an easy non-0 solution
sage: p.solve() # rel tol 100
1.0
sage: backend = p.get_backend()
sage: backend.get_relative_objective_gap() # random
46.99999999999999

```

```

>>> from sage.all import *
>>> # needs sage.graphs
>>> g = graphs.CubeGraph(Integer(9))
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.solver_parameter("mip_gap_tolerance", Integer(100))
>>> b = p.new_variable(binary=True)
>>> p.set_objective(p.sum(b[v] for v in g))
>>> for v in g:

```

(continues on next page)

(continued from previous page)

```

...     p.add_constraint(b[v]+p.sum(b[u] for u in g.neighbors(v)) <=
↳Integer(1))
>>> p.add_constraint(b[v] == Integer(1)) # Force an easy non-0 solution
>>> p.solve() # rel tol 100
1.0
>>> backend = p.get_backend()
>>> backend.get_relative_objective_gap() # random
46.99999999999999

```

get_row_dual (*variable*)

Return the dual value of a constraint.

The dual value of the *i*-th row is also the value of the *i*-th variable of the dual problem.

The dual value of a constraint is the shadow price of the constraint. The shadow price is the amount by which the objective value will change if the constraints bounds change by one unit under the precondition that the basis remains the same.

INPUT:

- *variable* – the number of the constraint

Note

Behaviour is undefined unless `solve` has been called before. If the simplex algorithm has not been used for solving 0.0 will be returned.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: lp = get_solver(solver = "GLPK")
sage: lp.add_variables(3)
2
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [8, 6, 1])), None, 48)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [4, 2, 1.5])), None, 20)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [2, 1.5, 0.5])), None, 8)
sage: lp.set_objective([60, 30, 20])
sage: import sage.numerical.backends.glpk_backend as backend
sage: lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
sage: lp.solve()
0
sage: lp.get_row_dual(0) # tolerance 0.00001
0.0
sage: lp.get_row_dual(1) # tolerance 0.00001
10.0

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> lp = get_solver(solver = "GLPK")
>>> lp.add_variables(Integer(3))
2
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],

```

(continues on next page)

(continued from previous page)

```

↳[Integer(8), Integer(6), Integer(1)]), None, Integer(48))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],↳
↳[Integer(4), Integer(2), RealNumber('1.5')])), None, Integer(20))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],↳
↳[Integer(2), RealNumber('1.5'), RealNumber('0.5')])), None, Integer(8))
>>> lp.set_objective([Integer(60), Integer(30), Integer(20)])
>>> import sage.numerical.backends.glpk_backend as backend
>>> lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
>>> lp.solve()
0
>>> lp.get_row_dual(Integer(0)) # tolerance 0.00001
0.0
>>> lp.get_row_dual(Integer(1)) # tolerance 0.00001
10.0

```

get_row_prim(i)

Return the value of the auxiliary variable associated with i-th row.

NoteBehaviour is undefined unless `solve` has been called before.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: lp = get_solver(solver = "GLPK")
sage: lp.add_variables(3)
2
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [8, 6, 1])), None, 48)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [4, 2, 1.5])), None, 20)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [2, 1.5, 0.5])), None, 8)
sage: lp.set_objective([60, 30, 20])
sage: import sage.numerical.backends.glpk_backend as backend
sage: lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
sage: lp.solve()
0
sage: lp.get_objective_value()
280.0
sage: lp.get_row_prim(0)
24.0
sage: lp.get_row_prim(1)
20.0
sage: lp.get_row_prim(2)
8.0

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> lp = get_solver(solver = "GLPK")
>>> lp.add_variables(Integer(3))

```

(continues on next page)

(continued from previous page)

```

2
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(8), Integer(6), Integer(1)])), None, Integer(48))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(4), Integer(2), RealNumber('1.5')])), None, Integer(20))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(2), RealNumber('1.5'), RealNumber('0.5')])), None, Integer(8))
>>> lp.set_objective([Integer(60), Integer(30), Integer(20)])
>>> import sage.numerical.backends.glpk_backend as backend
>>> lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
>>> lp.solve()
0
>>> lp.get_objective_value()
280.0
>>> lp.get_row_prim(Integer(0))
24.0
>>> lp.get_row_prim(Integer(1))
20.0
>>> lp.get_row_prim(Integer(2))
8.0

```

get_row_stat (*i*)

Retrieve the status of a constraint.

INPUT:

- *i* – the index of the constraint

OUTPUT:

Current status assigned to the auxiliary variable associated with *i*-th row:

- GLP_BS = 1 basic variable
- GLP_NL = 2 non-basic variable on lower bound
- GLP_NU = 3 non-basic variable on upper bound
- GLP_NF = 4 non-basic free (unbounded) variable
- GLP_NS = 5 non-basic fixed variable

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: lp = get_solver(solver = "GLPK")
sage: lp.add_variables(3)
2
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [8, 6, 1])), None, 48)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [4, 2, 1.5])), None, 20)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [2, 1.5, 0.5])), None, 8)
sage: lp.set_objective([60, 30, 20])
sage: import sage.numerical.backends.glpk_backend as backend
sage: lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
sage: lp.solve()

```

(continues on next page)

(continued from previous page)

```

0
sage: lp.get_row_stat(0)
1
sage: lp.get_row_stat(1)
3
sage: lp.get_row_stat(-1)
Traceback (most recent call last):
...
ValueError: The constraint's index i must satisfy 0 <= i < number_of_
↳constraints

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> lp = get_solver(solver = "GLPK")
>>> lp.add_variables(Integer(3))
2
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(8), Integer(6), Integer(1)])), None, Integer(48))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(4), Integer(2), RealNumber('1.5')])), None, Integer(20))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(2), RealNumber('1.5'), RealNumber('0.5')])), None, Integer(8))
>>> lp.set_objective([Integer(60), Integer(30), Integer(20)])
>>> import sage.numerical.backends.glpk_backend as backend
>>> lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
>>> lp.solve()
0
>>> lp.get_row_stat(Integer(0))
1
>>> lp.get_row_stat(Integer(1))
3
>>> lp.get_row_stat(-Integer(1))
Traceback (most recent call last):
...
ValueError: The constraint's index i must satisfy 0 <= i < number_of_
↳constraints

```

get_variable_value (*variable*)

Return the value of a variable given by the solver.

NoteBehaviour is undefined unless `solve` has been called before.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variables(2)
1

```

(continues on next page)

(continued from previous page)

```

sage: p.add_linear_constraint([[0, 1], [1, 2]], None, 3)
sage: p.set_objective([2, 5])
sage: p.solve()
0
sage: p.get_objective_value()
7.5
sage: p.get_variable_value(0) # abs tol 1e-15
0.0
sage: p.get_variable_value(1)
1.5
    
```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([[Integer(0), Integer(1)], [Integer(1),
↳Integer(2)]], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> p.solve()
0
>>> p.get_objective_value()
7.5
>>> p.get_variable_value(Integer(0)) # abs tol 1e-15
0.0
>>> p.get_variable_value(Integer(1))
1.5
    
```

`is_maximization()`

Test whether the problem is a maximization

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False
    
```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False
    
```

`is_slack_variable_basic(index)`

Test whether the slack variable of the given row is basic.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- `index` – integer; the variable's id

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(maximization=True,          ....:
↳ solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(5.5 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: import sage.numerical.backends.glpk_backend as backend
sage: b.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳ only)
sage: b.solve()
0
sage: b.is_slack_variable_basic(0)
True
sage: b.is_slack_variable_basic(1)
False
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True,          Ellipsis.:
↳ solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↳ <= Integer(17))
>>> p.set_objective(RealNumber('5.5') * x[Integer(0)] - Integer(3) *
↳ x[Integer(1)])
>>> b = p.get_backend()
>>> import sage.numerical.backends.glpk_backend as backend
>>> b.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳ only)
>>> b.solve()
0
>>> b.is_slack_variable_basic(Integer(0))
True
>>> b.is_slack_variable_basic(Integer(1))
False
```

`is_slack_variable_nonbasic_at_lower_bound` (*index*)

Test whether the slack variable of the given row is nonbasic at lower bound.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- `index` – integer; the variable's id

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(maximization=True,
    ↪                               solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(5.5 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: import sage.numerical.backends.glpk_backend as backend
sage: b.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
    ↪only)
sage: b.solve()
0
sage: b.is_slack_variable_nonbasic_at_lower_bound(0)
False
sage: b.is_slack_variable_nonbasic_at_lower_bound(1)
True
    
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True,
    ↪                               solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
    ↪<= Integer(17))
>>> p.set_objective(RealNumber('5.5') * x[Integer(0)] - Integer(3) *
    ↪x[Integer(1)])
>>> b = p.get_backend()
>>> import sage.numerical.backends.glpk_backend as backend
>>> b.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
    ↪only)
>>> b.solve()
0
>>> b.is_slack_variable_nonbasic_at_lower_bound(Integer(0))
False
>>> b.is_slack_variable_nonbasic_at_lower_bound(Integer(1))
True
    
```

`is_variable_basic` (*index*)

Test whether the given variable is basic.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- `index` – integer; the variable's id

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(maximization=True,
    ↪                               solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
    
```

(continues on next page)

(continued from previous page)

```

sage: p.set_objective(5.5 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: import sage.numerical.backends.glpk_backend as backend
sage: b.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
sage: b.solve()
0
sage: b.is_variable_basic(0)
True
sage: b.is_variable_basic(1)
False

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True, Ellipsis.:
↳ solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↳ <= Integer(17))
>>> p.set_objective(RealNumber('5.5') * x[Integer(0)] - Integer(3) *
↳ x[Integer(1)])
>>> b = p.get_backend()
>>> import sage.numerical.backends.glpk_backend as backend
>>> b.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
>>> b.solve()
0
>>> b.is_variable_basic(Integer(0))
True
>>> b.is_variable_basic(Integer(1))
False

```

is_variable_binary (*index*)

Test whether the given variable is of binary type.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.set_variable_type(0,0)
sage: p.is_variable_binary(0)
True

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver

```

(continues on next page)

(continued from previous page)

```

>>> p = get_solver(solver = "GLPK")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.set_variable_type(Integer(0), Integer(0))
>>> p.is_variable_binary(Integer(0))
True

```

is_variable_continuous (*index*)

Test whether the given variable is of continuous/real type.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.is_variable_continuous(0)
True
sage: p.set_variable_type(0, 1)
sage: p.is_variable_continuous(0)
False

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.is_variable_continuous(Integer(0))
True
>>> p.set_variable_type(Integer(0), Integer(1))
>>> p.is_variable_continuous(Integer(0))
False

```

is_variable_integer (*index*)

Test whether the given variable is of integer type.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.ncols()

```

(continues on next page)

(continued from previous page)

```

0
sage: p.add_variable()
0
sage: p.set_variable_type(0,1)
sage: p.is_variable_integer(0)
True

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.set_variable_type(Integer(0), Integer(1))
>>> p.is_variable_integer(Integer(0))
True

```

is_variable_nonbasic_at_lower_bound(*index*)

Test whether the given variable is nonbasic at lower bound. This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(maximization=True,          ....:
↳ solver='GLPK')
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(5.5 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: import sage.numerical.backends.glpk_backend as backend
sage: b.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳ only)
sage: b.solve()
0
sage: b.is_variable_nonbasic_at_lower_bound(0)
False
sage: b.is_variable_nonbasic_at_lower_bound(1)
True

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(maximization=True,          Ellipsis.:
↳ solver='GLPK')
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↳ <= Integer(17))
>>> p.set_objective(RealNumber('5.5') * x[Integer(0)] - Integer(3) *

```

(continues on next page)

(continued from previous page)

```

↪x[Integer(1)])
>>> b = p.get_backend()
>>> import sage.numerical.backends.glpk_backend as backend
>>> b.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↪only)
>>> b.solve()
0
>>> b.is_variable_nonbasic_at_lower_bound(Integer(0))
False
>>> b.is_variable_nonbasic_at_lower_bound(Integer(1))
True

```

ncols()

Return the number of columns/variables.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.ncols()
0
sage: p.add_variables(2)
1
sage: p.ncols()
2

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.ncols()
0
>>> p.add_variables(Integer(2))
1
>>> p.ncols()
2

```

nrows()

Return the number of rows/constraints.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.nrows()
0
sage: p.add_linear_constraints(2, 2, None)
sage: p.nrows()
2

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")

```

(continues on next page)

(continued from previous page)

```
>>> p.nrows()
0
>>> p.add_linear_constraints(Integer(2), Integer(2), None)
>>> p.nrows()
2
```

objective_coefficient (*variable, coeff=None*)

Set or get the coefficient of a variable in the objective function.

INPUT:

- *variable* – integer; the variable's id
- *coeff* – double; its coefficient or `None` for reading (default: `None`)

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variable()
0
sage: p.objective_coefficient(0)
0.0
sage: p.objective_coefficient(0,2)
sage: p.objective_coefficient(0)
2.0
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variable()
0
>>> p.objective_coefficient(Integer(0))
0.0
>>> p.objective_coefficient(Integer(0), Integer(2))
>>> p.objective_coefficient(Integer(0))
2.0
```

print_ranges (*filename=None*)

Print results of a sensitivity analysis

If no filename is given as an input the results of the sensitivity analysis are displayed on the screen. If a filename is given they are written to a file.

INPUT:

- *filename* – (optional) name of the file

OUTPUT: zero if the operations was successful otherwise nonzero

Note

This method is only effective if an optimal solution has been found for the lp using the simplex algorithm. In all other cases an error message is printed.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variables(2)
1
sage: p.add_linear_constraint(list(zip([0, 1], [1, 2])), None, 3)
sage: p.set_objective([2, 5])
sage: import sage.numerical.backends.glpk_backend as backend
sage: p.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
sage: p.print_ranges()
glp_print_ranges: optimal basic solution required
1
sage: p.solve()
0
sage: from tempfile import NamedTemporaryFile
sage: with NamedTemporaryFile(mode='r+t', suffix='.tmp') as f:
....:     p.print_ranges(f.name)
....:     for ll in f.readlines():
....:         if ll: print(ll)
...
GLPK ... - SENSITIVITY ANALYSIS REPORT
↳
↳                               Page 1
Problem:
Objective: 7.5 (MAXimum)
  No. Row name      St      Activity      Slack      Lower bound
↳Activity          Obj coef  Obj value at Limiting
↳range            range   break point variable
↳-----
↳
↳      1           NU      3.00000    .           -Inf
↳      -2.50000    .           2.50000    3.00000
↳+Inf            +Inf      +Inf
GLPK ... - SENSITIVITY ANALYSIS REPORT
↳
↳                               Page 2
Problem:
Objective: 7.5 (MAXimum)
  No. Column name  St      Activity      Obj coef      Lower bound
↳Activity          Obj coef  Obj value at Limiting
↳range            range   break point variable
↳-----
↳
↳      1           NL      .           2.00000    .           -
↳Inf            -Inf      +Inf           -.50000    +Inf      3.
↳00000         2.50000    6.00000    5.00000    .           -
↳      2           BS      1.50000    4.00000    .           -
↳Inf            4.00000    6.00000    .           +Inf      1.

```

(continues on next page)

(continued from previous page)

```
↪50000          +Inf          +Inf
End of report
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint(list(zip([Integer(0), Integer(1)], [Integer(1), ↪
↪Integer(2)])), None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> import sage.numerical.backends.glpk_backend as backend
>>> p.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↪only)
>>> p.print_ranges()
glp_print_ranges: optimal basic solution required
1
>>> p.solve()
0
>>> from tempfile import NamedTemporaryFile
>>> with NamedTemporaryFile(mode='r+t', suffix='.tmp') as f:
...     p.print_ranges(f.name)
...     for ll in f.readlines():
...         if ll: print(ll)
...
GLPK ... - SENSITIVITY ANALYSIS REPORT
↪
↪                               Page 1
Problem:
Objective: 7.5 (MAXimum)
  No. Row name      St      Activity      Slack      Lower bound      ↪
↪Activity          Obj coef  Obj value at Limiting
↪                               Marginal      Upper bound      ↪
↪range            range      break point variable
-----
↪- -----
↪ 1              NU      3.00000      .              -Inf              .      ↪
↪ -2.50000      .              2.50000      3.00000              ↪
↪+Inf            +Inf            +Inf
GLPK ... - SENSITIVITY ANALYSIS REPORT
↪
↪                               Page 2
Problem:
Objective: 7.5 (MAXimum)
  No. Column name  St      Activity      Obj coef      Lower bound      ↪
↪Activity          Obj coef  Obj value at Limiting
↪                               Marginal      Upper bound      ↪
↪range            range      break point variable
-----
↪- -----
↪ 1              NL      .              2.00000      .              -
↪-Inf            -Inf            +Inf
↪                               -.50000      +Inf              3.
```

(continues on next page)

(continued from previous page)

```

↪00000      2.50000      6.00000
      2          BS      1.50000      5.00000      .      -
↪Inf      4.00000      6.00000
↪50000      +Inf      +Inf
End of report
    
```

problem_name (*name=None*)

Return or define the problem's name.

INPUT:

- *name* – string; the problem's name. When set to `None` (default), the method returns the problem's name.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.problem_name("There once was a french fry")
sage: print(p.problem_name())
There once was a french fry
    
```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.problem_name("There once was a french fry")
>>> print(p.problem_name())
There once was a french fry
    
```

remove_constraint (*i*)

Remove a constraint from `self`.

INPUT:

- *i* – index of the constraint to remove

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x, y = p['x'], p['y']
sage: p.add_constraint(2*x + 3*y <= 6)
sage: p.add_constraint(3*x + 2*y <= 6)
sage: p.add_constraint(x >= 0)
sage: p.set_objective(x + y + 7)
sage: p.set_integer(x); p.set_integer(y)
sage: p.solve()
9.0
sage: p.remove_constraint(0)
sage: p.solve()
10.0
    
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x, y = p['x'], p['y']
    
```

(continues on next page)

(continued from previous page)

```

>>> p.add_constraint(Integer(2)*x + Integer(3)*y <= Integer(6))
>>> p.add_constraint(Integer(3)*x + Integer(2)*y <= Integer(6))
>>> p.add_constraint(x >= Integer(0))
>>> p.set_objective(x + y + Integer(7))
>>> p.set_integer(x); p.set_integer(y)
>>> p.solve()
9.0
>>> p.remove_constraint(Integer(0))
>>> p.solve()
10.0

```

Removing fancy constraints does not make Sage crash:

```

sage: MixedIntegerLinearProgram(solver = "GLPK").remove_constraint(-2)
Traceback (most recent call last):
...
ValueError: The constraint's index i must satisfy 0 <= i < number_of_
↳constraints

```

```

>>> from sage.all import *
>>> MixedIntegerLinearProgram(solver = "GLPK").remove_constraint(-Integer(2))
Traceback (most recent call last):
...
ValueError: The constraint's index i must satisfy 0 <= i < number_of_
↳constraints

```

`remove_constraints` (*constraints*)

Remove several constraints.

INPUT:

- `constraints` – an iterable containing the indices of the rows to remove

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: x, y = p['x'], p['y']
sage: p.add_constraint(2*x + 3*y <= 6)
sage: p.add_constraint(3*x + 2*y <= 6)
sage: p.add_constraint(x >= 0)
sage: p.set_objective(x + y + 7)
sage: p.set_integer(x); p.set_integer(y)
sage: p.solve()
9.0
sage: p.remove_constraints([0])
sage: p.solve()
10.0
sage: p.get_values([x,y])
[0.0, 3.0]

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> x, y = p['x'], p['y']

```

(continues on next page)

(continued from previous page)

```

>>> p.add_constraint(Integer(2)*x + Integer(3)*y <= Integer(6))
>>> p.add_constraint(Integer(3)*x + Integer(2)*y <= Integer(6))
>>> p.add_constraint(x >= Integer(0))
>>> p.set_objective(x + y + Integer(7))
>>> p.set_integer(x); p.set_integer(y)
>>> p.solve()
9.0
>>> p.remove_constraints([Integer(0)])
>>> p.solve()
10.0
>>> p.get_values([x,y])
[0.0, 3.0]
    
```

row (*index*)

Return a row.

INPUT:

- *index* – integer; the constraint's id

OUTPUT:

A pair (*indices*, *coeffs*) where *indices* lists the entries whose coefficient is nonzero, and to which *coeffs* associates their coefficient on the model of the `add_linear_constraint` method.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(list(zip(range(5), range(5))), 2, 2)
sage: p.row(0)
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0])
sage: p.row_bounds(0)
(2.0, 2.0)
    
```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(list(zip(range(Integer(5)), range(Integer(5))),
↳ Integer(2), Integer(2))
>>> p.row(Integer(0))
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0])
>>> p.row_bounds(Integer(0))
(2.0, 2.0)
    
```

row_bounds (*index*)

Return the bounds of a specific constraint.

INPUT:

- *index* – integer; the constraint's id

OUTPUT:

A pair (lower_bound, upper_bound). Each of them can be set to None if the constraint is not bounded in the corresponding direction, and is a real value otherwise.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(list(zip(range(5), range(5))), 2, 2)
sage: p.row(0)
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0])
sage: p.row_bounds(0)
(2.0, 2.0)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(list(zip(range(Integer(5)), range(Integer(5)))),
↳ Integer(2), Integer(2))
>>> p.row(Integer(0))
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0])
>>> p.row_bounds(Integer(0))
(2.0, 2.0)
```

row_name (*index*)

Return the index-th row name.

INPUT:

- index – integer; the row's id

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_linear_constraints(1, 2, None, names=['Empty constraint 1'])
sage: p.row_name(0)
'Empty constraint 1'
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_linear_constraints(Integer(1), Integer(2), None, names=['Empty_
↳ constraint 1'])
>>> p.row_name(Integer(0))
'Empty constraint 1'
```

set_col_stat (*j, stat*)

Set the status of a variable.

INPUT:

- `j` – the index of the constraint
- `stat` – the status to set to

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: lp = get_solver(solver = "GLPK")
sage: lp.add_variables(3)
2
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [8, 6, 1])), None, 48)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [4, 2, 1.5])), None, 20)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [2, 1.5, 0.5])), None, 8)
sage: lp.set_objective([60, 30, 20])
sage: import sage.numerical.backends.glpk_backend as backend
sage: lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
sage: lp.solve()
0
sage: lp.get_col_stat(0)
1
sage: lp.set_col_stat(0, 2)
sage: lp.get_col_stat(0)
2
    
```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> lp = get_solver(solver = "GLPK")
>>> lp.add_variables(Integer(3))
2
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(8), Integer(6), Integer(1)])), None, Integer(48))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(4), Integer(2), RealNumber('1.5')])), None, Integer(20))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(2), RealNumber('1.5'), RealNumber('0.5')])), None, Integer(8))
>>> lp.set_objective([Integer(60), Integer(30), Integer(20)])
>>> import sage.numerical.backends.glpk_backend as backend
>>> lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
>>> lp.solve()
0
>>> lp.get_col_stat(Integer(0))
1
>>> lp.set_col_stat(Integer(0), Integer(2))
>>> lp.get_col_stat(Integer(0))
2
    
```

set_objective (*coeff*, *d=0.0*)

Set the objective function.

INPUT:

- `coeff` – list of real values, whose `i`-th element is the coefficient of the `i`-th variable in the objective function

- `d` – double; the constant term in the linear function (set to 0 by default)

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variables(5)
4
sage: p.set_objective([1, 1, 2, 1, 3])
sage: [p.objective_coefficient(x) for x in range(5)]
[1.0, 1.0, 2.0, 1.0, 3.0]
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variables(Integer(5))
4
>>> p.set_objective([Integer(1), Integer(1), Integer(2), Integer(1), ↵
↵Integer(3)])
>>> [p.objective_coefficient(x) for x in range(Integer(5))]
[1.0, 1.0, 2.0, 1.0, 3.0]
```

set_row_stat (*i, stat*)

Set the status of a constraint.

INPUT:

- `i` – the index of the constraint
- `stat` – the status to set to

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: lp = get_solver(solver = "GLPK")
sage: lp.add_variables(3)
2
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [8, 6, 1])), None, 48)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [4, 2, 1.5])), None, 20)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [2, 1.5, 0.5])), None, 8)
sage: lp.set_objective([60, 30, 20])
sage: import sage.numerical.backends.glpk_backend as backend
sage: lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↵only)
sage: lp.solve()
0
sage: lp.get_row_stat(0)
1
sage: lp.set_row_stat(0, 3)
sage: lp.get_row_stat(0)
3
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> lp = get_solver(solver = "GLPK")
```

(continues on next page)

(continued from previous page)

```

>>> lp.add_variables(Integer(3))
2
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳ [Integer(8), Integer(6), Integer(1)])), None, Integer(48))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳ [Integer(4), Integer(2), RealNumber('1.5')])), None, Integer(20))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳ [Integer(2), RealNumber('1.5'), RealNumber('0.5')])), None, Integer(8))
>>> lp.set_objective([Integer(60), Integer(30), Integer(20)])
>>> import sage.numerical.backends.glpk_backend as backend
>>> lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳ only)
>>> lp.solve()
0
>>> lp.get_row_stat(Integer(0))
1
>>> lp.set_row_stat(Integer(0), Integer(3))
>>> lp.get_row_stat(Integer(0))
3

```

set_sense (*sense*)

Set the direction (maximization/minimization).

INPUT:

- `sense` – integer:
 - +1 => Maximization
 - -1 => Minimization

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False

```

set_variable_type (*variable*, *vtype*)

Set the type of a variable.

INPUT:

- `variable` – integer; the variable's id

- `vtype` – integer:
 - 1 Integer
 - 0 Binary
 - -1 Real

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.set_variable_type(0,1)
sage: p.is_variable_integer(0)
True
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.set_variable_type(Integer(0), Integer(1))
>>> p.is_variable_integer(Integer(0))
True
```

set_verbosity (*level*)

Set the verbosity level.

INPUT:

- `level` – integer; from 0 (no verbosity) to 3

EXAMPLES:

```
sage: p.<x> = MixedIntegerLinearProgram(solver='GLPK')
sage: p.add_constraint(10 * x[0] <= 1)
sage: p.add_constraint(5 * x[1] <= 1)
sage: p.set_objective(x[0] + x[1])
sage: p.solve()
0.30000000000000004
sage: p.get_backend().set_verbosity(3)
sage: p.solver_parameter("simplex_or_intopt", "intopt_only")
sage: p.solve()
GLPK Integer Optimizer...
2 rows, 2 columns, 2 non-zeros
0 integer variables, none of which are binary
Preprocessing...
Objective value = 3.000000000e-01
INTEGER OPTIMAL SOLUTION FOUND BY MIP PREPROCESSOR
0.30000000000000004
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK', names=('x',)); (x,) = p._
↳first_ngens(1)
>>> p.add_constraint(Integer(10) * x[Integer(0)] <= Integer(1))
>>> p.add_constraint(Integer(5) * x[Integer(1)] <= Integer(1))
>>> p.set_objective(x[Integer(0)] + x[Integer(1)])
>>> p.solve()
0.30000000000000004
>>> p.get_backend().set_verbosity(Integer(3))
>>> p.solver_parameter("simplex_or_intopt", "intopt_only")
>>> p.solve()
GLPK Integer Optimizer...
2 rows, 2 columns, 2 non-zeros
0 integer variables, none of which are binary
Preprocessing...
Objective value = 3.000000000e-01
INTEGER OPTIMAL SOLUTION FOUND BY MIP PREPROCESSOR
0.30000000000000004
    
```

```

sage: p.<x> = MixedIntegerLinearProgram(solver='GLPK/exact')
sage: p.add_constraint(10 * x[0] <= 1)
sage: p.add_constraint(5 * x[1] <= 1)
sage: p.set_objective(x[0] + x[1])
sage: p.solve() # tol 1e-14
0.3
sage: p.get_backend().set_verbosity(2)
sage: p.solve() # tol 1e-14
* 2: objval = 0.3 (0)
* 2: objval = 0.3 (0)
0.3
sage: p.get_backend().set_verbosity(3)
sage: p.solve() # tol 1e-14
glp_exact: 2 rows, 2 columns, 2 non-zeros
...
* 2: objval = 0.3 (0)
* 2: objval = 0.3 (0)
OPTIMAL SOLUTION FOUND
0.3
    
```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='GLPK/exact', names=('x',)); (x,) =
↳p._first_ngens(1)
>>> p.add_constraint(Integer(10) * x[Integer(0)] <= Integer(1))
>>> p.add_constraint(Integer(5) * x[Integer(1)] <= Integer(1))
>>> p.set_objective(x[Integer(0)] + x[Integer(1)])
>>> p.solve() # tol 1e-14
0.3
>>> p.get_backend().set_verbosity(Integer(2))
>>> p.solve() # tol 1e-14
* 2: objval = 0.3 (0)
* 2: objval = 0.3 (0)
0.3
    
```

(continues on next page)

(continued from previous page)

```

>>> p.get_backend().set_verbosity(Integer(3))
>>> p.solve() # tol 1e-14
glp_exact: 2 rows, 2 columns, 2 non-zeros
...
*      2:  objval =                0.3   (0)
*      2:  objval =                0.3   (0)
OPTIMAL SOLUTION FOUND
0.3

```

solve()

Solve the problem.

Sage uses GLPK's implementation of the branch-and-cut algorithm (`glp_intopt`) to solve the mixed-integer linear program. This algorithm can be requested explicitly by setting the solver parameter “simplex_or_intopt” to “intopt_only”. By default, the simplex method will be used first to detect pathological problems that the integer solver cannot handle. If all variables are continuous, the integer algorithm reduces to solving the linear program by the simplex method.

EXAMPLES:

```

sage: lp = MixedIntegerLinearProgram(solver = 'GLPK', maximization = False)
sage: x, y = lp[0], lp[1]
sage: lp.add_constraint(-2*x + y <= 1)
sage: lp.add_constraint(x - y <= 1)
sage: lp.add_constraint(x + y >= 2)
sage: lp.set_objective(x + y)
sage: lp.set_integer(x)
sage: lp.set_integer(y)
sage: lp.solve()
2.0
sage: lp.get_values([x, y])
[1.0, 1.0]

```

```

>>> from sage.all import *
>>> lp = MixedIntegerLinearProgram(solver = 'GLPK', maximization = False)
>>> x, y = lp[Integer(0)], lp[Integer(1)]
>>> lp.add_constraint(-Integer(2)*x + y <= Integer(1))
>>> lp.add_constraint(x - y <= Integer(1))
>>> lp.add_constraint(x + y >= Integer(2))
>>> lp.set_objective(x + y)
>>> lp.set_integer(x)
>>> lp.set_integer(y)
>>> lp.solve()
2.0
>>> lp.get_values([x, y])
[1.0, 1.0]

```

Note

This method raises `MIPSolverException` exceptions when the solution cannot be computed for any reason (none exists, or the LP solver was not able to find it, etc...)

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_linear_constraints(5, 0, None)
sage: p.add_col(range(5), range(5))
sage: p.solve()
0
sage: p.objective_coefficient(0,1)
sage: p.solve()
Traceback (most recent call last):
...
MIPSolverException: ...
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_linear_constraints(Integer(5), Integer(0), None)
>>> p.add_col(range(Integer(5)), range(Integer(5)))
>>> p.solve()
0
>>> p.objective_coefficient(Integer(0), Integer(1))
>>> p.solve()
Traceback (most recent call last):
...
MIPSolverException: ...
```

Warning

GLPK's `glp_intopt` sometimes fails catastrophically when given a system it cannot solve ([Issue #12309](#)). It can loop indefinitely, or just plain segfault. Upstream considers this behavior “essentially innate” to the current design, and suggests preprocessing with `glp_simplex`, which is what SageMath does by default. Set the `simplex_or_intopt` solver parameter to `glp_intopt_only` at your own risk.

EXAMPLES:

```
sage: lp = MixedIntegerLinearProgram(solver = "GLPK")
sage: v = lp.new_variable(nonnegative=True)
sage: lp.add_constraint(v[1] + v[2] - 2.0 * v[3], max=-1.0)
sage: lp.add_constraint(v[0] - 4.0/3 * v[1] + 1.0/3 * v[2], max=-1.0/3)
sage: lp.add_constraint(v[0] + 0.5 * v[1] - 0.5 * v[2] + 0.25 * v[3], max=-0.25)
sage: lp.solve()
0.0
sage: lp.add_constraint(v[0] + 4.0 * v[1] - v[2] + v[3], max=-1.0)
sage: lp.solve()
Traceback (most recent call last):
...
MIPSolverException: GLPK: Problem has no feasible solution
```

```
>>> from sage.all import *
>>> lp = MixedIntegerLinearProgram(solver = "GLPK")
```

(continues on next page)

(continued from previous page)

```

>>> v = lp.new_variable(nonnegative=True)
>>> lp.add_constraint(v[Integer(1)] +v[Integer(2)] -RealNumber('2.0')
↳*v[Integer(3)], max=-RealNumber('1.0'))
>>> lp.add_constraint(v[Integer(0)] -RealNumber('4.0')/Integer(3)
↳*v[Integer(1)] +RealNumber('1.0')/Integer(3) *v[Integer(2)], max=-
↳RealNumber('1.0')/Integer(3))
>>> lp.add_constraint(v[Integer(0)] +RealNumber('0.5') *v[Integer(1)] -
↳RealNumber('0.5') *v[Integer(2)] +RealNumber('0.25') *v[Integer(3)], max=-
↳RealNumber('0.25'))
>>> lp.solve()
0.0
>>> lp.add_constraint(v[Integer(0)] +RealNumber('4.0') *v[Integer(1)] -
↳v[Integer(2)] +v[Integer(3)], max=-RealNumber('1.0'))
>>> lp.solve()
Traceback (most recent call last):
...
MIPSolverException: GLPK: Problem has no feasible solution

```

If we switch to “simplex_only”, the integrality constraints are ignored, and we get an optimal solution to the continuous relaxation.

EXAMPLES:

```

sage: lp = MixedIntegerLinearProgram(solver = 'GLPK', maximization = False)
sage: x, y = lp[0], lp[1]
sage: lp.add_constraint(-2*x + y <= 1)
sage: lp.add_constraint(x - y <= 1)
sage: lp.add_constraint(x + y >= 2)
sage: lp.set_objective(x + y)
sage: lp.set_integer(x)
sage: lp.set_integer(y)
sage: lp.solver_parameter("simplex_or_intopt", "simplex_only") # use simplex_
↳only
sage: lp.solve()
2.0
sage: lp.get_values([x, y])
[1.5, 0.5]

```

```

>>> from sage.all import *
>>> lp = MixedIntegerLinearProgram(solver = 'GLPK', maximization = False)
>>> x, y = lp[Integer(0)], lp[Integer(1)]
>>> lp.add_constraint(-Integer(2)*x + y <= Integer(1))
>>> lp.add_constraint(x - y <= Integer(1))
>>> lp.add_constraint(x + y >= Integer(2))
>>> lp.set_objective(x + y)
>>> lp.set_integer(x)
>>> lp.set_integer(y)
>>> lp.solver_parameter("simplex_or_intopt", "simplex_only") # use simplex_
↳only
>>> lp.solve()
2.0
>>> lp.get_values([x, y])
[1.5, 0.5]

```

If one solves a linear program and wishes to access dual information (*get_col_dual* etc.) or tableau data (*get_row_stat* etc.), one needs to switch to “simplex_only” before solving.

GLPK also has an exact rational simplex solver. The only access to data is via double-precision floats, which means that rationals in the input data may be rounded before the exact solver sees them. Thus, it is unreasonable to expect that arbitrary LPs with rational coefficients are solved exactly. Once the LP has been read into the backend, it reconstructs rationals from doubles and does solve exactly over the rationals, but results are returned as as doubles.

EXAMPLES:

```
sage: lp.solver_parameter("simplex_or_intopt", "exact_simplex_only") # use_
↳exact simplex only
sage: lp.solve()
2.0
sage: lp.get_values([x, y])
[1.5, 0.5]
```

```
>>> from sage.all import *
>>> lp.solver_parameter("simplex_or_intopt", "exact_simplex_only") # use_
↳exact simplex only
>>> lp.solve()
2.0
>>> lp.get_values([x, y])
[1.5, 0.5]
```

If you need the rational solution, you need to retrieve the basis information via *get_col_stat* and *get_row_stat* and calculate the corresponding basic solution. Below we only test that the basis information is indeed available. Calculating the corresponding basic solution is left as an exercise.

EXAMPLES:

```
sage: lp.get_backend().get_row_stat(0)
1
sage: lp.get_backend().get_col_stat(0)
1
```

```
>>> from sage.all import *
>>> lp.get_backend().get_row_stat(Integer(0))
1
>>> lp.get_backend().get_col_stat(Integer(0))
1
```

Below we test that integers that can be exactly represented by IEEE 754 double-precision floating point numbers survive the rational reconstruction done by *glp_exact* and the subsequent conversion to double-precision floating point numbers.

EXAMPLES:

```
sage: lp = MixedIntegerLinearProgram(solver = 'GLPK', maximization = True)
sage: test = 2^53 - 43
sage: lp.solver_parameter("simplex_or_intopt", "exact_simplex_only") # use_
↳exact simplex only
sage: x = lp[0]
sage: lp.add_constraint(x <= test)
```

(continues on next page)

(continued from previous page)

```

sage: lp.set_objective(x)
sage: lp.solve() == test # yes, we want an exact comparison here
True
sage: lp.get_values(x) == test # yes, we want an exact comparison here
True

```

```

>>> from sage.all import *
>>> lp = MixedIntegerLinearProgram(solver = 'GLPK', maximization = True)
>>> test = Integer(2)**Integer(53) - Integer(43)
>>> lp.solver_parameter("simplex_or_intopt", "exact_simplex_only") # use_
↳exact simplex only
>>> x = lp[Integer(0)]
>>> lp.add_constraint(x <= test)
>>> lp.set_objective(x)
>>> lp.solve() == test # yes, we want an exact comparison here
True
>>> lp.get_values(x) == test # yes, we want an exact comparison here
True

```

Below we test that GLPK backend can detect unboundedness in “simplex_only” mode (Issue #18838).

EXAMPLES:

```

sage: lp = MixedIntegerLinearProgram(maximization=True, solver = "GLPK")
sage: lp.set_objective(lp[0])
sage: lp.solver_parameter("simplex_or_intopt", "simplex_only")
sage: lp.solve()
Traceback (most recent call last):
...
MIPSolverException: GLPK: Problem has unbounded solution
sage: lp.set_objective(lp[1])
sage: lp.solver_parameter("primal_v_dual", "GLP_DUAL")
sage: lp.solve()
Traceback (most recent call last):
...
MIPSolverException: GLPK: Problem has unbounded solution
sage: lp.solver_parameter("simplex_or_intopt", "simplex_then_intopt")
sage: lp.solve()
Traceback (most recent call last):
...
MIPSolverException: GLPK: The LP (relaxation) problem has no dual feasible_
↳solution
sage: lp.solver_parameter("simplex_or_intopt", "intopt_only")
sage: lp.solve()
Traceback (most recent call last):
...
MIPSolverException: GLPK: The LP (relaxation) problem has no dual feasible_
↳solution
sage: lp.set_max(lp[1],5)
sage: lp.solve()
5.0

```

```

>>> from sage.all import *
>>> lp = MixedIntegerLinearProgram(maximization=True, solver = "GLPK")
>>> lp.set_objective(lp[Integer(0)])
>>> lp.solver_parameter("simplex_or_intopt", "simplex_only")
>>> lp.solve()
Traceback (most recent call last):
...
MIPSolverException: GLPK: Problem has unbounded solution
>>> lp.set_objective(lp[Integer(1)])
>>> lp.solver_parameter("primal_v_dual", "GLP_DUAL")
>>> lp.solve()
Traceback (most recent call last):
...
MIPSolverException: GLPK: Problem has unbounded solution
>>> lp.solver_parameter("simplex_or_intopt", "simplex_then_intopt")
>>> lp.solve()
Traceback (most recent call last):
...
MIPSolverException: GLPK: The LP (relaxation) problem has no dual feasible_
↪solution
>>> lp.solver_parameter("simplex_or_intopt", "intopt_only")
>>> lp.solve()
Traceback (most recent call last):
...
MIPSolverException: GLPK: The LP (relaxation) problem has no dual feasible_
↪solution
>>> lp.set_max(lp[Integer(1)], Integer(5))
>>> lp.solve()
5.0
    
```

Solving a LP within the acceptable gap. No exception is raised, even if the result is not optimal. To do this, we try to compute the maximum number of disjoint balls (of diameter 1) in a hypercube:

```

sage: # needs sage.graphs
sage: g = graphs.CubeGraph(9)
sage: p = MixedIntegerLinearProgram(solver='GLPK')
sage: p.solver_parameter("mip_gap_tolerance", 100)
sage: b = p.new_variable(binary=True)
sage: p.set_objective(p.sum(b[v] for v in g))
sage: for v in g:
...:     p.add_constraint(b[v]+p.sum(b[u] for u in g.neighbors(v)) <= 1)
sage: p.add_constraint(b[v] == 1) # Force an easy non-0 solution
sage: p.solve() # rel tol 100
1
    
```

```

>>> from sage.all import *
>>> # needs sage.graphs
>>> g = graphs.CubeGraph(Integer(9))
>>> p = MixedIntegerLinearProgram(solver='GLPK')
>>> p.solver_parameter("mip_gap_tolerance", Integer(100))
>>> b = p.new_variable(binary=True)
>>> p.set_objective(p.sum(b[v] for v in g))
>>> for v in g:
    
```

(continues on next page)

(continued from previous page)

```

...     p.add_constraint(b[v]+p.sum(b[u] for u in g.neighbors(v)) <=
↳Integer(1))
>>> p.add_constraint(b[v] == Integer(1)) # Force an easy non-0 solution
>>> p.solve() # rel tol 100
1

```

Same, now with a time limit:

```

sage: # needs sage.graphs
sage: p.solver_parameter("mip_gap_tolerance",1)
sage: p.solver_parameter("timelimit",3.0)
sage: p.solve() # rel tol 100
1

```

```

>>> from sage.all import *
>>> # needs sage.graphs
>>> p.solver_parameter("mip_gap_tolerance",Integer(1))
>>> p.solver_parameter("timelimit",RealNumber('3.0'))
>>> p.solve() # rel tol 100
1

```

solver_parameter (*name*, *value=None*)

Return or define a solver parameter.

INPUT:

- *name* – string; the parameter
- *value* – the parameter's value if it is to be defined, or `None` (default) to obtain its current value

You can supply the name of a parameter and its value using either a string or a `glp_` constant (which are defined as Cython variables of this module).

In most cases, you can use the same name for a parameter as that given in the GLPK documentation, which is available by downloading GLPK from <http://www.gnu.org/software/glpk/>. The exceptions relate to parameters common to both methods; these require you to append `_simplex` or `_intopt` to the name to resolve ambiguity, since the interface allows access to both.

We have also provided more meaningful names, to assist readability.

Parameter **names** are specified in lower case. To use a constant instead of a string, prepend `glp_` to the name. For example, both `glp_gmi_cuts` or `'gmi_cuts'` control whether to solve using Gomory cuts.

Parameter **values** are specified as strings in upper case, or as constants in lower case. For example, both `glp_on` and `"GLP_ON"` specify the same thing.

Naturally, you can use `True` and `False` in cases where `glp_on` and `glp_off` would be used.

A list of parameter names, with their possible values:

General-purpose parameters:

| | | |
|---------------------------------------|-----|---|
| <code>timelimit</code> | | specify the time limit IN SECONDS. This affects both simplex and intopt. |
| <code>timelimit_simplex</code> | and | specify the time limit IN MILLISECONDS. (This is glpk's default.) |
| <code>timelimit_intopt</code> | | |
| <code>simplex_or_intopt</code> | | specify which solution routines in GLPK to use. Set this to either <code>simplex_only</code> , <code>exact_simplex_only</code> , <code>intopt_only</code> , or <code>simplex_then_intopt</code> (the default). The <code>simplex_then_intopt</code> option does some extra work, but avoids hangs/crashes in GLPK on problems with no solution; SageMath will try simplex first, then perform integer optimization only if a solution of the LP relaxation exists. If you know that your system is not pathological, one of the other options will be faster. |
| <code>verbosity_intopt</code> | and | one of <code>GLP_MSG_OFF</code> , <code>GLP_MSG_ERR</code> , <code>GLP_MSG_ON</code> , or <code>GLP_MSG_ALL</code> . |
| <code>verbosity_simplex</code> | | The default is <code>GLP_MSG_OFF</code> . |
| <code>output_frequency_intopt</code> | and | the output frequency, in milliseconds. Default is 5000. |
| <code>output_frequency_simplex</code> | | |
| <code>output_delay_intopt</code> | and | the output delay, in milliseconds, regarding the use of the simplex method on the LP relaxation. Default is 10000. |
| <code>output_delay_simplex</code> | | |

intopt-specific parameters:

| | |
|-------------------------|--|
| branching | <ul style="list-style-type: none"> • GLP_BR_FFV first fractional variable • GLP_BR_LFV last fractional variable • GLP_BR_MFV most fractional variable • GLP_BR_DTH Driebeck-Tomlin heuristic (default) • GLP_BR_PCH hybrid pseudocost heuristic |
| backtracking | <ul style="list-style-type: none"> • GLP_BT_DFS depth first search • GLP_BT_BFS breadth first search • GLP_BT_BLB best local bound (default) • GLP_BT_BPH best projection heuristic |
| preprocessing | <ul style="list-style-type: none"> • GLP_PP_NONE • GLP_PP_ROOT preprocessing only at root level • GLP_PP_ALL (default) |
| feasibility_pump | GLP_ON or GLP_OFF (default) |
| gomory_cuts | GLP_ON or GLP_OFF (default) |
| mixed_int_rounding_cuts | GLP_ON or GLP_OFF (default) |
| mixed_cover_cuts | GLP_ON or GLP_OFF (default) |
| clique_cuts | GLP_ON or GLP_OFF (default) |
| absolute_tolerance | (double) used to check if optimal solution to LP relaxation is integer feasible. GLPK manual advises, “do not change... without detailed understanding of its purpose.” |
| relative_tolerance | (double) used to check if objective value in LP relaxation is not better than best known integer solution. GLPK manual advises, “do not change... without detailed understanding of its purpose.” |
| mip_gap_tolerance | (double) relative mip gap tolerance. Default is 0.0. |
| presolve_intopt | GLP_ON (default) or GLP_OFF |
| binarize | GLP_ON or GLP_OFF (default) |

simplex-specific parameters:

| | |
|------------------|---|
| primal_v_dual | <ul style="list-style-type: none"> • GLP_PRIMAL (default) • GLP_DUAL • GLP_DUALP |
| pricing | <ul style="list-style-type: none"> • GLP_PT_STD standard (textbook) • GLP_PT_PSE projected steepest edge (default) |
| ratio_test | <ul style="list-style-type: none"> • GLP_RT_STD standard (textbook) • GLP_RT_HAR Harris' two-pass ratio test (default) |
| tolerance_primal | (double) tolerance used to check if basic solution is primal feasible. GLPK manual advises, "do not change... without detailed understanding of its purpose." |
| tolerance_dual | (double) tolerance used to check if basic solution is dual feasible. GLPK manual advises, "do not change... without detailed understanding of its purpose." |
| tolerance_pivot | (double) tolerance used to choose pivot. GLPK manual advises, "do not change... without detailed understanding of its purpose." |
| obj_lower_limit | (double) lower limit of the objective function. The default is <code>-DBL_MAX</code> . |
| obj_upper_limit | (double) upper limit of the objective function. The default is <code>DBL_MAX</code> . |
| iteration_limit | (int) iteration limit of the simplex algorithm. The default is <code>INT_MAX</code> . |
| presolve_simplex | <code>GLP_ON</code> or <code>GLP_OFF</code> (default). |

Note

The coverage for GLPK's control parameters for simplex and integer optimization is nearly complete. The only thing lacking is a wrapper for callback routines.

To date, no attempt has been made to expose the interior point methods.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.solver_parameter("timelimit", 60)
sage: p.solver_parameter("timelimit")
60.0
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.solver_parameter("timelimit", Integer(60))
>>> p.solver_parameter("timelimit")
60.0
```

- Don't forget the difference between `timelimit` and `timelimit_intopt`

```
sage: p.solver_parameter("timelimit_intopt")
60000
```

```
>>> from sage.all import *
>>> p.solver_parameter("timelimit_intopt")
60000
```

If you don't care for an integer answer, you can ask for an LP relaxation instead. The default solver performs integer optimization, but you can switch to the standard simplex algorithm through the `glp_simplex_or_intopt` parameter.

EXAMPLES:

```
sage: lp = MixedIntegerLinearProgram(solver = 'GLPK', maximization = False)
sage: x, y = lp[0], lp[1]
sage: lp.add_constraint(-2*x + y <= 1)
sage: lp.add_constraint(x - y <= 1)
sage: lp.add_constraint(x + y >= 2)
sage: lp.set_integer(x); lp.set_integer(y)
sage: lp.set_objective(x + y)
sage: lp.solve()
2.0
sage: lp.get_values([x,y])
[1.0, 1.0]
sage: import sage.numerical.backends.glpk_backend as backend
sage: lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
sage: lp.solve()
2.0
sage: lp.get_values([x,y])
[1.5, 0.5]
```

```
>>> from sage.all import *
>>> lp = MixedIntegerLinearProgram(solver = 'GLPK', maximization = False)
>>> x, y = lp[Integer(0)], lp[Integer(1)]
>>> lp.add_constraint(-Integer(2)*x + y <= Integer(1))
>>> lp.add_constraint(x - y <= Integer(1))
>>> lp.add_constraint(x + y >= Integer(2))
>>> lp.set_integer(x); lp.set_integer(y)
>>> lp.set_objective(x + y)
>>> lp.solve()
2.0
>>> lp.get_values([x,y])
[1.0, 1.0]
>>> import sage.numerical.backends.glpk_backend as backend
>>> lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
>>> lp.solve()
2.0
>>> lp.get_values([x,y])
[1.5, 0.5]
```

You can get GLPK to spout all sorts of information at you. The default is to turn this off, but sometimes (debugging) it's very useful:

```

sage: lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳then_intopt)
sage: lp.solver_parameter(backend.glp_mir_cuts, backend.glp_on)
sage: lp.solver_parameter(backend.glp_msg_lev_intopt, backend.glp_msg_all)
sage: lp.solver_parameter(backend.glp_mir_cuts)
1
    
```

```

>>> from sage.all import *
>>> lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳then_intopt)
>>> lp.solver_parameter(backend.glp_mir_cuts, backend.glp_on)
>>> lp.solver_parameter(backend.glp_msg_lev_intopt, backend.glp_msg_all)
>>> lp.solver_parameter(backend.glp_mir_cuts)
1
    
```

If you actually try to solve `lp`, you will get a lot of detailed information.

variable_lower_bound (*index*, *value=False*)

Return or define the lower bound on a variable.

INPUT:

- *index* – integer; the variable’s id
- *value* – real value, or `None` to mean that the variable has not lower bound. When set to `False` (default), the method returns the current value.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variable()
0
sage: p.col_bounds(0)
(0.0, None)
sage: p.variable_lower_bound(0, 5)
sage: p.col_bounds(0)
(5.0, None)
    
```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variable()
0
>>> p.col_bounds(Integer(0))
(0.0, None)
>>> p.variable_lower_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(5.0, None)
    
```

variable_upper_bound (*index*, *value=False*)

Return or define the upper bound on a variable.

INPUT:

- *index* – integer; the variable’s id

- `value` – real value, or `None` to mean that the variable has not upper bound. When set to `False` (default), the method returns the current value.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variable()
0
sage: p.col_bounds(0)
(0.0, None)
sage: p.variable_upper_bound(0, 5)
sage: p.col_bounds(0)
(0.0, 5.0)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variable()
0
>>> p.col_bounds(Integer(0))
(0.0, None)
>>> p.variable_upper_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(0.0, 5.0)
```

`warm_up()`

Warm up the basis using current statuses assigned to rows and cols.

OUTPUT: the warming up status

- 0 The operation has been successfully performed.
- GLP_EBADB The basis matrix is invalid.
- GLP_ESING The basis matrix is singular within the working precision.
- GLP_ECOND The basis matrix is ill-conditioned.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: lp = get_solver(solver = "GLPK")
sage: lp.add_variables(3)
2
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [8, 6, 1])), None, 48)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [4, 2, 1.5])), None, 20)
sage: lp.add_linear_constraint(list(zip([0, 1, 2], [2, 1.5, 0.5])), None, 8)
sage: lp.set_objective([60, 30, 20])
sage: import sage.numerical.backends.glpk_backend as backend
sage: lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
sage: lp.solve()
0
sage: lp.get_objective_value()
280.0
sage: lp.set_row_stat(0, 3)
```

(continues on next page)

(continued from previous page)

```
sage: lp.set_col_stat(1,1)
sage: lp.warm_up()
0
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> lp = get_solver(solver = "GLPK")
>>> lp.add_variables(Integer(3))
2
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(8), Integer(6), Integer(1)])), None, Integer(48))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(4), Integer(2), RealNumber('1.5')])), None, Integer(20))
>>> lp.add_linear_constraint(list(zip([Integer(0), Integer(1), Integer(2)],
↳[Integer(2), RealNumber('1.5'), RealNumber('0.5')])), None, Integer(8))
>>> lp.set_objective([Integer(60), Integer(30), Integer(20)])
>>> import sage.numerical.backends.glpk_backend as backend
>>> lp.solver_parameter(backend.glp_simplex_or_intopt, backend.glp_simplex_
↳only)
>>> lp.solve()
0
>>> lp.get_objective_value()
280.0
>>> lp.set_row_stat(Integer(0), Integer(3))
>>> lp.set_col_stat(Integer(1), Integer(1))
>>> lp.warm_up()
0
```

write_lp (*filename*)

Write the problem to a .lp file.

INPUT:

- filename – string

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([[0, 1], [1, 2]], None, 3)
sage: p.set_objective([2, 5])
sage: import tempfile
sage: with tempfile.NamedTemporaryFile(suffix='.lp') as f:
.....:     _ = p.write_lp(f.name)
.....:     len(f.readlines())
...
9 lines were written
9
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
```

(continues on next page)

(continued from previous page)

```

>>> p = get_solver(solver = "GLPK")
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([[Integer(0), Integer(1)], [Integer(1), ↵
↵Integer(2)]], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> import tempfile
>>> with tempfile.NamedTemporaryFile(suffix='.lp') as f:
...     _ = p.write_lp(f.name)
...     len(f.readlines())
...
9 lines were written
9

```

write_mps (*filename, modern*)

Write the problem to a .mps file.

INPUT:

- filename – string

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK")
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([[0, 1], [1, 2]], None, 3)
sage: p.set_objective([2, 5])
sage: import tempfile
sage: with tempfile.NamedTemporaryFile(suffix='.mps') as f:
....:     _ = p.write_mps(f.name, 2)
....:     len(f.readlines())
...
17 records were written
17

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK")
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([[Integer(0), Integer(1)], [Integer(1), ↵
↵Integer(2)]], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> import tempfile
>>> with tempfile.NamedTemporaryFile(suffix='.mps') as f:
...     _ = p.write_mps(f.name, Integer(2))
...     len(f.readlines())
...
17 records were written
17

```

11.4 GLPK/exact Backend (simplex method in exact rational arithmetic)

AUTHORS:

- Matthias Koeppel (2016-03)

class sage.numerical.backends.glpk_exact_backend.GLPKExactBackend

Bases: *GLPKBackend*

MIP Backend that runs the GLPK solver in exact rational simplex mode.

The only access to data is via double-precision floats, which means that rationals in the input data may be rounded before the exact solver sees them. Thus, it is unreasonable to expect that arbitrary LPs with rational coefficients are solved exactly. Once the LP has been read into the backend, it reconstructs rationals from doubles and does solve exactly over the rationals, but results are returned as as doubles.

There is no support for integer variables.

add_variable (*lower_bound=0.0, upper_bound=None, binary=False, continuous=False, integer=False, obj=0.0, name=None*)

Add a variable.

This amounts to adding a new column to the matrix. By default, the variable is both nonnegative and real.

In this backend, variables are always continuous (real). If integer variables are requested via the parameters `binary` and `integer`, an error will be raised.

INPUT:

- `lower_bound` – the lower bound of the variable (default: 0)
- `upper_bound` – the upper bound of the variable (default: None)
- `binary` – True if the variable is binary (default: False)
- `continuous` – True if the variable is continuous (default: True)
- `integer` – True if the variable is integer (default: False)
- `obj` – (optional) coefficient of this variable in the objective function (default: 0.0)
- `name` – an optional name for the newly added variable (default: None)

OUTPUT: the index of the newly created variable

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK/exact")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.ncols()
1
sage: p.add_variable()
1
sage: p.add_variable(lower_bound=-2.0)
2
sage: p.add_variable(continuous=True)
```

(continues on next page)

(continued from previous page)

```

3
sage: p.add_variable(name='x',obj=1.0)
4
sage: p.objective_coefficient(4)
1.0

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK/exact")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.ncols()
1
>>> p.add_variable()
1
>>> p.add_variable(lower_bound=-RealNumber('2.0'))
2
>>> p.add_variable(continuous=True)
3
>>> p.add_variable(name='x',obj=RealNumber('1.0'))
4
>>> p.objective_coefficient(Integer(4))
1.0

```

add_variables (*number*, *lower_bound*=0.0, *upper_bound*=None, *binary*=False, *continuous*=False, *integer*=False, *obj*=0.0, *names*=None)

Add number variables.

This amounts to adding new columns to the matrix. By default, the variables are both nonnegative and real.

In this backend, variables are always continuous (real). If integer variables are requested via the parameters `binary` and `integer`, an error will be raised.

INPUT:

- `n` – the number of new variables (must be > 0)
- `lower_bound` – the lower bound of the variable (default: 0)
- `upper_bound` – the upper bound of the variable (default: None)
- `binary` – True if the variable is binary (default: False)
- `continuous` – True if the variable is binary (default: True)
- `integer` – True if the variable is binary (default: False)
- `obj` – coefficient of all variables in the objective function (default: 0.0)
- `names` – list of names (default: None)

OUTPUT: the index of the variable created last

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK/exact")
sage: p.ncols()
0
sage: p.add_variables(5)
4
sage: p.ncols()
5
sage: p.add_variables(2, lower_bound=-2.0, obj=42.0, names=['a', 'b'])
6

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "GLPK/exact")
>>> p.ncols()
0
>>> p.add_variables(Integer(5))
4
>>> p.ncols()
5
>>> p.add_variables(Integer(2), lower_bound=-RealNumber('2.0'),
↳obj=RealNumber('42.0'), names=['a', 'b'])
6

```

set_variable_type(*variable*, *vtype*)

Set the type of a variable.

In this backend, variables are always continuous (real). If integer or binary variables are requested via the parameter *vtype*, an error will be raised.

INPUT:

- *variable* – integer; the variable's id
- *vtype* – integer:
 - 1 Integer
 - 0 Binary
 - -1 Real

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "GLPK/exact")
sage: p.add_variables(5)
4
sage: p.set_variable_type(3, -1)
sage: p.set_variable_type(3, -2)
Traceback (most recent call last):
...
ValueError: ...

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver

```

(continues on next page)

(continued from previous page)

```

>>> p = get_solver(solver = "GLPK/exact")
>>> p.add_variables(Integer(5))
4
>>> p.set_variable_type(Integer(3), -Integer(1))
>>> p.set_variable_type(Integer(3), -Integer(2))
Traceback (most recent call last):
...
ValueError: ...

```

11.5 GLPK Backend for access to GLPK graph functions

AUTHORS:

- Christian Kuper (2012-11): Initial implementation

11.5.1 Methods index

Graph creation and modification operations:

| | |
|------------------------------------|--|
| <code>add_vertex()</code> | Add an isolated vertex to the graph. |
| <code>add_vertices()</code> | Add vertices from an iterable container of vertices. |
| <code>set_vertex_demand()</code> | Set the vertex parameters. |
| <code>set_vertices_demand()</code> | Set the parameters of selected vertices. |
| <code>get_vertex()</code> | Return a specific vertex as a dictionary Object. |
| <code>get_vertices()</code> | Return a dictionary of the dictionaries associated to each vertex. |
| <code>vertices()</code> | Return a list of all vertices. |
| <code>delete_vertex()</code> | Remove a vertex from the graph. |
| <code>delete_vertices()</code> | Remove vertices from the graph. |
| <code>add_edge()</code> | Add an edge between vertices <code>u</code> and <code>v</code> . |
| <code>add_edges()</code> | Add edges to the graph. |
| <code>get_edge()</code> | Return an edge connecting two vertices. |
| <code>edges()</code> | Return a list of all edges in the graph. |
| <code>delete_edge()</code> | Delete an edge from the graph. |
| <code>delete_edges()</code> | Delete edges from the graph. |

Graph writing operations:

| | |
|------------------------------|--|
| <code>write_graph()</code> | Write the graph to a plain text file. |
| <code>write_ccdata()</code> | Write the graph to a text file in DIMACS format. |
| <code>write_mincost()</code> | Write the mincost flow problem data to a text file in DIMACS format. |
| <code>write_maxflow()</code> | Write the maximum flow problem data to a text file in DIMACS format. |

Network optimization operations:

| | |
|------------------------------|--|
| <code>mincost_okalg()</code> | Find solution to the mincost problem with the out-of-kilter algorithm. |
| <code>maxflow_ffalg()</code> | Find solution to the maxflow problem with Ford-Fulkerson algorithm. |
| <code>cpp()</code> | Solve the critical path problem of a project network. |

11.5.2 Classes and methods

class `sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend`

Bases: `object`

GLPK Backend for access to GLPK graph functions.

The constructor can either be called without arguments (which results in an empty graph) or with arguments to read graph data from a file.

INPUT:

- `data` – a filename or a `Graph` object
- `format` – when `data` is a filename, specifies the format of the data read from a file. The `format` parameter is a string and can take values as described in the table below.

Format parameters:

| | |
|----------------------|---|
| <code>plain</code> | Read data from a plain text file containing the following information: <code>nv na</code> <code>i[1] j[1]</code> <code>i[2] j[2]</code> <code>...</code> <code>i[na] j[na]</code> where: <ul style="list-style-type: none"> • <code>nv</code> is the number of vertices (nodes); • <code>na</code> is the number of arcs; • <code>i[k]</code>, $k = 1, \dots, na$, is the index of tail vertex of arc k; • <code>j[k]</code>, $k = 1, \dots, na$, is the index of head vertex of arc k. |
| <code>dimacs</code> | Read data from a plain ASCII text file in DIMACS format. A description of the DIMACS format can be found at http://dimacs.rutgers.edu/Challenges/ . |
| <code>mincost</code> | Reads the mincost flow problem data from a text file in DIMACS format |
| <code>maxflow</code> | Reads the maximum flow problem data from a text file in DIMACS format |

Note

When `data` is a `Graph`, the following restrictions are applied.

- `vertices` – the value of the demand of each vertex (see `set_vertex_demand()`) is obtained from the numerical value associated with the key “`rhs`” if it is a dictionary.
- `edges` – The edge values used in the algorithms are read from the edges labels (and left undefined if the edge labels are equal to `None`). To be defined, the labels must be dictionary objects with keys “`low`”, “`cap`” and “`cost`”. See `get_edge()` for details.

EXAMPLES:

The following example creates an empty graph:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
```

The following example creates an empty graph, adds some data, saves the data to a file and loads it:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: gbe.add_vertices([None, None])
['0', '1']
sage: a = gbe.add_edge('0', '1')
sage: import tempfile
sage: with tempfile.NamedTemporaryFile() as f:
.....:     _ = gbe.write_graph(f.name)
.....:     gbe1 = GLPKGraphBackend(f.name, "plain")
Writing graph to ...
4 lines were written
Reading graph from ...
Graph has 2 vertices and 1 edge
3 lines were read
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> gbe.add_vertices([None, None])
['0', '1']
>>> a = gbe.add_edge('0', '1')
>>> import tempfile
>>> with tempfile.NamedTemporaryFile() as f:
...     _ = gbe.write_graph(f.name)
...     gbe1 = GLPKGraphBackend(f.name, "plain")
Writing graph to ...
4 lines were written
Reading graph from ...
Graph has 2 vertices and 1 edge
3 lines were read
```

The following example imports a Sage Graph and then uses it to solve a maxflow problem:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: g = graphs.PappusGraph()
sage: for ed in g.edges(sort=False):
.....:     g.set_edge_label(ed[0], ed[1], {"cap":1})
sage: gbe = GLPKGraphBackend(g)
sage: gbe.maxflow_ffalg('1', '2')
3.0
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> g = graphs.PappusGraph()
>>> for ed in g.edges(sort=False):
...     g.set_edge_label(ed[Integer(0)], ed[Integer(1)], {"cap":Integer(1)})
>>> gbe = GLPKGraphBackend(g)
```

(continues on next page)

(continued from previous page)

```
>>> gbe.maxflow_ffalg('1', '2')
3.0
```

add_edge (*u*, *v*, *params=None*)

Add an edge between vertices *u* and *v*.

Allows adding an edge and optionally providing parameters used by the algorithms. If a vertex does not exist it is created.

INPUT:

- *u* – the name (as string) of the tail vertex
- *v* – the name (as string) of the head vertex
- *params* – an optional dictionary containing the edge parameters used for the algorithms. The following keys are used:
 - *low* – the minimum flow through the edge
 - *cap* – the maximum capacity of the edge
 - *cost* – the cost of transporting one unit through the edge

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: gbe.add_edge("A", "B", {"low":0.0, "cap":10.0, "cost":5})
sage: gbe.vertices()
['A', 'B']
sage: for ed in gbe.edges():
....:     print((ed[0], ed[1], ed[2]['cap'], ed[2]['cost'], ed[2]['low']))
('A', 'B', 10.0, 5.0, 0.0)
sage: gbe.add_edge("B", "C", {"low":0.0, "cap":10.0, "cost":'5'})
Traceback (most recent call last):
...
TypeError: Invalid edge parameter.
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> gbe.add_edge("A", "B", {"low":RealNumber('0.0'), "cap":RealNumber('10.0'),
↪ "cost":Integer(5)})
>>> gbe.vertices()
['A', 'B']
>>> for ed in gbe.edges():
...     print((ed[Integer(0)], ed[Integer(1)], ed[Integer(2)]['cap'], ↪
↪ed[Integer(2)]['cost'], ed[Integer(2)]['low']))
('A', 'B', 10.0, 5.0, 0.0)
>>> gbe.add_edge("B", "C", {"low":RealNumber('0.0'), "cap":RealNumber('10.0'),
↪ "cost":'5'})
Traceback (most recent call last):
...
TypeError: Invalid edge parameter.
```

add_edges (*edges*)

Add edges to the graph.

INPUT:

- *edges* – an iterable container of pairs of the form (*u*, *v*), where *u* is name (as string) of the tail vertex and *v* is the name (as string) of the head vertex or an iterable container of triples of the form (*u*, *v*, *params*) where *params* is a dictionary as described in `add_edge`.

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: edges = [("A", "B", {"low":0.0, "cap":10.0, "cost":5})]
sage: edges.append(("B", "C"))
sage: gbe.add_edges(edges)
sage: for ed in gbe.edges():
....:     print((ed[0], ed[1], ed[2]['cap'], ed[2]['cost'], ed[2]['low']))
('A', 'B', 10.0, 5.0, 0.0)
('B', 'C', 0.0, 0.0, 0.0)
sage: edges = [("C", "D", {"low":0.0, "cap":10.0, "cost":5})]
sage: edges.append(("C", "E", 5))
sage: gbe.add_edges(edges)
Traceback (most recent call last):
...
TypeError: Argument 'params' has incorrect type ...
sage: for ed in gbe.edges():
....:     print((ed[0], ed[1], ed[2]['cap'], ed[2]['cost'], ed[2]['low']))
('A', 'B', 10.0, 5.0, 0.0)
('B', 'C', 0.0, 0.0, 0.0)
('C', 'D', 10.0, 5.0, 0.0)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> edges = [("A", "B", {"low":RealNumber('0.0'), "cap":RealNumber('10.0'),
↳"cost":Integer(5)})]
>>> edges.append(("B", "C"))
>>> gbe.add_edges(edges)
>>> for ed in gbe.edges():
...     print((ed[Integer(0)], ed[Integer(1)], ed[Integer(2)]['cap'],
↳ed[Integer(2)]['cost'], ed[Integer(2)]['low']))
('A', 'B', 10.0, 5.0, 0.0)
('B', 'C', 0.0, 0.0, 0.0)
>>> edges = [("C", "D", {"low":RealNumber('0.0'), "cap":RealNumber('10.0'),
↳"cost":Integer(5)})]
>>> edges.append(("C", "E", Integer(5)))
>>> gbe.add_edges(edges)
Traceback (most recent call last):
...
TypeError: Argument 'params' has incorrect type ...
>>> for ed in gbe.edges():
...     print((ed[Integer(0)], ed[Integer(1)], ed[Integer(2)]['cap'],
↳ed[Integer(2)]['cost'], ed[Integer(2)]['low']))
```

(continues on next page)

(continued from previous page)

```

('A', 'B', 10.0, 5.0, 0.0)
('B', 'C', 0.0, 0.0, 0.0)
('C', 'D', 10.0, 5.0, 0.0)

```

add_vertex (*name=None*)

Add an isolated vertex to the graph.

If the vertex already exists, nothing is done.

INPUT:

- *name* – string of max 255 chars length. If no name is specified, then the vertex will be represented by the string representation of the ID of the vertex or - if this already exists - a string representation of the least integer not already representing a vertex.

OUTPUT:

If no *name* is passed as an argument, the new vertex name is returned. *None* otherwise.

EXAMPLES:

```

sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: gbe.add_vertex()
'0'
sage: gbe.add_vertex("2")
sage: gbe.add_vertex()
'1'

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> gbe.add_vertex()
'0'
>>> gbe.add_vertex("2")
>>> gbe.add_vertex()
'1'

```

add_vertices (*vertices*)

Add vertices from an iterable container of vertices.

Vertices that already exist in the graph will not be added again.

INPUT:

- *vertices* – iterator of vertex labels (string); a label can be *None*

OUTPUT:

Generated names of new vertices if there is at least one *None* value present in *vertices*. *None* otherwise.

EXAMPLES:

```

sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: vertices = [None for i in range(3)]
sage: gbe.add_vertices(vertices)
['0', '1', '2']

```

(continues on next page)

(continued from previous page)

```
sage: gbe.add_vertices(['A', 'B', None])
['5']
sage: gbe.add_vertices(['A', 'B', 'C'])
sage: gbe.vertices()
['0', '1', '2', 'A', 'B', '5', 'C']
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> vertices = [None for i in range(Integer(3))]
>>> gbe.add_vertices(vertices)
['0', '1', '2']
>>> gbe.add_vertices(['A', 'B', None])
['5']
>>> gbe.add_vertices(['A', 'B', 'C'])
>>> gbe.vertices()
['0', '1', '2', 'A', 'B', '5', 'C']
```

cpp()

Solve the critical path problem of a project network.

OUTPUT: the length of the critical path of the network

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: gbe.add_vertices([None for i in range(3)])
['0', '1', '2']
sage: gbe.set_vertex_demand('0', 3)
sage: gbe.set_vertex_demand('1', 1)
sage: gbe.set_vertex_demand('2', 4)
sage: a = gbe.add_edge('0', '2')
sage: a = gbe.add_edge('1', '2')
sage: gbe.cpp()
7.0
sage: v = gbe.get_vertex('1')
sage: 1, v["rhs"], v["es"], v["ls"] # abs tol 1e-6
(1, 1.0, 0.0, 2.0)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> gbe.add_vertices([None for i in range(Integer(3))])
['0', '1', '2']
>>> gbe.set_vertex_demand('0', Integer(3))
>>> gbe.set_vertex_demand('1', Integer(1))
>>> gbe.set_vertex_demand('2', Integer(4))
>>> a = gbe.add_edge('0', '2')
>>> a = gbe.add_edge('1', '2')
>>> gbe.cpp()
7.0
```

(continues on next page)

(continued from previous page)

```
>>> v = gbe.get_vertex('1')
>>> Integer(1), v["rhs"], v["es"], v["ls"] # abs tol 1e-6
(1, 1.0, 0.0, 2.0)
```

delete_edge (*u*, *v*, *params=None*)

Delete an edge from the graph.

If an edge does not exist it is ignored.

INPUT:

- *u* – the name (as string) of the tail vertex of the edge
- *v* – the name (as string) of the tail vertex of the edge
- *params* – an optional dictionary containing the edge parameters (see *add_edge()*). If this parameter is not provided, all edges connecting *u* and *v* are deleted. Otherwise only edges with matching parameters are deleted.

➔ See also

delete_edges()

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: edges = [("A", "B", {"low":0.0, "cap":10.0, "cost":5})]
sage: edges.append(("A", "B", {"low":0.0, "cap":15.0, "cost":10}))
sage: edges.append(("B", "C", {"low":0.0, "cap":20.0, "cost":1}))
sage: edges.append(("B", "C", {"low":0.0, "cap":10.0, "cost":20}))
sage: gbe.add_edges(edges)
sage: gbe.delete_edge("A", "B")
sage: gbe.delete_edge("B", "C", {"low":0.0, "cap":10.0, "cost":20})
sage: gbe.edges()[0][0], gbe.edges()[0][1], gbe.edges()[0][2]['cost']
('B', 'C', 1.0)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> edges = [("A", "B", {"low":RealNumber('0.0'), "cap":RealNumber('10.0'),
↳ "cost":Integer(5)})]
>>> edges.append(("A", "B", {"low":RealNumber('0.0'), "cap":RealNumber('15.0
↳ '), "cost":Integer(10)}))
>>> edges.append(("B", "C", {"low":RealNumber('0.0'), "cap":RealNumber('20.0
↳ '), "cost":Integer(1)}))
>>> edges.append(("B", "C", {"low":RealNumber('0.0'), "cap":RealNumber('10.0
↳ '), "cost":Integer(20)}))
>>> gbe.add_edges(edges)
>>> gbe.delete_edge("A", "B")
>>> gbe.delete_edge("B", "C", {"low":RealNumber('0.0'), "cap":RealNumber('10.0
↳ '), "cost":Integer(20)})
>>> gbe.edges()[Integer(0)][Integer(0)], gbe.edges()[Integer(0)][Integer(1)],
```

(continues on next page)

(continued from previous page)

```
↪gbe.edges()[Integer(0)][Integer(2)]['cost']
('B', 'C', 1.0)
```

delete_edges (*edges*)

Delete edges from the graph.

Non existing edges are ignored.

INPUT:

- *edges* – an iterable container of edges

See also[*delete_edge\(\)*](#)

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: edges = [("A", "B", {"low":0.0, "cap":10.0, "cost":5})]
sage: edges.append(("A", "B", {"low":0.0, "cap":15.0, "cost":10}))
sage: edges.append(("B", "C", {"low":0.0, "cap":20.0, "cost":1}))
sage: edges.append(("B", "C", {"low":0.0, "cap":10.0, "cost":20}))
sage: gbe.add_edges(edges)
sage: gbe.delete_edges(edges[1:])
sage: len(gbe.edges())
1
sage: gbe.edges()[0][0], gbe.edges()[0][1], gbe.edges()[0][2]['cap']
('A', 'B', 10.0)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> edges = [("A", "B", {"low":RealNumber('0.0'), "cap":RealNumber('10.0'),
↪"cost":Integer(5)})]
>>> edges.append(("A", "B", {"low":RealNumber('0.0'), "cap":RealNumber('15.0
↪'), "cost":Integer(10)}))
>>> edges.append(("B", "C", {"low":RealNumber('0.0'), "cap":RealNumber('20.0
↪'), "cost":Integer(1)}))
>>> edges.append(("B", "C", {"low":RealNumber('0.0'), "cap":RealNumber('10.0
↪'), "cost":Integer(20)}))
>>> gbe.add_edges(edges)
>>> gbe.delete_edges(edges[Integer(1):])
>>> len(gbe.edges())
1
>>> gbe.edges()[Integer(0)][Integer(0)], gbe.edges()[Integer(0)][Integer(1)], ↪
↪gbe.edges()[Integer(0)][Integer(2)]['cap']
('A', 'B', 10.0)
```

delete_vertex (*vert*)

Removes a vertex from the graph.

Trying to delete a non existing vertex will raise an exception.

INPUT:

- `vert` – the name (as string) of the vertex to delete

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: verts = ["A", "D"]
sage: gbe.add_vertices(verts)
sage: gbe.delete_vertex("A")
sage: gbe.vertices()
['D']
sage: gbe.delete_vertex("A")
Traceback (most recent call last):
...
RuntimeError: Vertex A does not exist.
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> verts = ["A", "D"]
>>> gbe.add_vertices(verts)
>>> gbe.delete_vertex("A")
>>> gbe.vertices()
['D']
>>> gbe.delete_vertex("A")
Traceback (most recent call last):
...
RuntimeError: Vertex A does not exist.
```

`delete_vertices` (*verts*)

Removes vertices from the graph.

Trying to delete a non existing vertex will raise an exception.

INPUT:

- `verts` – iterable container containing names (as string) of the vertices to delete

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: verts = ["A", "B", "C", "D"]
sage: gbe.add_vertices(verts)
sage: v_d = ["A", "B"]
sage: gbe.delete_vertices(v_d)
sage: gbe.vertices()
['C', 'D']
sage: gbe.delete_vertices(["C", "A"])
Traceback (most recent call last):
...
RuntimeError: Vertex A does not exist.
```

(continues on next page)

(continued from previous page)

```
sage: gbe.vertices()
['C', 'D']
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> verts = ["A", "B", "C", "D"]
>>> gbe.add_vertices(verts)
>>> v_d = ["A", "B"]
>>> gbe.delete_vertices(v_d)
>>> gbe.vertices()
['C', 'D']
>>> gbe.delete_vertices(["C", "A"])
Traceback (most recent call last):
...
RuntimeError: Vertex A does not exist.
>>> gbe.vertices()
['C', 'D']
```

edges()

Return a list of all edges in the graph.

OUTPUT: a list of triples representing the edges of the graph

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: edges = [("A", "B", {"low":0.0, "cap":10.0, "cost":5})]
sage: edges.append(("B", "C"))
sage: gbe.add_edges(edges)
sage: for ed in gbe.edges():
....:     print((ed[0], ed[1], ed[2]['cost']))
('A', 'B', 5.0)
('B', 'C', 0.0)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> edges = [("A", "B", {"low":RealNumber('0.0'), "cap":RealNumber('10.0'),
↳"cost":Integer(5)})]
>>> edges.append(("B", "C"))
>>> gbe.add_edges(edges)
>>> for ed in gbe.edges():
...     print((ed[Integer(0)], ed[Integer(1)], ed[Integer(2)]['cost']))
('A', 'B', 5.0)
('B', 'C', 0.0)
```

get_edge(u, v)

Return an edge connecting two vertices.

Note

If multiple edges connect the two vertices only the first edge found is returned.

INPUT:

- `u` – name (as string) of the tail vertex
- `v` – name (as string) of the head vertex

OUTPUT:

A triple describing if edge was found or `None` if not. The third value of the triple is a dictionary containing the following edge parameters:

- `low` – the minimum flow through the edge
- `cap` – the maximum capacity of the edge
- `cost` – the cost of transporting one unit through the edge
- `x` – the actual flow through the edge after solving

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: edges = [("A", "B"), ("A", "C"), ("B", "C")]
sage: gbe.add_edges(edges)
sage: ed = gbe.get_edge("A", "B")
sage: ed[0], ed[1], ed[2]['x']
('A', 'B', 0.0)
sage: gbe.get_edge("A", "F") is None
True
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> edges = [("A", "B"), ("A", "C"), ("B", "C")]
>>> gbe.add_edges(edges)
>>> ed = gbe.get_edge("A", "B")
>>> ed[Integer(0)], ed[Integer(1)], ed[Integer(2)]['x']
('A', 'B', 0.0)
>>> gbe.get_edge("A", "F") is None
True
```

get_vertex (*vertex*)

Return a specific vertex as a dictionary Object.

INPUT:

- `vertex` – the vertex label as string

OUTPUT:

The vertex as a dictionary object or `None` if the vertex does not exist. The dictionary contains the values used or created by the different algorithms. The values associated with the keys following keys contain:

- “`rhs`” – The supply / demand value the vertex (mincost alg)

- “pi” – The node potential (mincost alg)
- “cut” – The cut flag of the vertex (maxflow alg)
- “es” – The earliest start of task (cpp alg)
- “ls” – The latest start of task (cpp alg)

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: verts = ["A", "B", "C", "D"]
sage: gbe.add_vertices(verts)
sage: sorted(gbe.get_vertex("A").items())
[('cut', 0), ('es', 0.0), ('ls', 0.0), ('pi', 0.0), ('rhs', 0.0)]
sage: gbe.get_vertex("F") is None
True
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> verts = ["A", "B", "C", "D"]
>>> gbe.add_vertices(verts)
>>> sorted(gbe.get_vertex("A").items())
[('cut', 0), ('es', 0.0), ('ls', 0.0), ('pi', 0.0), ('rhs', 0.0)]
>>> gbe.get_vertex("F") is None
True
```

get_vertices (*verts*)

Return a dictionary of the dictionaries associated to each vertex.

INPUT:

- *verts* – iterable container of vertices

OUTPUT:

A list of pairs (*vertex*, *properties*) where *properties* is a dictionary containing the numerical values associated with a vertex. For more information, see the documentation of [GLPKGraphBackend.get_vertex\(\)](#).

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: verts = ['A', 'B']
sage: gbe.add_vertices(verts)
sage: sorted(gbe.get_vertices(verts)['B'].items())
[('cut', 0), ('es', 0.0), ('ls', 0.0), ('pi', 0.0), ('rhs', 0.0)]
sage: gbe.get_vertices(["C", "D"])
{}
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> verts = ['A', 'B']
```

(continues on next page)

(continued from previous page)

```

>>> gbe.add_vertices(verts)
>>> sorted(gbe.get_vertices(verts)['B'].items())
[('cut', 0), ('es', 0.0), ('ls', 0.0), ('pi', 0.0), ('rhs', 0.0)]
>>> gbe.get_vertices(["C", "D"])
{}

```

maxflow_ffalg (*u=None, v=None*)

Finds solution to the maxflow problem with Ford-Fulkerson algorithm.

INPUT:

- *u* – name (as string) of the tail vertex; default is `None`
- *v* – name (as string) of the head vertex; default is `None`

If *u* or *v* are `None`, the currently stored values for the head or tail vertex are used. This behavior is useful when reading maxflow data from a file. When calling this function with values for *u* and *v*, the head and tail vertex are stored for later use.

OUTPUT: the solution to the maxflow problem, i.e. the maximum flow

Note

- If the source or sink vertex does not exist, an `IndexError` is raised.
- If the source and sink are identical, a `ValueError` is raised.
- This method raises `MIPSolverException` exceptions when the solution cannot be computed for any reason (none exists, or the LP solver was not able to find it, etc...)

EXAMPLES:

```

sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: v = gbe.add_vertices([None for i in range(5)])
sage: edges = ((0, 1, 2), (0, 2, 3), (1, 2, 3), (1, 3, 4),
....:         (3, 4, 1), (2, 4, 2))
sage: for a in edges:
....:     edge = gbe.add_edge(str(a[0]), str(a[1]), {"cap":a[2]})
sage: gbe.maxflow_ffalg('0', '4')
3.0
sage: gbe.maxflow_ffalg()
3.0
sage: gbe.maxflow_ffalg('0', '8')
Traceback (most recent call last):
...
IndexError: Source or sink vertex does not exist

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> v = gbe.add_vertices([None for i in range(Integer(5))])
>>> edges = ((Integer(0), Integer(1), Integer(2)), (Integer(0), Integer(2),
↵Integer(3)), (Integer(1), Integer(2), Integer(3)), (Integer(1), Integer(3),
↵

```

(continues on next page)

(continued from previous page)

```

↪Integer(4)),
...     (Integer(3), Integer(4), Integer(1)), (Integer(2), Integer(4),
↪Integer(2)))
>>> for a in edges:
...     edge = gbe.add_edge(str(a[Integer(0)]), str(a[Integer(1)]), {"cap
↪":a[Integer(2)]})
>>> gbe.maxflow_ffalg('0', '4')
3.0
>>> gbe.maxflow_ffalg()
3.0
>>> gbe.maxflow_ffalg('0', '8')
Traceback (most recent call last):
...
IndexError: Source or sink vertex does not exist

```

mincost_okalg()

Finds solution to the mincost problem with the out-of-kilter algorithm.

The out-of-kilter algorithm requires all problem data to be integer valued.

OUTPUT:

The solution to the mincost problem, i.e. the total cost, if operation was successful.

Note

This method raises `MIPSolverException` exceptions when the solution cannot be computed for any reason (none exists, or the LP solver was not able to find it, etc...)

EXAMPLES:

```

sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: vertices = (35, 50, 40, -45, -20, -30, -30)
sage: vs = gbe.add_vertices([None for i in range(len(vertices))])
sage: v_dict = {}
sage: for i, v in enumerate(vs):
...:     v_dict[v] = vertices[i]
sage: gbe.set_vertices_demand(list(v_dict.items()))
sage: cost = ((8, 6, 10, 9), (9, 12, 13, 7), (14, 9, 16, 5))

sage: for i in range(len(cost)):
...:     for j in range(len(cost[0])):
...:         gbe.add_edge(str(i), str(j + len(cost)), {"cost":cost[i][j],
↪"cap":100})
sage: gbe.mincost_okalg()
1020.0
sage: for ed in gbe.edges():
...:     print("{} -> {} {}".format(ed[0], ed[1], ed[2]["x"]))
0 -> 6 0.0
0 -> 5 25.0
0 -> 4 10.0

```

(continues on next page)

(continued from previous page)

```

0 -> 3 0.0
1 -> 6 0.0
1 -> 5 5.0
1 -> 4 0.0
1 -> 3 45.0
2 -> 6 30.0
2 -> 5 0.0
2 -> 4 10.0
2 -> 3 0.0

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> vertices = (Integer(35), Integer(50), Integer(40), -Integer(45), -
↳Integer(20), -Integer(30), -Integer(30))
>>> vs = gbe.add_vertices([None for i in range(len(vertices))])
>>> v_dict = {}
>>> for i, v in enumerate(vs):
...     v_dict[v] = vertices[i]
>>> gbe.set_vertices_demand(list(v_dict.items()))
>>> cost = ((Integer(8), Integer(6), Integer(10), Integer(9)), (Integer(9),
↳Integer(12), Integer(13), Integer(7)), (Integer(14), Integer(9),
↳Integer(16), Integer(5)))

>>> for i in range(len(cost)):
...     for j in range(len(cost[Integer(0)])):
...         gbe.add_edge(str(i), str(j + len(cost)), {"cost":cost[i][j], "cap
↳":Integer(100)})
>>> gbe.mincost_okalg()
1020.0
>>> for ed in gbe.edges():
...     print("{} -> {} {}".format(ed[Integer(0)], ed[Integer(1)],
↳ed[Integer(2)]["x"]))
0 -> 6 0.0
0 -> 5 25.0
0 -> 4 10.0
0 -> 3 0.0
1 -> 6 0.0
1 -> 5 5.0
1 -> 4 0.0
1 -> 3 45.0
2 -> 6 30.0
2 -> 5 0.0
2 -> 4 10.0
2 -> 3 0.0

```

set_vertex_demand(*vertex*, *demand*)

Set the demand of the vertex in a mincost flow algorithm.

INPUT:

- *vertex* – name of the vertex
- *demand* – the numerical value representing demand of the vertex in a mincost flow algorithm (it could

be for instance -1 to represent a sink, or 1 to represent a source and 0 for a neutral vertex). This can either be an `int` or `float` value.

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: vertices = [None for i in range(3)]
sage: gbe.add_vertices(vertices)
['0', '1', '2']
sage: gbe.set_vertex_demand('0', 2)
sage: gbe.get_vertex('0')['rhs']
2.0
sage: gbe.set_vertex_demand('3', 2)
Traceback (most recent call last):
...
KeyError: 'Vertex 3 does not exist.'
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> vertices = [None for i in range(Integer(3))]
>>> gbe.add_vertices(vertices)
['0', '1', '2']
>>> gbe.set_vertex_demand('0', Integer(2))
>>> gbe.get_vertex('0')['rhs']
2.0
>>> gbe.set_vertex_demand('3', Integer(2))
Traceback (most recent call last):
...
KeyError: 'Vertex 3 does not exist.'
```

`set_vertices_demand` (*pairs*)

Set the parameters of selected vertices.

INPUT:

- *pairs* – list of pairs (vertex, demand) associating a demand to each vertex. For more information, see the documentation of `set_vertex_demand()`.

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: vertices = [None for i in range(3)]
sage: gbe.add_vertices(vertices)
['0', '1', '2']
sage: gbe.set_vertices_demand([('0', 2), ('1', 3), ('3', 4)])
sage: sorted(gbe.get_vertex('1').items())
[('cut', 0), ('es', 0.0), ('ls', 0.0), ('pi', 0.0), ('rhs', 3.0)]
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> vertices = [None for i in range(Integer(3))]
```

(continues on next page)

(continued from previous page)

```

>>> gbe.add_vertices(vertices)
['0', '1', '2']
>>> gbe.set_vertices_demand([('0', Integer(2)), ('1', Integer(3)), ('3', Integer(4))]
↳Integer(4)])
>>> sorted(gbe.get_vertex('1').items())
[('cut', 0), ('es', 0.0), ('ls', 0.0), ('pi', 0.0), ('rhs', 3.0)]

```

vertices()

Return the list of all vertices.

Note

Changing elements of the list will not change anything in the the graph.

Note

If a vertex in the graph does not have a name / label it will appear as None in the resulting list.

EXAMPLES:

```

sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: verts = ["A", "B", "C"]
sage: gbe.add_vertices(verts)
sage: a = gbe.vertices(); a
['A', 'B', 'C']
sage: a.pop(0)
'A'
sage: gbe.vertices()
['A', 'B', 'C']

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> verts = ["A", "B", "C"]
>>> gbe.add_vertices(verts)
>>> a = gbe.vertices(); a
['A', 'B', 'C']
>>> a.pop(Integer(0))
'A'
>>> gbe.vertices()
['A', 'B', 'C']

```

write_ccdata(*fname*)

Writes the graph to a text file in DIMACS format.

Writes the data to plain ASCII text file in DIMACS format. A description of the DIMACS format can be found at <http://dimacs.rutgers.edu/Challenges/>.

INPUT:

- `fname` – full name of the file

OUTPUT: zero if the operations was successful otherwise nonzero

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: a = gbe.add_edge("0", "1")
sage: import tempfile
sage: with tempfile.NamedTemporaryFile() as f:
....:     gbe.write_ccdata(f.name)
Writing graph to ...
6 lines were written
0
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> a = gbe.add_edge("0", "1")
>>> import tempfile
>>> with tempfile.NamedTemporaryFile() as f:
...     gbe.write_ccdata(f.name)
Writing graph to ...
6 lines were written
0
```

write_graph (*fname*)

Writes the graph to a plain text file

INPUT:

- `fname` – full name of the file

OUTPUT: zero if the operations was successful otherwise nonzero

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: a = gbe.add_edge("0", "1")
sage: import tempfile
sage: with tempfile.NamedTemporaryFile() as f:
....:     gbe.write_graph(f.name)
Writing graph to ...
4 lines were written
0
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> a = gbe.add_edge("0", "1")
>>> import tempfile
>>> with tempfile.NamedTemporaryFile() as f:
...     gbe.write_graph(f.name)
Writing graph to ...
```

(continues on next page)

(continued from previous page)

```
4 lines were written
0
```

write_maxflow(*fname*)

Writes the maximum flow problem data to a text file in DIMACS format.

INPUT:

- *fname* – full name of file

OUTPUT:

Zero if successful, otherwise nonzero

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: import tempfile
sage: with tempfile.NamedTemporaryFile() as f:
....:     gbe.write_maxflow(f.name)
Traceback (most recent call last):
...
OSError: Cannot write empty graph
sage: gbe.add_vertices([None for i in range(2)])
['0', '1']
sage: a = gbe.add_edge('0', '1')
sage: gbe.maxflow_ffalg('0', '1')
0.0
sage: with tempfile.NamedTemporaryFile() as f:
....:     gbe.write_maxflow(f.name)
Writing maximum flow problem data to ...
6 lines were written
0
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> import tempfile
>>> with tempfile.NamedTemporaryFile() as f:
...     gbe.write_maxflow(f.name)
Traceback (most recent call last):
...
OSError: Cannot write empty graph
>>> gbe.add_vertices([None for i in range(Integer(2))])
['0', '1']
>>> a = gbe.add_edge('0', '1')
>>> gbe.maxflow_ffalg('0', '1')
0.0
>>> with tempfile.NamedTemporaryFile() as f:
...     gbe.write_maxflow(f.name)
Writing maximum flow problem data to ...
6 lines were written
0
```

write_mincost (*fname*)

Writes the mincost flow problem data to a text file in DIMACS format

INPUT:

- *fname* – full name of file

OUTPUT: zero if successful, otherwise nonzero

EXAMPLES:

```
sage: from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
sage: gbe = GLPKGraphBackend()
sage: a = gbe.add_edge("0", "1")
sage: import tempfile
sage: with tempfile.NamedTemporaryFile() as f:
....:     gbe.write_mincost(f.name)
Writing min-cost flow problem data to ...
4 lines were written
0
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.glpk_graph_backend import GLPKGraphBackend
>>> gbe = GLPKGraphBackend()
>>> a = gbe.add_edge("0", "1")
>>> import tempfile
>>> with tempfile.NamedTemporaryFile() as f:
...     gbe.write_mincost(f.name)
Writing min-cost flow problem data to ...
4 lines were written
0
```

11.6 PPL Backend

AUTHORS:

- Risan (2012-02): initial implementation
- Jeroen Demeyer (2014-08-04) allow rational coefficients for constraints and objective function ([Issue #16755](#))

class `sage.numerical.backends.ppl_backend.PPLBackend`

Bases: *GenericBackend*

MIP Backend that uses the exact MIP solver from the Parma Polyhedra Library.

add_col (*indices*, *coeffs*)

Add a column.

INPUT:

- *indices* – list of integers; this list contains the indices of the constraints in which the variable's coefficient is nonzero
- *coeffs* – list of real values; associates a coefficient to the variable in each of the constraints in which it appears. Namely, the *i*-th entry of *coeffs* corresponds to the coefficient of the variable in the constraint represented by the *i*-th entry in *indices*.

Note

`indices` and `coeffs` are expected to be of the same length.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.ncols()
0
sage: p.nrows()
0
sage: p.add_linear_constraints(5, 0, None)
sage: p.add_col(list(range(5)), list(range(5)))
sage: p.nrows()
5
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.ncols()
0
>>> p.nrows()
0
>>> p.add_linear_constraints(Integer(5), Integer(0), None)
>>> p.add_col(list(range(Integer(5))), list(range(Integer(5))))
>>> p.nrows()
5
```

add_linear_constraint (*coefficients, lower_bound, upper_bound, name=None*)

Add a linear constraint.

INPUT:

- `coefficients` – an iterable with (c, v) pairs where c is a variable index (integer) and v is a value (real value).
- `lower_bound` – a lower bound, either a real value or `None`
- `upper_bound` – an upper bound, either a real value or `None`
- `name` – an optional name for this row (default: `None`)

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='PPL')
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(x[0]/2 + x[1]/3 <= 2/5)
sage: p.set_objective(x[1])
sage: p.solve()
6/5
sage: p.add_constraint(x[0] - x[1] >= 1/10)
sage: p.solve()
21/50
sage: p.set_max(x[0], 1/2)
```

(continues on next page)

(continued from previous page)

```

sage: p.set_min(x[1], 3/8)
sage: p.solve()
2/5

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(zip(range(5), range(5)), 2.0, 2.0)
sage: p.row(0)
([1, 2, 3, 4], [1, 2, 3, 4])
sage: p.row_bounds(0)
(2.0000000000000000, 2.0000000000000000)
sage: p.add_linear_constraint( zip(range(5), range(5)), 1.0, 1.0, name='foo')
sage: p.row_name(-1)
'foo'

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='PPL')
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(x[Integer(0)]/Integer(2) + x[Integer(1)]/Integer(3) <=
↳Integer(2)/Integer(5))
>>> p.set_objective(x[Integer(1)])
>>> p.solve()
6/5
>>> p.add_constraint(x[Integer(0)] - x[Integer(1)] >= Integer(1)/Integer(10))
>>> p.solve()
21/50
>>> p.set_max(x[Integer(0)], Integer(1)/Integer(2))
>>> p.set_min(x[Integer(1)], Integer(3)/Integer(8))
>>> p.solve()
2/5

>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))),
↳RealNumber('2.0'), RealNumber('2.0'))
>>> p.row(Integer(0))
([1, 2, 3, 4], [1, 2, 3, 4])
>>> p.row_bounds(Integer(0))
(2.0000000000000000, 2.0000000000000000)
>>> p.add_linear_constraint( zip(range(Integer(5)), range(Integer(5))),
↳RealNumber('1.0'), RealNumber('1.0'), name='foo')
>>> p.row_name(-Integer(1))
'foo'

```

add_linear_constraints (*number, lower_bound, upper_bound, names=None*)

Add constraints.

INPUT:

- `number` – integer; the number of constraints to add
- `lower_bound` – a lower bound, either a real value or `None`
- `upper_bound` – an upper bound, either a real value or `None`
- `names` – an optional list of names (default: `None`)

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_variables(5)
4
sage: p.add_linear_constraints(5, None, 2)
sage: p.row(4)
([], [])
sage: p.row_bounds(4)
(None, 2)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraints(Integer(5), None, Integer(2))
>>> p.row(Integer(4))
([], [])
>>> p.row_bounds(Integer(4))
(None, 2)
```

add_variable (*lower_bound=0, upper_bound=None, binary=False, continuous=False, integer=False, obj=0, name=None*)

Add a variable.

This amounts to adding a new column to the matrix. By default, the variable is both positive and real.

It has not been implemented for selecting the variable type yet.

INPUT:

- `lower_bound` – the lower bound of the variable (default: 0)
- `upper_bound` – the upper bound of the variable (default: `None`)
- `binary` – True if the variable is binary (default: `False`)
- `continuous` – True if the variable is continuous (default: `True`)
- `integer` – True if the variable is integral (default: `False`)
- `obj` – (optional) coefficient of this variable in the objective function (default: 0)
- `name` – an optional name for the newly added variable (default: `None`)

OUTPUT: the index of the newly created variable

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.ncols()
1
sage: p.add_variable(lower_bound=-2)
1
sage: p.add_variable(name='x',obj=2/3)
2
sage: p.col_name(2)
'x'
sage: p.objective_coefficient(2)
2/3
sage: p.add_variable(integer=True)
3

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.ncols()
1
>>> p.add_variable(lower_bound=-Integer(2))
1
>>> p.add_variable(name='x',obj=Integer(2)/Integer(3))
2
>>> p.col_name(Integer(2))
'x'
>>> p.objective_coefficient(Integer(2))
2/3
>>> p.add_variable(integer=True)
3

```

add_variables (*n*, *lower_bound*=0, *upper_bound*=None, *binary*=False, *continuous*=True, *integer*=False, *obj*=0, *names*=None)

Add *n* variables.

This amounts to adding new columns to the matrix. By default, the variables are both positive and real.

It has not been implemented for selecting the variable type yet.

INPUT:

- *n* – the number of new variables (must be > 0)
- *lower_bound* – the lower bound of the variable (default: 0)
- *upper_bound* – the upper bound of the variable (default: None)
- *binary* – True if the variable is binary (default: False)

- `continuous` – True if the variable is continuous (default: True)
- `integer` – True if the variable is integral (default: False)
- `obj` – coefficient of all variables in the objective function (default: 0)
- `names` – list of names (default: None)

OUTPUT: the index of the variable created last

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.ncols()
0
sage: p.add_variables(5)
4
sage: p.ncols()
5
sage: p.add_variables(2, lower_bound=-2.0, obj=42.0, names=['a','b'])
6
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.ncols()
0
>>> p.add_variables(Integer(5))
4
>>> p.ncols()
5
>>> p.add_variables(Integer(2), lower_bound=-RealNumber('2.0'),
↳ obj=RealNumber('42.0'), names=['a','b'])
6
```

`base_ring()`

`col_bounds` (*index*)

Return the bounds of a specific variable.

INPUT:

- `index` – integer; the variable's id

OUTPUT:

A pair (`lower_bound`, `upper_bound`). Each of them can be set to `None` if the variable is not bounded in the corresponding direction, and is a real value otherwise.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_variable()
0
sage: p.col_bounds(0)
(0, None)
```

(continues on next page)

(continued from previous page)

```
sage: p.variable_upper_bound(0, 5)
sage: p.col_bounds(0)
(0, 5)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_variable()
0
>>> p.col_bounds(Integer(0))
(0, None)
>>> p.variable_upper_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(0, 5)
```

col_name (*index*)

Return the index-th col name.

INPUT:

- *index* – integer; the col's id
- *name* – (char *) its name; when set to NULL (default), the method returns the current name

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_variable(name="I am a variable")
0
sage: p.col_name(0)
'I am a variable'
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_variable(name="I am a variable")
0
>>> p.col_name(Integer(0))
'I am a variable'
```

get_objective_value ()

Return the exact value of the objective function.

NoteBehaviour is undefined unless `solve` has been called before.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='PPL')
sage: x = p.new_variable(nonnegative=True)
```

(continues on next page)

(continued from previous page)

```

sage: p.add_constraint(5/13*x[0] + x[1]/2 == 8/7)
sage: p.set_objective(5/13*x[0] + x[1]/2)
sage: p.solve()
8/7

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([(0,1), (1,2)], None, 3)
sage: p.set_objective([2, 5])
sage: p.solve()
0
sage: p.get_objective_value()
15/2
sage: p.get_variable_value(0)
0
sage: p.get_variable_value(1)
3/2

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='PPL')
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(Integer(5)/Integer(13)*x[Integer(0)] + x[Integer(1)]/
↳Integer(2) == Integer(8)/Integer(7))
>>> p.set_objective(Integer(5)/Integer(13)*x[Integer(0)] + x[Integer(1)]/
↳Integer(2))
>>> p.solve()
8/7

>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([(Integer(0),Integer(1)), (Integer(1),
↳Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> p.solve()
0
>>> p.get_objective_value()
15/2
>>> p.get_variable_value(Integer(0))
0
>>> p.get_variable_value(Integer(1))
3/2

```

get_variable_value (*variable*)

Return the value of a variable given by the solver.

Note

Behaviour is undefined unless `solve` has been called before.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([(0,1), (1, 2)], None, 3)
sage: p.set_objective([2, 5])
sage: p.solve()
0
sage: p.get_objective_value()
15/2
sage: p.get_variable_value(0)
0
sage: p.get_variable_value(1)
3/2
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([(Integer(0),Integer(1)), (Integer(1),
↳Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> p.solve()
0
>>> p.get_objective_value()
15/2
>>> p.get_variable_value(Integer(0))
0
>>> p.get_variable_value(Integer(1))
3/2
```

`init_mip()`

Converting the matrix form of the MIP Problem to PPL MIP_Problem.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='PPL')
sage: p.base_ring()
Rational Field
sage: type(p.zero())
<class 'sage.rings.rational.Rational'>
sage: p.init_mip()
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='PPL')
```

(continues on next page)

(continued from previous page)

```
>>> p.base_ring()
Rational Field
>>> type(p.zero())
<class 'sage.rings.rational.Rational'>
>>> p.init_mip()
```

is_maximization()

Test whether the problem is a maximization

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False
```

is_variable_binary(index)

Test whether the given variable is of binary type.

INPUT:

- `index` – integer; the variable's id

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.is_variable_binary(0)
False
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.ncols()
0
>>> p.add_variable()
0
```

(continues on next page)

(continued from previous page)

```
>>> p.is_variable_binary(Integer(0))
False
```

is_variable_continuous (*index*)

Test whether the given variable is of continuous/real type.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.is_variable_continuous(0)
True
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.is_variable_continuous(Integer(0))
True
```

is_variable_integer (*index*)

Test whether the given variable is of integer type.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.is_variable_integer(0)
False
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.ncols()
0
```

(continues on next page)

(continued from previous page)

```
>>> p.add_variable()
0
>>> p.is_variable_integer(Integer(0))
False
```

ncols()

Return the number of columns/variables.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.ncols()
0
sage: p.add_variables(2)
1
sage: p.ncols()
2
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.ncols()
0
>>> p.add_variables(Integer(2))
1
>>> p.ncols()
2
```

nrows()

Return the number of rows/constraints.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.nrows()
0
sage: p.add_linear_constraints(2, 2.0, None)
sage: p.nrows()
2
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.nrows()
0
>>> p.add_linear_constraints(Integer(2), RealNumber('2.0'), None)
>>> p.nrows()
2
```

objective_coefficient (*variable, coeff=None*)

Set or get the coefficient of a variable in the objective function

INPUT:

- `variable` – integer; the variable's id
- `coeff` – integer; its coefficient

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_variable()
0
sage: p.objective_coefficient(0)
0
sage: p.objective_coefficient(0,2)
sage: p.objective_coefficient(0)
2
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_variable()
0
>>> p.objective_coefficient(Integer(0))
0
>>> p.objective_coefficient(Integer(0), Integer(2))
>>> p.objective_coefficient(Integer(0))
2
```

problem_name (*name=None*)

Return or define the problem's name.

INPUT:

- `name` – string; the problem's name. When set to `None` (default), the method returns the problem's name.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.problem_name("There once was a french fry")
sage: print(p.problem_name())
There once was a french fry
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.problem_name("There once was a french fry")
>>> print(p.problem_name())
There once was a french fry
```

row (*i*)

Return a row.

INPUT:

- `index` – integer; the constraint's id

OUTPUT:

A pair (indices, coeffs) where indices lists the entries whose coefficient is nonzero, and to which coeffs associates their coefficient on the model of the add_linear_constraint method.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(zip(range(5), range(5)), 2, 2)
sage: p.row(0)
([1, 2, 3, 4], [1, 2, 3, 4])
sage: p.row_bounds(0)
(2, 2)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))),
↳ Integer(2), Integer(2))
>>> p.row(Integer(0))
([1, 2, 3, 4], [1, 2, 3, 4])
>>> p.row_bounds(Integer(0))
(2, 2)
```

row_bounds (*index*)

Return the bounds of a specific constraint.

INPUT:

- index – integer; the constraint's id

OUTPUT:

A pair (lower_bound, upper_bound). Each of them can be set to None if the constraint is not bounded in the corresponding direction, and is a real value otherwise.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(zip(range(5), range(5)), 2, 2)
sage: p.row(0)
([1, 2, 3, 4], [1, 2, 3, 4])
sage: p.row_bounds(0)
(2, 2)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
```

(continues on next page)

(continued from previous page)

```

>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))),
↳Integer(2), Integer(2))
>>> p.row(Integer(0))
([1, 2, 3, 4], [1, 2, 3, 4])
>>> p.row_bounds(Integer(0))
(2, 2)

```

row_name (*index*)

Return the index-th row name.

INPUT:

- *index* – integer; the row's id

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_linear_constraints(1, 2, None, names=["Empty constraint 1"])
sage: p.row_name(0)
'Empty constraint 1'

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_linear_constraints(Integer(1), Integer(2), None, names=["Empty_
↳constraint 1"])
>>> p.row_name(Integer(0))
'Empty constraint 1'

```

set_objective (*coeff, d=0*)

Set the objective function.

INPUT:

- *coeff* – list of real values, whose i-th element is the coefficient of the i-th variable in the objective function

EXAMPLES:

```

sage: p = MixedIntegerLinearProgram(solver='PPL')
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(x[0]*5 + x[1]/11 <= 6)
sage: p.set_objective(x[0])
sage: p.solve()
6/5
sage: p.set_objective(x[0]/2 + 1)
sage: p.show()
Maximization:
  1/2 x_0 + 1
Constraints:
  constraint_0: 5 x_0 + 1/11 x_1 <= 6

```

(continues on next page)

(continued from previous page)

```

Variables:
  x_0 is a continuous variable (min=0, max=+oo)
  x_1 is a continuous variable (min=0, max=+oo)
sage: p.solve()
8/5

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_variables(5)
4
sage: p.set_objective([1, 1, 2, 1, 3])
sage: [p.objective_coefficient(x) for x in range(5)]
[1, 1, 2, 1, 3]

```

```

>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='PPL')
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(x[Integer(0)]*Integer(5) + x[Integer(1)]/Integer(11) <= 6)
↳Integer(6)
>>> p.set_objective(x[Integer(0)])
>>> p.solve()
6/5
>>> p.set_objective(x[Integer(0)]/Integer(2) + Integer(1))
>>> p.show()
Maximization:
  1/2 x_0 + 1
<BLANKLINE>
Constraints:
  constraint_0: 5 x_0 + 1/11 x_1 <= 6
Variables:
  x_0 is a continuous variable (min=0, max=+oo)
  x_1 is a continuous variable (min=0, max=+oo)
>>> p.solve()
8/5

>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_variables(Integer(5))
4
>>> p.set_objective([Integer(1), Integer(1), Integer(2), Integer(1),
↳Integer(3)])
>>> [p.objective_coefficient(x) for x in range(Integer(5))]
[1, 1, 2, 1, 3]

```

set_sense (*sense*)

Set the direction (maximization/minimization).

INPUT:

- *sense* – integer:
 - +1 => Maximization
 - -1 => Minimization

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False
```

set_variable_type (*variable*, *vtype*)

Set the type of a variable.

INPUT:

- *variable* – integer; the variable's id
- *vtype* – integer:
 - 1 Integer
 - 0 Binary
 - -1 Continuous

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_variables(5)
4
sage: p.set_variable_type(0, 1)
sage: p.is_variable_integer(0)
True
sage: p.set_variable_type(3, 0)
sage: p.is_variable_integer(3) or p.is_variable_binary(3)
True
sage: p.col_bounds(3) # tol 1e-6
(0, 1)
sage: p.set_variable_type(3, -1)
sage: p.is_variable_continuous(3)
True
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_variables(Integer(5))
```

(continues on next page)

(continued from previous page)

```

4
>>> p.set_variable_type(Integer(0), Integer(1))
>>> p.is_variable_integer(Integer(0))
True
>>> p.set_variable_type(Integer(3), Integer(0))
>>> p.is_variable_integer(Integer(3)) or p.is_variable_binary(Integer(3))
True
>>> p.col_bounds(Integer(3)) # tol 1e-6
(0, 1)
>>> p.set_variable_type(Integer(3), -Integer(1))
>>> p.is_variable_continuous(Integer(3))
True

```

set_verbosity (*level*)

Set the log (verbosity) level. Not Implemented.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.set_verbosity(0)

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.set_verbosity(Integer(0))

```

solve ()

Solve the problem.

Note

This method raises `MIPSolverException` exceptions when the solution cannot be computed for any reason (none exists, or the solver was not able to find it, etc...)

EXAMPLES:

A linear optimization problem:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_linear_constraints(5, 0, None)
sage: p.add_col(list(range(5)), list(range(5)))
sage: p.solve()
0

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_linear_constraints(Integer(5), Integer(0), None)
>>> p.add_col(list(range(Integer(5))), list(range(Integer(5))))

```

(continues on next page)

(continued from previous page)

```
>>> p.solve()
0
```

An unbounded problem:

```
sage: p.objective_coefficient(0,1)
sage: p.solve()
Traceback (most recent call last):
...
MIPSolverException: ...
```

```
>>> from sage.all import *
>>> p.objective_coefficient(Integer(0),Integer(1))
>>> p.solve()
Traceback (most recent call last):
...
MIPSolverException: ...
```

An integer optimization problem:

```
sage: p = MixedIntegerLinearProgram(solver='PPL')
sage: x = p.new_variable(integer=True, nonnegative=True)
sage: p.add_constraint(2*x[0] + 3*x[1], max = 6)
sage: p.add_constraint(3*x[0] + 2*x[1], max = 6)
sage: p.set_objective(x[0] + x[1] + 7)
sage: p.solve()
9
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='PPL')
>>> x = p.new_variable(integer=True, nonnegative=True)
>>> p.add_constraint(Integer(2)*x[Integer(0)] + Integer(3)*x[Integer(1)], max_
↳ Integer(6))
>>> p.add_constraint(Integer(3)*x[Integer(0)] + Integer(2)*x[Integer(1)], max_
↳ Integer(6))
>>> p.set_objective(x[Integer(0)] + x[Integer(1)] + Integer(7))
>>> p.solve()
9
```

variable_lower_bound (*index*, *value=False*)

Return or define the lower bound on a variable.

INPUT:

- *index* – integer; the variable's id
- *value* – real value, or `None` to mean that the variable has not lower bound. When set to `False` (default), the method returns the current value.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_variable()
```

(continues on next page)

(continued from previous page)

```

0
sage: p.col_bounds(0)
(0, None)
sage: p.variable_lower_bound(0, 5)
sage: p.col_bounds(0)
(5, None)
sage: p.variable_lower_bound(0, None)
sage: p.col_bounds(0)
(None, None)

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_variable()
0
>>> p.col_bounds(Integer(0))
(0, None)
>>> p.variable_lower_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(5, None)
>>> p.variable_lower_bound(Integer(0), None)
>>> p.col_bounds(Integer(0))
(None, None)

```

variable_upper_bound (*index, value=False*)

Return or define the upper bound on a variable.

INPUT:

- *index* – integer; the variable's id
- *value* – real value, or `None` to mean that the variable has not upper bound. When set to `False` (default), the method returns the current value.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver = "PPL")
sage: p.add_variable()
0
sage: p.col_bounds(0)
(0, None)
sage: p.variable_upper_bound(0, 5)
sage: p.col_bounds(0)
(0, 5)
sage: p.variable_upper_bound(0, None)
sage: p.col_bounds(0)
(0, None)

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver = "PPL")
>>> p.add_variable()

```

(continues on next page)

(continued from previous page)

```

0
>>> p.col_bounds(Integer(0))
(0, None)
>>> p.variable_upper_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(0, 5)
>>> p.variable_upper_bound(Integer(0), None)
>>> p.col_bounds(Integer(0))
(0, None)

```

`zero()`

11.7 CVXOPT Backend

AUTHORS:

- Ingolfur Edvardsson (2014-05): initial implementation

class `sage.numerical.backends.cvxopt_backend.CVXOPTBackend`

Bases: `GenericBackend`

MIP Backend that uses the CVXOPT solver.

There is no support for integer variables.

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='CVXOPT')
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='CVXOPT')
```

add_col (*indices*, *coeffs*)

Add a column.

INPUT:

- *indices* – list of integers; this list contains the indices of the constraints in which the variable's coefficient is nonzero
- *coeffs* – list of real values; associates a coefficient to the variable in each of the constraints in which it appears. Namely, the *i*-th entry of *coeffs* corresponds to the coefficient of the variable in the constraint represented by the *i*-th entry in *indices*.

Note

indices and *coeffs* are expected to be of the same length.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.ncols()
0
```

(continues on next page)

(continued from previous page)

```
sage: p.nrows()
0
sage: p.add_linear_constraints(5, 0, None)
sage: p.add_col(range(5), range(5))
sage: p.nrows()
5
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.ncols()
0
>>> p.nrows()
0
>>> p.add_linear_constraints(Integer(5), Integer(0), None)
>>> p.add_col(range(Integer(5)), range(Integer(5)))
>>> p.nrows()
5
```

add_linear_constraint (*coefficients, lower_bound, upper_bound, name=None*)

Add a linear constraint.

INPUT:

- *coefficients* an iterable with (c, v) pairs where c is a variable index (integer) and v is a value (real value).
- *lower_bound* – a lower bound, either a real value or `None`
- *upper_bound* – an upper bound, either a real value or `None`
- *name* – an optional name for this row (default: `None`)

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(zip(range(5), range(5)), 2.0, 2.0)
sage: p.row(0)
([1, 2, 3, 4], [1, 2, 3, 4])
sage: p.row_bounds(0)
(2.000000000000000, 2.000000000000000)
sage: p.add_linear_constraint(zip(range(5), range(5)), 1.0, 1.0, name='foo')
sage: p.row_name(-1)
'foo'
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))), 1,
```

(continues on next page)

(continued from previous page)

```

↪RealNumber('2.0'), RealNumber('2.0'))
>>> p.row(Integer(0))
([1, 2, 3, 4], [1, 2, 3, 4])
>>> p.row_bounds(Integer(0))
(2.0000000000000000, 2.0000000000000000)
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))), ↪
↪RealNumber('1.0'), RealNumber('1.0'), name='foo')
>>> p.row_name(-Integer(1))
'foo'

```

add_variable (*lower_bound=0.0, upper_bound=None, binary=False, continuous=True, integer=False, obj=None, name=None*)

Add a variable.

This amounts to adding a new column to the matrix. By default, the variable is both positive and real. Variable types are always continuous, and thus the parameters `binary`, `integer`, and `continuous` have no effect.

INPUT:

- `lower_bound` – the lower bound of the variable (default: 0)
- `upper_bound` – the upper bound of the variable (default: None)
- `binary` – True if the variable is binary (default: False)
- `continuous` – True if the variable is continuous (default: True)
- `integer` – True if the variable is integer (default: False)
- `obj` – (optional) coefficient of this variable in the objective function (default: 0.0)
- `name` – an optional name for the newly added variable (default: None)

OUTPUT: the index of the newly created variable

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.ncols()
1
sage: p.add_variable()
1
sage: p.add_variable(lower_bound=-2.0)
2
sage: p.add_variable(continuous=True)
3
sage: p.add_variable(name='x', obj=1.0)
4
sage: p.col_name(3)
'x_3'
sage: p.col_name(4)
'x'

```

(continues on next page)

(continued from previous page)

```
sage: p.objective_coefficient(4)
1.0000000000000000
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.ncols()
1
>>> p.add_variable()
1
>>> p.add_variable(lower_bound=-RealNumber('2.0'))
2
>>> p.add_variable(continuous=True)
3
>>> p.add_variable(name='x', obj=RealNumber('1.0'))
4
>>> p.col_name(Integer(3))
'x_3'
>>> p.col_name(Integer(4))
'x'
>>> p.objective_coefficient(Integer(4))
1.0000000000000000
```

col_bounds (*index*)

Return the bounds of a specific variable.

INPUT:

- *index* – integer; the variable's id

OUTPUT:

A pair (*lower_bound*, *upper_bound*). Each of them can be set to `None` if the variable is not bounded in the corresponding direction, and is a real value otherwise.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.add_variable()
0
sage: p.col_bounds(0)
(0.0, None)
sage: p.variable_upper_bound(0, 5)
sage: p.col_bounds(0)
(0.0, 5)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
```

(continues on next page)

(continued from previous page)

```

>>> p.add_variable()
0
>>> p.col_bounds(Integer(0))
(0.0, None)
>>> p.variable_upper_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(0.0, 5)

```

col_name (*index*)Return the *index*-th col name.

INPUT:

- *index* – integer; the col's id
- *name* – (char *) its name; when set to NULL (default), the method returns the current name

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.add_variable(name="I am a variable")
0
sage: p.col_name(0)
'I am a variable'

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.add_variable(name="I am a variable")
0
>>> p.col_name(Integer(0))
'I am a variable'

```

get_objective_value ()

Return the value of the objective function.

NoteBehaviour is undefined unless `solve` has been called before.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='cvxopt')
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([(0,1), (1,2)], None, 3)
sage: p.set_objective([2, 5])
sage: p.solve()
0
sage: N(p.get_objective_value(), 4)
7.5

```

(continues on next page)

(continued from previous page)

```
sage: N(p.get_variable_value(0),4)
3.6e-7
sage: N(p.get_variable_value(1),4)
1.5
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='cvxopt')
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([(Integer(0), Integer(1)), (Integer(1),
↳ Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> p.solve()
0
>>> N(p.get_objective_value(), Integer(4))
7.5
>>> N(p.get_variable_value(Integer(0)), Integer(4))
3.6e-7
>>> N(p.get_variable_value(Integer(1)), Integer(4))
1.5
```

get_variable_value (*variable*)

Return the value of a variable given by the solver.

NoteBehaviour is undefined unless `solve` has been called before.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([(0,1), (1, 2)], None, 3)
sage: p.set_objective([2, 5])
sage: p.solve()
0
sage: N(p.get_objective_value(),4)
7.5
sage: N(p.get_variable_value(0),4)
3.6e-7
sage: N(p.get_variable_value(1),4)
1.5
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.add_variables(Integer(2))
1
```

(continues on next page)

(continued from previous page)

```

>>> p.add_linear_constraint([(Integer(0), Integer(1)), (Integer(1), Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> p.solve()
0
>>> N(p.get_objective_value(), Integer(4))
7.5
>>> N(p.get_variable_value(Integer(0)), Integer(4))
3.6e-7
>>> N(p.get_variable_value(Integer(1)), Integer(4))
1.5

```

is_maximization()

Test whether the problem is a maximization

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False

```

is_variable_binary(index)

Test whether the given variable is of binary type. CVXOPT does not allow integer variables, so this is a bit moot.

INPUT:

- `index` – integer; the variable's id

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.set_variable_type(0, 0)
Traceback (most recent call last):
...
ValueError: ...

```

(continues on next page)

(continued from previous page)

```
sage: p.is_variable_binary(0)
False
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.set_variable_type(Integer(0), Integer(0))
Traceback (most recent call last):
...
ValueError: ...
>>> p.is_variable_binary(Integer(0))
False
```

is_variable_continuous (*index*)

Test whether the given variable is of continuous/real type. CVXOPT does not allow integer variables, so this is a bit moot.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.is_variable_continuous(0)
True
sage: p.set_variable_type(0, 1)
Traceback (most recent call last):
...
ValueError: ...
sage: p.is_variable_continuous(0)
True
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.is_variable_continuous(Integer(0))
True
>>> p.set_variable_type(Integer(0), Integer(1))
Traceback (most recent call last):
```

(continues on next page)

(continued from previous page)

```
...
ValueError: ...
>>> p.is_variable_continuous(Integer(0))
True
```

is_variable_integer (*index*)

Test whether the given variable is of integer type. CVXOPT does not allow integer variables, so this is a bit moot.

INPUT:

- *index* – integer; the variable's id

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.set_variable_type(0,-1)
sage: p.set_variable_type(0,1)
Traceback (most recent call last):
...
ValueError: ...
sage: p.is_variable_integer(0)
False
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.set_variable_type(Integer(0),-Integer(1))
>>> p.set_variable_type(Integer(0),Integer(1))
Traceback (most recent call last):
...
ValueError: ...
>>> p.is_variable_integer(Integer(0))
False
```

ncols ()

Return the number of columns/variables.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.ncols()
0
sage: p.add_variables(2)
```

(continues on next page)

(continued from previous page)

```

1
sage: p.ncols()
2

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.ncols()
0
>>> p.add_variables(Integer(2))
1
>>> p.ncols()
2

```

nrows()

Return the number of rows/constraints.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.nrows()
0
sage: p.add_variables(5)
4
sage: p.add_linear_constraints(2, 2.0, None)
sage: p.nrows()
2

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.nrows()
0
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraints(Integer(2), RealNumber('2.0'), None)
>>> p.nrows()
2

```

objective_coefficient (*variable, coeff=None*)

Set or get the coefficient of a variable in the objective function

INPUT:

- *variable* – integer; the variable's id
- *coeff* – double; its coefficient

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.add_variable()

```

(continues on next page)

(continued from previous page)

```

0
sage: p.objective_coefficient(0)
0.0
sage: p.objective_coefficient(0,2)
sage: p.objective_coefficient(0)
2.0

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.add_variable()
0
>>> p.objective_coefficient(Integer(0))
0.0
>>> p.objective_coefficient(Integer(0), Integer(2))
>>> p.objective_coefficient(Integer(0))
2.0

```

problem_name (*name=None*)

Return or define the problem's name.

INPUT:

- *name* – string; the problem's name. When set to *None* (default), the method returns the problem's name.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.problem_name()
''
sage: p.problem_name("There once was a french fry")
sage: print(p.problem_name())
There once was a french fry

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.problem_name()
''
>>> p.problem_name("There once was a french fry")
>>> print(p.problem_name())
There once was a french fry

```

row (*i*)

Return a row.

INPUT:

- *index* – integer; the constraint's id

OUTPUT:

A pair (*indices*, *coeffs*) where *indices* lists the entries whose coefficient is nonzero, and to which *coeffs* associates their coefficient on the model of the `add_linear_constraint` method.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(list(zip(range(5), range(5))), 2, 2)
sage: p.row(0)
([1, 2, 3, 4], [1, 2, 3, 4])
sage: p.row_bounds(0)
(2, 2)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(list(zip(range(Integer(5)), range(Integer(5))),
↳ Integer(2), Integer(2))
>>> p.row(Integer(0))
([1, 2, 3, 4], [1, 2, 3, 4])
>>> p.row_bounds(Integer(0))
(2, 2)
```

row_bounds (*index*)

Return the bounds of a specific constraint.

INPUT:

- *index* – integer; the constraint's id

OUTPUT:

A pair (*lower_bound*, *upper_bound*). Each of them can be set to `None` if the constraint is not bounded in the corresponding direction, and is a real value otherwise.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(list(zip(range(5), range(5))), 2, 2)
sage: p.row(0)
([1, 2, 3, 4], [1, 2, 3, 4])
sage: p.row_bounds(0)
(2, 2)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(list(zip(range(Integer(5)), range(Integer(5))),
↳ Integer(2), Integer(2))
```

(continues on next page)

(continued from previous page)

```
>>> p.row(Integer(0))
[[1, 2, 3, 4], [1, 2, 3, 4]]
>>> p.row_bounds(Integer(0))
(2, 2)
```

row_name (*index*)Return the *index*-th row name.

INPUT:

- *index* – integer; the row's id

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.add_linear_constraints(1, 2, None, names=["Empty constraint 1"])
sage: p.row_name(0)
'Empty constraint 1'
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.add_linear_constraints(Integer(1), Integer(2), None, names=["Empty_
↳constraint 1"])
>>> p.row_name(Integer(0))
'Empty constraint 1'
```

set_objective (*coeff*, *d=0.0*)

Set the objective function.

INPUT:

- *coeff* – list of real values, whose *i*-th element is the coefficient of the *i*-th variable in the objective function
- *d* – double; the constant term in the linear function (set to 0 by default)

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.add_variables(5)
4
sage: p.set_objective([1, 1, 2, 1, 3])
sage: [p.objective_coefficient(x) for x in range(5)]
[1, 1, 2, 1, 3]
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.add_variables(Integer(5))
4
>>> p.set_objective([Integer(1), Integer(1), Integer(2), Integer(1),
↳Integer(3)])
```

(continues on next page)

(continued from previous page)

```
>>> [p.objective_coefficient(x) for x in range(Integer(5))]
[1, 1, 2, 1, 3]
```

set_sense (*sense*)

Set the direction (maximization/minimization).

INPUT:

- *sense* – integer:
 - +1 => Maximization
 - -1 => Minimization

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False
```

set_variable_type (*variable*, *vtype*)

Set the type of a variable.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='cvxopt')
sage: p.add_variables(5)
4
sage: p.set_variable_type(3, -1)
sage: p.set_variable_type(3, -2)
Traceback (most recent call last):
...
ValueError: ...
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='cvxopt')
>>> p.add_variables(Integer(5))
4
>>> p.set_variable_type(Integer(3), -Integer(1))
```

(continues on next page)

(continued from previous page)

```
>>> p.set_variable_type(Integer(3), -Integer(2))
Traceback (most recent call last):
...
ValueError: ...
```

set_verbosity (*level*)

Do not apply for the cvxopt solver.

solve ()

Solve the problem.

Note

This method raises `MIPSolverException` exceptions when the solution cannot be computed for any reason (none exists, or the LP solver was not able to find it, etc...)

EXAMPLES:

```
sage: p = MixedIntegerLinearProgram(solver='cvxopt', maximization=False)
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(-4*x[0] - 5*x[1])
sage: p.add_constraint(2*x[0] + x[1] <= 3)
sage: p.add_constraint(2*x[1] + x[0] <= 3)
sage: N(p.solve(), digits=2)
-9.0

sage: p = MixedIntegerLinearProgram(solver='cvxopt', maximization=False)
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[0] + 2*x[1])
sage: p.add_constraint(-5*x[0] + x[1] <= 7)
sage: p.add_constraint(-5*x[0] + x[1] >= 7)
sage: p.add_constraint(x[0] + x[1] >= 26)
sage: p.add_constraint(x[0] >= 3)
sage: p.add_constraint(x[1] >= 4)
sage: N(p.solve(), digits=4)
48.83

sage: p = MixedIntegerLinearProgram(solver='cvxopt')
sage: x = p.new_variable(nonnegative=True)
sage: p.set_objective(x[0] + x[1] + 3*x[2])
sage: p.solver_parameter("show_progress", True)
sage: p.add_constraint(x[0] + 2*x[1] <= 4)
sage: p.add_constraint(5*x[2] - x[1] <= 8)
sage: N(p.solve(), digits=2)
      pcost      dcost      gap      pres      dres      k/t
...
      8.8
```

```
>>> from sage.all import *
>>> p = MixedIntegerLinearProgram(solver='cvxopt', maximization=False)
>>> x = p.new_variable(nonnegative=True)
```

(continues on next page)

(continued from previous page)

```

>>> p.set_objective(-Integer(4)*x[Integer(0)] - Integer(5)*x[Integer(1)])
>>> p.add_constraint(Integer(2)*x[Integer(0)] + x[Integer(1)] <= Integer(3))
>>> p.add_constraint(Integer(2)*x[Integer(1)] + x[Integer(0)] <= Integer(3))
>>> N(p.solve(), digits=Integer(2))
-9.0

>>> p = MixedIntegerLinearProgram(solver='cvxopt', maximization=False)
>>> x = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(0)] + Integer(2)*x[Integer(1)])
>>> p.add_constraint(-Integer(5)*x[Integer(0)] + x[Integer(1)] <= Integer(7))
>>> p.add_constraint(-Integer(5)*x[Integer(0)] + x[Integer(1)] >= Integer(7))
>>> p.add_constraint(x[Integer(0)] + x[Integer(1)] >= Integer(26))
>>> p.add_constraint(x[Integer(0)] >= Integer(3))
>>> p.add_constraint(x[Integer(1)] >= Integer(4))
>>> N(p.solve(), digits=Integer(4))
48.83

>>> p = MixedIntegerLinearProgram(solver='cvxopt')
>>> x = p.new_variable(nonnegative=True)
>>> p.set_objective(x[Integer(0)] + x[Integer(1)] + Integer(3)*x[Integer(2)])
>>> p.solver_parameter("show_progress", True)
>>> p.add_constraint(x[Integer(0)] + Integer(2)*x[Integer(1)] <= Integer(4))
>>> p.add_constraint(Integer(5)*x[Integer(2)] - x[Integer(1)] <= Integer(8))
>>> N(p.solve(), digits=Integer(2))
      pcost      dcost      gap      pres      dres      k/t
...
      8.8
    
```

When the optimal solution is not unique, CVXOPT as an interior point solver gives a different type of solution compared to the solvers that use the simplex method.

In the following example, the top face of the cube is optimal, and CVXOPT gives the center point of the top face, whereas the other tested solvers return a vertex:

```

sage: c = MixedIntegerLinearProgram(solver='cvxopt')
sage: p = MixedIntegerLinearProgram(solver='ppl')
sage: g = MixedIntegerLinearProgram()
sage: xc = c.new_variable(nonnegative=True)
sage: xp = p.new_variable(nonnegative=True)
sage: xg = g.new_variable(nonnegative=True)
sage: c.set_objective(xc[2])
sage: p.set_objective(xp[2])
sage: g.set_objective(xg[2])
sage: c.add_constraint(xc[0] <= 100)
sage: c.add_constraint(xc[1] <= 100)
sage: c.add_constraint(xc[2] <= 100)
sage: p.add_constraint(xp[0] <= 100)
sage: p.add_constraint(xp[1] <= 100)
sage: p.add_constraint(xp[2] <= 100)
sage: g.add_constraint(xg[0] <= 100)
sage: g.add_constraint(xg[1] <= 100)
sage: g.add_constraint(xg[2] <= 100)
sage: N(c.solve(), digits=4)
    
```

(continues on next page)

(continued from previous page)

```

100.0
sage: N(c.get_values(xc[0]), digits=3)
50.0
sage: N(c.get_values(xc[1]), digits=3)
50.0
sage: N(c.get_values(xc[2]), digits=4)
100.0
sage: N(p.solve(), digits=4)
100.0
sage: N(p.get_values(xp[0]), 2)
0.00
sage: N(p.get_values(xp[1]), 2)
0.00
sage: N(p.get_values(xp[2]), digits=4)
100.0
sage: N(g.solve(), digits=4)
100.0
sage: N(g.get_values(xg[0]), 2)      # abstol 1e-15
0.00
sage: N(g.get_values(xg[1]), 2)      # abstol 1e-15
0.00
sage: N(g.get_values(xg[2]), digits=4)
100.0

```

```

>>> from sage.all import *
>>> c = MixedIntegerLinearProgram(solver='cvxopt')
>>> p = MixedIntegerLinearProgram(solver='ppl')
>>> g = MixedIntegerLinearProgram()
>>> xc = c.new_variable(nonnegative=True)
>>> xp = p.new_variable(nonnegative=True)
>>> xg = g.new_variable(nonnegative=True)
>>> c.set_objective(xc[Integer(2)])
>>> p.set_objective(xp[Integer(2)])
>>> g.set_objective(xg[Integer(2)])
>>> c.add_constraint(xc[Integer(0)] <= Integer(100))
>>> c.add_constraint(xc[Integer(1)] <= Integer(100))
>>> c.add_constraint(xc[Integer(2)] <= Integer(100))
>>> p.add_constraint(xp[Integer(0)] <= Integer(100))
>>> p.add_constraint(xp[Integer(1)] <= Integer(100))
>>> p.add_constraint(xp[Integer(2)] <= Integer(100))
>>> g.add_constraint(xg[Integer(0)] <= Integer(100))
>>> g.add_constraint(xg[Integer(1)] <= Integer(100))
>>> g.add_constraint(xg[Integer(2)] <= Integer(100))
>>> N(c.solve(), digits=Integer(4))
100.0
>>> N(c.get_values(xc[Integer(0)]), digits=Integer(3))
50.0
>>> N(c.get_values(xc[Integer(1)]), digits=Integer(3))
50.0
>>> N(c.get_values(xc[Integer(2)]), digits=Integer(4))
100.0
>>> N(p.solve(), digits=Integer(4))

```

(continues on next page)

(continued from previous page)

```

100.0
>>> N(p.get_values(xp[Integer(0)]), Integer(2))
0.00
>>> N(p.get_values(xp[Integer(1)]), Integer(2))
0.00
>>> N(p.get_values(xp[Integer(2)]), digits=Integer(4))
100.0
>>> N(g.solve(), digits=Integer(4))
100.0
>>> N(g.get_values(xg[Integer(0)]), Integer(2))           # abstol 1e-15
0.00
>>> N(g.get_values(xg[Integer(1)]), Integer(2))           # abstol 1e-15
0.00
>>> N(g.get_values(xg[Integer(2)]), digits=Integer(4))
100.0

```

solver_parameter (*name*, *value=None*)

Return or define a solver parameter.

INPUT:

- *name* – string; the parameter
- *value* – the parameter's value if it is to be defined, or `None` (default) to obtain its current value

NoteThe list of available parameters is available at `solver_parameter()`.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.solver_parameter("show_progress")
False
sage: p.solver_parameter("show_progress", True)
sage: p.solver_parameter("show_progress")
True

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.solver_parameter("show_progress")
False
>>> p.solver_parameter("show_progress", True)
>>> p.solver_parameter("show_progress")
True

```

variable_lower_bound (*index*, *value=False*)

Return or define the lower bound on a variable.

INPUT:

- *index* – integer; the variable's id

- `value` – real value, or `None` to mean that the variable has not lower bound. When set to `False` (default), the method returns the current value.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.add_variable()
0
sage: p.col_bounds(0)
(0.0, None)
sage: p.variable_lower_bound(0, 5)
sage: p.col_bounds(0)
(5, None)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.add_variable()
0
>>> p.col_bounds(Integer(0))
(0.0, None)
>>> p.variable_lower_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(5, None)
```

`variable_upper_bound` (*index*, *value=False*)

Return or define the upper bound on a variable.

INPUT:

- `index` – integer; the variable's id
- `value` – real value, or `None` to mean that the variable has not upper bound. When set to `False` (default), the method returns the current value.

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.add_variable()
0
sage: p.col_bounds(0)
(0.0, None)
sage: p.variable_upper_bound(0, 5)
sage: p.col_bounds(0)
(0.0, 5)
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.add_variable()
0
>>> p.col_bounds(Integer(0))
(0.0, None)
```

(continues on next page)

(continued from previous page)

```
>>> p.variable_upper_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(0.0, 5)
```

Sage also supports, via optional packages, CBC (COIN-OR), CPLEX (ILOG), and Gurobi. In order to find out how to use them in Sage, please refer to the [Thematic Tutorial on Linear Programming](#).

The following backend is used for debugging and testing purposes.

11.8 Logging Backend

It records, for debugging and unit testing purposes, all calls to backend methods in one of three ways.

See `LoggingBackendFactory` for more information.

```
class sage.numerical.backends.logging_backend.LoggingBackend (backend, printing=True,
doctest=None, test_method=None,
base_ring=None)
```

Bases: `GenericBackend`

See `LoggingBackendFactory` for documentation.

EXAMPLES:

```
sage: import sage.numerical.backends.logging_backend
sage: from sage.numerical.backends.logging_backend import LoggingBackend
sage: from sage.numerical.backends.generic_backend import get_solver
sage: b = get_solver(solver = "GLPK")
sage: lb = LoggingBackend(backend=b)
sage: lb.add_variable(obj=42, name='Helloooooo')
# p.add_variable(obj=42, name='Helloooooo')
# result: 0
0
sage: lb.add_variable(obj=1789)
# p.add_variable(obj=1789)
# result: 1
1
```

```
>>> from sage.all import *
>>> import sage.numerical.backends.logging_backend
>>> from sage.numerical.backends.logging_backend import LoggingBackend
>>> from sage.numerical.backends.generic_backend import get_solver
>>> b = get_solver(solver = "GLPK")
>>> lb = LoggingBackend(backend=b)
>>> lb.add_variable(obj=Integer(42), name='Helloooooo')
# p.add_variable(obj=42, name='Helloooooo')
# result: 0
0
>>> lb.add_variable(obj=Integer(1789))
# p.add_variable(obj=1789)
# result: 1
1
```

add_col (*indices*, *coeffs*)

Add a column.

INPUT:

- *indices* – list of integers; this list contains the indices of the constraints in which the variable's coefficient is nonzero
- *coeffs* – list of real values; associates a coefficient to the variable in each of the constraints in which it appears. Namely, the *i*-th entry of *coeffs* corresponds to the coefficient of the variable in the constraint represented by the *i*-th entry in *indices*.

Note

indices and *coeffs* are expected to be of the same length.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.nrows()
0
sage: p.add_linear_constraints(5, 0, None)
sage: p.add_col(list(range(5)), list(range(5)))
sage: p.nrows()
5
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.nrows()
0
>>> p.add_linear_constraints(Integer(5), Integer(0), None)
>>> p.add_col(list(range(Integer(5))), list(range(Integer(5))))
>>> p.nrows()
5
```

add_linear_constraint (*coefficients*, *lower_bound*, *upper_bound*, *name=None*)

Add a linear constraint.

INPUT:

- *coefficients* – an iterable of pairs (*i*, *v*). In each pair, *i* is a variable index (integer) and *v* is a value (element of *base_ring()*).
- *lower_bound* – element of *base_ring()* or *None*; the lower bound
- *upper_bound* – element of *base_ring()* or *None*; the upper bound
- *name* – string or *None*; optional name for this row

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint( zip(range(5), range(5)), 2.0, 2.0)
sage: p.row(0)
([0, 1, 2, 3, 4], [0.0, 1.0, 2.0, 3.0, 4.0])
sage: p.row_bounds(0)
(2.0, 2.0)
sage: p.add_linear_constraint( zip(range(5), range(5)), 1.0, 1.0, name='foo')
sage: p.row_name(1)
'foo'
    
```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint( zip(range(Integer(5)), range(Integer(5))), ↵
↵RealNumber('2.0'), RealNumber('2.0'))
>>> p.row(Integer(0))
([0, 1, 2, 3, 4], [0.0, 1.0, 2.0, 3.0, 4.0])
>>> p.row_bounds(Integer(0))
(2.0, 2.0)
>>> p.add_linear_constraint( zip(range(Integer(5)), range(Integer(5))), ↵
↵RealNumber('1.0'), RealNumber('1.0'), name='foo')
>>> p.row_name(Integer(1))
'foo'
    
```

add_linear_constraint_vector (*degree, coefficients, lower_bound, upper_bound, name=None*)

Add a vector-valued linear constraint.

Note

This is the generic implementation, which will split the vector-valued constraint into components and add these individually. Backends are encouraged to replace it with their own optimized implementation.

INPUT:

- *degree* – integer; the vector degree, that is, the number of new scalar constraints
- *coefficients* – an iterable of pairs (*i*, *v*). In each pair, *i* is a variable index (integer) and *v* is a vector (real and of length *degree*).
- *lower_bound* – either a vector or *None*; the component-wise lower bound
- *upper_bound* – either a vector or *None*; the component-wise upper bound
- *name* – string or *None*; an optional name for all new rows

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: coeffs = ([0, vector([1, 2])], [1, vector([2, 3])])
sage: upper = vector([5, 5])
sage: lower = vector([0, 0])
sage: p.add_variables(2)
1
sage: p.add_linear_constraint_vector(2, coeffs, lower, upper, 'foo')

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> coeffs = ([Integer(0), vector([Integer(1), Integer(2)])], [Integer(1),
↳vector([Integer(2), Integer(3)])])
>>> upper = vector([Integer(5), Integer(5)])
>>> lower = vector([Integer(0), Integer(0)])
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint_vector(Integer(2), coeffs, lower, upper, 'foo')

```

add_linear_constraints (*number*, *lower_bound*, *upper_bound*, *names=None*)

Add 'number' linear constraints.

INPUT:

- *number* – integer; the number of constraints to add
- *lower_bound* – a lower bound, either a real value or None
- *upper_bound* – an upper bound, either a real value or None
- *names* – an optional list of names (default: None)

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
5
sage: p.add_linear_constraints(5, None, 2)
sage: p.row(4)
([], [])
sage: p.row_bounds(4)
(None, 2.0)

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
5
>>> p.add_linear_constraints(Integer(5), None, Integer(2))

```

(continues on next page)

(continued from previous page)

```
>>> p.row(Integer(4))
([], [])
>>> p.row_bounds(Integer(4))
(None, 2.0)
```

add_variable (*args, **kwdargs)

Add a variable.

This amounts to adding a new column to the matrix. By default, the variable is both positive and real.

INPUT:

- lower_bound – the lower bound of the variable (default: 0)
- upper_bound – the upper bound of the variable (default: None)
- binary – True if the variable is binary (default: False)
- continuous – True if the variable is continuous (default: True)
- integer – True if the variable is integral (default: False)
- obj – (optional) coefficient of this variable in the objective function (default: 0.0)
- name – an optional name for the newly added variable (default: None)

OUTPUT: the index of the newly created variable

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.ncols()
1
sage: p.add_variable(binary=True)
1
sage: p.add_variable(lower_bound=-2.0, integer=True)
2
sage: p.add_variable(continuous=True, integer=True)
Traceback (most recent call last):
...
ValueError: ...
sage: p.add_variable(name='x', obj=1.0)
3
sage: p.col_name(3)
'x'
sage: p.objective_coefficient(3)
1.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
```

(continues on next page)

(continued from previous page)

```

>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.ncols()
1
>>> p.add_variable(binary=True)
1
>>> p.add_variable(lower_bound=-RealNumber('2.0'), integer=True)
2
>>> p.add_variable(continuous=True, integer=True)
Traceback (most recent call last):
...
ValueError: ...
>>> p.add_variable(name='x', obj=RealNumber('1.0'))
3
>>> p.col_name(Integer(3))
'x'
>>> p.objective_coefficient(Integer(3))
1.0

```

add_variables (*args, **kwargs)Add n variables.

This amounts to adding new columns to the matrix. By default, the variables are both nonnegative and real.

INPUT:

- n – the number of new variables (must be > 0)
- `lower_bound` – the lower bound of the variable (default: 0)
- `upper_bound` – the upper bound of the variable (default: None)
- `binary` – True if the variable is binary (default: False)
- `continuous` – True if the variable is binary (default: True)
- `integer` – True if the variable is binary (default: False)
- `obj` – coefficient of all variables in the objective function (default: 0.0)
- `names` – list of names (default: None)

OUTPUT: the index of the variable created last

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variables(5)
4
sage: p.ncols()
5

```

(continues on next page)

(continued from previous page)

```
sage: p.add_variables(2, lower_bound=-2.0, integer=True, names=['a', 'b'])
6
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variables(Integer(5))
4
>>> p.ncols()
5
>>> p.add_variables(Integer(2), lower_bound=-RealNumber('2.0'), integer=True,
↳ names=['a', 'b'])
6
```

base_ring()

Return the base ring.

The backend's base ring can be overridden. It is best to run the tests with GLPK and override the base ring to \mathbb{Q} . Then default input to backend methods, prepared by *MixedIntegerLinearProgram*, depends on the base ring. This way input will be rational and so suitable for both exact and inexact methods; whereas output will be float and will thus trigger `assertAlmostEqual()` tests.

EXAMPLES:

```
sage: import sage.numerical.backends.logging_backend
sage: from sage.numerical.backends.logging_backend import LoggingBackend
sage: from sage.numerical.backends.generic_backend import get_solver
sage: b = get_solver(solver = "GLPK")
sage: lb = LoggingBackend(backend=b)
sage: lb.base_ring()
Real Double Field
sage: from sage.rings.rational_field import QQ
sage: lb = LoggingBackend(backend=b, base_ring=QQ)
sage: lb.base_ring()
Rational Field
```

```
>>> from sage.all import *
>>> import sage.numerical.backends.logging_backend
>>> from sage.numerical.backends.logging_backend import LoggingBackend
>>> from sage.numerical.backends.generic_backend import get_solver
>>> b = get_solver(solver = "GLPK")
>>> lb = LoggingBackend(backend=b)
>>> lb.base_ring()
Real Double Field
>>> from sage.rings.rational_field import QQ
>>> lb = LoggingBackend(backend=b, base_ring=QQ)
>>> lb.base_ring()
Rational Field
```

best_known_objective_bound()

Return the value of the currently best known bound.

This method returns the current best upper (resp. lower) bound on the optimal value of the objective function in a maximization (resp. minimization) problem. It is equal to the output of `get_objective_value()` if the MILP found an optimal solution, but it can differ if it was interrupted manually or after a time limit (cf `solver_parameter()`).

Note

Has no meaning unless `solve` has been called before.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
sage: b = p.new_variable(binary=True)
sage: for u,v in graphs.CycleGraph(5).edges(labels=False):
...:     p.add_constraint(b[u]+b[v]<=1)
sage: p.set_objective(p.sum(b[x] for x in range(5)))
sage: p.solve()
2.0
sage: pb = p.get_backend()
sage: pb.get_objective_value()
2.0
sage: pb.best_known_objective_bound()
2.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
>>> b = p.new_variable(binary=True)
>>> for u,v in graphs.CycleGraph(Integer(5)).edges(labels=False):
...:     p.add_constraint(b[u]+b[v]<=Integer(1))
>>> p.set_objective(p.sum(b[x] for x in range(Integer(5))))
>>> p.solve()
2.0
>>> pb = p.get_backend()
>>> pb.get_objective_value()
2.0
>>> pb.best_known_objective_bound()
2.0
```

`category()`

`col_bounds(index)`

Return the bounds of a specific variable.

INPUT:

- `index` – integer; the variable's id

OUTPUT:

A pair (`lower_bound`, `upper_bound`). Each of them can be set to `None` if the variable is not bounded in the corresponding direction, and is a real value otherwise.

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variable()
0
sage: p.col_bounds(0)
(0.0, None)
sage: p.variable_upper_bound(0, 5)
sage: p.col_bounds(0)
(0.0, 5.0)
    
```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variable()
0
>>> p.col_bounds(Integer(0))
(0.0, None)
>>> p.variable_upper_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(0.0, 5.0)
    
```

col_name (*index*)

Return the index-th column name.

INPUT:

- index – integer; the column id
- name – (char *) its name; when set to NULL (default), the method returns the current name

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variable(name="I am a variable")
1
sage: p.col_name(0)
'I am a variable'
    
```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variable(name="I am a variable")
1
>>> p.col_name(Integer(0))
'I am a variable'
    
```

copy ()

Return a copy of self.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
sage: b = p.new_variable()
sage: p.add_constraint(b[1] + b[2] <= 6)
sage: p.set_objective(b[1] + b[2])
sage: copy(p).solve()
6.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
>>> b = p.new_variable()
>>> p.add_constraint(b[Integer(1)] + b[Integer(2)] <= Integer(6))
>>> p.set_objective(b[Integer(1)] + b[Integer(2)])
>>> copy(p).solve()
6.0
```

dump (*filename*, *compress=True*)

Same as `self.save(filename, compress)`

dumps (*compress=True*)

Dump `self` to a string `s`, which can later be reconstituted as `self` using `loads(s)`.

There is an optional boolean argument `compress` which defaults to `True`.

EXAMPLES:

```
sage: from sage.misc.persist import comp
sage: O = SageObject()
sage: p_comp = O.dumps()
sage: p_uncomp = O.dumps(compress=False)
sage: comp.decompress(p_comp) == p_uncomp
True
sage: import pickletools
sage: pickletools.dis(p_uncomp)
0: \x80 PROTO      2
2: c    GLOBAL     'sage.structure.sage_object SageObject'
41: q   BININPUT   ...
43: )   EMPTY_TUPLE
44: \x81 NEWOBJ
45: q   BININPUT   ...
47: .   STOP
highest protocol among opcodes = 2
```

```
>>> from sage.all import *
>>> from sage.misc.persist import comp
>>> O = SageObject()
>>> p_comp = O.dumps()
>>> p_uncomp = O.dumps(compress=False)
>>> comp.decompress(p_comp) == p_uncomp
```

(continues on next page)

(continued from previous page)

```

True
>>> import pickletools
>>> pickletools.dis(p_uncomp)
  0: \x80 PROTO      2
  2: c    GLOBAL     'sage.structure.sage_object SageObject'
 41: q    BININPUT   ...
 43: )    EMPTY_TUPLE
 44: \x81 NEWOBJ
 45: q    BININPUT   ...
 47: .    STOP
highest protocol among opcodes = 2

```

get_custom_name()

Return the custom name of this object, or None if it is not renamed.

EXAMPLES:

```

sage: P.<x> = QQ[]
sage: P.get_custom_name() is None
True
sage: P.rename('A polynomial ring')
sage: P.get_custom_name()
'A polynomial ring'
sage: P.reset_name()
sage: P.get_custom_name() is None
True

```

```

>>> from sage.all import *
>>> P = QQ['x']; (x,) = P._first_ngens(1)
>>> P.get_custom_name() is None
True
>>> P.rename('A polynomial ring')
>>> P.get_custom_name()
'A polynomial ring'
>>> P.reset_name()
>>> P.get_custom_name() is None
True

```

get_objective_value()

Return the value of the objective function.

Note

Behavior is undefined unless `solve` has been called before.

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(2)

```

(continues on next page)

(continued from previous page)

```

1
sage: p.add_linear_constraint([(0,1), (1,2)], None, 3)
sage: p.set_objective([2, 5])
sage: p.solve()
0
sage: p.get_objective_value()
7.5
sage: p.get_variable_value(0)
0.0
sage: p.get_variable_value(1)
1.5

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([(Integer(0), Integer(1)), (Integer(1),
↳ Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> p.solve()
0
>>> p.get_objective_value()
7.5
>>> p.get_variable_value(Integer(0))
0.0
>>> p.get_variable_value(Integer(1))
1.5

```

get_relative_objective_gap()

Return the relative objective gap of the best known solution.

For a minimization problem, this value is computed by $(\text{bestinteger} - \text{bestobjective}) / (1e - 10 + |\text{bestobjective}|)$, where `bestinteger` is the value returned by `get_objective_value()` and `bestobjective` is the value returned by `best_known_objective_bound()`. For a maximization problem, the value is computed by $(\text{bestobjective} - \text{bestinteger}) / (1e - 10 + |\text{bestobjective}|)$.

Note

Has no meaning unless `solve` has been called before.

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
sage: b = p.new_variable(binary=True)
sage: for u,v in graphs.CycleGraph(5).edges(labels=False):
....:     p.add_constraint(b[u]+b[v]<=1)
sage: p.set_objective(p.sum(b[x] for x in range(5)))
sage: p.solve()

```

(continues on next page)

(continued from previous page)

```

2.0
sage: pb = p.get_backend()
sage: pb.get_objective_value()
2.0
sage: pb.get_relative_objective_gap()
0.0

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
>>> b = p.new_variable(binary=True)
>>> for u,v in graphs.CycleGraph(Integer(5)).edges(labels=False):
...     p.add_constraint(b[u]+b[v]<=Integer(1))
>>> p.set_objective(p.sum(b[x] for x in range(Integer(5))))
>>> p.solve()
2.0
>>> pb = p.get_backend()
>>> pb.get_objective_value()
2.0
>>> pb.get_relative_objective_gap()
0.0

```

get_variable_value (*variable*)

Return the value of a variable given by the solver.

NoteBehavior is undefined unless `solve` has been called before.

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([(0,1), (1, 2)], None, 3)
sage: p.set_objective([2, 5])
sage: p.solve()
0
sage: p.get_objective_value()
7.5
sage: p.get_variable_value(0)
0.0
sage: p.get_variable_value(1)
1.5

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")

```

(continues on next page)

(continued from previous page)

```

>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([(Integer(0), Integer(1)), (Integer(1), Integer(2)), (Integer(2), Integer(3))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> p.solve()
0
>>> p.get_objective_value()
7.5
>>> p.get_variable_value(Integer(0))
0.0
>>> p.get_variable_value(Integer(1))
1.5

```

is_maximization (*args, **kwdargs)

Test whether the problem is a maximization

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False

```

is_slack_variable_basic (*args, **kwdargs)

Test whether the slack variable of the given row is basic.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- index – integer; the variable's id

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(maximization=True,
...:                               solver="Nonexistent_LP_solver")
sage: x = p.new_variable(nonnegative=True)

```

(continues on next page)

(continued from previous page)

```

sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(5.5 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: # Backend-specific commands to instruct solver to use simplex method
↳here
sage: b.solve()
0
sage: b.is_slack_variable_basic(0)
True
sage: b.is_slack_variable_basic(1)
False

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(maximization=True,
...                               solver="Nonexistent_LP_solver")
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↳<= Integer(17))
>>> p.set_objective(RealNumber('5.5') * x[Integer(0)] - Integer(3) *
↳x[Integer(1)])
>>> b = p.get_backend()
>>> # Backend-specific commands to instruct solver to use simplex method here
>>> b.solve()
0
>>> b.is_slack_variable_basic(Integer(0))
True
>>> b.is_slack_variable_basic(Integer(1))
False

```

is_slack_variable_nonbasic_at_lower_bound(*args, **kwdargs)

Test whether the given variable is nonbasic at lower bound.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- index – integer; the variable's id

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(maximization=True,
...:                               solver="Nonexistent_LP_solver")
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(5.5 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: # Backend-specific commands to instruct solver to use simplex method
↳here

```

(continues on next page)

(continued from previous page)

```

sage: b.solve()
0
sage: b.is_slack_variable_nonbasic_at_lower_bound(0)
False
sage: b.is_slack_variable_nonbasic_at_lower_bound(1)
True

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(maximization=True,
...                               solver="Nonexistent_LP_solver")
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↳<= Integer(17))
>>> p.set_objective(RealNumber('5.5') * x[Integer(0)] - Integer(3) *
↳x[Integer(1)])
>>> b = p.get_backend()
>>> # Backend-specific commands to instruct solver to use simplex method here
>>> b.solve()
0
>>> b.is_slack_variable_nonbasic_at_lower_bound(Integer(0))
False
>>> b.is_slack_variable_nonbasic_at_lower_bound(Integer(1))
True

```

is_variable_basic (*args, **kwdargs)

Test whether the given variable is basic.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- index – integer; the variable's id

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(maximization=True,
...:                               solver="Nonexistent_LP_solver")
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(5.5 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: # Backend-specific commands to instruct solver to use simplex method
↳here
sage: b.solve()
0
sage: b.is_variable_basic(0)
True
sage: b.is_variable_basic(1)
False

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(maximization=True,
...                               solver="Nonexistent_LP_solver")
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↳<= Integer(17))
>>> p.set_objective(RealNumber('5.5') * x[Integer(0)] - Integer(3) * x[Integer(1)])
>>> b = p.get_backend()
>>> # Backend-specific commands to instruct solver to use simplex method here
>>> b.solve()
0
>>> b.is_variable_basic(Integer(0))
True
>>> b.is_variable_basic(Integer(1))
False
    
```

is_variable_binary (*args, **kwdargs)

Test whether the given variable is of binary type.

INPUT:

- index – integer; the variable's id

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.set_variable_type(0,0)
sage: p.is_variable_binary(0)
True
    
```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.set_variable_type(Integer(0), Integer(0))
>>> p.is_variable_binary(Integer(0))
True
    
```

is_variable_continuous (*args, **kwdargs)

Test whether the given variable is of continuous/real type.

INPUT:

- `index` – integer; the variable's id

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.is_variable_continuous(0)
True
sage: p.set_variable_type(0,1)
sage: p.is_variable_continuous(0)
False
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.is_variable_continuous(Integer(0))
True
>>> p.set_variable_type(Integer(0), Integer(1))
>>> p.is_variable_continuous(Integer(0))
False
```

`is_variable_integer` (*args, **kwdargs)

Test whether the given variable is of integer type.

INPUT:

- `index` – integer; the variable's id

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.set_variable_type(0,1)
sage: p.is_variable_integer(0)
True
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
```

(continues on next page)

(continued from previous page)

```

>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.set_variable_type(Integer(0), Integer(1))
>>> p.is_variable_integer(Integer(0))
True

```

is_variable_nonbasic_at_lower_bound(*args, **kwdargs)

Test whether the given variable is nonbasic at lower bound.

This assumes that the problem has been solved with the simplex method and a basis is available. Otherwise an exception will be raised.

INPUT:

- index – integer; the variable's id

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(maximization=True,
...:                               solver="Nonexistent_LP_solver")
sage: x = p.new_variable(nonnegative=True)
sage: p.add_constraint(-x[0] + x[1] <= 2)
sage: p.add_constraint(8 * x[0] + 2 * x[1] <= 17)
sage: p.set_objective(5.5 * x[0] - 3 * x[1])
sage: b = p.get_backend()
sage: # Backend-specific commands to instruct solver to use simplex method
↪here
sage: b.solve()
0
sage: b.is_variable_nonbasic_at_lower_bound(0)
False
sage: b.is_variable_nonbasic_at_lower_bound(1)
True

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(maximization=True,
...:                               solver="Nonexistent_LP_solver")
>>> x = p.new_variable(nonnegative=True)
>>> p.add_constraint(-x[Integer(0)] + x[Integer(1)] <= Integer(2))
>>> p.add_constraint(Integer(8) * x[Integer(0)] + Integer(2) * x[Integer(1)]
↪<= Integer(17))
>>> p.set_objective(RealNumber('5.5') * x[Integer(0)] - Integer(3) *
↪x[Integer(1)])
>>> b = p.get_backend()
>>> # Backend-specific commands to instruct solver to use simplex method here
>>> b.solve()
0
>>> b.is_variable_nonbasic_at_lower_bound(Integer(0))
False

```

(continues on next page)

(continued from previous page)

```
>>> b.is_variable_nonbasic_at_lower_bound(Integer(1))
True
```

ncols (*args, **kwdargs)

Return the number of columns/variables.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variables(2)
1
sage: p.ncols()
2
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variables(Integer(2))
1
>>> p.ncols()
2
```

nrows (*args, **kwdargs)

Return the number of rows/constraints.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.nrows()
0
sage: p.add_linear_constraints(2, 2.0, None)
sage: p.nrows()
2
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.nrows()
0
>>> p.add_linear_constraints(Integer(2), RealNumber('2.0'), None)
>>> p.nrows()
2
```

objective_coefficient (*variable, coeff=None*)

Set or get the coefficient of a variable in the objective function

INPUT:

- *variable* – integer; the variable's id
- *coeff* – double; its coefficient

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variable()
0
sage: p.objective_coefficient(0)
0.0
sage: p.objective_coefficient(0,2)
sage: p.objective_coefficient(0)
2.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variable()
0
>>> p.objective_coefficient(Integer(0))
0.0
>>> p.objective_coefficient(Integer(0), Integer(2))
>>> p.objective_coefficient(Integer(0))
2.0
```

objective_constant_term (*d=None*)

Set or get the constant term in the objective function.

INPUT:

- *d* – double; its coefficient. If *None* (default), return the current value.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.objective_constant_term()
0.0
sage: p.objective_constant_term(42)
sage: p.objective_constant_term()
42.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
```

(continues on next page)

(continued from previous page)

```

>>> p.objective_constant_term()
0.0
>>> p.objective_constant_term(Integer(42))
>>> p.objective_constant_term()
42.0

```

parent ()Return the type of `self` to support the coercion framework.

EXAMPLES:

```

sage: t = log(sqrt(2) - 1) + log(sqrt(2) + 1); t #_
↳needs sage.symbolic
log(sqrt(2) + 1) + log(sqrt(2) - 1)
sage: u = t.maxima_methods() #_
↳needs sage.symbolic
sage: u.parent() #_
↳needs sage.symbolic
<class 'sage.symbolic.maxima_wrapper.MaximaWrapper'>

```

```

>>> from sage.all import *
>>> t = log(sqrt(Integer(2)) - Integer(1)) + log(sqrt(Integer(2)) +
↳Integer(1)); t # needs sage.symbolic
log(sqrt(2) + 1) + log(sqrt(2) - 1)
>>> u = t.maxima_methods() #_
↳needs sage.symbolic
>>> u.parent() #_
↳needs sage.symbolic
<class 'sage.symbolic.maxima_wrapper.MaximaWrapper'>

```

problem_name (name=None)

Return or define the problem's name.

INPUT:

- `name` – string; the problem's name. When set to `None` (default), the method returns the problem's name.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver") # optional -_
↳Nonexistent_LP_solver
sage: p.problem_name("There once was a french fry") # optional - Nonexistent_
↳LP_solver
sage: print(p.problem_name()) # optional - Nonexistent_
↳LP_solver
There once was a french fry

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver") # optional - Nonexistent_
↳LP_solver
>>> p.problem_name("There once was a french fry") # optional - Nonexistent_LP_

```

(continues on next page)

(continued from previous page)

```

↪solver
>>> print(p.problem_name())           # optional - Nonexistent_LP_
↪solver
There once was a french fry

```

remove_constraint (*i*)

Remove a constraint.

INPUT:

- *i* – index of the constraint to remove

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
sage: v = p.new_variable(nonnegative=True)
sage: x,y = v[0], v[1]
sage: p.add_constraint(2*x + 3*y, max=6)
sage: p.add_constraint(3*x + 2*y, max=6)
sage: p.set_objective(x + y + 7)
sage: p.set_integer(x); p.set_integer(y)
sage: p.solve()
9.0
sage: p.remove_constraint(0)
sage: p.solve()
10.0
sage: p.get_values([x,y])
[0.0, 3.0]

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(solver="Nonexistent_LP_solver")
>>> v = p.new_variable(nonnegative=True)
>>> x,y = v[Integer(0)], v[Integer(1)]
>>> p.add_constraint(Integer(2)*x + Integer(3)*y, max=Integer(6))
>>> p.add_constraint(Integer(3)*x + Integer(2)*y, max=Integer(6))
>>> p.set_objective(x + y + Integer(7))
>>> p.set_integer(x); p.set_integer(y)
>>> p.solve()
9.0
>>> p.remove_constraint(Integer(0))
>>> p.solve()
10.0
>>> p.get_values([x,y])
[0.0, 3.0]

```

remove_constraints (*constraints*)

Remove several constraints.

INPUT:

- *constraints* – an iterable containing the indices of the rows to remove

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(2)
1
sage: p.add_linear_constraint([(0, 2), (1, 3)], None, 6)
sage: p.add_linear_constraint([(0, 3), (1, 2)], None, 6)
sage: p.remove_constraints([0, 1])

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(2))
1
>>> p.add_linear_constraint([(Integer(0), Integer(2)), (Integer(1),
↳Integer(3))], None, Integer(6))
>>> p.add_linear_constraint([(Integer(0), Integer(3)), (Integer(1),
↳Integer(2))], None, Integer(6))
>>> p.remove_constraints([Integer(0), Integer(1)])

```

rename ($x=None$)

Change self so it prints as x, where x is a string.

If x is None, the existing custom name is removed.

Note

This is *only* supported for Python classes that derive from SageObject.

EXAMPLES:

```

sage: x = PolynomialRing(QQ, 'x', sparse=True).gen()
sage: g = x^3 + x - 5
sage: g
x^3 + x - 5
sage: g.rename('a polynomial')
sage: g
a polynomial
sage: g + x
x^3 + 2*x - 5
sage: h = g^100
sage: str(h)[:20]
'x^300 + 100*x^298 - '
sage: h.rename('x^300 + ...')
sage: h
x^300 + ...
sage: g.rename(None)
sage: g
x^3 + x - 5

```

```

>>> from sage.all import *
>>> x = PolynomialRing(QQ, 'x', sparse=True).gen()
>>> g = x**Integer(3) + x - Integer(5)
>>> g
x^3 + x - 5
>>> g.rename('a polynomial')
>>> g
a polynomial
>>> g + x
x^3 + 2*x - 5
>>> h = g**Integer(100)
>>> str(h)[:Integer(20)]
'x^300 + 100*x^298 - '
>>> h.rename('x^300 + ...')
>>> h
x^300 + ...
>>> g.rename(None)
>>> g
x^3 + x - 5
    
```

Real numbers are not Python classes, so rename is not supported:

```

sage: a = 3.14
sage: type(a) #_
↪needs sage.rings.real_mpfr
<... 'sage.rings.real_mpfr.RealLiteral'>
sage: a.rename('pi') #_
↪needs sage.rings.real_mpfr
Traceback (most recent call last):
...
NotImplementedError: object does not support renaming: 3.140000000000000
    
```

```

>>> from sage.all import *
>>> a = RealNumber('3.14')
>>> type(a) #_
↪needs sage.rings.real_mpfr
<... 'sage.rings.real_mpfr.RealLiteral'>
>>> a.rename('pi') #_
↪needs sage.rings.real_mpfr
Traceback (most recent call last):
...
NotImplementedError: object does not support renaming: 3.140000000000000
    
```

Note

The reason C-extension types are not supported by default is if they were then every single one would have to carry around an extra attribute, which would be slower and waste a lot of memory.

To support them for a specific class, add a `cdef public _SageObject__custom_name` attribute.

`reset_name()`

Remove the custom name of an object.

EXAMPLES:

```
sage: P.<x> = QQ[]
sage: P
Univariate Polynomial Ring in x over Rational Field
sage: P.rename('A polynomial ring')
sage: P
A polynomial ring
sage: P.reset_name()
sage: P
Univariate Polynomial Ring in x over Rational Field
```

```
>>> from sage.all import *
>>> P = QQ['x']; (x,) = P._first_ngens(1)
>>> P
Univariate Polynomial Ring in x over Rational Field
>>> P.rename('A polynomial ring')
>>> P
A polynomial ring
>>> P.reset_name()
>>> P
Univariate Polynomial Ring in x over Rational Field
```

row(*i*)

Return a row.

INPUT:

- *index* – integer; the constraint's id

OUTPUT:

A pair (*indices*, *coeffs*) where *indices* lists the entries whose coefficient is nonzero, and to which *coeffs* associates their coefficient on the model of the `add_linear_constraint` method.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(zip(range(5), range(5)), 2, 2)
sage: p.row(0)
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0]) ## FIXME: Why backwards?
sage: p.row_bounds(0)
(2.0, 2.0)
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))), 2,
```

(continues on next page)

(continued from previous page)

```

↪Integer(2), Integer(2))
>>> p.row(Integer(0))
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0]) ## FIXME: Why backwards?
>>> p.row_bounds(Integer(0))
(2.0, 2.0)

```

row_bounds (*index*)

Return the bounds of a specific constraint.

INPUT:

- *index* – integer; the constraint's id

OUTPUT:

A pair (*lower_bound*, *upper_bound*). Each of them can be set to *None* if the constraint is not bounded in the corresponding direction, and is a real value otherwise.

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(list(range(5)), list(range(5)), 2, 2)
sage: p.row(0)
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0]) ## FIXME: Why backwards?
sage: p.row_bounds(0)
(2.0, 2.0)

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(list(range(Integer(5))), list(range(Integer(5))), ↪
↪Integer(2), Integer(2))
>>> p.row(Integer(0))
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0]) ## FIXME: Why backwards?
>>> p.row_bounds(Integer(0))
(2.0, 2.0)

```

row_name (*index*)Return the *index*-th row name.

INPUT:

- *index* – integer; the row's id

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")

```

(continues on next page)

(continued from previous page)

```
sage: p.add_linear_constraints(1, 2, None, names=['Empty constraint 1'])
sage: p.row_name(0)
'Empty constraint 1'
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_linear_constraints(Integer(1), Integer(2), None, names=['Empty_
↳constraint 1'])
>>> p.row_name(Integer(0))
'Empty constraint 1'
```

save (*filename=None, compress=True*)

Save self to the given filename.

EXAMPLES:

```
sage: # needs sage.symbolic
sage: x = SR.var("x")
sage: f = x^3 + 5
sage: from tempfile import NamedTemporaryFile
sage: with NamedTemporaryFile(suffix='.sobj') as t:
....:     f.save(t.name)
....:     load(t.name)
x^3 + 5
```

```
>>> from sage.all import *
>>> # needs sage.symbolic
>>> x = SR.var("x")
>>> f = x**Integer(3) + Integer(5)
>>> from tempfile import NamedTemporaryFile
>>> with NamedTemporaryFile(suffix='.sobj') as t:
...     f.save(t.name)
...     load(t.name)
x^3 + 5
```

set_objective (*coeff, d=0.0*)

Set the objective function.

INPUT:

- *coeff* – list of real values, whose *i*-th element is the coefficient of the *i*-th variable in the objective function
- *d* – double; the constant term in the linear function (set to 0 by default)

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
4
```

(continues on next page)

(continued from previous page)

```
sage: p.set_objective([1, 1, 2, 1, 3])
sage: [p.objective_coefficient(x) for x in range(5)]
[1.0, 1.0, 2.0, 1.0, 3.0]
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
4
>>> p.set_objective([Integer(1), Integer(1), Integer(2), Integer(1), Integer(3)])
>>> [p.objective_coefficient(x) for x in range(Integer(5))]
[1.0, 1.0, 2.0, 1.0, 3.0]
```

Constants in the objective function are respected:

```
sage: # optional - nonexistent_lp_solver
sage: p = MixedIntegerLinearProgram(solver='Nonexistent_LP_solver')
sage: x,y = p[0], p[1]
sage: p.add_constraint(2*x + 3*y, max=6)
sage: p.add_constraint(3*x + 2*y, max=6)
sage: p.set_objective(x + y + 7)
sage: p.set_integer(x); p.set_integer(y)
sage: p.solve()
9.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = MixedIntegerLinearProgram(solver='Nonexistent_LP_solver')
>>> x,y = p[Integer(0)], p[Integer(1)]
>>> p.add_constraint(Integer(2)*x + Integer(3)*y, max=Integer(6))
>>> p.add_constraint(Integer(3)*x + Integer(2)*y, max=Integer(6))
>>> p.set_objective(x + y + Integer(7))
>>> p.set_integer(x); p.set_integer(y)
>>> p.solve()
9.0
```

set_sense (*sense*)

Set the direction (maximization/minimization).

INPUT:

- *sense* – integer:
 - +1 => Maximization
 - -1 => Minimization

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
```

(continues on next page)

(continued from previous page)

```
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False
```

set_variable_type (*variable*, *vtype*)

Set the type of a variable.

INPUT:

- *variable* – integer; the variable's id
- *vtype* – integer:
 - 1 Integer
 - 0 Binary
 - -1 Continuous

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.set_variable_type(0,1)
sage: p.is_variable_integer(0)
True
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.set_variable_type(Integer(0), Integer(1))
>>> p.is_variable_integer(Integer(0))
True
```

set_verbosity (*level*)

Set the log (verbosity) level.

INPUT:

- *level* – integer; from 0 (no verbosity) to 3

EXAMPLES:

```
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver") # optional -
↳Nonexistent_LP_solver
sage: p.set_verbosity(2) # optional -
↳Nonexistent_LP_solver
```

```
>>> from sage.all import *
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver") # optional - Nonexistent_
↳LP_solver
>>> p.set_verbosity(Integer(2)) # optional -
↳Nonexistent_LP_solver
```

solve (**args, **kwdargs*)

Solve the problem.

Note

This method raises `MIPSolverException` exceptions when the solution cannot be computed for any reason (none exists, or the LP solver was not able to find it, etc...)

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_linear_constraints(5, 0, None)
sage: p.add_col(list(range(5)), list(range(5)))
sage: p.solve()
0
sage: p.objective_coefficient(0,1)
sage: p.solve()
Traceback (most recent call last):
...
MIPSolverException: ...
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_linear_constraints(Integer(5), Integer(0), None)
>>> p.add_col(list(range(Integer(5))), list(range(Integer(5))))
>>> p.solve()
0
```

(continues on next page)

(continued from previous page)

```
>>> p.objective_coefficient(Integer(0), Integer(1))
>>> p.solve()
Traceback (most recent call last):
...
MIPSolverException: ...
```

solver_parameter (*name*, *value=None*)

Return or define a solver parameter.

INPUT:

- *name* – string; the parameter
- *value* – the parameter's value if it is to be defined, or `None` (default) to obtain its current value

NoteThe list of available parameters is available at `solver_parameter()`.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.solver_parameter("timelimit")
sage: p.solver_parameter("timelimit", 60)
sage: p.solver_parameter("timelimit")
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.solver_parameter("timelimit")
>>> p.solver_parameter("timelimit", Integer(60))
>>> p.solver_parameter("timelimit")
```

variable_lower_bound (*index*, *value=False*)

Return or define the lower bound on a variable.

INPUT:

- *index* – integer; the variable's id
- *value* – real value, or `None` to mean that the variable has not lower bound. When set to `False` (default), the method returns the current value.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variable()
0
sage: p.col_bounds(0)
```

(continues on next page)

(continued from previous page)

```
(0.0, None)
sage: p.variable_lower_bound(0, 5)
sage: p.col_bounds(0)
(5.0, None)
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variable()
0
>>> p.col_bounds(Integer(0))
(0.0, None)
>>> p.variable_lower_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(5.0, None)
```

variable_upper_bound (*index, value=False*)

Return or define the upper bound on a variable.

INPUT:

- *index* – integer; the variable's id
- *value* – real value, or `None` to mean that the variable has not upper bound. When set to `False` (default), the method returns the current value.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variable()
0
sage: p.col_bounds(0)
(0.0, None)
sage: p.variable_upper_bound(0, 5)
sage: p.col_bounds(0)
(0.0, 5.0)
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variable()
0
>>> p.col_bounds(Integer(0))
(0.0, None)
>>> p.variable_upper_bound(Integer(0), Integer(5))
>>> p.col_bounds(Integer(0))
(0.0, 5.0)
```

write_lp (*name*)Write the problem to a `.lp` file.

INPUT:

- filename – string

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(2)
2
sage: p.add_linear_constraint([(0, 1), (1, 2)], None, 3)
sage: p.set_objective([2, 5])
sage: from tempfile import NamedTemporaryFile
sage: with NamedTemporaryFile(suffix='.lp') as f:
.....:     p.write_lp(f.name)
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(2))
2
>>> p.add_linear_constraint([(Integer(0), Integer(1)), (Integer(1),
↳Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> from tempfile import NamedTemporaryFile
>>> with NamedTemporaryFile(suffix='.lp') as f:
...     p.write_lp(f.name)
```

write_mps (name, modern)

Write the problem to a .mps file.

INPUT:

- filename – string

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(2)
2
sage: p.add_linear_constraint([(0, 1), (1, 2)], None, 3)
sage: p.set_objective([2, 5])
sage: from tempfile import NamedTemporaryFile
sage: with NamedTemporaryFile(suffix='.lp') as f:
.....:     p.write_lp(f.name)
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(2))
```

(continues on next page)

(continued from previous page)

```

2
>>> p.add_linear_constraint([(Integer(0), Integer(1)), (Integer(1),
↳Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> from tempfile import NamedTemporaryFile
>>> with NamedTemporaryFile(suffix='.lp') as f:
...     p.write_lp(f.name)

```

```

sage.numerical.backends.logging_backend.LoggingBackendFactory (solver=None, printing=True,
                                                              doctest_file=None,
                                                              test_method_file=None,
                                                              test_method=None,
                                                              base_ring=Rational Field)

```

Factory that constructs a *LoggingBackend* for debugging and testing.

An instance of it can be passed as the solver argument of *sage.numerical.backends.generic_backend.get_solver()* and *MixedIntegerLinearProgram*.

EXAMPLES:

Assume that we have the following function that does some computation using *MixedIntegerLinearProgram* (or MIP backend methods), and suppose we have observed that it works with the GLPK backend, but not with the COIN backend:

```

sage: def compute_something(solver='GLPK'):
...:     from sage.numerical.mip import MIPSolverException
...:     mip = MixedIntegerLinearProgram(solver=solver)
...:     lb = mip.get_backend()
...:     lb.add_variable(obj=42, name='Helloooooo')
...:     lb.add_variable(obj=1789)
...:     try:
...:         lb.solve()
...:     except MIPSolverException:
...:         return 4711
...:     else:
...:         return 91

```

```

>>> from sage.all import *
>>> def compute_something(solver='GLPK'):
...     from sage.numerical.mip import MIPSolverException
...     mip = MixedIntegerLinearProgram(solver=solver)
...     lb = mip.get_backend()
...     lb.add_variable(obj=Integer(42), name='Helloooooo')
...     lb.add_variable(obj=Integer(1789))
...     try:
...         lb.solve()
...     except MIPSolverException:
...         return Integer(4711)
...     else:
...         return Integer(91)

```

We can investigate what the backend methods are doing by running a *LoggingBackend* in its in-terminal logging mode:

```

sage: import sage.numerical.backends.logging_backend
sage: from sage.numerical.backends.logging_backend import LoggingBackendFactory
sage: compute_something(solver = LoggingBackendFactory(solver='GLPK'))
# p = get_solver(solver='GLPK')
# p.add_variable(obj=42, name='Helloooooo')
# result: 0
# p.add_variable(obj=1789)
# result: 1
# p.solve()
# exception: GLPK: The LP (relaxation) problem has no dual feasible solution
4711

```

```

>>> from sage.all import *
>>> import sage.numerical.backends.logging_backend
>>> from sage.numerical.backends.logging_backend import LoggingBackendFactory
>>> compute_something(solver = LoggingBackendFactory(solver='GLPK'))
# p = get_solver(solver='GLPK')
# p.add_variable(obj=42, name='Helloooooo')
# result: 0
# p.add_variable(obj=1789)
# result: 1
# p.solve()
# exception: GLPK: The LP (relaxation) problem has no dual feasible solution
4711

```

By replacing 'GLPK' by 'COIN' above, we can then compare the two logs and see where they differ.

Imagine that we have now fixed the bug in the COIN backend, and we want to add a doctest that documents this fact. We do not want to call `compute_something` in the doctest, but rather just have a sequence of calls to backend methods.

We can have the doctest autogenerated by running a `LoggingBackend` in its doctest-writing mode:

```

sage: fname = tmp_filename()
sage: compute_something(solver = LoggingBackendFactory(solver='GLPK',
↳printing=False,
.....:                                     doctest_file=fname))
4711
sage: with open(fname) as f:
.....:     for line in f.readlines(): _ = sys.stdout.write('|{}'.format(line))
|     sage: p = get_solver(solver='GLPK')
|     sage: p.add_variable(obj=42, name='Helloooooo')
|     0
|     sage: p.add_variable(obj=1789)
|     1
|     sage: p.solve()
|     Traceback (most recent call last):
|     ...
|     MIPSolverException: GLPK: The LP (relaxation) problem has no dual
↳feasible solution

```

```

>>> from sage.all import *
>>> fname = tmp_filename()

```

(continues on next page)

(continued from previous page)

```

>>> compute_something(solver = LoggingBackendFactory(solver='GLPK',
↳printing=False,
...
doctest_file=fname))
4711
>>> with open(fname) as f:
...     for line in f.readlines(): _ = sys.stdout.write('|{}'.format(line))
|         sage: p = get_solver(solver='GLPK')
|         sage: p.add_variable(obj=42, name='Helloooooo')
|         0
|         sage: p.add_variable(obj=1789)
|         1
|         sage: p.solve()
|         Traceback (most recent call last):
|         ...
|         MIPSolverException: GLPK: The LP (relaxation) problem has no dual
↳feasible solution

```

We then copy from the generated file and paste into the source code of the COIN backend.

If this test seems valuable enough that all backends should be tested against it, we should create a test method instead of a docstring.

We can have the test method autogenerated by running a *LoggingBackend* in its test-method-writing mode:

```

sage: fname = tmp_filename()
sage: compute_something(solver= LoggingBackendFactory(solver='GLPK',
↳printing=False,
...:
doctest_file=fname,
...:
test_method='something'))
4711
sage: with open(fname) as f:
...:     for line in f.readlines(): _ = sys.stdout.write('|{}'.format(line))
|
| @classmethod
| def _test_something(cls, tester=None, **options):
|     ...
|     Run tests on ...
|
|     TESTS::
|
|         sage: from sage.numerical.backends.generic_backend import
↳GenericBackend
|         sage: p = GenericBackend()
|         sage: p._test_something()
|         Traceback (most recent call last):
|         ...
|         NotImplementedError
|
|     ...
|     p = cls() # fresh instance of the backend
|     if tester is None:
|         tester = p._tester(**options)
|     tester.assertEqual(p.add_variable(obj=42, name='Helloooooo'), 0)
|     tester.assertEqual(p.add_variable(obj=1789), 1)

```

(continues on next page)

(continued from previous page)

```

|         with tester.assertRaises(MIPSolverException) as cm:
|             p.solve()

```

```

>>> from sage.all import *
>>> fname = tmp_filename()
>>> compute_something(solver= LoggingBackendFactory(solver='GLPK', printing=False,
...                                               test_method_file=fname,
...                                               test_method='something'))
...
4711
>>> with open(fname) as f:
...     for line in f.readlines(): _ = sys.stdout.write('{}\n'.format(line))
|
|     @classmethod
|     def _test_something(cls, tester=None, **options):
|         ...
|         Run tests on ...
|
|         TESTS::
|
|             sage: from sage.numerical.backends.generic_backend import_
↳GenericBackend
|             sage: p = GenericBackend()
|             sage: p._test_something()
|             Traceback (most recent call last):
|                 ...
|             NotImplementedError
|
|         ...
|         p = cls() # fresh instance of the backend
|         if tester is None:
|             tester = p._tester(**options)
|         tester.assertEqual(p.add_variable(obj=42, name='Helloooooo'), 0)
|         tester.assertEqual(p.add_variable(obj=1789), 1)
|         with tester.assertRaises(MIPSolverException) as cm:
|             p.solve()

```

We then copy from the generated file and paste into the source code of the generic backend, where all test methods are defined.

If `test_method_file` is not provided, a default output file name will be computed from `test_method`.

SEMIDEFINITE OPTIMIZATION (SDP) SOLVER BACKENDS

12.1 Generic Backend for SDP solvers

This class only lists the methods that should be defined by any interface with a SDP Solver. All these methods immediately raise `NotImplementedError` exceptions when called, and are obviously meant to be replaced by the solver-specific method. This file can also be used as a template to create a new interface : one would only need to replace the occurrences of `"Nonexistent_SDP_solver"` by the solver's name, and replace `GenericSDPBackend` by `SolverName(GenericSDPBackend)` so that the new solver extends this class.

AUTHORS:

- Ingolfur Edvardsson (2014-07): initial implementation

class sage.numerical.backends.generic_sdp_backend.**GenericSDPBackend**

Bases: object

add_linear_constraint (*coefficients, name=None*)

Add a linear constraint.

INPUT:

- *coefficients* an iterable with (c, v) pairs where c is a variable index (integer) and v is a value (real value).
- *lower_bound* – a lower bound, either a real value or None
- *upper_bound* – an upper bound, either a real value or None
- *name* – an optional name for this row (default: None)

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
4
sage: p.add_linear_constraint(zip(range(5), range(5)), 2.0, 2.0)
sage: p.row(0)
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0]) # optional -
↳Nonexistent_LP_solver
sage: p.row_bounds(0)
(2.0, 2.0)
sage: p.add_linear_constraint(zip(range(5), range(5)), 1.0, 1.0, name='foo')
sage: p.row_name(-1)
"foo"
```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
4
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))),
↳RealNumber('2.0'), RealNumber('2.0'))
>>> p.row(Integer(0))
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0]) # optional -
↳Nonexistent_LP_solver
>>> p.row_bounds(Integer(0))
(2.0, 2.0)
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))),
↳RealNumber('1.0'), RealNumber('1.0'), name='foo')
>>> p.row_name(-Integer(1))
"foo"
    
```

add_linear_constraints (*number*, *names=None*)

Add constraints.

INPUT:

- *number* – integer; the number of constraints to add
- *lower_bound* – a lower bound, either a real value or None
- *upper_bound* – an upper bound, either a real value or None
- *names* – an optional list of names (default: None)

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
5
sage: p.add_linear_constraints(5, None, 2)
sage: p.row(4)
([], [])
sage: p.row_bounds(4)
(None, 2.0)
    
```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
5
>>> p.add_linear_constraints(Integer(5), None, Integer(2))
>>> p.row(Integer(4))
([], [])
>>> p.row_bounds(Integer(4))
(None, 2.0)
    
```

add_variable (*obj=0.0, name=None*)

Add a variable.

This amounts to adding a new column to the matrix. By default, the variable is both positive and real.

INPUT:

- *obj* – (optional) coefficient of this variable in the objective function (default: 0.0)
- *name* – an optional name for the newly added variable (default: None)

OUTPUT: the index of the newly created variable

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variable()
0
sage: p.ncols()
1
sage: p.add_variable(name='x', obj=1.0)
3
sage: p.col_name(3)
'x'
sage: p.objective_coefficient(3)
1.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variable()
0
>>> p.ncols()
1
>>> p.add_variable(name='x', obj=RealNumber('1.0'))
3
>>> p.col_name(Integer(3))
'x'
>>> p.objective_coefficient(Integer(3))
1.0
```

add_variables (*n, names=None*)

Add *n* variables.

This amounts to adding new columns to the matrix. By default, the variables are both positive and real.

INPUT:

- *n* – the number of new variables (must be > 0)
- *obj* – coefficient of all variables in the objective function (default: 0.0)

- `names` – list of names (default: None)

OUTPUT: the index of the variable created last

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variables(5)
4
sage: p.ncols()
5
sage: p.add_variables(2, lower_bound=-2.0, integer=True, names=['a', 'b'])
6
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variables(Integer(5))
4
>>> p.ncols()
5
>>> p.add_variables(Integer(2), lower_bound=-RealNumber('2.0'), integer=True,
↳ names=['a', 'b'])
6
```

base_ring()

The base ring.

col_name(index)

Return the index-th col name.

INPUT:

- `index` – integer; the col's id
- `name` – (char *) its name; when set to NULL (default), the method returns the current name

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variable(name="I am a variable")
1
sage: p.col_name(0)
'I am a variable'
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
```

(continues on next page)

(continued from previous page)

```

>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variable(name="I am a variable")
1
>>> p.col_name(Integer(0))
'I am a variable'

```

`dual_variable(i, sparse=False)`

The i -th dual variable.

Available after `self.solve()` is called, otherwise the result is undefined

- index – integer; the constraint's id

OUTPUT: the matrix of the i -th dual variable

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: p = SemidefiniteProgram(maximization=False, solver="Nonexistent_LP_
↳solver")
sage: x = p.new_variable()
sage: p.set_objective(x[0] - x[1])
sage: a1 = matrix([[1, 2.], [2., 3.]])
sage: a2 = matrix([[3, 4.], [4., 5.]])
sage: a3 = matrix([[5, 6.], [6., 7.]])
sage: b1 = matrix([[1, 1.], [1., 1.]])
sage: b2 = matrix([[2, 2.], [2., 2.]])
sage: b3 = matrix([[3, 3.], [3., 3.]])
sage: p.add_constraint(a1*x[0] + a2*x[1] <= a3)
sage: p.add_constraint(b1*x[0] + b2*x[1] <= b3)
sage: p.solve()
-3.0
sage: B = p.get_backend()
sage: x = p.get_values(x).values()
sage: -(a3*B.dual_variable(0)).trace() - (b3*B.dual_variable(1)).trace()
-3.0
sage: g = sum((B.slack(j)*B.dual_variable(j)).trace() for j in range(2)); g
0.0

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = SemidefiniteProgram(maximization=False, solver="Nonexistent_LP_solver
↳")
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(0)] - x[Integer(1)])
>>> a1 = matrix([[Integer(1), RealNumber('2.']), [RealNumber('2. '),
↳RealNumber('3.')]])
>>> a2 = matrix([[Integer(3), RealNumber('4.']), [RealNumber('4. '),
↳RealNumber('5.')]])
>>> a3 = matrix([[Integer(5), RealNumber('6.']), [RealNumber('6. '),
↳RealNumber('7.')]])
>>> b1 = matrix([[Integer(1), RealNumber('1.']), [RealNumber('1. '),
↳RealNumber('1.')]])

```

(continues on next page)

(continued from previous page)

```

>>> b2 = matrix([[Integer(2), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('2.')]])
>>> b3 = matrix([[Integer(3), RealNumber('3.')] , [RealNumber('3.')] ,
↳RealNumber('3.')]])
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] <= a3)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] <= b3)
>>> p.solve()
-3.0
>>> B = p.get_backend()
>>> x = p.get_values(x).values()
>>> -(a3*B.dual_variable(Integer(0))).trace()-(b3*B.dual_
↳variable(Integer(1))).trace()
-3.0
>>> g = sum((B.slack(j)*B.dual_variable(j)).trace() for j in_
↳range(Integer(2))); g
0.0

```

get_objective_value()

Return the value of the objective function.

NoteBehaviour is undefined unless `solve` has been called before.

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(2)
2
sage: p.add_linear_constraint([(0,1), (1,2)], None, 3)
sage: p.set_objective([2, 5])
sage: p.solve()
0
sage: p.get_objective_value()
7.5
sage: p.get_variable_value(0)
0.0
sage: p.get_variable_value(1)
1.5

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(2))
2
>>> p.add_linear_constraint([(Integer(0),Integer(1)), (Integer(1),
↳Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])

```

(continues on next page)

(continued from previous page)

```

>>> p.solve()
0
>>> p.get_objective_value()
7.5
>>> p.get_variable_value(Integer(0))
0.0
>>> p.get_variable_value(Integer(1))
1.5

```

get_variable_value (*variable*)

Return the value of a variable given by the solver.

NoteBehaviour is undefined unless `solve` has been called before.

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(2)
2
sage: p.add_linear_constraint([(0,1), (1, 2)], None, 3)
sage: p.set_objective([2, 5])
sage: p.solve()
0
sage: p.get_objective_value()
7.5
sage: p.get_variable_value(0)
0.0
sage: p.get_variable_value(1)
1.5

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(2))
2
>>> p.add_linear_constraint([(Integer(0), Integer(1)), (Integer(1), ↵
↵Integer(2))], None, Integer(3))
>>> p.set_objective([Integer(2), Integer(5)])
>>> p.solve()
0
>>> p.get_objective_value()
7.5
>>> p.get_variable_value(Integer(0))
0.0
>>> p.get_variable_value(Integer(1))
1.5

```

is_maximization()

Test whether the problem is a maximization

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False
```

ncols()

Return the number of columns/variables.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.ncols()
0
sage: p.add_variables(2)
2
sage: p.ncols()
2
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.ncols()
0
>>> p.add_variables(Integer(2))
2
>>> p.ncols()
2
```

nrows()

Return the number of rows/constraints.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.nrows()
0
sage: p.add_linear_constraints(2, 2.0, None)
sage: p.nrows()
2
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.nrows()
0
>>> p.add_linear_constraints(Integer(2), RealNumber('2.0'), None)
>>> p.nrows()
2
```

objective_coefficient (*variable, coeff=None*)

Set or get the coefficient of a variable in the objective function

INPUT:

- *variable* – integer; the variable’s id
- *coeff* – double; its coefficient

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variable()
1
sage: p.objective_coefficient(0)
0.0
sage: p.objective_coefficient(0,2)
sage: p.objective_coefficient(0)
2.0
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variable()
1
>>> p.objective_coefficient(Integer(0))
0.0
>>> p.objective_coefficient(Integer(0), Integer(2))
>>> p.objective_coefficient(Integer(0))
2.0
```

problem_name (*name=None*)

Return or define the problem’s name.

INPUT:

- name – string; the problem’s name. When set to NULL (default), the method returns the problem’s name.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.problem_name("There once was a french fry")
sage: print(p.problem_name())
There once was a french fry
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.problem_name("There once was a french fry")
>>> print(p.problem_name())
There once was a french fry
```

row(i)

Return a row.

INPUT:

- index – integer; the constraint’s id

OUTPUT:

A pair (indices, coeffs) where indices lists the entries whose coefficient is nonzero, and to which coeffs associates their coefficient on the model of the add_linear_constraint method.

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
5
sage: p.add_linear_constraint(zip(range(5), range(5)), 2, 2)
sage: p.row(0)
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0])
sage: p.row_bounds(0)
(2.0, 2.0)
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
5
>>> p.add_linear_constraint(zip(range(Integer(5)), range(Integer(5))),
↳ Integer(2), Integer(2))
>>> p.row(Integer(0))
([4, 3, 2, 1], [4.0, 3.0, 2.0, 1.0])
```

(continues on next page)

(continued from previous page)

```
>>> p.row_bounds(Integer(0))
(2.0, 2.0)
```

row_name (*index*)Return the *index*-th row name.

INPUT:

- *index* – integer; the row's id

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_linear_constraints(1, 2, None, name="Empty constraint 1")
sage: p.row_name(0)
'Empty constraint 1'
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_linear_constraints(Integer(1), Integer(2), None, name="Empty_
↳constraint 1")
>>> p.row_name(Integer(0))
'Empty constraint 1'
```

set_objective (*coeff*, *d=0.0*)

Set the objective function.

INPUT:

- *coeff* – list of real values, whose *i*-th element is the coefficient of the *i*-th variable in the objective function
- *d* – double; the constant term in the linear function (set to 0 by default)

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_variables(5)
5
sage: p.set_objective([1, 1, 2, 1, 3])
sage: [p.objective_coefficient(x) for x in range(5)]
[1.0, 1.0, 2.0, 1.0, 3.0]
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_variables(Integer(5))
5
```

(continues on next page)

(continued from previous page)

```
>>> p.set_objective([Integer(1), Integer(1), Integer(2), Integer(1), ↵
↵Integer(3)])
>>> [p.objective_coefficient(x) for x in range(Integer(5))]
[1.0, 1.0, 2.0, 1.0, 3.0]
```

Constants in the objective function are respected.

set_sense (*sense*)

Set the direction (maximization/minimization).

INPUT:

- *sense* – integer:
 - +1 => Maximization
 - -1 => Minimization

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.is_maximization()
True
sage: p.set_sense(-1)
sage: p.is_maximization()
False
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.is_maximization()
True
>>> p.set_sense(-Integer(1))
>>> p.is_maximization()
False
```

slack (*i*, *sparse=False*)

Slack of the *i*-th constraint.

Available after `self.solve()` is called, otherwise the result is undefined.

- *index* – integer; the constraint's id

OUTPUT: the matrix of the slack of the *i*-th constraint

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: p = SemidefiniteProgram(maximization=False, solver="Nonexistent_LP_
↵solver")
sage: x = p.new_variable()
sage: p.set_objective(x[0] - x[1])
sage: a1 = matrix([[1, 2.], [2., 3.]])
sage: a2 = matrix([[3, 4.], [4., 5.]])
```

(continues on next page)

(continued from previous page)

```

sage: a3 = matrix([[5, 6.], [6., 7.]])
sage: b1 = matrix([[1, 1.], [1., 1.]])
sage: b2 = matrix([[2, 2.], [2., 2.]])
sage: b3 = matrix([[3, 3.], [3., 3.]])
sage: p.add_constraint(a1*x[0] + a2*x[1] <= a3)
sage: p.add_constraint(b1*x[0] + b2*x[1] <= b3)
sage: p.solve()
-3.0
sage: B = p.get_backend()
sage: B1 = B.slack(1); B1
[0.0 0.0]
[0.0 0.0]
sage: B1.is_positive_definite()
True
sage: x = p.get_values(x).values()
sage: x[0]*b1 + x[1]*b2 - b3 + B1
[0.0 0.0]
[0.0 0.0]

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> p = SemidefiniteProgram(maximization=False, solver="Nonexistent_LP_solver
↳")
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(0)] - x[Integer(1)])
>>> a1 = matrix([[Integer(1), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('3.')]])
>>> a2 = matrix([[Integer(3), RealNumber('4.')] , [RealNumber('4.')] ,
↳RealNumber('5.')]])
>>> a3 = matrix([[Integer(5), RealNumber('6.')] , [RealNumber('6.')] ,
↳RealNumber('7.')]])
>>> b1 = matrix([[Integer(1), RealNumber('1.')] , [RealNumber('1.')] ,
↳RealNumber('1.')]])
>>> b2 = matrix([[Integer(2), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('2.')]])
>>> b3 = matrix([[Integer(3), RealNumber('3.')] , [RealNumber('3.')] ,
↳RealNumber('3.')]])
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] <= a3)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] <= b3)
>>> p.solve()
-3.0
>>> B = p.get_backend()
>>> B1 = B.slack(Integer(1)); B1
[0.0 0.0]
[0.0 0.0]
>>> B1.is_positive_definite()
True
>>> x = p.get_values(x).values()
>>> x[Integer(0)]*b1 + x[Integer(1)]*b2 - b3 + B1
[0.0 0.0]
[0.0 0.0]

```

`solve()`

Solve the problem.

Note

This method raises `SDPSolverException` exceptions when the solution cannot be computed for any reason (none exists, or the LP solver was not able to find it, etc...)

EXAMPLES:

```
sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.add_linear_constraints(5, 0, None)
sage: p.add_col(range(5), range(5))
sage: p.solve()
0
sage: p.objective_coefficient(0,1)
sage: p.solve()
Traceback (most recent call last):
...
SDPSolverException: ...
```

```
>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.add_linear_constraints(Integer(5), Integer(0), None)
>>> p.add_col(range(Integer(5)), range(Integer(5)))
>>> p.solve()
0
>>> p.objective_coefficient(Integer(0), Integer(1))
>>> p.solve()
Traceback (most recent call last):
...
SDPSolverException: ...
```

solver_parameter (*name*, *value=None*)

Return or define a solver parameter.

INPUT:

- *name* – string; the parameter
- *value* – the parameter's value if it is to be defined, or `None` (default) to obtain its current value

Note

The list of available parameters is available at `solver_parameter()`.

EXAMPLES:

```

sage: # optional - nonexistent_lp_solver
sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver="Nonexistent_LP_solver")
sage: p.solver_parameter("timelimit")
sage: p.solver_parameter("timelimit", 60)
sage: p.solver_parameter("timelimit")

```

```

>>> from sage.all import *
>>> # optional - nonexistent_lp_solver
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver="Nonexistent_LP_solver")
>>> p.solver_parameter("timelimit")
>>> p.solver_parameter("timelimit", Integer(60))
>>> p.solver_parameter("timelimit")

```

zero()

Zero of the base ring.

`sage.numerical.backends.generic_sdp_backend.default_sdp_solver(solver=None)`

Return/set the default SDP solver used by Sage.

INPUT:

- `solver` – one of the following:
 - the string 'CVXOPT', to make the use of the CVXOPT solver (see the [CVXOPT](#) web site) the default;
 - a subclass of `sage.numerical.backends.generic_sdp_backend.GenericSDPBackend`, to make it the default; or
 - None – (default) in which case the current default solver (a string or a class) is returned

OUTPUT:

This function returns the current default solver (a string or a class) if `solver = None` (default). Otherwise, it sets the default solver to the one given. If this solver does not exist, or is not available, a `ValueError` exception is raised.

EXAMPLES:

```

sage: former_solver = default_sdp_solver()
sage: default_sdp_solver("Cvxopt")
sage: default_sdp_solver()
'cvxopt'
sage: default_sdp_solver("Yeahhhhhhhhhhh")
Traceback (most recent call last):
...
ValueError: 'solver' should be set to ...
sage: default_sdp_solver(former_solver)
sage: from sage.numerical.backends.generic_sdp_backend import GenericSDPBackend
sage: class my_sdp_solver(GenericSDPBackend): pass
sage: default_sdp_solver(my_sdp_solver)
sage: default_sdp_solver() is my_sdp_solver
True

```

```

>>> from sage.all import *
>>> former_solver = default_sdp_solver()
>>> default_sdp_solver("Cvxopt")
>>> default_sdp_solver()
' Cvxopt '
>>> default_sdp_solver("Yeahhhhhhhhhhh")
Traceback (most recent call last):
...
ValueError: 'solver' should be set to ...
>>> default_sdp_solver(former_solver)
>>> from sage.numerical.backends.generic_sdp_backend import GenericSDPBackend
>>> class my_sdp_solver(GenericSDPBackend): pass
>>> default_sdp_solver(my_sdp_solver)
>>> default_sdp_solver() is my_sdp_solver
True

```

`sage.numerical.backends.generic_sdp_backend.get_solver` (*solver=None, base_ring=None*)

Return a solver according to the given preferences.

INPUT:

- `solver` – one of the following:
 - the string 'CVXOPT', designating the use of the CVXOPT solver (see the [CVXOPT](#) web site);
 - a subclass of `sage.numerical.backends.generic_sdp_backend.GenericSDPBackend`
 - None – (default) in which case the default solver is used (see `default_sdp_solver()`)

➔ See also

- `default_sdp_solver()` – returns/sets the default SDP solver

EXAMPLES:

```

sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver()

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver()

```

Passing a class:

```

sage: from sage.numerical.backends.generic_sdp_backend import GenericSDPBackend
sage: class MockSDPBackend(GenericSDPBackend):
.....:     def solve(self):
.....:         raise RuntimeError("SDP is too slow")
sage: P = SemidefiniteProgram(solver=MockSDPBackend)
sage: P.solve()
Traceback (most recent call last):
...
RuntimeError: SDP is too slow

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_sdp_backend import GenericSDPBackend
>>> class MockSDPBackend(GenericSDPBackend):
...     def solve(self):
...         raise RuntimeError("SDP is too slow")
>>> P = SemidefiniteProgram(solver=MockSDPBackend)
>>> P.solve()
Traceback (most recent call last):
...
RuntimeError: SDP is too slow

```

12.2 CVXOPT SDP Backend

AUTHORS:

- Ingolfur Edvardsson (2014-05): initial implementation
- Dima Pasechnik (2015-12): minor fixes

class sage.numerical.backends.cvxopt_sdp_backend.CVXOPTSDPBackend

Bases: MatrixSDPBackend

Cython constructor.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver='CVXOPT')

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver='CVXOPT')

```

dual_variable (*i*, *sparse=False*)

The *i*-th dual variable.

Available after `self.solve()` is called, otherwise the result is undefined.

- `index` – integer; the constraint's id

OUTPUT: the matrix of the *i*-th dual variable

EXAMPLES:

```

sage: p = SemidefiniteProgram(maximization=False, solver='cvxopt')
sage: x = p.new_variable()
sage: p.set_objective(x[0] - x[1])
sage: a1 = matrix([[1, 2.], [2., 3.]])
sage: a2 = matrix([[3, 4.], [4., 5.]])
sage: a3 = matrix([[5, 6.], [6., 7.]])
sage: b1 = matrix([[1, 1.], [1., 1.]])
sage: b2 = matrix([[2, 2.], [2., 2.]])
sage: b3 = matrix([[3, 3.], [3., 3.]])
sage: p.add_constraint(a1*x[0] + a2*x[1] <= a3)
sage: p.add_constraint(b1*x[0] + b2*x[1] <= b3)

```

(continues on next page)

(continued from previous page)

```

sage: p.solve()                                     # tol 1e-08
-3.0
sage: B = p.get_backend()
sage: x = p.get_values(x).values()
sage: -(a3*B.dual_variable(0)).trace() - (b3*B.dual_variable(1)).trace()
↪ # tol 1e-07
-3.0
sage: g = sum((B.slack(j)*B.dual_variable(j)).trace() for j in range(2)); g
↪ # tol 1.5e-08
0.0

```

```

>>> from sage.all import *
>>> p = SemidefiniteProgram(maximization=False, solver='cvxopt')
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(0)] - x[Integer(1)])
>>> a1 = matrix([[Integer(1), RealNumber('2.')] , [RealNumber('2.')] ,
↪ RealNumber('3.')]])
>>> a2 = matrix([[Integer(3), RealNumber('4.')] , [RealNumber('4.')] ,
↪ RealNumber('5.')]])
>>> a3 = matrix([[Integer(5), RealNumber('6.')] , [RealNumber('6.')] ,
↪ RealNumber('7.')]])
>>> b1 = matrix([[Integer(1), RealNumber('1.')] , [RealNumber('1.')] ,
↪ RealNumber('1.')]])
>>> b2 = matrix([[Integer(2), RealNumber('2.')] , [RealNumber('2.')] ,
↪ RealNumber('2.')]])
>>> b3 = matrix([[Integer(3), RealNumber('3.')] , [RealNumber('3.')] ,
↪ RealNumber('3.')]])
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] <= a3)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] <= b3)
>>> p.solve()                                     # tol 1e-08
-3.0
>>> B = p.get_backend()
>>> x = p.get_values(x).values()
>>> -(a3*B.dual_variable(Integer(0))).trace() - (b3*B.dual_
↪ variable(Integer(1))).trace()                 # tol 1e-07
-3.0
>>> g = sum((B.slack(j)*B.dual_variable(j)).trace() for j in
↪ range(Integer(2))); g # tol 1.5e-08
0.0

```

get_objective_value()

Return the value of the objective function.

NoteBehaviour is undefined unless `solve` has been called before.**EXAMPLES:**

```

sage: p = SemidefiniteProgram(solver='cvxopt', maximization=False)
sage: x = p.new_variable()

```

(continues on next page)

(continued from previous page)

```

sage: p.set_objective(x[0] - x[1] + x[2])
sage: a1 = matrix([[ -7., -11.], [-11., 3.]])
sage: a2 = matrix([[ 7., -18.], [-18., 8.]])
sage: a3 = matrix([[ -2., -8.], [-8., 1.]])
sage: a4 = matrix([[33., -9.], [-9., 26.]])
sage: b1 = matrix([[ -21., -11., 0.], [-11., 10., 8.], [0., 8., 5.]])
sage: b2 = matrix([[0., 10., 16.], [10., -10., -10.], [16., -10., 3.]])
sage: b3 = matrix([[ -5., 2., -17.], [2., -6., 8.], [-17., 8., 6.]])
sage: b4 = matrix([[14., 9., 40.], [9., 91., 10.], [40., 10., 15.]])
sage: p.add_constraint(a1*x[0] + a2*x[1] + a3*x[2] <= a4)
sage: p.add_constraint(b1*x[0] + b2*x[1] + b3*x[2] <= b4)
sage: N(p.solve(), digits=4)
-3.154
sage: N(p.get_backend().get_objective_value(), digits=4)
-3.154

```

```

>>> from sage.all import *
>>> p = SemidefiniteProgram(solver='cvxopt', maximization=False)
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(0)] - x[Integer(1)] + x[Integer(2)])
>>> a1 = matrix([[ -RealNumber('7.'), -RealNumber('11.'], [-RealNumber('11.'),
↳ RealNumber('3.')]])
>>> a2 = matrix([[RealNumber('7.'), -RealNumber('18.'], [-RealNumber('18.'),
↳ RealNumber('8.')]])
>>> a3 = matrix([[ -RealNumber('2.'), -RealNumber('8.'], [-RealNumber('8.'),
↳ RealNumber('1.')]])
>>> a4 = matrix([[RealNumber('33.'), -RealNumber('9.'], [-RealNumber('9.'),
↳ RealNumber('26.')]])
>>> b1 = matrix([[ -RealNumber('21.'), -RealNumber('11.'), RealNumber('0.'],
↳ [-RealNumber('11.'), RealNumber('10.'), RealNumber('8.'], [RealNumber('0.
↳ '), RealNumber('8.'), RealNumber('5.')]])
>>> b2 = matrix([[RealNumber('0.'), RealNumber('10.'), RealNumber('16.'],
↳ [RealNumber('10.'), -RealNumber('10.'), -RealNumber('10.'], [RealNumber(
↳ '16.'), -RealNumber('10.'), RealNumber('3.')]])
>>> b3 = matrix([[ -RealNumber('5.'), RealNumber('2.'), -RealNumber('17.'],
↳ [RealNumber('2.'), -RealNumber('6.'), RealNumber('8.'], [-RealNumber(
↳ '17.'), RealNumber('8.'), RealNumber('6.')]])
>>> b4 = matrix([[RealNumber('14.'), RealNumber('9.'), RealNumber('40.'],
↳ [RealNumber('9.'), RealNumber('91.'), RealNumber('10.'], [RealNumber('40.
↳ '), RealNumber('10.'), RealNumber('15.')]])
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] + a3*x[Integer(2)]
↳ <= a4)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] + b3*x[Integer(2)]
↳ <= b4)
>>> N(p.solve(), digits=Integer(4))
-3.154
>>> N(p.get_backend().get_objective_value(), digits=Integer(4))
-3.154

```

get_variable_value (*variable*)

Return the value of a variable given by the solver.

Note

Behaviour is undefined unless `solve` has been called before.

EXAMPLES:

```
sage: p = SemidefiniteProgram(solver='cvxopt', maximization=False)
sage: x = p.new_variable()
sage: p.set_objective(x[0] - x[1] + x[2])
sage: a1 = matrix([[ -7., -11.], [-11., 3.]])
sage: a2 = matrix([[ 7., -18.], [-18., 8.]])
sage: a3 = matrix([[ -2., -8.], [-8., 1.]])
sage: a4 = matrix([[33., -9.], [-9., 26.]])
sage: b1 = matrix([[ -21., -11., 0.], [-11., 10., 8.], [0., 8., 5.]])
sage: b2 = matrix([[0., 10., 16.], [10., -10., -10.], [16., -10., 3.]])
sage: b3 = matrix([[ -5., 2., -17.], [2., -6., 8.], [-17., 8., 6.]])
sage: b4 = matrix([[14., 9., 40.], [9., 91., 10.], [40., 10., 15.]])
sage: p.add_constraint(a1*x[0] + a2*x[1] + a3*x[2] <= a4)
sage: p.add_constraint(b1*x[0] + b2*x[1] + b3*x[2] <= b4)
sage: N(p.solve(), digits=4)
-3.154
sage: N(p.get_backend().get_variable_value(0), digits=3)
-0.368
sage: N(p.get_backend().get_variable_value(1), digits=4)
1.898
sage: N(p.get_backend().get_variable_value(2), digits=3)
-0.888
```

```
>>> from sage.all import *
>>> p = SemidefiniteProgram(solver='cvxopt', maximization=False)
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(0)] - x[Integer(1)] + x[Integer(2)])
>>> a1 = matrix([[ -RealNumber('7.'), -RealNumber('11.'), [-RealNumber('11.'),
↪ RealNumber('3.')]])
>>> a2 = matrix([[RealNumber('7.'), -RealNumber('18.'), [-RealNumber('18.'),
↪ RealNumber('8.')]])
>>> a3 = matrix([[ -RealNumber('2.'), -RealNumber('8.'), [-RealNumber('8.'),
↪ RealNumber('1.')]])
>>> a4 = matrix([[RealNumber('33.'), -RealNumber('9.'), [-RealNumber('9.'),
↪ RealNumber('26.')]])
>>> b1 = matrix([[ -RealNumber('21.'), -RealNumber('11.'), RealNumber('0.'),
↪ [-RealNumber('11.'), RealNumber('10.'), RealNumber('8.')] , [RealNumber('0.
↪ '), RealNumber('8.'), RealNumber('5.')]])
>>> b2 = matrix([[RealNumber('0.'), RealNumber('10.'), RealNumber('16.'),
↪ [RealNumber('10.'), -RealNumber('10.'), -RealNumber('10.')] , [RealNumber(
↪ '16.'), -RealNumber('10.'), RealNumber('3.')]])
>>> b3 = matrix([[ -RealNumber('5.'), RealNumber('2.'), -RealNumber('17.'),
↪ [RealNumber('2.'), -RealNumber('6.'), RealNumber('8.')] , [-RealNumber(
↪ '17.'), RealNumber('8.'), RealNumber('6.')]])
>>> b4 = matrix([[RealNumber('14.'), RealNumber('9.'), RealNumber('40.'),
↪ [RealNumber('9.'), RealNumber('91.'), RealNumber('10.')] , [RealNumber('40.
↪ '), RealNumber('10.'), RealNumber('15.')]])
```

(continues on next page)

(continued from previous page)

```

>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] + a3*x[Integer(2)]
↳<= a4)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] + b3*x[Integer(2)]
↳<= b4)
>>> N(p.solve(), digits=Integer(4))
-3.154
>>> N(p.get_backend().get_variable_value(Integer(0)), digits=Integer(3))
-0.368
>>> N(p.get_backend().get_variable_value(Integer(1)), digits=Integer(4))
1.898
>>> N(p.get_backend().get_variable_value(Integer(2)), digits=Integer(3))
-0.888

```

slack (*i*, *sparse=False*)Slack of the *i*-th constraint.Available after `self.solve()` is called, otherwise the result is undefined.

- `index` – integer; the constraint's id

OUTPUT: the matrix of the slack of the *i*-th constraint

EXAMPLES:

```

sage: p = SemidefiniteProgram(maximization = False, solver='cvxopt')
sage: x = p.new_variable()
sage: p.set_objective(x[0] - x[1])
sage: a1 = matrix([[1, 2.], [2., 3.]])
sage: a2 = matrix([[3, 4.], [4., 5.]])
sage: a3 = matrix([[5, 6.], [6., 7.]])
sage: b1 = matrix([[1, 1.], [1., 1.]])
sage: b2 = matrix([[2, 2.], [2., 2.]])
sage: b3 = matrix([[3, 3.], [3., 3.]])
sage: p.add_constraint(a1*x[0] + a2*x[1] <= a3)
sage: p.add_constraint(b1*x[0] + b2*x[1] <= b3)
sage: p.solve() # tol 1e-08
-3.0
sage: B = p.get_backend()
sage: B1 = B.slack(1); B1 # tol 1e-08
[0.0 0.0]
[0.0 0.0]
sage: B1.is_positive_definite()
True
sage: x = sorted(p.get_values(x).values())
sage: x[0]*b1 + x[1]*b2 - b3 + B1 # tol 1e-09
[0.0 0.0]
[0.0 0.0]

```

```

>>> from sage.all import *
>>> p = SemidefiniteProgram(maximization = False, solver='cvxopt')
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(0)] - x[Integer(1)])
>>> a1 = matrix([[Integer(1), RealNumber('2.']), [RealNumber('2. '),
↳RealNumber('3.')]])

```

(continues on next page)

(continued from previous page)

```

>>> a2 = matrix([[Integer(3), RealNumber('4.')] , [RealNumber('4.')] ,
↳RealNumber('5.')]])
>>> a3 = matrix([[Integer(5), RealNumber('6.')] , [RealNumber('6.')] ,
↳RealNumber('7.')]])
>>> b1 = matrix([[Integer(1), RealNumber('1.')] , [RealNumber('1.')] ,
↳RealNumber('1.')]])
>>> b2 = matrix([[Integer(2), RealNumber('2.')] , [RealNumber('2.')] ,
↳RealNumber('2.')]])
>>> b3 = matrix([[Integer(3), RealNumber('3.')] , [RealNumber('3.')] ,
↳RealNumber('3.')]])
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] <= a3)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] <= b3)
>>> p.solve() # tol 1e-08
-3.0
>>> B = p.get_backend()
>>> B1 = B.slack(Integer(1)); B1 # tol 1e-08
[0.0 0.0]
[0.0 0.0]
>>> B1.is_positive_definite()
True
>>> x = sorted(p.get_values(x).values())
>>> x[Integer(0)]*b1 + x[Integer(1)]*b2 - b3 + B1 # tol 1e-09
[0.0 0.0]
[0.0 0.0]
    
```

`solve()`

Solve the problem.

Note

This method raises `SDPSolverException` exceptions when the solution cannot be computed for any reason (none exists, or the LP solver was not able to find it, etc...)

EXAMPLES:

```

sage: p = SemidefiniteProgram(solver='cvxopt', maximization=False)
sage: x = p.new_variable()
sage: p.set_objective(x[0] - x[1] + x[2])
sage: a1 = matrix([[ -7., -11.], [-11., 3.]])
sage: a2 = matrix([[ 7., -18.], [-18., 8.]])
sage: a3 = matrix([[ -2., -8.], [-8., 1.]])
sage: a4 = matrix([[33., -9.], [-9., 26.]])
sage: b1 = matrix([[ -21., -11., 0.], [-11., 10., 8.], [0., 8., 5.]])
sage: b2 = matrix([[ 0., 10., 16.], [10., -10., -10.], [16., -10., 3.]])
sage: b3 = matrix([[ -5., 2., -17.], [2., -6., 8.], [-17., 8., 6.]])
sage: b4 = matrix([[14., 9., 40.], [9., 91., 10.], [40., 10., 15.]])
sage: p.add_constraint(a1*x[0] + a3*x[2] <= a4)
sage: p.add_constraint(b1*x[0] + b2*x[1] + b3*x[2] <= b4)
sage: N(p.solve(), digits=4)
-3.225
sage: p = SemidefiniteProgram(solver='cvxopt', maximization=False)
    
```

(continues on next page)

(continued from previous page)

```

sage: x = p.new_variable()
sage: p.set_objective(x[0] - x[1] + x[2])
sage: a1 = matrix([[ -7., -11.], [-11., 3.]])
sage: a2 = matrix([[ 7., -18.], [-18., 8.]])
sage: a3 = matrix([[ -2., -8.], [-8., 1.]])
sage: a4 = matrix([[33., -9.], [-9., 26.]])
sage: b1 = matrix([[ -21., -11., 0.], [-11., 10., 8.], [0., 8., 5.]])
sage: b2 = matrix([[0., 10., 16.], [10., -10., -10.], [16., -10., 3.]])
sage: b3 = matrix([[ -5., 2., -17.], [2., -6., 8.], [-17., 8., 6.]])
sage: b4 = matrix([[14., 9., 40.], [9., 91., 10.], [40., 10., 15.]])
sage: p.add_constraint(a1*x[0] + a2*x[1] + a3*x[2] <= a4)
sage: p.add_constraint(b1*x[0] + b2*x[1] + b3*x[2] <= b4)
sage: N(p.solve(), digits=4)
-3.154

```

```

>>> from sage.all import *
>>> p = SemidefiniteProgram(solver='cvxopt', maximization=False)
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(0)] - x[Integer(1)] + x[Integer(2)])
>>> a1 = matrix([[ -RealNumber('7. '), -RealNumber('11. ')], [-RealNumber('11. '),
↳ RealNumber('3. ')]])
>>> a2 = matrix([[RealNumber('7. '), -RealNumber('18. ')], [-RealNumber('18. '),
↳ RealNumber('8. ')]])
>>> a3 = matrix([[ -RealNumber('2. '), -RealNumber('8. ')], [-RealNumber('8. '),
↳ RealNumber('1. ')]])
>>> a4 = matrix([[RealNumber('33. '), -RealNumber('9. ')], [-RealNumber('9. '),
↳ RealNumber('26. ')]])
>>> b1 = matrix([[ -RealNumber('21. '), -RealNumber('11. '), RealNumber('0. ')],
↳ [-RealNumber('11. '), RealNumber('10. '), RealNumber('8. ')], [RealNumber('0.
↳ '), RealNumber('8. '), RealNumber('5. ')]])
>>> b2 = matrix([[RealNumber('0. '), RealNumber('10. '), RealNumber('16. ')],
↳ [RealNumber('10. '), -RealNumber('10. '), -RealNumber('10. ')], [RealNumber(
↳ '16. '), -RealNumber('10. '), RealNumber('3. ')]])
>>> b3 = matrix([[ -RealNumber('5. '), RealNumber('2. '), -RealNumber('17. ')],
↳ [RealNumber('2. '), -RealNumber('6. '), RealNumber('8. ')], [-RealNumber(
↳ '17. '), RealNumber('8. '), RealNumber('6. ')]])
>>> b4 = matrix([[RealNumber('14. '), RealNumber('9. '), RealNumber('40. ')],
↳ [RealNumber('9. '), RealNumber('91. '), RealNumber('10. ')], [RealNumber('40.
↳ '), RealNumber('10. '), RealNumber('15. ')]])
>>> p.add_constraint(a1*x[Integer(0)] + a3*x[Integer(2)] <= a4)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] + b3*x[Integer(2)]
↳ <= b4)
>>> N(p.solve(), digits=Integer(4))
-3.225
>>> p = SemidefiniteProgram(solver='cvxopt', maximization=False)
>>> x = p.new_variable()
>>> p.set_objective(x[Integer(0)] - x[Integer(1)] + x[Integer(2)])
>>> a1 = matrix([[ -RealNumber('7. '), -RealNumber('11. ')], [-RealNumber('11. '),
↳ RealNumber('3. ')]])
>>> a2 = matrix([[RealNumber('7. '), -RealNumber('18. ')], [-RealNumber('18. '),
↳ RealNumber('8. ')]])
>>> a3 = matrix([[ -RealNumber('2. '), -RealNumber('8. ')], [-RealNumber('8. '),

```

(continues on next page)

(continued from previous page)

```

↪RealNumber('1.')]])
>>> a4 = matrix([[RealNumber('33.'), -RealNumber('9.')] , [-RealNumber('9.')] , ↪
↪RealNumber('26.')]])
>>> b1 = matrix([[ -RealNumber('21.'), -RealNumber('11.'), RealNumber('0.')] , ↪
↪[-RealNumber('11.'), RealNumber('10.'), RealNumber('8.')] , [RealNumber('0.
↪'), RealNumber('8.'), RealNumber('5.')]])
>>> b2 = matrix([[RealNumber('0.'), RealNumber('10.'), RealNumber('16.')] , ↪
↪[RealNumber('10.'), -RealNumber('10.'), -RealNumber('10.')] , [RealNumber(
↪'16.'), -RealNumber('10.'), RealNumber('3.')]])
>>> b3 = matrix([[ -RealNumber('5.'), RealNumber('2.'), -RealNumber('17.')] , ↪
↪[RealNumber('2.'), -RealNumber('6.'), RealNumber('8.')] , [-RealNumber(
↪'17.'), RealNumber('8.'), RealNumber('6.')]])
>>> b4 = matrix([[RealNumber('14.'), RealNumber('9.'), RealNumber('40.')] , ↪
↪[RealNumber('9.'), RealNumber('91.'), RealNumber('10.')] , [RealNumber('40.
↪'), RealNumber('10.'), RealNumber('15.')]])
>>> p.add_constraint(a1*x[Integer(0)] + a2*x[Integer(1)] + a3*x[Integer(2)]
↪<= a4)
>>> p.add_constraint(b1*x[Integer(0)] + b2*x[Integer(1)] + b3*x[Integer(2)]
↪<= b4)
>>> N(p.solve(), digits=Integer(4))
-3.154

```

solver_parameter (*name*, *value=None*)

Return or define a solver parameter.

INPUT:

- *name* – string; the parameter
- *value* – the parameter's value if it is to be defined, or `None` (default) to obtain its current value

NoteThe list of available parameters is available at `solver_parameter()`.

EXAMPLES:

```

sage: from sage.numerical.backends.generic_sdp_backend import get_solver
sage: p = get_solver(solver='CVXOPT')
sage: p.solver_parameter("show_progress")
False
sage: p.solver_parameter("show_progress", True)
sage: p.solver_parameter("show_progress")
True

```

```

>>> from sage.all import *
>>> from sage.numerical.backends.generic_sdp_backend import get_solver
>>> p = get_solver(solver='CVXOPT')
>>> p.solver_parameter("show_progress")
False
>>> p.solver_parameter("show_progress", True)
>>> p.solver_parameter("show_progress")

```

(continues on next page)

(continued from previous page)

True

For more details on CVXOPT, see [CVXOPT documentation](#).

INDICES AND TABLES

- [Index](#)
- [Module Index](#)
- [Search Page](#)

PYTHON MODULE INDEX

n

sage.numerical.backends.cvxopt_backend, 375
sage.numerical.backends.cvxopt_sdp_backend,
449
sage.numerical.backends.generic_backend,
225
sage.numerical.backends.generic_sdp_back-
end, 433
sage.numerical.backends.glpk_backend, 279
sage.numerical.backends.glpk_exact_backend,
332
sage.numerical.backends.glpk_graph_backend,
335
sage.numerical.backends.interac-
tively_backend, 257
sage.numerical.backends.logging_backend,
394
sage.numerical.backends.ppl_backend, 355
sage.numerical.gauss_legendre, 219
sage.numerical.interactive_simplex_method,
133
sage.numerical.knapsack, 1
sage.numerical.linear_functions, 85
sage.numerical.linear_tensor, 101
sage.numerical.linear_tensor_constraints,
113
sage.numerical.linear_tensor_element, 109
sage.numerical.mip, 9
sage.numerical.optimize, 119
sage.numerical.sdp, 61

A

- A () (*sage.numerical.interactive_simplex_method.InteractiveLPProblem method*), 138
- A () (*sage.numerical.interactive_simplex_method.LPRevisedDictionary method*), 201
- A_N () (*sage.numerical.interactive_simplex_method.LPRevisedDictionary method*), 202
- Abcx () (*sage.numerical.interactive_simplex_method.InteractiveLPProblem method*), 138
- add_col () (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend method*), 375
- add_col () (*sage.numerical.backends.generic_backend.GenericBackend method*), 225
- add_col () (*sage.numerical.backends.glpk_backend.GLPKBackend method*), 279
- add_col () (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend method*), 257
- add_col () (*sage.numerical.backends.logging_backend.LoggingBackend method*), 394
- add_col () (*sage.numerical.backends.ppl_backend.PPLBackend method*), 355
- add_constraint () (*sage.numerical.interactive_simplex_method.InteractiveLPProblem method*), 139
- add_constraint () (*sage.numerical.interactive_simplex_method.InteractiveLPProblemStandardForm method*), 157
- add_constraint () (*sage.numerical.mip.MixedIntegerLinearProgram method*), 21
- add_constraint () (*sage.numerical.sdp.SemidefiniteProgram method*), 70
- add_edge () (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend method*), 338
- add_edges () (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend method*), 338
- add_linear_constraint () (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend method*), 376
- add_linear_constraint () (*sage.numerical.backends.generic_backend.GenericBackend method*), 226
- add_linear_constraint () (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend method*), 433
- add_linear_constraint () (*sage.numerical.backends.glpk_backend.GLPKBackend method*), 280
- add_linear_constraint () (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend method*), 258
- add_linear_constraint () (*sage.numerical.backends.logging_backend.LoggingBackend method*), 395
- add_linear_constraint () (*sage.numerical.backends.ppl_backend.PPLBackend method*), 356
- add_linear_constraint_vector () (*sage.numerical.backends.generic_backend.GenericBackend method*), 227
- add_linear_constraint_vector () (*sage.numerical.backends.logging_backend.LoggingBackend method*), 396
- add_linear_constraints () (*sage.numerical.backends.generic_backend.GenericBackend method*), 228
- add_linear_constraints () (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend method*), 434
- add_linear_constraints () (*sage.numerical.backends.glpk_backend.GLPKBackend method*), 281
- add_linear_constraints () (*sage.numerical.backends.logging_backend.LoggingBackend method*), 397
- add_linear_constraints () (*sage.numerical.backends.ppl_backend.PPLBackend method*), 357
- add_row () (*sage.numerical.interactive_simplex_method.LPAbstractDictionary method*), 170
- add_row () (*sage.numerical.interactive_simplex_method.LPDictionary method*), 193
- add_row () (*sage.numerical.interactive_simplex_method.LPRevisedDictionary method*), 204

- `add_variable()` (*sage.numerical.backends.cvx_opt_backend.CVXOPTBackend* method), 377
`add_variable()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 228
`add_variable()` (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend* method), 434
`add_variable()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 282
`add_variable()` (*sage.numerical.backends.glpk_exact_backend.GLPKExactBackend* method), 332
`add_variable()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 259
`add_variable()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 398
`add_variable()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 358
`add_variables()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 230
`add_variables()` (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend* method), 435
`add_variables()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 283
`add_variables()` (*sage.numerical.backends.glpk_exact_backend.GLPKExactBackend* method), 333
`add_variables()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 399
`add_variables()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 359
`add_vertex()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 340
`add_vertices()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 340
`auxiliary_problem()` (*sage.numerical.interactive_simplex_method.InteractiveLPProblemStandardForm* method), 159
`auxiliary_variable()` (*sage.numerical.interactive_simplex_method.InteractiveLPProblemStandardForm* method), 159
- B**
- `b()` (*sage.numerical.interactive_simplex_method.InteractiveLPProblem* method), 140
`B()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary* method), 202
`B_inverse()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary* method), 203
`base_ring()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 230
`base_ring()` (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend* method), 436
`base_ring()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 260
`base_ring()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 400
`base_ring()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 360
`base_ring()` (*sage.numerical.interactive_simplex_method.InteractiveLPProblem* method), 140
`base_ring()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary* method), 171
`base_ring()` (*sage.numerical.mip.MixedIntegerLinearProgram* method), 24
`base_ring()` (*sage.numerical.sdp.SemidefiniteProgram* method), 71
`basic_indices()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary* method), 206
`basic_solution()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary* method), 171
`basic_variables()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary* method), 172
`basic_variables()` (*sage.numerical.interactive_simplex_method.LPDictionary* method), 194
`basic_variables()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary* method), 207
`best_known_objective_bound()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 231
`best_known_objective_bound()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 284
`best_known_objective_bound()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 400
`best_known_objective_bound()` (*sage.numerical.mip.MixedIntegerLinearProgram* method), 25
`binpacking()` (*in module sage.numerical.optimize*), 119

C

`c()` (*sage.numerical.interactive_simplex_method.InteractiveLPProblem* method), 141

`c_B()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary* method), 207

`c_N()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary* method), 208

`category()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 401

`coefficient()` (*sage.numerical.linear_functions.LinearFunction* method), 92

`coefficient()` (*sage.numerical.linear_tensor_element.LinearTensor* method), 109

`col_bounds()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 378

`col_bounds()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 231

`col_bounds()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 285

`col_bounds()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 260

`col_bounds()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 401

`col_bounds()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 360

`col_name()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 379

`col_name()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 232

`col_name()` (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend* method), 436

`col_name()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 285

`col_name()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 261

`col_name()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 402

`col_name()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 361

`column_coefficients()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary* method), 173

`column_coefficients()` (*sage.numerical.interactive_simplex_method.LPDictionary* method), 194

`column_coefficients()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary* method), 208

`constant_terms()` (*sage.numerical.interactive_simplex_method.InteractiveLPProblem* method), 141

`constant_terms()` (*sage.numerical.interactive_sim-*

plex_method.LPAbstractDictionary method), 173

`constant_terms()` (*sage.numerical.interactive_simplex_method.LPDictionary* method), 195

`constant_terms()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary* method), 209

`constraint_coefficients()` (*sage.numerical.interactive_simplex_method.InteractiveLPProblem* method), 141

`constraint_types()` (*sage.numerical.interactive_simplex_method.InteractiveLPProblem* method), 142

`constraints()` (*sage.numerical.mip.MixedIntegerLinearProgram* method), 26

`coordinate_ring()` (*sage.numerical.interactive_simplex_method.InteractiveLPProblemStandardForm* method), 160

`coordinate_ring()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary* method), 174

`copy()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 232

`copy()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 402

`copy_for_mip()` (*sage.numerical.mip.MIPVariable* method), 15

`cpp()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 341

`CVXOPTBackend` (class in *sage.numerical.backends.cvxopt_backend*), 375

`CVXOPTSDPBackend` (class in *sage.numerical.backends.cvxopt_sdp_backend*), 449

D

`decision_variables()` (*sage.numerical.interactive_simplex_method.InteractiveLPProblem* method), 142

`default_mip_solver()` (in module *sage.numerical.backends.generic_backend*), 253

`default_sdp_solver()` (in module *sage.numerical.backends.generic_sdp_backend*), 447

`default_variable()` (*sage.numerical.mip.MixedIntegerLinearProgram* method), 27

`default_variable_name()` (in module *sage.numerical.interactive_simplex_method*), 215

`delete_edge()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 342

`delete_edges()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 343

`delete_vertex()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend*

method), 343

delete_vertices() (sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend method), 344

dict() (sage.numerical.linear_functions.LinearFunction method), 93

dict() (sage.numerical.linear_tensor_element.LinearTensor method), 110

dictionary() (sage.numerical.backends.interactivelp_backend.InteractiveLPBackend method), 262

dictionary() (sage.numerical.interactive_simplex_method.InteractiveLPPProblemStandardForm method), 161

dictionary() (sage.numerical.interactive_simplex_method.LPRevisedDictionary method), 209

dual() (sage.numerical.interactive_simplex_method.InteractiveLPPProblem method), 143

dual_ratios() (sage.numerical.interactive_simplex_method.LPAbstractDictionary method), 174

dual_variable() (sage.numerical.backends.cvxopt_sdp_backend.CVXOPTSDPBackend method), 449

dual_variable() (sage.numerical.backends.generic_sdp_backend.GenericSDPBackend method), 437

dual_variable() (sage.numerical.sdp.SemidefiniteProgram method), 72

dump() (sage.numerical.backends.logging_backend.LoggingBackend method), 403

dumps() (sage.numerical.backends.logging_backend.LoggingBackend method), 403

E

E() (sage.numerical.interactive_simplex_method.LPRevisedDictionary method), 203

E_inverse() (sage.numerical.interactive_simplex_method.LPRevisedDictionary method), 204

edges() (sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend method), 345

Element (sage.numerical.linear_tensor_constraints.LinearTensorConstraintsParent_class attribute), 117

Element (sage.numerical.linear_tensor.LinearTensorParent_class attribute), 104

Element (sage.numerical.sdp.SDPVariableParent attribute), 69

enter() (sage.numerical.interactive_simplex_method.LPAbstractDictionary method), 175

entering() (sage.numerical.interactive_simplex_method.LPAbstractDictionary method), 176

entering_coefficients() (sage.numerical.interactive_simplex_method.LPAbstractDictionary method), 177

equals() (sage.numerical.linear_functions.LinearConstraint method), 87

equals() (sage.numerical.linear_functions.LinearFunction method), 93

equations() (sage.numerical.linear_functions.LinearConstraint method), 88

estimate_error() (in module sage.numerical.gauss_legendre), 219

eval_tab_col() (sage.numerical.backends.glpk_backend.GLPKBackend method), 286

eval_tab_row() (sage.numerical.backends.glpk_backend.GLPKBackend method), 288

F

feasible_dictionary() (sage.numerical.interactive_simplex_method.InteractiveLPPProblemStandardForm method), 161

feasible_set() (sage.numerical.interactive_simplex_method.InteractiveLPPProblem method), 143

final_dictionary() (sage.numerical.interactive_simplex_method.InteractiveLPPProblemStandardForm method), 163

final_revised_dictionary() (sage.numerical.interactive_simplex_method.InteractiveLPPProblemStandardForm method), 163

find_fit() (in module sage.numerical.optimize), 121

find_local_maximum() (in module sage.numerical.optimize), 123

find_local_minimum() (in module sage.numerical.optimize), 124

find_root() (in module sage.numerical.optimize), 126

free_module() (sage.numerical.linear_tensor.LinearTensorParent_class method), 104

G

gen() (sage.numerical.linear_functions.LinearFunctionsParent_class method), 96

gen() (sage.numerical.sdp.SemidefiniteProgram method), 73

GenericBackend (class in sage.numerical.backends.generic_backend), 225

GenericSDPBackend (class in sage.numerical.backends.generic_sdp_backend), 433

get_backend() (sage.numerical.mip.MixedIntegerLinearProgram method), 27

get_backend() (sage.numerical.sdp.SemidefiniteProgram method), 73

- `get_col_dual()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 290
- `get_col_stat()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 291
- `get_custom_name()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 404
- `get_edge()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 345
- `get_max()` (*sage.numerical.mip.MixedIntegerLinearProgram* method), 28
- `get_min()` (*sage.numerical.mip.MixedIntegerLinearProgram* method), 29
- `get_objective_value()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 379
- `get_objective_value()` (*sage.numerical.backends.cvxopt_sdp_backend.CVXOPTSDPBackend* method), 450
- `get_objective_value()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 233
- `get_objective_value()` (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend* method), 438
- `get_objective_value()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 292
- `get_objective_value()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 262
- `get_objective_value()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 404
- `get_objective_value()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 361
- `get_objective_value()` (*sage.numerical.mip.MixedIntegerLinearProgram* method), 29
- `get_relative_objective_gap()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 234
- `get_relative_objective_gap()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 293
- `get_relative_objective_gap()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 405
- `get_relative_objective_gap()` (*sage.numerical.mip.MixedIntegerLinearProgram* method), 30
- `get_row_dual()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 294
- `get_row_prim()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 295
- `get_row_stat()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 296
- `get_solver()` (*in module sage.numerical.backends.generic_backend*), 254
- `get_solver()` (*in module sage.numerical.backends.generic_sdp_backend*), 448
- `get_values()` (*sage.numerical.mip.MixedIntegerLinearProgram* method), 31
- `get_values()` (*sage.numerical.sdp.SemidefiniteProgram* method), 74
- `get_variable_value()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 380
- `get_variable_value()` (*sage.numerical.backends.cvxopt_sdp_backend.CVXOPTSDPBackend* method), 451
- `get_variable_value()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 235
- `get_variable_value()` (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend* method), 439
- `get_variable_value()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 297
- `get_variable_value()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 263
- `get_variable_value()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 406
- `get_variable_value()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 362
- `get_vertex()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 346
- `get_vertices()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 347
- `GLPKBackend` (class *in sage.numerical.backends.glpk_backend*), 279
- `GLPKExactBackend` (class *in sage.numerical.backends.glpk_exact_backend*), 332
- `GLPKGraphBackend` (class *in sage.numerical.backends.glpk_graph_backend*), 336
- I**
- `inequalities()` (*sage.numerical.linear_functions.LinearConstraint* method), 88
- `init_mip()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 363
- `initial_dictionary()` (*sage.numerical.interactive_simplex_method.InteractiveLPPProblemStandardForm* method), 164
- `inject_variables()` (*sage.numerical.interactive_simplex_method.InteractiveLPPProblemStandardForm* method), 164

`integrate_vector()` (in module `sage.numerical.gauss_legendre`), 220
`integrate_vector_N()` (in module `sage.numerical.gauss_legendre`), 222
`interactive_lp_problem()` (`sage.numerical.backends.interactivelp_backend.InteractiveLPBackend` method), 264
`interactive_lp_problem()` (`sage.numerical.mip.MixedIntegerLinearProgram` method), 35
`InteractiveLPBackend` (class in `sage.numerical.backends.interactivelp_backend`), 257
`InteractiveLPPProblem` (class in `sage.numerical.interactive_simplex_method`), 137
`InteractiveLPPProblemStandardForm` (class in `sage.numerical.interactive_simplex_method`), 156
`is_binary()` (`sage.numerical.mip.MixedIntegerLinearProgram` method), 36
`is_bounded()` (`sage.numerical.interactive_simplex_method.InteractiveLPPProblem` method), 144
`is_dual_feasible()` (`sage.numerical.interactive_simplex_method.LPAbstractDictionary` method), 177
`is_equation()` (`sage.numerical.linear_functions.LinearConstraint` method), 89
`is_equation()` (`sage.numerical.linear_tensor_constraints.LinearTensorConstraint` method), 114
`is_feasible()` (`sage.numerical.interactive_simplex_method.InteractiveLPPProblem` method), 145
`is_feasible()` (`sage.numerical.interactive_simplex_method.LPAbstractDictionary` method), 178
`is_integer()` (`sage.numerical.mip.MixedIntegerLinearProgram` method), 36
`is_less_or_equal()` (`sage.numerical.linear_functions.LinearConstraint` method), 89
`is_less_or_equal()` (`sage.numerical.linear_tensor_constraints.LinearTensorConstraint` method), 114
`is_LinearConstraint()` (in module `sage.numerical.linear_functions`), 97
`is_LinearFunction()` (in module `sage.numerical.linear_functions`), 98
`is_LinearTensor()` (in module `sage.numerical.linear_tensor`), 106
`is_LinearTensorConstraint()` (in module `sage.numerical.linear_tensor_constraints`), 118
`is_matrix_space()` (`sage.numerical.linear_tensor.LinearTensorParent_class` method), 105
`is_maximization()` (`sage.numerical.backends.cvxopt_backend.CVXOPTBackend` method), 381
`is_maximization()` (`sage.numerical.backends.generic_backend.GenericBackend` method), 235
`is_maximization()` (`sage.numerical.backends.generic_sdp_backend.GenericSDPBackend` method), 439
`is_maximization()` (`sage.numerical.backends.glpk_backend.GLPKBackend` method), 298
`is_maximization()` (`sage.numerical.backends.interactivelp_backend.InteractiveLPBackend` method), 265
`is_maximization()` (`sage.numerical.backends.logging_backend.LoggingBackend` method), 407
`is_maximization()` (`sage.numerical.backends.ppl_backend.PPLBackend` method), 364
`is_negative()` (`sage.numerical.interactive_simplex_method.InteractiveLPPProblem` method), 145
`is_optimal()` (`sage.numerical.interactive_simplex_method.InteractiveLPPProblem` method), 146
`is_optimal()` (`sage.numerical.interactive_simplex_method.LPAbstractDictionary` method), 178
`is_primal()` (`sage.numerical.interactive_simplex_method.InteractiveLPPProblem` method), 147
`is_real()` (`sage.numerical.mip.MixedIntegerLinearProgram` method), 37
`is_slack_variable_basic()` (`sage.numerical.backends.generic_backend.GenericBackend` method), 236
`is_slack_variable_basic()` (`sage.numerical.backends.glpk_backend.GLPKBackend` method), 298
`is_slack_variable_basic()` (`sage.numerical.backends.interactivelp_backend.InteractiveLPBackend` method), 265
`is_slack_variable_basic()` (`sage.numerical.backends.logging_backend.LoggingBackend` method), 407
`is_slack_variable_nonbasic_at_lower_bound()` (`sage.numerical.backends.generic_backend.GenericBackend` method), 237
`is_slack_variable_nonbasic_at_lower_bound()` (`sage.numerical.backends.glpk_backend.GLPKBackend` method), 299
`is_slack_variable_nonbasic_at_lower_bound()` (`sage.numerical.backends.interactivelp_backend.InteractiveLPBackend` method), 266

- `is_slack_variable_nonbasic_at_lower_bound()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 408
- `is_superincreasing()` (*sage.numerical.knapsack.Superincreasing* method), 3
- `is_trivial()` (*sage.numerical.linear_functions.LinearConstraint* method), 90
- `is_variable_basic()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 238
- `is_variable_basic()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 300
- `is_variable_basic()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 267
- `is_variable_basic()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 409
- `is_variable_binary()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 381
- `is_variable_binary()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 239
- `is_variable_binary()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 301
- `is_variable_binary()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 267
- `is_variable_binary()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 410
- `is_variable_binary()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 364
- `is_variable_continuous()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 382
- `is_variable_continuous()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 239
- `is_variable_continuous()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 302
- `is_variable_continuous()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 268
- `is_variable_continuous()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 410
- `is_variable_continuous()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 365
- `is_variable_integer()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 383
- `is_variable_integer()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 240
- `is_variable_integer()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 302
- `is_variable_integer()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 268
- `is_variable_integer()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 411
- `is_variable_integer()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 365
- `is_variable_nonbasic_at_lower_bound()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 240
- `is_variable_nonbasic_at_lower_bound()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 303
- `is_variable_nonbasic_at_lower_bound()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 269
- `is_variable_nonbasic_at_lower_bound()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 412
- `is_vector_space()` (*sage.numerical.linear_tensor.LinearTensorParent_class* method), 105
- `is_zero()` (*sage.numerical.linear_functions.LinearFunction* method), 94
- `items()` (*sage.numerical.linear_functions.LinearFunction* method), 94
- `items()` (*sage.numerical.mip.MIPVariable* method), 17
- `items()` (*sage.numerical.sdp.SDPVariable* method), 67
- `iteritems()` (*sage.numerical.linear_functions.LinearFunction* method), 95
- ## K
- `keys()` (*sage.numerical.mip.MIPVariable* method), 17
- `keys()` (*sage.numerical.sdp.SDPVariable* method), 68
- `knapsack()` (*in module sage.numerical.knapsack*), 7
- ## L
- `largest_less_than()` (*sage.numerical.knapsack.Superincreasing* method), 5
- `leave()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary* method), 179
- `leaving()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary* method), 180
- `leaving_coefficients()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary* method), 181

- lhs() (*sage.numerical.linear_tensor_constraints.LinearTensorConstraint* method), 115
 - linear_constraints_parent() (*sage.numerical.mip.MixedIntegerLinearProgram* method), 38
 - linear_constraints_parent() (*sage.numerical.sdp.SemidefiniteProgram* method), 75
 - linear_function() (*sage.numerical.sdp.SemidefiniteProgram* method), 76
 - linear_functions() (*sage.numerical.linear_tensor_constraints.LinearTensorConstraintsParent_class* method), 117
 - linear_functions() (*sage.numerical.linear_tensor.LinearTensorParent_class* method), 106
 - linear_functions_parent() (*sage.numerical.linear_functions.LinearConstraintsParent_class* method), 91
 - linear_functions_parent() (*sage.numerical.mip.MixedIntegerLinearProgram* method), 38
 - linear_functions_parent() (*sage.numerical.sdp.SemidefiniteProgram* method), 76
 - linear_tensors() (*sage.numerical.linear_tensor_constraints.LinearTensorConstraintsParent_class* method), 117
 - LinearConstraint (*class in sage.numerical.linear_functions*), 87
 - LinearConstraintsParent() (*in module sage.numerical.linear_functions*), 90
 - LinearConstraintsParent_class (*class in sage.numerical.linear_functions*), 91
 - LinearFunction (*class in sage.numerical.linear_functions*), 92
 - LinearFunctionOrConstraint (*class in sage.numerical.linear_functions*), 95
 - LinearFunctionsParent() (*in module sage.numerical.linear_functions*), 95
 - LinearFunctionsParent_class (*class in sage.numerical.linear_functions*), 95
 - LinearTensor (*class in sage.numerical.linear_tensor_element*), 109
 - LinearTensorConstraint (*class in sage.numerical.linear_tensor_constraints*), 113
 - LinearTensorConstraintsParent() (*in module sage.numerical.linear_tensor_constraints*), 116
 - LinearTensorConstraintsParent_class (*class in sage.numerical.linear_tensor_constraints*), 116
 - LinearTensorParent() (*in module sage.numerical.linear_tensor*), 103
 - LinearTensorParent_class (*class in sage.numerical.linear_tensor*), 104
 - LoggingBackend (*class in sage.numerical.backends.logging_backend*), 394
 - LoggingBackendFactory() (*in module sage.numerical.backends.logging_backend*), 428
 - LPAbstractDictionary (*class in sage.numerical.interactive_simplex_method*), 170
 - LPDictionary (*class in sage.numerical.interactive_simplex_method*), 192
 - LPRevisedDictionary (*class in sage.numerical.interactive_simplex_method*), 199
- ## M
- m() (*sage.numerical.interactive_simplex_method.InteractiveLPPProblem* method), 147
 - maxflow_ffalg() (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 348
 - mincost_okalg() (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 349
 - minimize() (*in module sage.numerical.optimize*), 128
 - minimize_constrained() (*in module sage.numerical.optimize*), 130
 - mip() (*sage.numerical.mip.MIPVariable* method), 17
 - MIPSolverException, 15
 - MIPVariable (*class in sage.numerical.mip*), 15
 - MixedIntegerLinearProgram (*class in sage.numerical.mip*), 19
 - module
 - sage.numerical.backends.cvxopt_backend, 375
 - sage.numerical.backends.cvx-opt_sdp_backend, 449
 - sage.numerical.backends.generic_backend, 225
 - sage.numerical.backends.generic_sdp_backend, 433
 - sage.numerical.backends.glpk_backend, 279
 - sage.numerical.backends.glpk_exact_backend, 332
 - sage.numerical.backends.glpk_graph_backend, 335
 - sage.numerical.backends.interactivelylp_backend, 257
 - sage.numerical.backends.logging_backend, 394
 - sage.numerical.backends.ppl_backend, 355
 - sage.numerical.gauss_legendre, 219
 - sage.numerical.interactive_simplex_method, 133
 - sage.numerical.knapsack, 1
 - sage.numerical.linear_functions, 85
 - sage.numerical.linear_tensor, 101
 - sage.numerical.linear_tensor_constraints, 113

sage.numerical.linear_tensor_element,
109
sage.numerical.mip, 9
sage.numerical.optimize, 119
sage.numerical.sdp, 61

N

n() (sage.numerical.interactive_simplex_method.InteractiveLPPProblem method), 147
n_constraints() (sage.numerical.interactive_simplex_method.InteractiveLPPProblem method), 147
n_variables() (sage.numerical.interactive_simplex_method.InteractiveLPPProblem method), 148
ncols() (sage.numerical.backends.cvxopt_backend.CVXOPTBackend method), 383
ncols() (sage.numerical.backends.generic_backend.GenericBackend method), 241
ncols() (sage.numerical.backends.generic_sdp_backend.GenericSDPBackend method), 440
ncols() (sage.numerical.backends.glpk_backend.GLPKBackend method), 304
ncols() (sage.numerical.backends.interactivelp_backend.InteractiveLPBackend method), 270
ncols() (sage.numerical.backends.logging_backend.LoggingBackend method), 413
ncols() (sage.numerical.backends.ppl_backend.PPLBackend method), 366
new_variable() (sage.numerical.mip.MixedIntegerLinearProgram method), 38
new_variable() (sage.numerical.sdp.SemidefiniteProgram method), 76
nodes() (in module sage.numerical.gauss_legendre), 222
nodes_uncached() (in module sage.numerical.gauss_legendre), 223
nonbasic_indices() (sage.numerical.interactive_simplex_method.LPRevisedDictionary method), 210
nonbasic_variables() (sage.numerical.interactive_simplex_method.LPAbstractDictionary method), 181
nonbasic_variables() (sage.numerical.interactive_simplex_method.LPDictionar method), 195
nonbasic_variables() (sage.numerical.interactive_simplex_method.LPRevisedDictionary method), 210
nrows() (sage.numerical.backends.cvxopt_backend.CVXOPTBackend method), 384
nrows() (sage.numerical.backends.generic_backend.GenericBackend method), 242
nrows() (sage.numerical.backends.generic_sdp_backend.GenericSDPBackend method), 440

nrows() (sage.numerical.backends.glpk_backend.GLPKBackend method), 304
nrows() (sage.numerical.backends.interactivelp_backend.InteractiveLPBackend method), 270
nrows() (sage.numerical.backends.logging_backend.LoggingBackend method), 413
nrows() (sage.numerical.backends.ppl_backend.PPLBackend method), 366
number_of_constraints() (sage.numerical.mip.MixedIntegerLinearProgram method), 41
number_of_constraints() (sage.numerical.sdp.SemidefiniteProgram method), 77
number_of_variables() (sage.numerical.mip.MixedIntegerLinearProgram method), 42
number_of_variables() (sage.numerical.sdp.SemidefiniteProgram method), 78

O

objective_coefficient() (sage.numerical.backends.cvxopt_backend.CVXOPTBackend method), 384
objective_coefficient() (sage.numerical.backends.generic_backend.GenericBackend method), 242
objective_coefficient() (sage.numerical.backends.generic_sdp_backend.GenericSDPBackend method), 441
objective_coefficient() (sage.numerical.backends.glpk_backend.GLPKBackend method), 305
objective_coefficient() (sage.numerical.backends.interactivelp_backend.InteractiveLPBackend method), 271
objective_coefficient() (sage.numerical.backends.logging_backend.LoggingBackend method), 413
objective_coefficient() (sage.numerical.backends.ppl_backend.PPLBackend method), 366
objective_coefficients() (sage.numerical.interactive_simplex_method.InteractiveLPPProblem method), 148
objective_coefficients() (sage.numerical.interactive_simplex_method.LPAbstractDictionary method), 182
objective_coefficients() (sage.numerical.interactive_simplex_method.LPDictionar method), 196
objective_coefficients() (sage.numerical.interactive_simplex_method.LPRevisedDictionary method), 211
objective_constant_term() (sage.numerical.backends.generic_backend.GenericBackend method), 243

- `objective_constant_term()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend method*), 271
- `objective_constant_term()` (*sage.numerical.backends.logging_backend.LoggingBackend method*), 414
- `objective_constant_term()` (*sage.numerical.interactive_simplex_method.InteractiveLPPProblem method*), 149
- `objective_name()` (*sage.numerical.interactive_simplex_method.InteractiveLPPProblemStandardForm method*), 165
- `objective_name()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary method*), 182
- `objective_name()` (*sage.numerical.interactive_simplex_method.LPDictionary method*), 196
- `objective_name()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary method*), 211
- `objective_value()` (*sage.numerical.interactive_simplex_method.InteractiveLPPProblem method*), 149
- `objective_value()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary method*), 183
- `objective_value()` (*sage.numerical.interactive_simplex_method.LPDictionary method*), 197
- `objective_value()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary method*), 212
- `optimal_solution()` (*sage.numerical.interactive_simplex_method.InteractiveLPPProblem method*), 150
- `optimal_value()` (*sage.numerical.interactive_simplex_method.InteractiveLPPProblem method*), 150
- P**
- `parent()` (*sage.numerical.backends.logging_backend.LoggingBackend method*), 415
- `plot()` (*sage.numerical.interactive_simplex_method.InteractiveLPPProblem method*), 151
- `plot_feasible_set()` (*sage.numerical.interactive_simplex_method.InteractiveLPPProblem method*), 152
- `polyhedron()` (*sage.numerical.mip.MixedIntegerLinearProgram method*), 42
- `possible_dual_simplex_method_steps()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary method*), 183
- `possible_entering()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary method*), 184
- `possible_leaving()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary method*), 184
- `possible_simplex_method_steps()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary method*), 185
- `PPLBackend` (*class in sage.numerical.backends.ppl_backend*), 355
- `print_ranges()` (*sage.numerical.backends.glpk_backend.GLPKBackend method*), 305
- `problem()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary method*), 212
- `problem_name()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend method*), 385
- `problem_name()` (*sage.numerical.backends.generic_backend.GenericBackend method*), 243
- `problem_name()` (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend method*), 441
- `problem_name()` (*sage.numerical.backends.glpk_backend.GLPKBackend method*), 308
- `problem_name()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend method*), 272
- `problem_name()` (*sage.numerical.backends.logging_backend.LoggingBackend method*), 415
- `problem_name()` (*sage.numerical.backends.ppl_backend.PPLBackend method*), 367
- `problem_type()` (*sage.numerical.interactive_simplex_method.InteractiveLPPProblem method*), 153
- R**
- `random_dictionary()` (*in module sage.numerical.interactive_simplex_method*), 215
- `random_element()` (*sage.numerical.interactive_simplex_method.InteractiveLPPProblemStandardForm static method*), 165
- `random_element()` (*sage.numerical.interactive_simplex_method.LPDictionary static method*), 197
- `ratios()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary method*), 186
- `remove_constraint()` (*sage.numerical.backends.generic_backend.GenericBackend method*), 244
- `remove_constraint()` (*sage.numerical.backends.glpk_backend.GLPKBackend method*), 308
- `remove_constraint()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend method*), 272

`remove_constraint()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 416
`remove_constraint()` (*sage.numerical.mip.MixedIntegerLinearProgram* method), 45
`remove_constraints()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 245
`remove_constraints()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 309
`remove_constraints()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 416
`remove_constraints()` (*sage.numerical.mip.MixedIntegerLinearProgram* method), 46
`rename()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 417
`reset_name()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 418
`revised_dictionary()` (*sage.numerical.interactive_simplex_method.InteractiveLPProblemStandardForm* method), 166
`rhs()` (*sage.numerical.linear_tensor_constraints.LinearTensorConstraint* method), 115
`row()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 385
`row()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 245
`row()` (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend* method), 442
`row()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 310
`row()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 273
`row()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 419
`row()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 367
`row_bounds()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 386
`row_bounds()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 246
`row_bounds()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 310
`row_bounds()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 273
`row_bounds()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 420
`row_bounds()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 368
`row_coefficients()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary* method), 186
`row_coefficients()` (*sage.numerical.interactive_simplex_method.LPDictionary* method), 198
`row_coefficients()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary* method), 213
`row_name()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 387
`row_name()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 247
`row_name()` (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend* method), 443
`row_name()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 311
`row_name()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 274
`row_name()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 420
`row_name()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 369
`run_dual_simplex_method()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary* method), 187
`run_revised_simplex_method()` (*sage.numerical.interactive_simplex_method.InteractiveLPProblemStandardForm* method), 167
`run_simplex_method()` (*sage.numerical.interactive_simplex_method.InteractiveLPProblemStandardForm* method), 168
`run_simplex_method()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary* method), 189

S

`sage.numerical.backends.cvxopt_backend` module, 375
`sage.numerical.backends.cvxopt_sdp_backend` module, 449
`sage.numerical.backends.generic_backend` module, 225
`sage.numerical.backends.generic_sdp_backend` module, 433
`sage.numerical.backends.glpk_backend` module, 279
`sage.numerical.backends.glpk_exact_backend` module, 332
`sage.numerical.backends.glpk_graph_backend` module, 335
`sage.numerical.backends.interactivelp_backend` module, 257
`sage.numerical.backends.logging_backend` module, 394
`sage.numerical.backends.ppl_backend`

module, 355
 sage.numerical.gauss_legendre
 module, 219
 sage.numerical.interactive_simplex_method
 module, 133
 sage.numerical.knapsack
 module, 1
 sage.numerical.linear_functions
 module, 85
 sage.numerical.linear_tensor
 module, 101
 sage.numerical.linear_tensor_constraints
 module, 113
 sage.numerical.linear_tensor_element
 module, 109
 sage.numerical.mip
 module, 9
 sage.numerical.optimize
 module, 119
 sage.numerical.sdp
 module, 61
 save() (*sage.numerical.backends.logging_backend.LoggingBackend* method), 421
 SDPSolverException, 67
 SDPVariable (*class in sage.numerical.sdp*), 67
 SDPVariableParent (*class in sage.numerical.sdp*), 68
 SemidefiniteProgram (*class in sage.numerical.sdp*), 69
 set_binary() (*sage.numerical.mip.MixedIntegerLinearProgram* method), 48
 set_col_stat() (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 311
 set_integer() (*sage.numerical.mip.MixedIntegerLinearProgram* method), 49
 set_max() (*sage.numerical.mip.MIPVariable* method), 18
 set_max() (*sage.numerical.mip.MixedIntegerLinearProgram* method), 49
 set_min() (*sage.numerical.mip.MIPVariable* method), 18
 set_min() (*sage.numerical.mip.MixedIntegerLinearProgram* method), 50
 set_multiplication_symbol() (*sage.numerical.linear_functions.LinearFunctionsParent_class* method), 96
 set_objective() (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 387
 set_objective() (*sage.numerical.backends.generic_backend.GenericBackend* method), 247
 set_objective() (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend* method), 443
 set_objective() (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 312
 set_objective() (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 274
 set_objective() (*sage.numerical.backends.logging_backend.LoggingBackend* method), 421
 set_objective() (*sage.numerical.backends.ppl_backend.PPLBackend* method), 369
 set_objective() (*sage.numerical.mip.MixedIntegerLinearProgram* method), 51
 set_objective() (*sage.numerical.sdp.SemidefiniteProgram* method), 78
 set_problem_name() (*sage.numerical.mip.MixedIntegerLinearProgram* method), 52
 set_problem_name() (*sage.numerical.sdp.SemidefiniteProgram* method), 79
 set_real() (*sage.numerical.mip.MixedIntegerLinearProgram* method), 52
 set_row_stat() (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 313
 set_sense() (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 388
 set_sense() (*sage.numerical.backends.generic_backend.GenericBackend* method), 248
 set_sense() (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend* method), 444
 set_sense() (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 314
 set_sense() (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 275
 set_sense() (*sage.numerical.backends.logging_backend.LoggingBackend* method), 422
 set_sense() (*sage.numerical.backends.ppl_backend.PPLBackend* method), 370
 set_variable_type() (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 388
 set_variable_type() (*sage.numerical.backends.generic_backend.GenericBackend* method), 249
 set_variable_type() (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 314
 set_variable_type() (*sage.numerical.backends.glpk_exact_backend.GLPKExactBackend* method), 334
 set_variable_type() (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 276
 set_variable_type() (*sage.numerical.backends.logging_backend.LoggingBackend* method), 423
 set_variable_type() (*sage.numerical.backends.ppl_backend.PPLBackend* method), 371
 set_verbosity() (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 389
 set_verbosity() (*sage.numerical.backends*

- `ends.generic_backend.GenericBackend method`), 249
 - `set_verbosity()` (*sage.numerical.backends.glpk_backend.GLPKBackend method*), 315
 - `set_verbosity()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend method*), 276
 - `set_verbosity()` (*sage.numerical.backends.logging_backend.LoggingBackend method*), 423
 - `set_verbosity()` (*sage.numerical.backends.ppl_backend.PPLBackend method*), 372
 - `set_vertex_demand()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend method*), 350
 - `set_vertices_demand()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend method*), 351
 - `show()` (*sage.numerical.mip.MixedIntegerLinearProgram method*), 53
 - `show()` (*sage.numerical.sdp.SemidefiniteProgram method*), 79
 - `slack()` (*sage.numerical.backends.cvxopt_sdp_backend.CVXOPTSDPBackend method*), 453
 - `slack()` (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend method*), 444
 - `slack()` (*sage.numerical.sdp.SemidefiniteProgram method*), 80
 - `slack_variables()` (*sage.numerical.interactive_simplex_method.InteractiveLPPStandardForm method*), 169
 - `solve()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend method*), 389
 - `solve()` (*sage.numerical.backends.cvxopt_sdp_backend.CVXOPTSDPBackend method*), 454
 - `solve()` (*sage.numerical.backends.generic_backend.GenericBackend method*), 250
 - `solve()` (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend method*), 445
 - `solve()` (*sage.numerical.backends.glpk_backend.GLPKBackend method*), 317
 - `solve()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend method*), 277
 - `solve()` (*sage.numerical.backends.logging_backend.LoggingBackend method*), 424
 - `solve()` (*sage.numerical.backends.ppl_backend.PPLBackend method*), 372
 - `solve()` (*sage.numerical.mip.MixedIntegerLinearProgram method*), 55
 - `solve()` (*sage.numerical.sdp.SemidefiniteProgram method*), 81
 - `solver_parameter()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend method*), 392
 - `solver_parameter()` (*sage.numerical.backends.cvxopt_sdp_backend.CVXOPTSDPBackend method*), 456
 - `solver_parameter()` (*sage.numerical.backends.generic_backend.GenericBackend method*), 250
 - `solver_parameter()` (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend method*), 446
 - `solver_parameter()` (*sage.numerical.backends.glpk_backend.GLPKBackend method*), 323
 - `solver_parameter()` (*sage.numerical.backends.logging_backend.LoggingBackend method*), 425
 - `solver_parameter()` (*sage.numerical.mip.MixedIntegerLinearProgram method*), 57
 - `solver_parameter()` (*sage.numerical.sdp.SemidefiniteProgram method*), 82
 - `standard_form()` (*sage.numerical.interactive_simplex_method.InteractiveLPPMethod method*), 153
 - `style()` (in module *sage.numerical.interactive_simplex_method*), 215
 - `subset_sum()` (*sage.numerical.knapsack.Superincreasing method*), 6
 - `sum()` (*sage.numerical.mip.MixedIntegerLinearProgram method*), 58
 - `sum()` (*sage.numerical.sdp.SemidefiniteProgram method*), 83
 - `Superincreasing` (class in *sage.numerical.knapsack*), 2
- ## T
- `tensor()` (*sage.numerical.linear_functions.LinearFunctionsParent_class method*), 97
- ## U
- `update()` (*sage.numerical.interactive_simplex_method.LPAbstractDictionary method*), 191
 - `update()` (*sage.numerical.interactive_simplex_method.LPDictionary method*), 199
 - `update()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary method*), 214
- ## V
- `values()` (*sage.numerical.mip.MIPVariable method*), 19
 - `values()` (*sage.numerical.sdp.SDPVariable method*), 68
 - `variable()` (in module *sage.numerical.interactive_simplex_method*), 217
 - `variable_lower_bound()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend method*), 392
 - `variable_lower_bound()` (*sage.numerical.backends.generic_backend.GenericBackend method*), 251

`variable_lower_bound()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 328
`variable_lower_bound()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 277
`variable_lower_bound()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 425
`variable_lower_bound()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 373
`variable_types()` (*sage.numerical.interactive_simplex_method.InteractiveLPPProblem* method), 155
`variable_upper_bound()` (*sage.numerical.backends.cvxopt_backend.CVXOPTBackend* method), 393
`variable_upper_bound()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 252
`variable_upper_bound()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 328
`variable_upper_bound()` (*sage.numerical.backends.interactivelp_backend.InteractiveLPBackend* method), 278
`variable_upper_bound()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 426
`variable_upper_bound()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 374
`vertices()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 352

W

`warm_up()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 329
`write_ccdata()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 352
`write_graph()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 353
`write_lp()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 252
`write_lp()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 330
`write_lp()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 426
`write_lp()` (*sage.numerical.mip.MixedIntegerLinearProgram* method), 59
`write_maxflow()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 354

`write_mincost()` (*sage.numerical.backends.glpk_graph_backend.GLPKGraphBackend* method), 354
`write_mps()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 253
`write_mps()` (*sage.numerical.backends.glpk_backend.GLPKBackend* method), 331
`write_mps()` (*sage.numerical.backends.logging_backend.LoggingBackend* method), 427
`write_mps()` (*sage.numerical.mip.MixedIntegerLinearProgram* method), 60

X

`x()` (*sage.numerical.interactive_simplex_method.InteractiveLPPProblem* method), 156
`x_B()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary* method), 214
`x_N()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary* method), 214

Y

`y()` (*sage.numerical.interactive_simplex_method.LPRevisedDictionary* method), 214

Z

`zero()` (*sage.numerical.backends.generic_backend.GenericBackend* method), 253
`zero()` (*sage.numerical.backends.generic_sdp_backend.GenericSDPBackend* method), 447
`zero()` (*sage.numerical.backends.ppl_backend.PPLBackend* method), 375